

MEASURES AND ASSUMPTIONS FOR DEMAND SIDE MANAGEMENT (DSM) PLANNING

APPENDIX C: SUBSTANTIATION SHEETS

Presented to



Ontario Energy Board

**Ontario Energy Board
2300 Yonge Street,
27th Floor
Toronto, Ontario M4P 1E4**

APRIL 16, 2009

Navigant Consulting Inc.
1 Adelaide Street East, Suite 2601
Toronto, ON M5C 2V9
416.927.1641
www.navigantconsulting.com

TABLE OF CONTENTS

| | |
|--|------------|
| GLOSSARY AND DEFINITION OF TERMS..... | 4 |
| RESIDENTIAL SPACE HEATING..... | 6 |
| 1. AIR SEALING..... | 7 |
| 2. BASEMENT WALL INSULATION (R-12) | 12 |
| 3. CEILING INSULATION (R-40)..... | 16 |
| 4. ENHANCED FURNACE (ELECTRONICALLY COMMUTATED MOTOR) – EXISTING RESIDENTIAL..... | 20 |
| 5. ENHANCED FURNACE (ELECTRONICALLY COMMUTATED MOTOR) – NEW CONSTRUCTION | 26 |
| 6. ENERGY STAR WINDOWS (LOW-E)..... | 32 |
| 7. HEAT REFLECTIVE PANELS..... | 37 |
| 8. HIGH EFFICIENCY (CONDENSING) FURNACE - RESIDENTIAL..... | 40 |
| 9. PROGRAMMABLE THERMOSTAT - RESIDENTIAL | 43 |
| 10. WALL INSULATION (R-19)..... | 49 |
| RESIDENTIAL WATER HEATING..... | 55 |
| 11. FAUCET AERATOR (RESIDENTIAL BATHROOM) | 56 |
| 12. FAUCET AERATOR (RESIDENTIAL KITCHEN) | 60 |
| 13. LOW-FLOW SHOWERHEAD (1.5 GPM, RESIDENTIAL, UG ESK, PER HOUSEHOLD)..... | 64 |
| 14. LOW-FLOW SHOWERHEAD (1.25 GPM, RESIDENTIAL, UG ESK, PER HOUSEHOLD)..... | 68 |
| 15. LOW-FLOW SHOWERHEAD (1.25 GPM, RESIDENTIAL, ENBRIDGE TAPS, PER HOUSEHOLD)..... | 72 |
| 16. PIPE WRAP (R-4) | 77 |
| 17. SOLAR POOL HEATERS | 81 |
| 18. TANKLESS GAS WATER HEATER | 85 |
| LOW INCOME SPACE HEATING..... | 89 |
| 19. PROGRAMMABLE THERMOSTAT (LIA) | 90 |
| 20. WEATHERIZATION (LIA) | 96 |
| LOW INCOME WATER HEATING..... | 99 |
| 21. FAUCET AERATOR (BATHROOM) (LIA) | 100 |
| 22. FAUCET AERATOR (KITCHEN) (LIA) | 104 |
| 23. LOW-FLOW SHOWERHEAD (1.5 GPM, UG ESK, LIA, PER HOUSEHOLD) | 108 |
| 24. LOW-FLOW SHOWERHEAD (1.25 GPM, LIA, UG ESK, PER HOUSEHOLD) | 112 |
| 25. LOW-FLOW SHOWERHEAD (1.25 GPM, LIA, ENBRIDGE TAPS, PER HOUSEHOLD) | 116 |
| 26. PIPE WRAP – R4 (LIA) | 121 |
| COMMERCIAL COOKING | 125 |
| 27. ENERGY STAR COMMERCIAL FRYER | 126 |
| 28. HIGH EFFICIENCY COMMERCIAL GRIDDLE | 130 |
| COMMERCIAL SPACE HEATING | 134 |
| 29. AIR CURTAINS – SINGLE DOOR (8’ x 6’)..... | 135 |
| 30. AIR CURTAINS – DOUBLE DOOR (2 x 8’ x 6’) | 138 |
| 31. CONDENSING BOILERS..... | 141 |
| 32. DEMAND CONTROL KITCHEN VENTILATION (DCKV – 5000 CFM) | 146 |
| 33. DEMAND CONTROL KITCHEN VENTILATION (DCKV – 10000 CFM) | 150 |
| 34. DEMAND CONTROL KITCHEN VENTILATION (DCKV – 15000 CFM) | 154 |
| 35. DESTRATIFICATION FAN – NEW OR EXISTING COMMERCIAL | 158 |
| 36. ENERGY RECOVERY VENTILATOR (ERV) – EXISTING COMMERCIAL | 162 |
| 37. ENERGY RECOVERY VENTILATOR (ERV) – NEW COMMERCIAL..... | 166 |
| 38. ENHANCED FURNACE (ELECTRONICALLY COMMUTATED MOTOR) – EXISTING COMMERCIAL..... | 170 |
| 39. ENHANCED FURNACE (ELECTRONICALLY COMMUTATED MOTOR) – NEW COMMERCIAL | 175 |
| 40. HEAT RECOVERY VENTILATOR (HRV) – EXISTING COMMERCIAL | 181 |
| 41. HEAT RECOVERY VENTILATOR (HRV) – NEW COMMERCIAL | 185 |
| 42. HIGH EFFICIENCY (CONDENSING) FURNACE - COMMERCIAL..... | 189 |
| 43. INFRARED HEATERS..... | 192 |
| 44. GAS-FIRED ROOFTOP UNIT | 196 |
| 45. PROGRAMMABLE THERMOSTAT - COMMERCIAL..... | 199 |

| | |
|---|------------|
| 46. PRESCRIPTIVE SCHOOLS – ELEMENTARY | 204 |
| 47. PRESCRIPTIVE SCHOOLS – SECONDARY | 207 |
| COMMERCIAL WATER HEATING | 210 |
| 48. CONDENSING GAS WATER HEATER - COMMERCIAL | 211 |
| 49. PRE-RINSE SPRAY NOZZLE (1.6 GPM) | 216 |
| 50. PRE-RINSE SPRAY NOZZLE (1.24 GPM) | 221 |
| 51. TANKLESS WATER HEATER - COMMERCIAL | 226 |
| MULTI-FAMILY WATER HEATING | 232 |
| 52. ENERGY STAR FRONT-LOADING CLOTHES WASHER | 233 |
| 53. CEE TIER 2 FRONT-LOADING CLOTHES WASHER | 238 |
| 54. FAUCET AERATOR (MULTI-FAMILY BATHROOM)..... | 243 |
| 55. FAUCET AERATOR (MULTI-FAMILY KITCHEN)..... | 247 |
| 56. LOW-FLOW SHOWERHEAD (1.5 GPM, MULTI-FAMILY, UG ESK, PER HOUSEHOLD) | 251 |
| 57. LOW-FLOW SHOWERHEAD (1.25 GPM, MULTI-FAMILY, UG ESK, PER HOUSEHOLD) | 255 |
| 58. LOW-FLOW SHOWERHEAD (1.25 GPM, MULTI-FAMILY, ENBRIDGE TAPS, PER HOUSEHOLD)..... | 259 |

GLOSSARY AND DEFINITION OF TERMS

Measure Name

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Description of energy efficient technology

Base Equipment and Technologies Description

Description of base technology.

| Decision Type | Target Market(s) | End Use |
|--|---|--|
| Description of the decision type (e.g. New, Retrofit, Removal) | Description of the target market(s) for the measure (e.g. Residential / Small Commercial, New homes / Existing Homes, Single-Family / Multi-Family) | Description of the end use of the measure (e.g., space heating, water heating) |

Codes, Standards, and Regulations

Description of any applicable codes, standards, and / or regulations that governing the performance (e.g, energy consumption) of the equipment.

Resource Savings Table (10 year Effective Useful Life [EUL] illustrated)

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|---|---|---|---|---|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | Annual natural gas savings for lifetime of measure | Annual electricity savings for life of measure (if applicable) | Annual water savings for life of measure (if applicable) | Annual equipment and operations and maintenance cost of energy efficient measure | Annual equipment and operations and maintenance cost of baseline measure |
| 2 | | | | | |
| ... | | | | | |
| 9 | | | | | |
| 10 | | | | | |
| TOTALS | Total natural gas savings | Total electricity savings | Total water savings | Total equipment and O&M cost | Total equipment and O&M cost |

Resource Savings Assumptions

| | |
|---|----------------------|
| Annual Natural Gas Savings | m³ |
| Basis for determination of natural gas savings. | |
| Annual Electricity Savings | kWh |
| Basis for determination of electricity savings. | |
| Annual Water Savings | L |
| Basis for determination of water savings. | |

Other Input Assumptions

| | |
|--|-------------------|
| Effective Useful Life (EUL) | Years |
| Description and rationale of how many years the savings for the energy efficient measure are expected to last. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$ |
| Description and rationale of difference in the equipment cost and any operation and maintenance cost associated for the energy efficient measure and the baseline measure. | |
| Customer Payback Period (Natural Gas Only) | Years |
| Rationale used to determine the length of time required to recover the cost of the energy efficient measure based on the natural gas savings only. | |
| Market Penetration or Market Share | % or level |
| High level description and rationale used to determine the current penetration level of the energy efficient measure in the target market area or the current market share of the energy efficient measure in the target market area. When available, the current market penetration or market share percentage is provided, else, an estimated "low", "medium" or "high" scale is used, where "low" is below 5%, "medium" is between 5 and 50%, and "high" is greater than 50%. | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---|--|--|---|
| Source of database reported by other jurisdiction | Annual gas savings reported by other jurisdiction | Effective useful life reported by other jurisdiction | Incremental cost by reported by jurisdiction | Market penetration/share reported in other jurisdiction |
| Comments Description of any input assumptions or values used by the other jurisdictions to determine their savings. | | | | |

RESIDENTIAL SPACE HEATING

1. Air Sealing

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Air infiltration control; caulking, weather stripping of doors and windows, etc. (6 ACH₅₀)

Base Equipment and Technologies Description

Existing infiltration controls (8 ACH₅₀)¹

| Decision Type | Target Market(s) | End Use |
|---------------|----------------------------------|---------------|
| Retrofit | Existing Residential (Pre-1980s) | Space heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)² requires:

- Windows that separate heated space from unheated space are designed to limit the rate of air infiltration to no more than 0.77 L/s for each metre of sash crack when tested at pressure differential of 75 Pa.
- Sliding glass door assemblies that separate heated space from unheated space are designed to limit the rate of air infiltration to no more than 2.5 L/s for each square metre of door area when tested at a pressure differential of 75 Pa.
- Swinging doors that separate heated space from unheated space are designed to limit the rate of air infiltration to no more than 6.35 L/s for each square metre of door area when tested at a pressure differential of 75 Pa.
- Caulking material to reduce air infiltration is: non-hardening, compatible with the substrate to which it is applied.
- Any location where there is a possibility of air leakage into heated spaces in a building through exterior walls will be caulked, gasketed or sealed.

¹ Base and efficient equipment air change rates are estimates of the average scenario for a home built in the 1950s to 1980s.

² Determined from communication with a local contractor specializing in the sale and installation of air infiltration control measures.

² Ontario Regulations 350/06, 2006 Building Code

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 177 | 66.7 | 0 | 1,000 | 0 |
| 2 | 177 | 66.7 | 0 | 0 | 0 |
| 3 | 177 | 66.7 | 0 | 0 | 0 |
| 4 | 177 | 66.7 | 0 | 0 | 0 |
| 5 | 177 | 66.7 | 0 | 0 | 0 |
| 6 | 177 | 66.7 | 0 | 0 | 0 |
| 7 | 177 | 66.7 | 0 | 0 | 0 |
| 8 | 177 | 66.7 | 0 | 0 | 0 |
| 9 | 177 | 66.7 | 0 | 0 | 0 |
| 10 | 177 | 66.7 | 0 | 0 | 0 |
| 11 | 177 | 66.7 | 0 | 0 | 0 |
| 12 | 177 | 66.7 | 0 | 0 | 0 |
| 13 | 177 | 66.7 | 0 | 0 | 0 |
| 14 | 177 | 66.7 | 0 | 0 | 0 |
| 15 | 177 | 66.7 | 0 | 0 | 0 |
| TOTALS | 2,655 | 1,000 | 0 | 1,000 | 0 |

Resource Savings Assumptions

Annual Natural Gas Savings

177 m³

Assumptions and inputs:

- Navigant Consulting used HOT2000³ to model energy savings resulting from the energy efficient upgrade. The following input assumptions were based on a candidate house for a typical pre-1980 home⁴.

³ NRCan, http://canmetenergy-canmetenergie.nrcan-rncan.gc.ca/eng/software_tools/hot2000.html

⁴ Candidate home characteristics are based on previous weatherization study completed by Marbek in 2008 for Union Gas and Navigant Consulting input assumptions.

| House Characteristics using HOT2000 | |
|---|--|
| Location | Toronto, ON |
| Storeys | 2 |
| Above Grade Wall Insulation | R-Value = 3.42 |
| Below Grade Wall Insulation | R-Value = 1.13 |
| Attic Insulation | R-Value = 12.90 |
| Foundation Floor Insulation | R-Value = 2.68 |
| Air Leakage (ACH) | 8.0 |
| Number of Windows | 8 on the main floor, 4 in the basement |
| Ceiling Area (ft ²) | 829 |
| Main Level Wall Area (ft ²) | 944 |
| Living Space Area (ft ²) | 1,658 |
| Basement Wall Area (ft ²) | 827 |
| Basement Floor Area (ft ²) | 829 |
| Base Loads Use | Defaults |
| Furnace Efficiency (AFUE) | 80 |
| Furnace Capacity (Btu/hr) | 58,006.4 (Calculated) |
| Fans Mode | Auto |
| A/C Efficiency (SEER) | 10 |
| A/C Capacity (Btu/hr) | 13000 [†] |

† The current version of HOT2000 has limitation on A/C capacities under specified conditions. 13000 Btu/hr is the maximum value it allows.

- Based on the assumptions above, the following results are obtained:

| HOT2000 Simulation Results | Space Heating NG Consumption (m ³) | Space Cooling Consumption (kWh) | Annual Furnace Fan Consumption (kWh) |
|----------------------------|--|---------------------------------|--------------------------------------|
| Base Case | 3,331 | 697 | 665 |
| Air Sealing Upgrade | 3,133 | 693 | 631 |
| Savings | 198 | 4 | 34 |
| Savings% | 5.9% | 0.5% | 5.1% |

- Energy savings estimated by the three other jurisdictions listed below (Washington State, Iowa and New Hampshire⁵) are between 6 to 35% over their baseline. The large variation is due to differing input assumptions for both the base case scenario and the energy efficient scenario.
- In terms of the baseline consumption, Navigant Consulting estimates that a typical pre-1980's home consumes approximately 25% more natural gas then a typical baseline home used by Enbridge⁶ (2,436 m³), approximately 3,000 m³.
- Applying the 5.9% savings calculated in the table above to the average annual consumption of natural gas cited directly above yields:
- Natural gas savings = 5.9% x 3,000 = 177 m³

Annual Electricity Savings

66.7 kWh

Annual electricity savings are derived from two sources:

- Space cooling consumption
- Furnace fan consumption

⁵ Opinion Dynamics Corporation, *The New Hampshire Electric Utilities' Low-income Retrofit Program – Impact Evaluation*, January 2006 http://www.cee1.org/eval/db_pdf/556.pdf

⁶ Enbridge Gas Customer Profiling Yearly Average End Use, November 23, 2004

Space cooling consumption:

- Assumed penetration rate of central air conditioners in Ontario = 57%⁷
- Assuming that baseline house is equipped with a SEER 10, 2.5 ton⁸ A/C unit and is used 500 hours per year⁹, this implies that:
$$\text{Base A/C electricity use} = 500 \text{ (cooling hours)} \times [30,000 \text{ (Btu/hr)} / (10 \text{ (SEER)} \times 1,000)] = 1,500 \text{ kWh}$$
- Applying the 0.5% savings calculated in the table in the previous section to the average annual consumption of electricity cited directly above yields:
$$\text{Electricity savings (A/C)} = 0.5 \% \times 1,500 \text{ kWh} = 7.5 \text{ kWh}$$

Furnace fan consumption:

- Annual furnace fan consumption for a typical Toronto home with a non-continuous mid-efficiency furnace = 1,150 kWh¹⁰
- Applying the 5.1% savings calculated in the table in the previous section to the annual furnace fan electricity consumption cited directly above yields:
$$\text{Electricity savings (furnace fan)} = 5.15 \% \times 1,150 = 59.23 \text{ kWh.}$$

Total Electricity Savings

- Total electricity savings are the sum of furnace fan savings and air conditioner savings:
$$\text{Total electricity savings} = 7.5 + 59.23 = 66.73 \text{ kWh}$$

Annual Water Savings

0 L

N/A.

Other Input Assumptions

Effective Useful Life (EUL)

15 Years

Based on a survey of the EUL used in other jurisdictions (Vermont¹¹ – 20 years, Washington State¹² – 10 years, Iowa¹³ – 15 years and Oregon¹⁴ – 15 years) Navigant Consulting estimates a EUL of 15 years.

Base & Incremental Conservation Measure Equipment and O&M Costs

\$1,000

Incremental cost determined from communication with local contractor¹⁵.

Customer Payback Period (Natural Gas Only)¹⁶

10.9 Years

Using a 5-year average commodity cost (avoided cost)¹⁷ of \$0.38 / m³ and an average residential distribution cost¹⁸ of \$0.14 / m³, the payback period for natural gas savings is determined to be 10.9 years, based on the following:

⁷ Natural Resource Canada, Survey of Household Energy Use (SHEU), December 2005

⁸ Implying input of 30,000 Btu/hr, Energy Star Savings Calculator, http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Calc_CAC.xls

⁹ Number of full-load cooling hours provided by <http://energyexperts.org/ac%5Fcalc/> and based on the assumption that Ontario's climate is sufficiently similar to that of the north-eastern U.S.

¹⁰ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

¹¹ Efficiency Vermont, *Technical Reference User Manual (TRM)*, February 2006

¹² Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹³ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

¹⁴ Ecotope Inc. *Natural Gas Efficiency and Conservation Measure Assessment for Residential and Commercial Sectors* Prepared for Energy Trust of Oregon. August, 2003.

¹⁵ Incremental cost is an increasing function of the magnitude change in air tightness and a decreasing function of the base ACH₅₀ – improving a house's air tightness from 8 to 5 ACH₅₀ will be **more** than 50% more expensive than improving it from 8 to 6 ACH₅₀, and improving a house's air tightness from 10 ACH₅₀ to 8 ACH₅₀ will cost much less than improving a house's air tightness from 8 ACH₅₀ to 6 ACH₅₀.

¹⁶ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹⁷ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

Payback Period = Incremental cost / (natural gas savings x natural gas cost)
 = \$1000 / (177 m³/year * \$0.52 / m³)
 = 10.9 years

Market Penetration¹⁹

Medium

Based on the observation of high penetration in one jurisdiction (Washington State²⁰ – 60%), of medium penetration in another (Iowa²¹ – 25%) and on communication with a local contractor, Navigant Consulting estimates the penetration in Ontario to be medium.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| State of Iowa Utilities Board ²² | 193 | 15 | 363 | 25% |
| Comments Furnace central heating of a single family existing home. Annual electricity savings for central A/C: 257.5 kWh. Measure saves 10% of 1,935 m ³ required for space heating. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Puget Sound Energy, 2007 ²³ | 102 | 10 | 650 | 60% |
| Comments No indication of base or efficient air tightness. Measure saves 6% of 1,707 m ³ required for space heating. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Energy Trust of Oregon, 2003 ²⁴ | 106 | 15 | 250 | N/A |
| Comments Changing from a base of 10 ACH ₅₀ to 8 ACH ₅₀ . No indication given of percentage savings or base natural gas consumption for space heating. | | | | |

¹⁸ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁹ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

²⁰ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

²¹ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

²² Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

²³ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

²⁴ Ecotope Inc. *Natural Gas Efficiency and Conservation Measure Assessment for Residential and Commercial Sectors* Prepared for Energy Trust of Oregon. August, 2003.
http://www.cce1.org/eval/db_pdf/544.pdf

2. Basement Wall Insulation (R-12)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Basement wall insulation R-12

Base Equipment and Technologies Description

Basement wall insulation R-1

| Decision Type | Target Market(s) | End Use |
|---------------|---------------------------------|---------------|
| Retrofit | Existing Residential (Pre-1980) | Space Heating |

Codes, Standards, and Regulations

The minimum R value required by Ontario Building Code¹ for foundation wall is R-12.

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$/ft ²) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 462 | 145 | 0 | 2 | 0 |
| 2 | 462 | 145 | 0 | 0 | 0 |
| 3 | 462 | 145 | 0 | 0 | 0 |
| 4 | 462 | 145 | 0 | 0 | 0 |
| 5 | 462 | 145 | 0 | 0 | 0 |
| 6 | 462 | 145 | 0 | 0 | 0 |
| 7 | 462 | 145 | 0 | 0 | 0 |
| 8 | 462 | 145 | 0 | 0 | 0 |
| 9 | 462 | 145 | 0 | 0 | 0 |
| 10 | 462 | 145 | 0 | 0 | 0 |
| 11 | 462 | 145 | 0 | 0 | 0 |
| 12 | 462 | 145 | 0 | 0 | 0 |
| 13 | 462 | 145 | 0 | 0 | 0 |
| 14 | 462 | 145 | 0 | 0 | 0 |
| 15 | 462 | 145 | 0 | 0 | 0 |
| 16 | 462 | 145 | 0 | 0 | 0 |
| 17 | 462 | 145 | 0 | 0 | 0 |
| 18 | 462 | 145 | 0 | 0 | 0 |
| 19 | 462 | 145 | 0 | 0 | 0 |
| 20 | 462 | 145 | 0 | 0 | 0 |
| 21 | 462 | 145 | 0 | 0 | 0 |
| 22 | 462 | 145 | 0 | 0 | 0 |
| 23 | 462 | 145 | 0 | 0 | 0 |
| 24 | 462 | 145 | 0 | 0 | 0 |
| 25 | 462 | 145 | 0 | 0 | 0 |
| TOTALS | 11,550 | 3,625 | 0 | 2 | 0 |

¹ Ontario Regulations 350/06, 2006 Building Code

Resource Savings Assumptions

Annual Natural Gas Savings

462 m³

- Navigant Consulting used HOT2000² to model energy savings resulting from the energy efficient upgrade. The following input assumptions were based on a candidate house for a typical pre-1980 home³.

| House Characteristics using HOT2000 | |
|---|--|
| Location | Toronto, ON |
| Storeys | 2 |
| Above Grade Wall Insulation | R-Value = 3.42 |
| Below Grade Wall Insulation | R-Value = 1.13 |
| Attic Insulation | R-Value = 12.90 |
| Foundation Floor Insulation | R-Value = 2.68 |
| Air Leakage (ACH) | 8.0 |
| Number of Windows | 8 on the main floor, 4 in the basement |
| Ceiling Area (ft ²) | 829 |
| Main Level Wall Area (ft ²) | 944 |
| Living Space Area (ft ²) | 1,658 |
| Basement Wall Area (ft ²) | 827 |
| Basement Floor Area (ft ²) | 829 |
| Base Loads Use | Defaults |
| Furnace Efficiency (AFUE) | 80 |
| Furnace Capacity (Btu/hr) | 58,006.4 (Calculated) |
| Fans Mode | Auto |
| A/C Efficiency (SEER) | 10 |
| A/C Capacity (Btu/hr) | 13000 [†] |

† The current version of HOT2000 has limitation on A/C capacities under specified conditions. 13000 Btu/hr is the maximum value it allows.

- Based on the above assumptions, the following results are obtained:

| HOT2000 Simulation Results | Space Heating NG Consumption (m ³) | Space Cooling Consumption (kWh) | Annual Furnace Fan Consumption (kWh) |
|----------------------------|--|---------------------------------|--------------------------------------|
| Base Case | 3,331 | 697 | 665 |
| Basement Wall Upgrade | 2,817 | 699 | 579 |
| Savings | 514 | -2 | 86 |
| Savings% | 15.4% | -0.3% | 13.0% |

- Annual natural gas savings for space heating is 15.4%.
- In terms of the baseline consumption, Navigant Consulting estimates that a typical pre-1980's home consumes approximately 25% more natural gas than a typical baseline home used by Enbridge⁴ (2,436 m³), approximately 3,000 m³.
- Applying the 15.4% savings calculated in the table above to the average annual consumption of natural gas cited directly above yields:

$$\text{Natural Gas Savings} = 3,000 \text{ m}^3 \times 15.4\% = 462 \text{ m}^3$$

² NRCan, http://canmetenergy-canmetenergie.nrcan-rncan.gc.ca/eng/software_tools/hot2000.html

³ Candidate home characteristics are based on previous weatherization study completed by Marbek in 2008 for Union Gas and Navigant Consulting input assumptions.

⁴ Enbridge Gas Customer Profiling Yearly Average End Use, November 23, 2004

| Annual Electricity Savings | 145 kWh |
|--|---------|
| <p>Annual electricity savings are derived from two sources:</p> <ol style="list-style-type: none"> 1. Space cooling consumption 2. Furnace fan consumption <p><i>Space cooling consumption:</i></p> <ul style="list-style-type: none"> Assuming that baseline house is equipped with a SEER 10, 2.5 ton⁵ A/C unit and is used 500 hours per year⁶, this implies that: Base A/C electricity use = 500 (cooling hours)*[30,000 (Btu/hr)/(10 (SEER)* 1,000)] = 1,500 kWh Applying the -0.3% savings calculated in the table in the previous section to the average annual consumption of electricity cited directly above yields: Electricity savings (A/C) = -0.3% x 1,500 kWh/year = - 4.5 kWh. <p><i>Furnace fan consumption:</i></p> <ul style="list-style-type: none"> Annual furnace fan consumption for a typical Toronto home with a non-continuous mid-efficiency furnace = 1,150 kWh⁷ Applying the 13.0% savings calculated in the table in the previous section to the annual furnace fan electricity consumption cited directly above yields: Electricity savings (furnace fan) = 13% x 1150 kWh = 149.5 kWh <p><i>Total Electricity Savings:</i></p> <ul style="list-style-type: none"> Total electricity savings are the sum of furnace fan savings and air conditioner savings: Total electricity savings = -4.5 kWh + 149.5 kWh = 145 kWh | |
| Annual Water Savings | 0 L |
| N/A | |

Other Input Assumptions

| Effective Useful Life (EUL) | 25 Years |
|---|-----------------------|
| The EUL is reported to be 25 years by the Iowa Utilities Board ⁸ . Navigant Consulting estimates an EUL of 25 years. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$2 / ft ² |
| Based on communication with various local vendors, the incremental cost of wall insulation from R-1 to R-12 is approximately \$2 per ft ² , which includes only the insulation material and labour but not the costs of wall removal and reconstruction required for installation. For the candidate home, the incremental cost is estimated to be \$1,654 (\$2.00 x 827 ft ² = \$1,645). | |
| Customer Payback Period (Natural Gas Only) ⁹ | 6.9 Years |
| Using an 5-year average commodity cost (avoided cost) ¹⁰ of \$0.38 / m ³ and an average residential distribution cost ¹¹ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 6.9 years, based on the following: | |

⁵ Implying input of 30,000 Btu/hr, Energy Star Savings Calculator, http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Calc_CAC.xls

⁶ Number of full-load cooling hours provided by <http://energyexperts.org/ac/%5Fcalc/> and based on the assumption that Ontario's climate is sufficiently similar to that of the north-eastern U.S.

⁷ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

⁸ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

⁹ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹⁰ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

Payback Period = Incremental cost / (natural gas savings x natural gas cost)
 = \$2 /ft² x 827 ft² / (462 m³/year * \$0.52 / m³)
 = 6.9 years

Market Penetration¹²

High

Based on penetration rates of other jurisdictions (63% in Iowa State) and communication with local contractors, Navigant Consulting estimates the penetration in Ontario to be high.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|--|-------------------------------|-----------------------|--------------------------|
| State of Iowa Utilities Board ¹³ | 122.5 | 25 | 1,933 | 63% |

Comments

Assuming baseline R-value of basement wall insulation is 8 and upgrade R-value of basement wall insulation is 13. Estimated 6.4% savings are based on 696 therms, which would translate to 44.5 therms (122.5 m³).

¹¹ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹² Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹³ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

3. Ceiling Insulation (R-40)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Ceiling insulation R-40

Base Equipment and Technologies Description

Ceiling insulation R-10

| Decision Type | Target Market(s) | End Use |
|---------------|----------------------------------|---------------|
| Retrofit | Existing Residential (Pre-1980s) | Space Heating |

Codes, Standards, and Regulations

The minimum R value required by Ontario Building Code¹ for ceiling below attic or roof space is 40.

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$/ft ²) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 186 | 105 | 0 | 0.7 | 0 |
| 2 | 186 | 105 | 0 | 0 | 0 |
| 3 | 186 | 105 | 0 | 0 | 0 |
| 4 | 186 | 105 | 0 | 0 | 0 |
| 5 | 186 | 105 | 0 | 0 | 0 |
| 6 | 186 | 105 | 0 | 0 | 0 |
| 7 | 186 | 105 | 0 | 0 | 0 |
| 8 | 186 | 105 | 0 | 0 | 0 |
| 9 | 186 | 105 | 0 | 0 | 0 |
| 10 | 186 | 105 | 0 | 0 | 0 |
| 11 | 186 | 105 | 0 | 0 | 0 |
| 12 | 186 | 105 | 0 | 0 | 0 |
| 13 | 186 | 105 | 0 | 0 | 0 |
| 14 | 186 | 105 | 0 | 0 | 0 |
| 15 | 186 | 105 | 0 | 0 | 0 |
| 16 | 186 | 105 | 0 | 0 | 0 |
| 17 | 186 | 105 | 0 | 0 | 0 |
| 18 | 186 | 105 | 0 | 0 | 0 |
| 19 | 186 | 105 | 0 | 0 | 0 |
| 20 | 186 | 105 | 0 | 0 | 0 |
| TOTALS | 3,720 | 2,100 | 0 | 0.7 | 0 |

¹ Ontario Regulations 350/06, 2006 Building Code

Resource Savings Assumptions

Annual Natural Gas Savings

186 m³

- Navigant Consulting used HOT2000² to model energy savings resulting from the energy efficient upgrade. The following input assumptions were based on a candidate house for a typical pre-1980 home³.

| House Characteristics using HOT2000 | |
|---|--|
| Location | Toronto, ON |
| Storeys | 2 |
| Above Grade Wall Insulation | R-Value = 3.42 |
| Below Grade Wall Insulation | R-Value = 1.13 |
| Attic Insulation | R-Value = 12.90 |
| Foundation Floor Insulation | R-Value = 2.68 |
| Air Leakage (ACH) | 8.0 |
| Number of Windows | 8 on the main floor, 4 in the basement |
| Ceiling Area (ft ²) | 829 |
| Main Level Wall Area (ft ²) | 944 |
| Living Space Area (ft ²) | 1,658 |
| Basement Wall Area (ft ²) | 827 |
| Basement Floor Area (ft ²) | 829 |
| Base Loads Use | Defaults |
| Furnace Efficiency (AFUE) | 80 |
| Furnace Capacity (Btu/hr) | 58,006.4 (Calculated) |
| Fans Mode | Auto |
| A/C Efficiency (SEER) | 10 |
| A/C Capacity (Btu/hr) | 13000 [†] |

† The current version of HOT2000 has limitation on A/C capacities under specified conditions. 13000 Btu/hr is the maximum value it allows.

- Based on the above assumptions, the following results are obtained:

| HOT2000 Simulation Results | Space Heating NG Consumption (m ³) | Space Cooling Consumption (kWh) | Annual Furnace Fan Consumption (kWh) |
|----------------------------|--|---------------------------------|--------------------------------------|
| Base Case | 3,331 | 697 | 665 |
| Ceiling Upgrade | 3,126 | 679 | 626 |
| Savings | 205 | 17 | 39 |
| Savings% | 6.2% | 2.5% | 5.9% |

- Annual natural gas savings for space heating is 6.2%.
- Energy savings estimated by the three other jurisdictions listed below (Washington State, Iowa and New Hampshire) estimate savings are between 5 to 25% over their baseline. The large variation is due to differing input assumptions for both the base case and the energy efficient scenario.
- In terms of the baseline consumption, Navigant Consulting estimates that a typical pre-1980's home consumes approximately 25% more natural gas than a typical baseline home used by Enbridge⁴ (2,436 m³), approximately 3,000 m³.
- Applying the 6.2% savings calculated in the table above to the average annual consumption of natural gas cited directly above yields:

² NRCan, http://canmetenergy-canmetenergie.nrcan-rncan.gc.ca/eng/software_tools/hot2000.html

³ Candidate home characteristics are based on previous weatherization study completed by Marbek in 2008 for Union Gas and Navigant Consulting input assumptions.

⁴ Enbridge Gas Customer Profiling Yearly Average End Use, November 23, 2004

$$\text{Natural Gas Savings} = 3,000 \text{ m}^3 \times 6.2\% = 186 \text{ m}^3$$

| Annual Electricity Savings | 105 kWh |
|--|---------|
| <p>Annual electricity savings are derived from two sources:</p> <ol style="list-style-type: none"> 1. Space cooling consumption 2. Furnace fan consumption <p><i>Space cooling consumption:</i></p> <ul style="list-style-type: none"> Assuming that baseline house is equipped with a SEER 10, 2.5 ton⁵ A/C unit and is used 500 hours per year⁶, this implies that: $\text{Base A/C electricity use} = 500 \text{ (cooling hours)} \times [30,000 \text{ (Btu/hr)} / (10 \text{ (SEER)} \times 1,000)] = 1,500 \text{ kWh}$ Applying the 2.5% savings calculated in the table in the previous section to the average annual consumption of electricity cited directly above yields: $\text{Electricity savings (A/C)} = 2.5\% \times 1,500 \text{ kWh/year} = 37.5 \text{ kWh.}$ <p><i>Furnace fan consumption:</i></p> <ul style="list-style-type: none"> Annual furnace fan consumption for a typical Toronto home with a non-continuous mid-efficiency furnace = 1,150 kWh⁷ Applying the 5.9% savings calculated in the table in the previous section to the annual furnace fan electricity consumption cited directly above yields: $\text{Electricity savings (furnace fan)} = 5.9\% \times 1150 \text{ kWh} = 67.85 \text{ kWh}$ <p><i>Total Electricity Savings:</i></p> <ul style="list-style-type: none"> Total electricity savings are the sum of furnace fan savings and air conditioner savings: $\text{Total electricity savings} = 37.5 \text{ kWh} + 67.85 \text{ kWh} = 105.4 \text{ kWh}$ | |
| Annual Water Savings | 0 L |
| N/A | |

Other Input Assumptions

| Effective Useful Life (EUL) | 20 Years |
|---|-------------------------|
| <p>The EUL is reported to be 25 years by the Iowa Utilities Board⁸ and 30 years by Puget Sound Energy⁹. The OPA reports the EUL as 20 years. Navigant Consulting is assuming 20 years.</p> | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$0.7 / ft ² |
| <p>Based on communication with various local vendors, the incremental cost of ceiling insulation from R-10 to R-40 is approximately 70 cents per ft². For the candidate home, the incremental cost is estimated to be \$580 ($\\$0.70 \times 829 \text{ ft}^2 = \\580).</p> | |
| Customer Payback Period (Natural Gas Only) ¹⁰ | 5.9 Years |
| <p>Using a 5-year average commodity cost (avoided cost)¹¹ of \$0.38 / m³ and an average residential distribution cost¹² of \$0.14 / m³, the payback period for natural gas savings is determined to be 5.9</p> | |

⁵ Implying input of 30,000 Btu/hr, Energy Star Savings Calculator,

http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Calc_CAC.xls

⁶ Number of full-load cooling hours provided by <http://energyexperts.org/ac%5Fcalc/> and based on the assumption that Ontario's climate is sufficiently similar to that of the north-eastern U.S.

⁷ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and

Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

⁸ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

⁹ Quantec, Puget Sound Energy Demand-Side Management Resource Assessment

¹⁰ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

years, based on the following:

$$\begin{aligned}\text{Payback Period} &= \text{Incremental cost} / (\text{natural gas savings} \times \text{natural gas cost}) \\ &= \$0.7/\text{ft}^2 \times 829 \text{ ft}^2 / (186 \text{ m}^3/\text{year} \times \$0.52 / \text{m}^3) \\ &= 5.9 \text{ years}\end{aligned}$$

Market Penetration¹³

Medium

Based on the penetration rates in other jurisdictions (25% in Iowa State and 20% in Washington State) and communication with local contractors, Navigant Consulting estimates the penetration in Ontario to be medium.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|--|-------------------------------|-----------------------|--------------------------|
| State of Iowa Utilities Board ¹⁴ | 88 | 25 | 287 | 25% |
| Comments Assuming baseline R-value of ceiling insulation is 19 and upgrade R-value of ceiling insulation is 49. Estimated 4.6% savings are based on 696 therms, which would translate to 32 therms (88 m ³). | | | | |
| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Puget Sound Energy ¹⁵ | 556.3 | 30 | 720 | 20% |
| Comments Assuming baseline R-value of ceiling insulation is 11 and upgrade R-value of ceiling insulation is 38. Estimated 9% savings are based on 6,181 m ³ , which would translate to 556.3 m ³ . | | | | |
| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| New Hampshire Electric Utilities ¹⁶ | 223 | N/A | N/A | N/A |
| Comments New Hampshire Electric Utilities Estimates 25% natural gas savings on ceiling insulation. | | | | |

¹¹ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹² Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹³ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁴ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

¹⁵ Quantec, Puget Sound Energy Demand-Side Management Resource Assessment

¹⁶ ODC, The New Hampshire Electric Utilities' Low-income Retrofit Program Impact Evaluation, Jan 16, 2006

4. Enhanced Furnace (Electronically Commutated Motor) – Existing Residential

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Gas furnace equipped with an electronically commutated motor (ECM)

Base Equipment and Technologies Description

Gas Furnace with a permanent split capacitor (PSC) Motor

| Decision Type | Target Market(s) | End Use |
|---------------|----------------------------|---------------|
| Retrofit | Residential Existing Homes | Space Heating |

Codes, Standards, and Regulations

- Under Ontario's building code, all gas furnaces installed in new residential constructions must meet a minimum condensing efficiency level effective January 1, 2007.¹
- However, effective December 31, 2009, NRCan requires the minimum performance level, or the Annual Fuel Utilization Efficiency (AFUE), for residential gas-fired furnaces with an input rate not exceeding 65.92 kW (225 000 Btu/h) to be 90%².
- Presently, there is no minimum energy performance standard restricting the electricity consumption of furnace fan blowers

² Office of Energy Efficiency, Canada's Energy Efficiency Regulations, Final Bulletin, December 2008.
<http://oee.nrcan.gc.ca/regulations/bulletin/gas-furnaces-dec08.cfm?attr=0>

Resource Savings Table (for 2 different cases)

Continuous Fan Usage

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure ³ (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | -132 | 1,387 | 0 | 960 | 0 |
| 2 | -132 | 1,387 | 0 | 0 | 0 |
| 3 | -132 | 1,387 | 0 | 0 | 0 |
| 4 | -132 | 1,387 | 0 | 0 | 0 |
| 5 | -132 | 1,387 | 0 | 0 | 0 |
| 6 | -132 | 1,387 | 0 | 0 | 0 |
| 7 | -132 | 1,387 | 0 | 0 | 0 |
| 8 | -132 | 1,387 | 0 | 0 | 0 |
| 9 | -132 | 1,387 | 0 | 0 | 0 |
| 10 | -132 | 1,387 | 0 | 0 | 0 |
| 11 | -132 | 1,387 | 0 | 0 | 0 |
| 12 | -132 | 1,387 | 0 | 0 | 0 |
| 13 | -132 | 1,387 | 0 | 0 | 0 |
| 14 | -132 | 1,387 | 0 | 0 | 0 |
| 15 | -132 | 1,387 | 0 | 0 | 0 |
| TOTALS | -1980 | 20,805 | 0 | 960 | 0 |

³ US DOE Energy Star Furnace Calculator, "Assumptions" tab.
http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Calc_Furnaces.xls

Resource Savings Assumptions

| | |
|--|---------------------------|
| Annual Natural Gas Savings | -132 m³ |
| <p>Continuous fan use and non-continuous fan use is estimated to be 26% and 74%, respectively, based on Ontario customer survey results⁴.</p> <p>A study conducted by the Canadian Center for Housing Technologies determined that the annual gas use of a typical existing home with a continuous ECM actually <i>increases</i> by 180 m³ for high efficiency furnaces (AFUE 92)⁵. The increase in natural gas consumption is a result of the reduction of heat added to the home from the decrease in electricity usage by the furnace motor. Using the study's baseline gas usage of 2,769m³ for a high efficiency furnace, this represents an increase of 6.5% over the baseline.</p> <p>Applying the percent savings to Enbridge's baseline natural gas consumption for high-efficiency furnaces⁶ (2,045 m³):</p> <ul style="list-style-type: none"> Natural Gas Savings = 2,045 m³ * (-6.5%) = - 132 m³ | |
| Annual Electricity Savings | 1,387 kWh |
| <p>Based on the Ontario Power Authority's 2009 OPA Measure and Assumptions Lists⁷, the electricity savings for an existing home using an ECM are estimated to be 1,387 kWh/year for continuous furnace fan usage. This represents a saving of 72% over a conventional PSC motor.</p> <p>These results are based on the same CCHT study, which determined that annual electricity savings for an existing home using a gas furnace with a continuous ECM for heating only are 1,387 kWh for high efficiency furnaces (AFUE 92)⁸. Since it is unlikely that the furnace fan is running continuously during the shoulder season, the OPA assumes that during the shoulder season, the same electricity savings from a non-continuous ECM are applicable.</p> | |
| Annual Water Savings | 0 L |
| N/A | |

⁴ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, based on Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

⁵ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

⁶ Enbridge Gas Customer Profiling Yearly Average End Use, November 23, 2004

⁷ Ontario Power Authority, 2009 OPA Measures and Assumptions List (Mass Market), November 2008.

⁸ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

Non-Continuous Fan Usage

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure ⁹ (\$) |
|-----------------|--|----------------------|--------------|---|---|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | -18.4 | 324 | 0 | 960 | 0 |
| 2 | -18.4 | 324 | 0 | 0 | 0 |
| 3 | -18.4 | 324 | 0 | 0 | 0 |
| 4 | -18.4 | 324 | 0 | 0 | 0 |
| 5 | -18.4 | 324 | 0 | 0 | 0 |
| 6 | -18.4 | 324 | 0 | 0 | 0 |
| 7 | -18.4 | 324 | 0 | 0 | 0 |
| 8 | -18.4 | 324 | 0 | 0 | 0 |
| 9 | -18.4 | 324 | 0 | 0 | 0 |
| 10 | -18.4 | 324 | 0 | 0 | 0 |
| 11 | -18.4 | 324 | 0 | 0 | 0 |
| 12 | -18.4 | 324 | 0 | 0 | 0 |
| 13 | -18.4 | 324 | 0 | 0 | 0 |
| 14 | -18.4 | 324 | 0 | 0 | 0 |
| 15 | -18.4 | 324 | 0 | 0 | 0 |
| TOTALS | -276 | 4,860 | 0 | 960 | 0 |

Resource Savings Assumptions

| | |
|--|----------------------------|
| Annual Natural Gas Savings | -18.4 m³ |
| <p>Continuous fan use and non-continuous fan use is estimated to be 26% and 74%, respectively, based on customer survey results¹⁰.</p> <p>A study conducted by the Canadian Center for Housing Technologies determined that the annual gas use of a typical existing home with a non-continuous ECM actually <i>increases</i> by 26 m³ for high efficiency furnaces (AFUE 92)¹¹. The increase in natural gas consumption is a result of the reduction of heat added to the home from the decrease in electricity usage by the furnace motor. Using the study's baseline gas usage of 2,769m³ for a high efficiency furnace, this represents an increase of 0.9 % over the baseline.</p> <p>Applying the percent savings to Enbridge's baseline natural gas consumption for high-efficiency furnaces¹² (2,045 m³):</p> <ul style="list-style-type: none"> Natural Gas Savings = 2,045 m³ * (-0.9%) = - 18.4 m³ | |
| Annual Electricity Savings | 324 kWh |
| <p>Based on the Ontario Power Authority's 2009 OPA Measure and Assumptions List¹³, the electricity savings for a new home using an ECM are estimated to be 324 kWh/year for non-continuous furnace fan usage. This represents a saving of 40% over a conventional PSC motor.</p> <p>These results are based on the same CCHT study, which determined that annual electricity savings for a existing home using a gas furnace with an ECM for heating is 324 kWh for a high efficiency furnace.</p> | |

⁹ US DOE Energy Star Furnace Calculator, "Assumptions" tab.

http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Calc_Furnaces.xls

¹⁰ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, based on Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

¹¹ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

¹² Enbridge Gas Customer Profiling Yearly Average End Use, November 23, 2004

¹³ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008.

| | |
|-----------------------------|------------|
| Annual Water Savings | 0 L |
| N/A | |

Other Input Assumptions

| | |
|---|--|
| Effective Useful Life (EUL) | 15 Years |
| An OPA commissioned study by Seeline Group Inc. suggests a useful life of 15 years. Furthermore, a June 2007 study by GDS Associates, Inc. ¹⁴ for New England State Program Working Group (SPWG) also suggest 15 years. Finally, the Iowa Utilities Board ¹⁵ also uses 15 years as an effective useful life for an ECM. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$960 |
| Based on the average of a survey of prices from HVAC contractors in Ontario ¹⁶ , the incremental cost is estimated to be \$960. Incremental costs were confirmed through communication with additional HVAC contractors. | |
| Customer Payback Period (Natural Gas and Electricity) | Continuous = 14 years Non-Continuous = 42 years |
| <p>Since natural gas usage increases with an ECM, Navigant Consulting has used both natural gas and electricity savings to calculate the customer payback period.</p> <p><i>For Natural Gas Usage:</i></p> <p>Combining a 5-year average commodity cost (avoided cost)¹⁷ of \$0.38 / m³ and an average residential distribution cost¹⁸ of \$0.14 / m³, the total cost of natural gas for residential customers is determined to be \$0.52.</p> <p><i>For Electricity Savings:</i></p> <p>An average commodity and distribution cost of \$0.10 / kWh is assumed for residential customers.</p> <p>The payback period incorporating both natural gas usage and electricity savings is determined to be 14 years for continuous usage and 42 years for non-continuous furnace fan usage, based on the following:</p> <p>Payback Period = Incremental cost / [(natural gas savings x natural gas cost) + (electricity savings x electricity cost)]</p> <p><i>Continuous Fan Usage:</i></p> $= \$960 / [(-132 \text{ m}^3/\text{year} * \$0.52 / \text{m}^3) + (1,387 \text{ kWh/year} * \$0.10 / \text{kWh})]$ $= 14 \text{ years}$ <p><i>Non-Continuous Fan Usage:</i></p> $= \$960 / [(-18.4 \text{ m}^3/\text{year} * \$0.52 / \text{m}^3) + (324 \text{ kWh/year} * \$0.10 / \text{kWh})]$ $= 42 \text{ years}$ | |
| Market Share¹⁹ | Low |

¹⁴ GDS Associates Inc, Measure Life Report: Residential and Commercial/Industrial Lighting and HVAC Measures, Prepared for The New England State Program Working Group (SPWG) For use as an Energy Efficiency Measures/Programs Reference Document for the ISO Forward Capacity Market (FCM), June 2007.

¹⁵ Joint Assessment Study, MidAmerican Energy Company, Appendix C. State of Iowa Utilities Board Docket No. EEP-08-2, 2008, C-131

¹⁶ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, based on Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

¹⁷ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁸ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁹ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

Although the benefits of electronically commutated motors are increasingly being promoted by the industry, the overall market share still remains low in the residential retrofit market, as seen in another jurisdiction (Iowa reports a 5% market penetration for residential homes²⁰). Therefore, Navigant Consulting estimates the market share in Ontario to be low.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/ Market Share |
|--|---|-------------------------------|-----------------------|---------------------------|
| 2009 OPA Measures and Assumptions List ²¹ | -80.1m ³ (continuous) 22.6m ³ (non-continuous) | 15 | \$960 | N/A |
| Comments Assumptions made in the OPA Measures and Assumptions List are the same assumptions that are made in the above tables. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/ Market Share |
| Iowa State Utility Board ²² | n/a | 15 | \$76 | 5% |
| Comments Only electricity savings reported (75% over base equipment). Base equipment is a standard motor on a gas fired furnace. Baseline consumption is reported on an annual basis (e.g. 723 kWh for a single family). | | | | |

²⁰ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

²¹ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008.

²² Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

5. Enhanced Furnace (Electronically Commutated Motor) – New Construction

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Gas furnace equipped with an electronically commutated motor (ECM)

Base Equipment and Technologies Description

Gas Furnace with a permanent split capacitor (PSC) Motor

| Decision Type | Target Market(s) | End Use |
|---------------|----------------------|---------------|
| New | Residential New Home | Space Heating |

Codes, Standards, and Regulations

- Under Ontario's building code, all gas furnaces installed in new residential constructions must meet a minimum condensing efficiency level effective January 1, 2007.¹
- Presently, there is no minimum energy performance standard restricting the electricity consumption of furnace fan blowers.
- However, effective December 31, 2009, NRCan requires the minimum performance level, or the Annual Fuel Utilization Efficiency (AFUE), for residential gas-fired furnaces with an input rate not exceeding 65.92 kW (225 000 Btu/h) to be 90%².

¹ Ministry of Energy, "Heating and Cooling your Home: A Conservation Guide", Reproduced with the permission of Natural Resource Canada, 2004. http://www.energy.gov.on.ca/english/pdf/conservation/heating_and_cooling_your_home.pdf

² Office of Energy Efficiency, Canada's Energy Efficiency Regulations, Final Bulletin, December 2008. <http://oee.nrcan.gc.ca/regulations/bulletin/gas-furnaces-dec08.cfm?attr=0>

Resource Savings Table (for 2 different cases)

Continuous Fan Usage

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure ³ (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | -121 | 1403 | 0 | 960 | 0 |
| 2 | -121 | 1403 | 0 | 0 | 0 |
| 3 | -121 | 1403 | 0 | 0 | 0 |
| 4 | -121 | 1403 | 0 | 0 | 0 |
| 5 | -121 | 1403 | 0 | 0 | 0 |
| 6 | -121 | 1403 | 0 | 0 | 0 |
| 7 | -121 | 1403 | 0 | 0 | 0 |
| 8 | -121 | 1403 | 0 | 0 | 0 |
| 9 | -121 | 1403 | 0 | 0 | 0 |
| 10 | -121 | 1403 | 0 | 0 | 0 |
| 11 | -121 | 1403 | 0 | 0 | 0 |
| 12 | -121 | 1403 | 0 | 0 | 0 |
| 13 | -121 | 1403 | 0 | 0 | 0 |
| 14 | -121 | 1403 | 0 | 0 | 0 |
| 15 | -121 | 1403 | 0 | 0 | 0 |
| TOTALS | -1,815 | 20,805 | 0 | 960 | 0 |

³ US DOE Energy Star Furnace Calculator, "Assumptions" tab.
http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Calc_Furnaces.xls

Resource Savings Assumptions

| | |
|---|---------------------------|
| Annual Natural Gas Savings | -121 m³ |
| <p>Continuous fan use and non-continuous fan use is estimated to be 26% and 74%, respectively, based on Ontario customer survey results⁴.</p> <p>A study conducted by the Canadian Center for Housing Technologies determined that a the annual gas use of a typical new home with a continuous ECM actually <i>increases</i> by 164m³ for high efficiency furnaces (AFUE 92)⁵. The increase in natural gas consumption is a result of the reduction of heat added to the home from the decrease in electricity usage by the furnace motor. Using the study's baseline gas usage of 2,769 m³ for a high efficiency furnace, this represents an increase of 5.9% over the baseline.</p> <p>Applying the percent savings to Enbridge's baseline natural gas consumption for high-efficiency furnaces⁶ (2,045 m³):</p> <ul style="list-style-type: none"> Natural Gas Savings = 2,045 m³ * (-5.9%) = - 121 m³ | |
| Annual Electricity Savings | 1,403 kWh |
| <p>Based on the Ontario Power Authority's 2009 OPA Measure and Assumptions Lists⁷, the electricity savings for a new home using an ECM are estimated to be 1,403 kWh/year for continuous furnace fan usage. This represents a savings of 78% over a conventional PSC motor.</p> <p>These results are based on the same CCHT study, which determined that annual electricity savings for a new home using a gas furnace with an ECM for heating is 1,569 kWh for a high efficiency furnace (AFUE 92)⁸. Since it is unlikely that the furnace fan is running continuously during the shoulder season, the OPA assumes that during the shoulder season, the same electricity savings from a non-continuous ECM are applicable.</p> | |
| Annual Water Savings | 0 L |
| N/A | |

⁴ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, based on Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

⁵ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

⁶ Enbridge Gas Customer Profiling Yearly Average End Use, November 23, 2004

⁷ Ontario Power Authority, 2009 OPA Measures and Assumptions List (Mass Market), November 2008.

⁸ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

Non-Continuous Fan Usage

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure ⁹ (\$) |
|-----------------|--|----------------------|--------------|---|---|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | -18.4 | 207 | 0 | 960 | 0 |
| 2 | -18.4 | 207 | 0 | 0 | 0 |
| 3 | -18.4 | 207 | 0 | 0 | 0 |
| 4 | -18.4 | 207 | 0 | 0 | 0 |
| 5 | -18.4 | 207 | 0 | 0 | 0 |
| 6 | -18.4 | 207 | 0 | 0 | 0 |
| 7 | -18.4 | 207 | 0 | 0 | 0 |
| 8 | -18.4 | 207 | 0 | 0 | 0 |
| 9 | -18.4 | 207 | 0 | 0 | 0 |
| 10 | -18.4 | 207 | 0 | 0 | 0 |
| 11 | -18.4 | 207 | 0 | 0 | 0 |
| 12 | -18.4 | 207 | 0 | 0 | 0 |
| 13 | -18.4 | 207 | 0 | 0 | 0 |
| 14 | -18.4 | 207 | 0 | 0 | 0 |
| 15 | -18.4 | 207 | 0 | 0 | 0 |
| TOTALS | -276 | 3,105 | 0 | 960 | 0 |

Resource Savings Assumptions

| Annual Natural Gas Savings | -18.4 m ³ |
|---|----------------------|
| <p>Continuous fan use and non-continuous fan use is estimated to be 26% and 74%, respectively, based on customer survey results¹⁰.</p> <p>A study conducted by the Canadian Center for Housing Technologies determined that the annual gas use of a typical existing home with a non-continuous ECM actually <i>increases</i> by 26 m³ for high efficiency furnaces (AFUE 92)¹¹. The increase in natural gas consumption is a result of the reduction of heat added to the home from the decrease in electricity usage by the furnace motor. Using the study's baseline gas usage of 2,769 m³ for a high efficiency furnace, this represents an increase of 0.9% over the baseline.</p> <p>Applying the percent savings to Enbridge's baseline natural gas consumption for high-efficiency furnaces¹² (2,045 m³):</p> <ul style="list-style-type: none"> Natural Gas Savings = 2,045 m³ * (-0.9%) = -18.4 m³ | |
| Annual Electricity Savings | 207 kWh |
| <p>Based on the Ontario Power Authority's 2009 OPA Measure and Assumptions List¹³, electricity savings for a new home using an ECM are estimated to be 207 kWh/year for non-continuous furnace fan usage. This represents a savings of 40% over a traditional PSC motor.</p> <p>These results are based on the same CCHT study, which determined that annual electricity savings for a new home using a gas furnace with an ECM for heating is 207 kWh efficiency high efficiency furnace (AFUE 92)¹⁴.</p> | |

⁹ US DOE Energy Star Furnace Calculator, "Assumptions" tab.

http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Calc_Furnaces.xls

¹⁰ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, based on Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

¹¹ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

¹² Enbridge Gas Customer Profiling Yearly Average End Use, November 23, 2004

¹³ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008.

¹⁴ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and

| | |
|-----------------------------|------------|
| Annual Water Savings | 0 L |
| N/A | |

Other Input Assumptions

| | |
|---|--|
| Effective Useful Life (EUL) | 15 Years |
| An OPA commissioned study by Seeline Group Inc. suggests a useful life of 15 years. Furthermore, a June 2007 study by GDS Associates, Inc. ¹⁵ for New England State Program Working Group (SPWG) also suggest 15 years. Finally, the Iowa Utilities Board ¹⁶ also uses 15 years as an effective useful life for an ECM. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$960 |
| Based on the average of a survey of prices from HVAC contractors in Ontario ¹⁷ , the incremental cost is estimated to be \$960. Incremental costs were confirmed through communication with additional HVAC contractors. | |
| Customer Payback Period (Natural Gas and Electricity) | Continuous = 12 years Non-Continuous = 86 years |
| <p>Since natural gas usage increases with an ECM, Navigant Consulting has used both natural gas and electricity savings to calculate the customer payback period.</p> <p><i>For Natural Gas Usage:</i></p> <p>Combining a 5-year average commodity cost (avoided cost)¹⁸ of \$0.38 / m³ and an average residential distribution cost¹⁹ of \$0.14 / m³, the total cost of natural gas for residential customers is determined to be \$0.52.</p> <p><i>For Electricity Savings:</i></p> <p>An average commodity and distribution cost of \$0.10 / kWh is assumed for residential customers.</p> <p>The payback period incorporating both natural gas usage and electricity savings is determined to be 12 years for continuous usage and 86 years for non-continuous furnace fan usage, based on the following:</p> <p>Payback Period = Incremental cost / [(natural gas savings x natural gas cost) + (electricity savings x electricity cost)]</p> <p><i>Continuous Fan Usage:</i></p> $= \$960 / [(-121 \text{ m}^3/\text{year} * \$0.52 / \text{m}^3) + (1,403 \text{ kWh/year} * \$0.10 / \text{kWh})]$ $= 12 \text{ years}$ <p><i>Non-Continuous Fan Usage:</i></p> $= \$960 / [(-18.4 \text{ m}^3/\text{year} * \$0.52 / \text{m}^3) + (207 \text{ kWh/year} * \$0.10 / \text{kWh})]$ $= 86 \text{ years}$ | |
| Market Share²⁰ | Low |

Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

¹⁵ GDS Associates Inc, Measure Life Report: Residential and Commercial/Industrial Lighting and HVAC Measures, Prepared for The New England State Program Working Group (SPWG) For use as an Energy Efficiency Measures/Programs Reference Document for the ISO Forward Capacity Market (FCM), June 2007.

¹⁶ Joint Assessment Study, MidAmerican Energy Company, Appendix C. State of Iowa Utilities Board Docket No. EEP-08-2, 2008, C-131

¹⁷ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, based on Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

¹⁸ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁹ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

Although the benefits of electronically commutated motors are increasingly being promoted by the industry, the overall market share still remains low in the residential retrofit market, as seen in another jurisdiction (Iowa reports a 5% market penetration for residential homes²¹). Therefore, Navigant Consulting estimates the share in Ontario to be low.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/ Market Share |
|---|--|-------------------------------|-----------------------|---------------------------|
| 2009 OPA Measures and Assumptions List ²² | -66.8 m ³ (continuous usage) 30.6 m ³ (non-continuous) | 15 | \$960 | N/A |
| Comments Assumptions made in the OPA Measures and Assumptions List are the same assumptions that are made in the above tables. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/ Market Share |
| Iowa State Utility Board ²³ | n/a | 15 | \$76 | 5% |
| Comments Only electric savings reported (75% over base equipment). Base equipment is a standard motor on a gas fired furnace. Baseline consumption is reported on an annual basis (e.g. 723 kWh for a single family). | | | | |

²⁰ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

²¹ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

²² Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008.

²³ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

6. Energy Star Windows (Low-E)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Energy Star Low-E Windows, argon filled (U=0.26 or R=3.8)

Base Equipment and Technologies Description

Double pane with standard glazing (U=0.49 or R = R=2.0)

| Decision Type | Target Market(s) | End Use |
|---------------|---------------------|---------------|
| Retrofit | Exiting Residential | Space heating |

Codes, Standards, and Regulations

Minimum ENERGY STAR® requirements are based on either a U-value or Energy Rating (ER) for each of the four Canadian zones¹.

| Zone | Maximum U-values and Minimum R-Values | | | Minimum Energy Rating (ER) Values (Maximum U-value 2.00 W/m ² •K) | | | | |
|------|--|---|---|--|--|-------|-------------------------|-------|
| | U-value (W/m ² •K) | U-value (Btu/h•ft. ² •°F) | R-Value (ft. ² •h•°F/Btu) | | Most Windows and All Doors (includes fixed casement style windows) | | Picture Windows Only | |
| | | | | | 1998 | 2004* | 1998 | 2004* |
| A | 2 | 0.35 | 2.9 | or | -16 | 17 | -6 | 27 |
| B | 1.8 | 0.32 | 3.2 | or | -12 | 21 | -2 | 31 |
| C | 1.6 | 0.28 | 3.6 | or | -8 | 25 | 2 | 35 |
| D | 1.4 | 0.25 | 4 | or | -5 | 29 | 5 | 39 |

¹ NRCan, Office of Energy Efficiency, <http://www.oeo.nrcan.gc.ca/energystar/english/consumers/ratings.cfm?text=N&printview=N>

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$/window) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 121 | 117 | 0 | 150 | 0 |
| 2 | 121 | 117 | 0 | 0 | 0 |
| 3 | 121 | 117 | 0 | 0 | 0 |
| 4 | 121 | 117 | 0 | 0 | 0 |
| 5 | 121 | 117 | 0 | 0 | 0 |
| 6 | 121 | 117 | 0 | 0 | 0 |
| 7 | 121 | 117 | 0 | 0 | 0 |
| 8 | 121 | 117 | 0 | 0 | 0 |
| 9 | 121 | 117 | 0 | 0 | 0 |
| 10 | 121 | 117 | 0 | 0 | 0 |
| 11 | 121 | 117 | 0 | 0 | 0 |
| 12 | 121 | 117 | 0 | 0 | 0 |
| 13 | 121 | 117 | 0 | 0 | 0 |
| 14 | 121 | 117 | 0 | 0 | 0 |
| 15 | 121 | 117 | 0 | 0 | 0 |
| 16 | 121 | 117 | 0 | 0 | 0 |
| 17 | 121 | 117 | 0 | 0 | 0 |
| 18 | 121 | 117 | 0 | 0 | 0 |
| 19 | 121 | 117 | 0 | 0 | 0 |
| 20 | 121 | 117 | 0 | 0 | 0 |
| TOTALS | 2,420 | 2,340 | 0 | \$150 | 0 |

Resource Savings Assumptions

| Annual Natural Gas Savings | 121 m ³ |
|---|--------------------|
| <p>Natural gas savings based on REFREN 5.0 modeling using the following assumptions:</p> <ul style="list-style-type: none"> Existing frame 2,000 ft² 2-storey residential home, with a gas furnace, central air conditioner 300 ft² in windows (15% floor area) Toronto, ON weather Baseline windows assumed wood/vinyl double pane, clear (air filled) windows (U=0.49) Energy efficient windows assumes wood/vinyl double pane, low-E, argon filled windows (U=0.26)² <p>Based on the above assumptions, the following results were obtained:</p> <ul style="list-style-type: none"> Baseline heating consumption = 141.3 MMBtu (3,884 m³) of natural gas Energy efficient heating consumption = 134.2 MMBtu (3,689 m³) of natural gas Savings = 3,884 m³ – 3,689 m³ = 195 m³ or 5.0% <p>Applying the percent savings to Enbridge's baseline natural gas consumption for mid-efficiency furnaces³ (2,436 m³):</p> <ul style="list-style-type: none"> Natural Gas Savings = 2,436 m³ * 5.0% = 121 m³ | |
| Annual Electricity Savings | 117 kWh |
| <p>Electric saving from space cooling reduction is based on the same assumptions as above:</p> <ul style="list-style-type: none"> Baseline cooling consumption = 590 kWh/year Energy efficient cooling consumption = 342 kWh/year Savings = 590 kWh – 384 kWh = 206 kWh/year or 35% Assuming a penetration rate of central air conditioners in Ontario of 57%⁴, the average Ontario home is assumed to save 117 kWh/year (206 kWh x 57% = 117 kWh), | |
| Annual Water Savings | 0 L |
| N/A | |

Other Input Assumptions

| Effective Useful Life (EUL) | 20 Years |
|--|--------------|
| <p>The EUL is reported to be 25 years by The New England State Program Working Group (SPWG)⁵, the Iowa Utilities Board⁶ and Efficiency Vermont⁷. NYSERDA⁸ and the OPA⁹ report an EUL of 20 years. Navigant is assuming 20 years.</p> | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$150/window |
| <p>Based on communication with various local vendors, the incremental cost of purchasing a new low-e, argon windows over the traditional regular double pane, is approximately \$100-200 per window, or an average of \$150 per window¹⁰. For the modeled candidate home, 300 ft² of windows is estimated to be approximately 12 windows, which translates to a total incremental cost of \$1,800.</p> | |

² Based on communication with various local window vendors, majority of customers are choosing low-e argon filled windows, with R-value approximately 4.

³ Enbridge Gas Customer Profiling Yearly Average End Use, November 23, 2004

⁴ Natural Resource Canada, Survey of Household Energy Use (SHEU), December 2005

⁵ GDS Associates, Measure Life Report: Residential and Commercial/Industrial Lighting and HVAC Measures prepared for The New England State Program Working Group (SPWG), June 2007

⁶ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

⁷ Vermont Residential Master Technical Reference Manual No.2005-37

⁸ NYSERDA, New York Energy Smart Programs, Deemed Savings Database, August 2008

⁹ Ontario Power Authority. 2009 OPA Measures and Assumptions List. November 2008.

¹⁰ Prices of new windows can vary considerably depending on type and size.

| | |
|--|-----------------|
| Customer Payback Period (Natural Gas Only)¹¹ | 28 Years |
| <p>Using an 5-year average commodity cost (avoided cost)¹² of \$0.38 / m³ and an average residential distribution cost¹³ of \$0.14 / m³, the payback period for natural gas savings is determined to be 28 years, based on the following:</p> <p>Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="padding-left: 40px;">= \$1,800 / (121 m³/year * \$0.52 / m³)</p> <p style="padding-left: 40px;">= 28 years</p> | |
| Market Share¹⁴ | High |
| <p>According to NRCan, in 2003, almost 70% of Ontario residents who replaced their windows opted for either low-e or gas filled windows. Furthermore, based on communications with local contractors and distributors, the majority of customers are replacing their windows with low-e, gas filled windows. Therefore, Navigant Consulting estimates the market share in Ontario to be high.</p> | |

¹¹ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹² 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹³ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁴ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|--|-------------------------------|-----------------------|--------------------------|
| Questar Gas ¹⁵ | 6.23 DTh (22.7 m ³) | 35 | \$201 | N/A |
| Comments Details regarding baseline and new technology are not listed. | | | | |
| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁶ | 3.8 | 25 | 3,868 US\$ | 75% |
| Comments Assuming baseline technology of existing windows (U=0.51, SHGC = 0.67) is being replaced with state code windows (U= 0.35, SHGC= 0.32). Savings reported as 0.2% of baseline consumption of 696 therms, which would translate to 1.39 therms, or 3.8 m ³ . | | | | |
| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| 2009 OPA Measures and Assumptions List ¹⁷ | 319 | 25 | \$500/window | N/A |
| Comments Assuming baseline technology of eight (8) existing windows (single pane with storm windows) being replaced by double pane, low-e argon, wood frame windows. Per window savings also reported as 39.8 m ³ . | | | | |

¹⁵ Nexant, DSM Market Characterization Report, prepared for Questar Gas, August 2006

¹⁶ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

¹⁷ Ontario Power Authority. 2009 OPA Measures and Assumptions List. November 2008.

7. Heat Reflective Panels

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

A saw tooth panel made of clear PVC with a reflective surface placed behind a gas radiator reducing heat lost to poorly insulated exterior walls.

Base Equipment and Technologies Description

Existing housing with gas radiant heat with no reflecting panels.

| Decision Type | Target Market(s) | End Use |
|---------------|---|---------------|
| New | Existing single family residential homes (pre-1980) | Space Heating |

Codes, Standards, and Regulations

No code or standard exists for heat reflective panels.

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|-------------|----------|---|--|
| | Natural Gas | Electricity | Water | | |
| | (m ³) | (kWh) | (L) | | |
| 1 | 143 | 0 | 0 | 229 | 0 |
| 2 | 143 | 0 | 0 | 0 | 0 |
| 3 | 143 | 0 | 0 | 0 | 0 |
| 4 | 143 | 0 | 0 | 0 | 0 |
| 5 | 143 | 0 | 0 | 0 | 0 |
| 6 | 143 | 0 | 0 | 0 | 0 |
| 7 | 143 | 0 | 0 | 0 | 0 |
| 8 | 143 | 0 | 0 | 0 | 0 |
| 9 | 143 | 0 | 0 | 0 | 0 |
| 10 | 143 | 0 | 0 | 0 | 0 |
| 11 | 143 | 0 | 0 | 0 | 0 |
| 12 | 143 | 0 | 0 | 0 | 0 |
| 13 | 143 | 0 | 0 | 0 | 0 |
| 14 | 143 | 0 | 0 | 0 | 0 |
| 15 | 143 | 0 | 0 | 0 | 0 |
| 16 | 143 | 0 | 0 | 0 | 0 |
| 17 | 143 | 0 | 0 | 0 | 0 |
| 18 | 143 | 0 | 0 | 0 | 0 |
| TOTALS | 2,574 | 0 | 0 | 229 | 0 |

Resource Savings Assumptions

| | |
|--|--------------------------|
| Annual Natural Gas Savings | 143 m³ |
| <p>A 2006 Enbridge Gas Distribution Load Research Study¹ reports an average boiler consumption of 3,493 m³ for single family homes. A 2008 heat reflective panel pilot study conducted by Enbridge determined an annual gas savings of 4.1% in a single family environment².</p> <p>Applying this savings to the average annual gas consumption results in an annual gas savings of 143 m³ (3,493 m³ x 4.1%).</p> | |
| Annual Electricity Savings | 0 kWh |
| No electricity savings result from heat reflective panels. | |
| Annual Water Savings | 0 L |
| No water savings result from heat reflective panels. | |

Other Input Assumptions

| | |
|--|------------------|
| Effective Useful Life (EUL) | 18 Years |
| <p>Reflective panels are assumed to have the same effective useful life as a furnace. The US DOE reports an 18 year measure life for gas furnaces, according to a Lawrence Berkeley National Laboratory study³. Furthermore, ACEEE⁴ and State of Iowa⁵ both estimate an effective useful life of furnaces to be 18 years. Puget Sound Energy⁶ and New England State Program Working Group (SPWG)⁷ also suggest 18 years for high efficiency furnaces.</p> | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$229 |
| The manufacturer of heat reflective panels, Novitherm, provides the average price for reflectors in a single family home (typically installed by the homeowner) ⁸ . | |
| Customer Payback Period (Natural Gas Only) | 3.1 Years |
| <p>Using an 5-year average commodity cost (avoided cost)⁹ of \$0.38 / m³ and an average residential distribution cost¹⁰ of \$0.14 / m³, the payback period for natural gas savings is determined to be 3.1 years, based on the following:</p> <p>Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="margin-left: 40px;">= \$229/ (143 m³/year * \$0.52 / m³)</p> <p style="margin-left: 40px;">= 3.1 years</p> | |

¹ Enbridge Gas Distribution. Residential Boiler Consumption Research: Summary.

² Ibid.

³ US DOE Energy Star Program. Lifecycle Cost Estimate for an Energy Star Qualified Residential Furnace. Assumptions Tab. http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Calc_Furnaces.xls

⁴ Powerful Priorities: Updating Energy Efficiency Standards for Residential Furnaces, Commercial Air Conditioners, and Distribution Transformers. ACEEE, September 2004.

⁵ Joint Assessment Study, MidAmerican Energy Company, Appendix C. State of Iowa Utilities Board Docket No. EEP-08-2, 2008, C-131

⁶ Quantec, Comprehensive Demand-Side Management Resource Assessment, Prepared for Puget Sound Energy, May 2007

⁷ GDS Associates, Inc., Measure Life Report: Residential and Commercial/Industrial Lighting and HVAC Measures, Prepared for The New England State Program Working Group (SPWG), For use as an Energy Efficiency Measures/Programs Reference Document for the ISO Forward Capacity Market (FCM), June 2007

⁸ Novitherm Heat Reflectors, Residential - Reduce Heating Costs www.novitherm.com, Cost excludes any additional shipping requirements.

⁹ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁰ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

| | |
|--|------------|
| Market Penetration¹¹ | Low |
| Given the relative novelty of this technology, Navigant Consulting estimates the penetration in Ontario to be low. | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|------------------------|---------------------------------|-------------------------------|-----------------------|--------------------------|
| N/A | N/A | N/A | N/A | N/A |
| Comments N/A | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| N/A | N/A | N/A | N/A | N/A |
| Comments N/A | | | | |

¹¹ Navigant Consulting is defining “Low” as below 5%, “Medium” as between 5-50%, and “High” as above 50%.

8. High Efficiency (Condensing) Furnace - Residential

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

High-efficiency (condensing) furnace with regular PSC motor – AFUE 96

Base Equipment and Technologies Description

Minimum standard gas-fired furnace AFUE 90

| Decision Type | Target Market(s) | End Use |
|---------------|------------------|---------------|
| New, Retrofit | Residential | Space Heating |

Codes, Standards, and Regulations

- Under Ontario's building code, all gas furnaces installed in new residential construction must meet a minimum condensing efficiency level effective January 1, 2007.¹
- However, effective December 31, 2009, NRCan requires the minimum performance level, or the Annual Fuel Utilization Efficiency (AFUE), for residential gas-fired furnaces with an input rate not exceeding 65.92 kW (225 000 Btu/h) to be 90%².

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 129 | 0 | 0 | 4,667 | 2,900 |
| 2 | 129 | 0 | 0 | 0 | 0 |
| 3 | 129 | 0 | 0 | 0 | 0 |
| 4 | 129 | 0 | 0 | 0 | 0 |
| 5 | 129 | 0 | 0 | 0 | 0 |
| 6 | 129 | 0 | 0 | 0 | 0 |
| 7 | 129 | 0 | 0 | 0 | 0 |
| 8 | 129 | 0 | 0 | 0 | 0 |
| 9 | 129 | 0 | 0 | 0 | 0 |
| 10 | 129 | 0 | 0 | 0 | 0 |
| 11 | 129 | 0 | 0 | 0 | 0 |
| 12 | 129 | 0 | 0 | 0 | 0 |
| 13 | 129 | 0 | 0 | 0 | 0 |
| 14 | 129 | 0 | 0 | 0 | 0 |
| 15 | 129 | 0 | 0 | 0 | 0 |
| 16 | 129 | 0 | 0 | 0 | 0 |
| 17 | 129 | 0 | 0 | 0 | 0 |
| 18 | 129 | 0 | 0 | 0 | 0 |
| TOTALS | 2,322 | 0 | 0 | 4,667 | 2,900 |

¹ Ministry of Energy, "Heating and Cooling your Home: A Conservation Guide." Reproduced with the permission of Natural Resource Canada, 2004. http://www.energy.gov.on.ca/english/pdf/conservation/heating_and_cooling_your_home.pdf

² Office of Energy Efficiency, Canada's Energy Efficiency Regulations, Final Bulletin, December 2008. <http://oee.nrcan.gc.ca/regulations/bulletin/gas-furnaces-dec08.cfm?attr=0>

Resource Savings Assumptions

| | |
|---|--------------------------|
| Annual Natural Gas Savings | 129 m³ |
| <ul style="list-style-type: none"> Gas savings associated with upgrading from a mid-efficiency furnace to a high efficiency furnace are based on the following formula: Annual Savings = $1 - \text{Base Technology AFUE} / \text{Efficient Equipment AFUE}$ $= 1 - 90/96$ $= 6.3 \%$ The US DOE reports a 4.9.1% gas savings for an AFUE 96 furnace (based on an AFUE 90 baseline)³. Natural gas savings are based on Enbridge research⁴ indicating that the average consumption for a high-efficiency furnace is 2,045 m³. Using the calculated percent savings (6.3%) multiplied by the base energy consumption (2,045 m³) the annual gas savings are estimated to be 129 m³. | |
| Annual Electricity Savings | 0 kWh |
| Electricity savings resulting from high efficiency furnaces are negligible. | |
| Annual Water Savings | 0 L |
| N/A | |

Other Input Assumptions

| | |
|---|-------------------|
| Effective Useful Life (EUL) | 18 Years |
| ACEEE ⁵ and State of Iowa ⁶ both estimate an effective useful life of 18 years. Puget Sound Energy ⁷ and New England State Program Working Group (SPWG) ⁸ also suggest 18 years for high efficiency furnaces. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$1,767 |
| Average equipment cost were determined based on communication with several Ontario HVAC contractors. The average baseline equipment cost (AFUE 90) was determined to be \$2,900 and the average cost of a 96 AFUE condensing gas furnace was determined to be \$4,667, resulting in an incremental cost of \$1,767. | |
| Payback Period | 26.3 Years |
| Using an 5-year average commodity cost (avoided cost) ⁹ of \$0.38 / m ³ and an average residential distribution cost ¹⁰ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 26.3 years, based on the following: | |

³ US DOE Residential Furnaces and Boilers Technical Support Document Analytical Tools. Life Cycle Cost Results for Non-Weatherized Gas Furnaces. http://www1.eere.energy.gov/buildings/appliance_standards/residential/docs/lcc_nwqf_gt6000hdd.xls

⁴ Based on information provided by Enbridge Gas, based on Decision for the Enbridge 2006 DSM Plan (EB2005-0001).

⁵ Powerful Priorities: Updating Energy Efficiency Standards for Residential Furnaces, Commercial Air Conditioners, and Distribution Transformers. ACEEE, September 2004.

⁶ Joint Assessment Study, MidAmerican Energy Company, Appendix C. State of Iowa Utilities Board Docket No. EEP-08-2, 2008, C-131

⁷ Quantec, Comprehensive Demand-Side Management Resource Assessment, Prepared for Puget Sound Energy, May 2007

⁸ GDS Associates, Inc., Measure Life Report: Residential and Commercial/Industrial Lighting and HVAC Measures, Prepared for The New England State Program Working Group (SPWG), For use as an Energy Efficiency Measures/Programs Reference Document for the ISO Forward Capacity Market (FCM), June 2007

⁹ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁰ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

Payback Period = Incremental cost / (natural gas savings x natural gas cost)
 = \$1,767 / (129 m³/year * \$0.52 / m³)
 = 26.3 years

Market Share¹¹

Low

According to NRCAN, the market penetration of gas fired high efficiency furnaces (AFUE 90+) in single family homes is approximately 27% in Ontario¹². However, based on communications with local contractors and distributors, the market share of AFUE 96 furnaces remains low (niche market), although steadily growing, specifically with new regulations on minimum efficiency levels.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/ Market Share |
|---|--|-------------------------------|-----------------------|---------------------------|
| State of Iowa Utilities Board ¹³ | AFUE 96: 18.8% or 366 m ³ | 18 | US\$305 | N/A |
| Comments The State of Iowa reports a baseline gas furnace as AFUE 78 (state code) using 701 therms/year or 1947.2 m ³ /year. No savings were made available for a baseline efficiency of AFUE 90. | | | | |
| Puget Sound Energy ¹⁴ | AFUE 96: 19% or 324 m ³ | 18 | US\$950 | N/A |
| Comments Puget Sound reports their savings based on a baseline gas furnace of AFUE 78 using 614 therms/year or 1,707 m ³ /year. No savings were made available for a baseline efficiency of AFUE 90. | | | | |

¹¹ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹² NRCAN, Office of Energy Efficiency, Comprehensive Energy Use Database: Table 22: Single detached heating system stock by heating system type, http://oee.nrcan.gc.ca/corporate/statistics/neud/dpa/trends_res_on.cfm, updated September 2008.

¹³ Joint Assessment Study, MidAmerican Energy Company, Appendix C. State of Iowa Utilities Board Docket No. EEP-08-2, 2008, C-131

¹⁴ Quantec, Comprehensive Demand-Side Management Resource Assessment, Prepared for Puget Sound Energy, May 2007
C-42

9. Programmable Thermostat - Residential

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Programmable thermostat.

Base Equipment and Technologies Description

Standard thermostat.

| Decision Type | Target Market(s) | End Use |
|---------------|----------------------------|---------------|
| Retrofit | Residential existing homes | Space Heating |

Codes, Standards, and Regulations

- For a programmable thermostat to receive Energy Star® qualification, it must meet specific criteria such as having at least two different programming periods (for weekday and weekend programming), at least four possible temperature settings and allow for temporary overriding by the user.
- In Canada, applicable CSA standards can be found in CSA C828-99- CAN/CSA Performance Requirements for Thermostats used with Individual Room Electric Space Heating Devices.

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 53 | 54 | 0 | 25 | 0 |
| 2 | 53 | 54 | 0 | 0 | 0 |
| 3 | 53 | 54 | 0 | 0 | 0 |
| 4 | 53 | 54 | 0 | 0 | 0 |
| 5 | 53 | 54 | 0 | 0 | 0 |
| 6 | 53 | 54 | 0 | 0 | 0 |
| 7 | 53 | 54 | 0 | 0 | 0 |
| 8 | 53 | 54 | 0 | 0 | 0 |
| 9 | 53 | 54 | 0 | 0 | 0 |
| 10 | 53 | 54 | 0 | 0 | 0 |
| 11 | 53 | 54 | 0 | 0 | 0 |
| 12 | 53 | 54 | 0 | 0 | 0 |
| 13 | 53 | 54 | 0 | 0 | 0 |
| 14 | 53 | 54 | 0 | 0 | 0 |
| 15 | 53 | 54 | 0 | 0 | 0 |
| TOTALS | 2,190 | 2,730 | 0 | 25 | 0 |

Resource Savings Assumptions

Annual Natural Gas Savings

53 m³

- Two utility studies¹ are used to determine savings resulting from residential programmable thermostats on natural gas consumptions.
 - In the **GasNetworks** study², 4,061 mail-in surveys and bills were analyzed. Results were normalized for temperature and the energy impacts were determined through a multivariate regression analysis. The study found that programmable thermostat saved 6 % of total household annual natural gas use. GasNetworks is proposing 75 ccf (212 m³) natural gas savings based on a Non-Programmable Thermostat annual consumption of 1,253 ccf (3,548 m³) natural gas.
 - In the **Enbridge Billing Analysis**³, 911 customers' natural gas consumption was analyzed in 2005. Enbridge determined an average savings of 159 m³ for a house using 2,878 m³ of natural gas.
- Canadian Centre for Housing Technology (CCHT) also conducted a study in 2005 on programmable thermostat natural gas savings⁴. The study was done in two identical research homes located in Ottawa to allow direct comparison of changes in operating conditions in a home. It reports a 6.5% predicted savings for 18°C night setback.
- Based on these three studies, Navigant Consulting is assuming an average saving at 6% for natural gas consumptions for full temperature set back.

| Studies | Baseline Gas Consumption (m ³) | Gas Savings (m ³) | Gas Savings% |
|--------------------|--|-------------------------------|--------------|
| GasNetworks (2007) | 3,548 | 212 | 6.0% |
| Enbridge (2005) | 2,878 | 159 | 5.5% |
| CCHT (2005) | - | - | 6.5% |
| NCI Average | | | 6.0% |

Taking into account behavioural changes:

- Based on a recent Statistics Canada report⁵, approximately 41% of Ontario households with non-programmable or non-programmed thermostats manually set back their thermostat at night (19% lowered by 3 or more degrees, 21% lowered by 1 or 2 degrees) in the winter season, where as 59% did not lower their thermostat before going to sleep.
- Similar values were found based on a recent evaluation Ontario Power Authority's 2007 Hot and Cool Savings Program conservation program. A household survey determined that of the 59% of Ontario households with non-programmable thermostats who manually set back their thermostat, after installing their new programmable thermostat, 68% stated they continued with the same set back behaviour (no change), while 32% increased their set back temperature (19% by 3 or more degrees, 81% by 1 or 2 degrees)⁶.
- Furthermore, Navigant Consulting also determined from the survey that of the 41% of households who previously did not have a programmable thermostat and did not lower their thermostat at night, 67% of households changed their behaviour by programming their thermostat to lower the

¹ "Resource Savings Values in Selected Residential DSM Prescriptive Programs", Summit Blue Consulting, June 2008.

² RLW Analytics, Validating the impact of programmable thermostats: final report. Prepared for GasNetworks by RLW Analytics. Middletown, CT, January 2007.

³ "Resource Savings Values in Selected Residential DSM Prescriptive Programs", Summit Blue Consulting, June 2008.

⁴ The Effects of Thermostat Setting on Seasonal Energy Consumption at the CCHT Research Facility, Manning, Swinton, Szadkowski, Gusdorf, Ruest, February 14, 2005, <http://irc.nrc-cnrc.gc.ca/pubs/rr/rr191/rr191.pdf>

⁵ Statistics Canada, Household and Environment Survey, 2006

⁶ Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

temperature at night when they sleep (44% by 3 or more degrees, 56% by 1 or 2 degrees).

- Therefore, using Statistics Canada values for typical winter behaviour of non-programmable thermostat households and Navigant Consulting findings for post installation of a programmable thermostat, the following natural gas savings should be attributed for each installed programmable thermostat:

| <i>Savings</i> | <i>Distribution of Households</i> | <i>Natural Gas Savings</i> |
|--|-----------------------------------|----------------------------|
| No change in behaviour or no set back | 47% | 0% |
| Full change in behaviour - 3 + degrees set back | 20% | 6% |
| Partial change in behaviour: 1 -2 degrees set back | 33% | 3% |

Using Enbridge's baseline natural gas consumption of 2,436 m³ for mid-efficiency furnaces, NCI estimates the following natural gas savings from the installation of programmable thermostats:

$$2,436 \text{ m}^3 \times (47\% \times 0\% + 20\% \times 6\% + 33\% \times 3\%) = 53 \text{ m}^3$$

- This represents an overall savings of 2% over the baseline ($53 \text{ m}^3 / 2436 \text{ m}^3 = 2\%$)

Annual Electricity Savings

54 kWh

Heating Season Savings (Furnace fan)

- The following table is based on the CCHT study analysing furnace fan consumption in relation to set back temperatures from programmable thermostats⁷.

| <i>Temp Set Back</i> | <i>Total Winter Furnace Electricity Consumption (kWh)</i> | <i>Seasonal Savings (%)</i> |
|--------------------------------------|---|-----------------------------|
| None (22C) | 2,314 | 0 % |
| 18 C night time set back | 2,295 | 0.8% |
| 18 C daytime and night time set back | 2,270 | 1.9% |

- Using the CCHT study results from a full night-time set back of 4 degrees:
Approximate savings is expected for the winter season⁸ = 2,314 – 2,295 = 19 kWh/year
- Applying the same behaviour changes as presented above (natural gas savings), furnace fan savings during the heating season are estimated to be as follows:
 $47\% \times 0 \text{ kWh} + 20\% \times 19 \text{ kWh} + 33\% \times 9.5 \text{ kWh} = 7 \text{ kWh}$

Cooling Season Savings

- A side-by-side housing study conducted by the CCHT⁹ determined seasonal energy savings for a residential unit from a programmable thermostat as follows:

CAC:**

| <i>Temp Set Back</i> | <i>Total Summer Furnace and CAC Electricity Consumption (kWh)</i> | <i>Seasonal Savings (%)</i> |
|-----------------------|---|-----------------------------|
| None (22C) | 3,099 | 0 |
| 25 C daytime set back | 2,767 | 11 |
| 24 C daytime set back | 2,376 | 23 |

** 12 SEER , 2 ton capacity CAC, 362 cooling degree days (18C)

⁷ The Effects of Thermostat Setting on Seasonal Energy Consumption at the CCHT Research Facility, Manning, Swinton, Szadkowski, Gusdorf, Ruest, February 14, 2005, <http://irc.nrc-cnrc.gc.ca/pubs/rr/rr191/rr191.pdf>

⁸ Although furnace fan consumption is significantly higher than reported by other studies, the change in electricity consumption by using a programmable thermostat is assumed to be appropriate for this analysis.

⁹ The Effects of Thermostat Setting on Seasonal Energy Consumption at the CCHT Research Facility, Manning, Swinton, Szadkowski, Gusdorf, Ruest, February 14, 2005, <http://irc.nrc-cnrc.gc.ca/pubs/rr/rr191/rr191.pdf>

- A BC Hydro study¹⁰ reports savings between 10% and 15% for 4°C set back during night and unoccupied periods, Energy Star Calculator¹¹ reports 6% saving per degree (Fahrenheit) for *cooling season*.
- Assuming that baseline house is equipped with a SEER 10, 2.5 ton A/C unit¹² and is used 500 hours per year¹³, this implies that:

$$\text{Base A/C electricity use} = 500 \text{ (cooling hours)} \times [30,000 \text{ (Btu/hr)} / (10 \text{ (SEER)} \times 1,000)] = 1,500 \text{ kWh}$$

Taking into Account Changes in Behaviour (Cooling Season)

- Based on the same program evaluation survey for the OPA¹⁴, NCI determined that of the households who previously had non-programmable thermostats and did not manually adjust the thermostat to increase when they were away from home, 46% of respondents indicated they changed their behaviour when they installed a programmable thermostat by raising the temperature of their home when they were away (55% by 3 or more degrees, 45% by 1 or 2 degrees).
- Of the households who previously had non-programmable thermostats and manually adjusted their thermostat in the summer when they were away, 32% indicated they have increased their thermostats setting¹⁵, where as 68% of respondents indicated they had no change in temperature settings.
- Therefore, using Statistics Canada values for typical summer behaviour of non-programmable thermostat households and Navigant Consulting findings for post installation of a programmable thermostat, the following electricity savings should be attributed to each installed programmable thermostat:

| <i>Savings</i> | <i>Distribution of Households</i> | <i>Natural Gas Savings</i> |
|--|-----------------------------------|----------------------------|
| No change in behaviour or no set back | 60% | 0% |
| Full change in behaviour - 3 + degrees set back | 17% | 11% |
| Partial change in behaviour: 1 -2 degrees set back | 23% | 5.5% |

- Assuming that baseline house is equipped with a SEER 10, 2.5 ton¹⁶ A/C unit and is used 500 hours per year¹⁷, this implies that:

$$\text{Base A/C electricity use} = 500 \text{ (cooling hours)} \times [30,000 \text{ (Btu/hr)} / (10 \text{ (SEER)} \times 1,000)] = 1,500 \text{ kWh}$$
- NCI estimates the following cooling season electricity savings for each programmable thermostat installed in households with central air conditioning:

$$1,500 \text{ kWh} \times (60\% \times 0\% + 17\% \times 11\% + 23\% \times 5.5\%) = 47 \text{ kWh}$$
- However, assuming a penetration rate of central air conditioners in Ontario = 57%¹⁸, NCI estimates that the average home in Ontario will save the following in electricity during the cooling savings:

$$57\% \times 47 \text{ kWh} = 26.8 \text{ kWh}$$

¹⁰ Marbek Resource Consultants, The Sheltair Group Inc., BC Hydro BC Hydro Conservation Potential Review 2002, Residential Sector Report (Base Year: Fiscal 2000/01) (Revision 1) Submitted to: BC Hydro, June 2003

¹¹ US EPA (EPA Energy Star® Simple Savings Calculator – Programmable Thermostat),

http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/CalculatorProgrammableThermostat.xls

¹² Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, referenced from: Heating, Refrigeration and Air Conditioning Institute of Canada (HRAI), 2006 Cool Savings Rebate Program, Prepared for the Ontario Power Authority, April 2007.

¹³ US EPA (EPA Energy Star® Simple Savings Calculator – Programmable Thermostat),

http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/CalculatorProgrammableThermostat.xls

¹⁴ Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

¹⁵ Although the survey results did not indicate the change in degree-value in temperature for summer behaviour, Navigant Consulting is assuming it is the same as the winter change in behaviour (e.g., 19% by 3 or more degrees, 81% by 1-2 degrees).

¹⁶ Implying input of 30,000 Btu/hr, Energy Star Savings Calculator,

http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Calc_CAC.xls

¹⁷ Number of full-load cooling hours provided by <http://energyexperts.org/ac%5Fcalc/> and based on the assumption that Ontario's climate is sufficiently similar to that of the north-eastern U.S.

¹⁸ Natural Resource Canada, Survey of Household Energy Use (SHEU), December 2005

- Total electricity savings for both heating (furnace fan) and cooling savings for an average Ontario home are estimated to be 54 kWh (7 kWh + 47 kWh = 54 kWh).

Annual Water Savings

0 L

N/A

Other Input Assumptions

Effective Useful Life (EUL)

15 Years

Navigant Consulting is estimating 15 years as the effective useful life based on the average lifetime of programmable thermostat from Energy Star ® website.

Base & Incremental Conservation Measure Equipment and O&M Costs

\$ 25

Average incremental cost of programmable thermostats determined to be \$25 based on average cost of non-programmable and programmable thermostats from Home Depot and Canadian Tire website in 2008.

Customer Payback Period (Natural Gas Only)¹⁹

0.9 Years

Using an 5-year average commodity cost (avoided cost)²⁰ of \$0.38 / m³ and an average residential distribution cost²¹ of \$0.14 / m³, the payback period for natural gas savings is determined to be 0.9 years, based on the following:

$$\begin{aligned} \text{Payback Period} &= \text{Incremental cost} / (\text{natural gas savings} \times \text{natural gas cost}) \\ &= \$25 / (53 \text{ m}^3/\text{year} \times \$0.52 / \text{m}^3) \\ &= 0.9 \text{ years} \end{aligned}$$

Market Penetration

65%

Due to the number of conservation programs in Ontario currently offering programmable thermostats and based on previous research conducted for the OPA²², Navigant Consulting estimates the penetration of programmable thermostats amongst single family residents in Ontario to be 65%.

¹⁹ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

²⁰ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

²¹ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

²² Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| State of Iowa Utilities Board ²³ | 276 | 15 | \$25 | 46% (single family) |
| Comments Measure provides savings of 11.5% over 2,399 m ³ required for space heating with base equipment. Behavioural adjustments were not included in results. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Ontario Power Authority ²⁴ | 182 | 15 | \$140 | N/A |
| Comments Based on gas savings from Canadian Centre for Housing Technology study for an 80% AFUE gas furnace using standard PCS motor and furnace size of 67,500 BTU/hr, using 4761 heating degree hours. Behavioural adjustments were not included in results. | | | | |

²³ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

²⁴ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008

10. Wall Insulation (R-19)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Main floor wall insulation R-19

Base Equipment and Technologies Description

Main floor wall insulation R-8

| Decision Type | Target Market(s) | End Use |
|---------------|---------------------------------|---------------|
| Retrofit | Existing Residential (Pre-1980) | Space Heating |

Codes, Standards, and Regulations

The minimum R value required by Ontario Building Code¹ for walls other than the foundation wall is 19.

¹ Ontario Regulations 350/06, 2006 Building Code

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$/ft ²) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 921 | 415 | 0 | 2.5 | 0 |
| 2 | 921 | 415 | 0 | 0 | 0 |
| 3 | 921 | 415 | 0 | 0 | 0 |
| 4 | 921 | 415 | 0 | 0 | 0 |
| 5 | 921 | 415 | 0 | 0 | 0 |
| 6 | 921 | 415 | 0 | 0 | 0 |
| 7 | 921 | 415 | 0 | 0 | 0 |
| 8 | 921 | 415 | 0 | 0 | 0 |
| 9 | 921 | 415 | 0 | 0 | 0 |
| 10 | 921 | 415 | 0 | 0 | 0 |
| 11 | 921 | 415 | 0 | 0 | 0 |
| 12 | 921 | 415 | 0 | 0 | 0 |
| 13 | 921 | 415 | 0 | 0 | 0 |
| 14 | 921 | 415 | 0 | 0 | 0 |
| 15 | 921 | 415 | 0 | 0 | 0 |
| 16 | 921 | 415 | 0 | 0 | 0 |
| 17 | 921 | 415 | 0 | 0 | 0 |
| 18 | 921 | 415 | 0 | 0 | 0 |
| 19 | 921 | 415 | 0 | 0 | 0 |
| 20 | 921 | 415 | 0 | 0 | 0 |
| 21 | 921 | 415 | 0 | 0 | 0 |
| 22 | 921 | 415 | 0 | 0 | 0 |
| 23 | 921 | 415 | 0 | 0 | 0 |
| 24 | 921 | 415 | 0 | 0 | 0 |
| 25 | 921 | 415 | 0 | 0 | 0 |
| 26 | 921 | 415 | 0 | 0 | 0 |
| 27 | 921 | 415 | 0 | 0 | 0 |
| 28 | 921 | 415 | 0 | 0 | 0 |
| 29 | 921 | 415 | 0 | 0 | 0 |
| 30 | 921 | 415 | 0 | 0 | 0 |
| TOTALS | 27,630 | 12,450 | 0 | 2.5 | 0 |

Resource Savings Assumptions

| Annual Natural Gas Savings | 921 m ³ |
|--|--------------------|
| <ul style="list-style-type: none"> • Navigant Consulting used HOT2000² to model energy savings resulting from the energy efficient upgrade. The following input assumptions were based on a candidate house for a typical pre-1980 home³. | |

² NRCAN, http://canmetenergy-canmetenergie.nrcan-rncan.gc.ca/eng/software_tools/hot2000.html

³ Candidate home characteristics are based on previous weatherization study completed by Marbek in 2008 for Union Gas and Navigant Consulting input assumptions.

| House Characteristics using HOT2000 | |
|---|--|
| Location | Toronto, ON |
| Storeys | 2 |
| Above Grade Wall Insulation | R-Value = 3.42 |
| Below Grade Wall Insulation | R-Value = 1.13 |
| Attic Insulation | R-Value = 12.90 |
| Foundation Floor Insulation | R-Value = 2.68 |
| Air Leakage (ACH) | 8.0 |
| Number of Windows | 8 on the main floor, 4 in the basement |
| Ceiling Area (ft ²) | 829 |
| Main Level Wall Area (ft ²) | 944 |
| Living Space Area (ft ²) | 1,658 |
| Basement Wall Area (ft ²) | 827 |
| Basement Floor Area (ft ²) | 829 |
| Base Loads Use | Defaults |
| Furnace Efficiency (AFUE) | 80 |
| Furnace Capacity (Btu/hr) | 58,006.4 (Calculated) |
| Fans Mode | Auto |
| A/C Efficiency (SEER) | 10 |
| A/C Capacity (Btu/hr) | 13000 [†] |

† The current version of HOT2000 has limitation on A/C capacities under specified conditions. 13000 Btu/hr is the maximum value it allows.

- Based on the above assumptions, the following results are obtained:

| HOT2000 Simulation Results | Space Heating NG Consumption (m ³) | Space Cooling Consumption (kWh) | Annual Furnace Fan Consumption (kWh) |
|----------------------------|--|---------------------------------|--------------------------------------|
| Base Case | 3,331 | 697 | 665 |
| Main Floor Wall Upgrade | 2,307 | 652 | 481 |
| Savings | 1,024 | 44 | 184 |
| Savings% | 30.7% | 6.4% | 27.7% |

- Annual natural gas savings for space heating is 30.7%.
- Energy savings estimated by the three other jurisdictions listed below (Washington State, Iowa and New Hampshire) are between 10 to 15% over their baseline. The variation is due to differing input assumptions for both the base case and the energy efficient scenarios.
- In terms of the baseline consumption, Navigant Consulting estimates that a typical pre-1980's home consumes approximately 25% more natural gas than a typical baseline home used by Enbridge⁴ (2,436 m³), approximately 3,000 m³.
- Applying the 30.7 % percent savings calculated in the table above to the average annual consumption of natural gas cited directly above yields:

$$\text{Natural Gas Savings} = 3,000 \text{ m}^3 \times 30.7 \% = 921 \text{ m}^3$$

| | |
|-----------------------------------|----------------|
| Annual Electricity Savings | 415 kWh |
|-----------------------------------|----------------|

Annual electricity savings are derived from two sources:

- Space cooling consumption
- Furnace fan consumption

⁴ Enbridge Gas Customer Profiling Yearly Average End Use, November 23, 2004

Space cooling consumption:

- Assuming that baseline house is equipped with a SEER 10, 2.5 ton⁵ A/C unit and is used 500 hours per year⁶, this implies that:

$$\text{Base A/C electricity use} = 500 \text{ (cooling hours)} \times [30,000 \text{ (Btu/hr)} / (10 \text{ (SEER)} \times 1,000)] = 1,500 \text{ kWh}$$

- Applying the 6.4% savings calculated in the table in the previous section to the average annual consumption of electricity cited directly above yields:

$$\text{Electricity savings (A/C)} = 6.4 \% \times 1,500 \text{ kWh/year} = 96 \text{ kWh.}$$

Furnace fan consumption:

- Annual furnace fan consumption for a typical Toronto home with a non-continuous mid-efficiency furnace = 1,150 kWh⁷
- Applying the 27.7% savings calculated in the table in the previous section to the annual furnace fan electricity consumption cited directly above yields:

$$\text{Electricity savings (furnace fan)} = 27.7 \% \times 1150 \text{ kWh} = 318.55 \text{ kWh}$$

Total Electricity Savings:

- Total electricity savings are the sum of furnace fan savings and air conditioner savings:

$$\text{Total electricity savings} = 96 \text{ kWh} + 318.55 \text{ kWh} = 414.55 \text{ kWh}$$

Annual Water Savings

0 L

N/A

⁵ Implied input of 30,000 Btu/hr, Energy Star Savings Calculator, http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Calc_CAC.xls

⁶ Number of full-load cooling hours provided by <http://energyexperts.org/ac%5Fcalc/> and based on the assumption that Ontario's climate is sufficiently similar to that of the north-eastern U.S.

⁷ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

Other Input Assumptions

| | |
|---|-------------------------------|
| Effective Useful Life (EUL) | 30 Years |
| The EUL is reported to be 25 years by the Iowa Utilities Board ⁸ and 30 years by Puget Sound Energy ⁹ . The OPA reports the EUL to be 30 years, so Navigant Consulting estimates an EUL of 30 years. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$2.5 / ft² |
| Based on communication with various local vendors, the incremental cost of wall insulation from R=8 to R=19 is approximately \$2.5 per ft ² , which includes only the insulation material and labour but not the costs of wall removal and reconstruction required for installation. For the candidate home, the incremental cost is estimated to be \$2,360 (\$2.50 x 944 ft ² / floor = \$2,360). | |
| Customer Payback Period (Natural Gas Only)¹⁰ | 4.9 Years |
| Using a 5-year average commodity cost (avoided cost) ¹¹ of \$0.38 / m ³ and an average residential distribution cost ¹² of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 4.9 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$2.5/ft ² x 944 ft ² / (921 m ³ /year * \$0.52 / m ³) = 4.9 years | |
| Market Penetration¹³ | High |
| Based on penetration rates of other jurisdictions (63% in Iowa State and 85% in Washington State) and communication with local contractors, Navigant Consulting estimates the penetration in Ontario is high. | |

⁸ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

⁹ Quantec, Puget Sound Energy Demand-Side Management Resource Assessment

¹⁰ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹¹ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹² Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹³ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|--|-------------------------------|-----------------------|--------------------------|
| State of Iowa Utilities Board ¹⁴ | 211.7 | 25 | 1,933 | 63% |
| Comments Assuming baseline R-value of wall insulation is 8 and upgrade R-value of wall insulation is 11. Estimated 11.1% savings are based on 696 therms, which would translate to 77.3 therms (211.7 m ³). | | | | |
| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Puget Sound Energy ¹⁵ | 618 | 30 | 1,064 | 85% |
| Comments Assuming baseline R-value of wall insulation is 0 and upgrade R-value of wall insulation is 13. Estimated 10% savings are based on 6,181 m ³ , which would translate to 618 m ³ . | | | | |
| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| New Hampshire Electric Utilities ¹⁶ | 625 | N/A | N/A | N/A |
| Comments New Hampshire Electric Utilities Estimates 15% natural gas savings on wall insulation. | | | | |

¹⁴ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

¹⁵ Quantec, Comprehensive Demand-Side Management Resource Assessment, Prepared for Puget Sound Energy, May 2007

¹⁶ ODC, The New Hampshire Electric Utilities' Low-income Retrofit Program Impact Evaluation, Jan 16, 2006

RESIDENTIAL WATER HEATING

11. Faucet Aerator (Residential Bathroom)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Faucet Aerator (Bathroom) (1.5 GPM)

Base Equipment and Technologies Description

Average existing stock (2.2 GPM)¹

| Decision Type | Target Market(s) | End Use |
|---------------|------------------------|---------------|
| Retrofit | Residential (existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)² requires bathroom and kitchen faucets to have a maximum flow of 2.2 GPM (8.35 L/min).

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|---------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 6 | 0 | 2,004 | 2 | 0 |
| 2 | 6 | 0 | 2,004 | 0 | 0 |
| 3 | 6 | 0 | 2,004 | 0 | 0 |
| 4 | 6 | 0 | 2,004 | 0 | 0 |
| 5 | 6 | 0 | 2,004 | 0 | 0 |
| 6 | 6 | 0 | 2,004 | 0 | 0 |
| 7 | 6 | 0 | 2,004 | 0 | 0 |
| 8 | 6 | 0 | 2,004 | 0 | 0 |
| 9 | 6 | 0 | 2,004 | 0 | 0 |
| 10 | 6 | 0 | 2,004 | 0 | 0 |
| TOTALS | 60 | 0 | 20,040 | 2 | 0 |

¹ From on-site audit data. Resource Management Strategies, Inc. *Regional Municipality of York Water Efficiency Master Plan*

Update, 2007. Cited in: Summit Blue, *Resource Savings Values in Selected Residential DSM Prescriptive Programs*, June 2008.

² Ontario Regulations 350/06, 2006 Building Code

Resource Savings Assumptions

| Annual Natural Gas Savings | 6 m ³ |
|--|------------------|
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> • Average faucet water temperature: 30 °C (86 °F)³ • Average water inlet temperature: 9.33 °C (48.8 °F)⁴ • Average water heater recovery efficiency: 0.76⁵ <p>Annual gas savings calculated as follows:</p> $Savings = W * 8.33 * (T_{out} - T_{in}) * \frac{1}{EF} * 10^{-6} * 27.8$ <p>Where:</p> <p>W = Water savings (gallons) 8.33 = Energy content of water (Btu/gallon/°F) T_{out} = Faucet water temperature (°F) T_{in} = Water inlet temperature (°F) EF = Water heater recovery efficiency 10⁻⁶ = Factor to convert Btu to MMBtu 27.8 = Factor to convert MMBtu to m³</p> <p>Gas savings were determined to be 22% over base case:</p> $Percent\ Savings = \frac{(G_{base} - G_{new})}{G_{base}}$ <p>Where:</p> <p>G_{eff} = Annual natural gas use with efficient equipment, 27 m³ G_{base} = Annual natural gas use with base equipment, 21 m³</p> | |
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 2,004 L |
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> • Average household size: 3.1 persons⁶ • Baseline faucet use (all faucets) per capita per day: 53 litres (14 gallons)⁷ • Bathroom faucet use as a percentage of total faucet use: 15%⁸ • Point estimate of quantity of water that goes straight down the drain: 70%⁹ | |

³ Average of findings in two studies, adjusted for Toronto water inlet temperature. Mayer, P. W. et al, *Residential Indoor Water Conservation Study: Evaluation of High Efficiency Indoor Plumbing Fixture Retrofits in Single-Family Homes in East Bay Municipal Utility District Service Area*, 2003 and Skeel, T. and Hill, S. *Evaluation of Savings from Seattle's "Home Water Saver" Apartment/Condominium Program*, 1994. Both cited in: Summit Blue (2008).

⁴ Cited in the following as personal communication with City of Toronto Works Dept. VEIC, *Comments on Navigant's Draft Gas Measure Characterizations*, March 2009.

⁵ Assumption used by Energy Center of Wisconsin, citing GAMA, Pigg, Scott. *Water Heater Savings Calculator* 2003. www.doa.state.wi.us/docs_view2.asp?docid=2249

⁶ Summit Blue (2008).

⁷ Ibid.

⁸ DeOreo, W. and P. Mayer, *The End Uses of Hot Water in Single Family Homes from Flow Trace Analysis*, 1999 cited in Summit Blue (2008).

⁹ Summit Blue (2008).

Annual water savings calculated as follows:

$$Savings = Fu * Ppl * 365 * Ba * \left(\frac{Fl_{base} - Fl_{eff}}{Fl_{base}} \right) * Dr$$

Where:

Fu = Faucet use per capita (gallons)
Ppl = Number of people per household
365 = Days per year
Dr = Percentage of water that goes straight down the drain
Ba = Individual bathroom faucet use as a percentage of total faucet use
Fl_{base} = Flow rate of base equipment (GPM)
Fl_{eff} = Flow rate of efficient equipment (GPM)

Water savings was determined to be 22% over base case:

$$Percent Savings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water use with efficient equipment: 6,993 litres (1,847 gallons)
W_{base} = Annual water use with base equipment: 8,997 litres (2,376 gallons)

Other Input Assumptions

| | |
|--|------------------|
| Effective Useful Life (EUL) | 10 Years |
| The U.S. DOE assumes a 10 year life for faucet aerators ¹⁰ . | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 2 \$ |
| Average equipment cost based on communication with local hardware stores. This does not include installation costs. | |
| Customer Payback Period (Natural Gas Only)¹¹ | 0.6 Years |
| Using a 5-year average commodity cost (avoided cost) ¹² of \$0.38 / m ³ and an average residential distribution cost ¹³ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 0.6 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$2/ (6 m ³ /year * \$0.52 / m ³) = 0.4 years | |

¹⁰ U.S. Department of Energy, Federal Energy Management Program, *FEMP Designated Product: Lavatory Faucets*
http://www1.eere.energy.gov/femp/procurement/eep_faucets.html

¹¹ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹² 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹³ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

| | |
|--|------------|
| Market Penetration | 90% |
| Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of faucet aerators (bathroom and kitchen) across all sectors to be 90% ¹⁴ . | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy ¹⁵ | 8 | 5 | N/A | 45% |
| Comments For a switch from a 2.5 GPM to a 1.8 GPM aerator. Measure saves 1% of 759 m ³ required for water heating. Note that no distinction is made, in this study, between kitchen and bathroom faucet use. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁶ | 32 | 9 | 20 US\$ | 90% |
| Comments For a switch from a 3.0 GPM to a 1.5 GPM aerator. Measure saves 6.2% of 514 m ³ required for water heating. Note that no distinction is made, in this study, between kitchen and bathroom faucet use. Note also that the flow rate reduction for this jurisdiction is more than twice that of the measure addressed by this substantiation sheet. | | | | |

¹⁴ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

¹⁵ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁶ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

12. Faucet Aerator (Residential Kitchen)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Faucet Aerator (kitchen) (1.5 GPM)

Base Equipment and Technologies Description

Average existing stock (2.5 GPM)¹

| Decision Type | Target Market(s) | End Use |
|---------------|------------------------|---------------|
| Retrofit | Residential (existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)² requires bathroom and kitchen faucets to have a maximum flow of 2.2 GPM (8.35 L/min).

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|---------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 23 | 0 | 7,797 | 2 | 0 |
| 2 | 23 | 0 | 7,797 | 0 | 0 |
| 3 | 23 | 0 | 7,797 | 0 | 0 |
| 4 | 23 | 0 | 7,797 | 0 | 0 |
| 5 | 23 | 0 | 7,797 | 0 | 0 |
| 6 | 23 | 0 | 7,797 | 0 | 0 |
| 7 | 23 | 0 | 7,797 | 0 | 0 |
| 8 | 23 | 0 | 7,797 | 0 | 0 |
| 9 | 23 | 0 | 7,797 | 0 | 0 |
| 10 | 23 | 0 | 7,797 | 0 | 0 |
| TOTALS | 230 | 0 | 77,970 | 2 | 0 |

¹ From on-site audit data. Resource Management Strategies, Inc. *Regional Municipality of York Water Efficiency Master Plan Update*, 2007. Cited in: Summit Blue, *Resource Savings Values in Selected Residential DSM Prescriptive Programs*, June 2008.

² Ontario Regulations 350/06, 2006 Building Code

Resource Savings Assumptions

| Annual Natural Gas Savings | 23 m ³ |
|---|-------------------|
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> • Average faucet water temperature: 30 °C (86 °F)³ • Average water inlet temperature: 9.33 °C (48.8 °F)⁴ • Average water heater energy factor: 0.76⁵ <p>Annual gas savings calculated as follows:</p> $Savings = W * 8.33 * (T_{out} - T_{in}) * \frac{1}{EF} * 10^{-6} * 27.8$ <p>Where:</p> <p>W = Water savings (gallons) 8.33 = Energy content of water (Btu/gallon/°F) T_{out} = Faucet water temperature (°F) T_{in} = Water inlet temperature (°F) EF = Water heater recovery efficiency 10⁻⁶ = Factor to convert Btu to MMBtu 27.8 = Factor to convert MMBtu to m³</p> <p>Gas savings were determined to be 20% over base case:</p> $Percent\ Savings = \frac{(G_{base} - G_{new})}{G_{base}}$ <p>Where:</p> <p>G_{eff} = Annual natural gas use with efficient equipment, 94 m³ G_{base} = Annual natural gas use with base equipment, 117 m³</p> | |
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 7,797 L |
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> • Average household size: 3.1 persons⁶ • Baseline faucet use (all faucets) per capita per day: 53 litres (14 gallons)⁷ • Kitchen faucet use as a percentage of total faucet use: 65%⁸ • Point estimate of quantity of water that goes straight down the drain: 50%⁹ | |

³ Average of findings in two studies, adjusted for Toronto inlet temperature. Mayer, P. W. et al, *Residential Indoor Water Conservation Study: Evaluation of High Efficiency Indoor Plumbing Fixture Retrofits in Single-Family Homes in East Bay Municipal Utility District Service Area*, 2003 and Skeel, T. and Hill, S. *Evaluation of Savings from Seattle's "Home Water Saver" Apartment/Condominium Program*, 1994. Both cited in: Summit Blue (2008).

⁴ Cited in the following as personal communication with City of Toronto Works Dept.
 VEIC, *Comments on Navigant's Draft Gas Measure Characterizations*, March 2009

⁵ Assumption used by Energy Center Wisconsin, citing GAMA,
 Pigg, Scott. *Water Heating Savings Calculator*, 2003. www.doa.state.wi.us/docs_view2.asp?docid=2249

⁶ Summit Blue (2008).

⁷ Ibid.

⁸ DeOreo, W. and P. Mayer, *The End Uses of Hot Water in Single Family Homes from Flow Trace Analysis*, 1999 cited in Summit Blue (2008).

⁹ Summit Blue (2008).

Annual water savings calculated as follows:

$$Savings = Fu * Ppl * 365 * Ba * \left(\frac{Fl_{base} - Fl_{eff}}{Fl_{base}} \right) * Dr$$

Where:

Fu = Faucet use per capita (gallons)
Ppl = Number of people per household
365 = Days per year
Dr = Percentage of water that goes straight down the drain
Ki = Kitchen faucet use as a percentage of total faucet use
Fl_{base} = Flow rate of base equipment (GPM)
Fl_{eff} = Flow rate of efficient equipment (GPM)

Water savings was determined to be 20% over base case:

$$Percent Savings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water use with efficient equipment: 38,986 litres (10,297 gallons)
W_{base} = Annual water use with base equipment: 31,188 litres (8,237 gallons)

Other Input Assumptions

| | |
|--|-------------------|
| Effective Useful Life (EUL) | 10 Years |
| The U.S. DOE assumes a 10 year life for faucet aerators ¹⁰ . | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 2 \$ |
| Average equipment cost based on communication with local hardware stores. This does not include installation costs. | |
| Customer Payback Period (Natural Gas Only)¹¹ | 0.17 Years |
| Using a 5-year average commodity cost (avoided cost) ¹² of \$0.38 / m ³ and an average residential distribution cost ¹³ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 0.17 years, based on the following: | |
| Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$2/ (23 m ³ /year * \$0.52 / m ³) = 0.17 years | |

¹⁰ U.S. Department of Energy, Federal Energy Management Program, *FEMP Designated Product: Lavatory Faucets*
http://www1.eere.energy.gov/femp/procurement/eep_faucets.html

¹¹ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹² 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹³ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

| | |
|--|------------|
| Market Penetration | 90% |
| Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of faucet aerators (bathroom and kitchen) across all sectors to be 90% ¹⁴ . | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy ¹⁵ | 8 | 5 | N/A | 45% |
| Comments For a switch from a 2.5 GPM to a 1.8 GPM aerator. Measure saves 1% of 759 m ³ required for water heating. Note that no distinction is made, in this study, between kitchen and bathroom faucet use. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁶ | 32 | 9 | 20 US\$ | 90% |
| Comments For a switch from a 3.0 GPM to a 1.5 GPM aerator. Measure saves 6.2% of 514 m ³ required for water heating. Note that no distinction is made, in this study, between kitchen and bathroom faucet use. Note also that the flow rate reduction for this jurisdiction is more than twice that of the measure addressed by this substantiation sheet. | | | | |

¹⁴ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

¹⁵ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁶ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

13. Low-Flow Showerhead (1.5 GPM, Residential, UG ESK, per Household)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Low-flow Showerhead (1.5 GPM) – distributed to participants under Union Gas' ESK program.

Base Equipment and Technologies Description

Average existing stock (2.2 GPM)¹.

| Decision Type | Target Market(s) | End Use |
|---------------|------------------------|---------------|
| Retrofit | Residential (Existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)² requires shower heads to have a maximum flow of 2.5 GPM (9.5 L/min).

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|---------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 46 | 0 | 6,334 | 6 | 0 |
| 2 | 46 | 0 | 6,334 | 0 | 0 |
| 3 | 46 | 0 | 6,334 | 0 | 0 |
| 4 | 46 | 0 | 6,334 | 0 | 0 |
| 5 | 46 | 0 | 6,334 | 0 | 0 |
| 6 | 46 | 0 | 6,334 | 0 | 0 |
| 7 | 46 | 0 | 6,334 | 0 | 0 |
| 8 | 46 | 0 | 6,334 | 0 | 0 |
| 9 | 46 | 0 | 6,334 | 0 | 0 |
| 10 | 46 | 0 | 6,334 | 0 | 0 |
| TOTALS | 460 | 0 | 63,340 | 6 | 0 |

Resource Savings Assumptions

| Annual Natural Gas Savings | 46 m ³ |
|--|-------------------|
| Enbridge Gas commissioned a study by the SAS Institute (Canada) ³ to estimate natural gas savings for low-flow showerheads using a sample of 69 households in Enbridge territory between August 3, 2007 to December 31, 2008. Replacement low-flow showerheads were installed between August 13, 2008 and October 18, 2008. | |

¹ Shower-heads distributed under Union Gas's ESK program are installed by homeowners rather than Union contractors. No observation is made of the base equipment's GPM. It is therefore assumed to be the full-on flow rate corresponding to the as-used flow from York Region monitoring study calculated using the equation cited below.

Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007. Cited by: Summit Blue, *Resource Savings Values in Selected Residential DSM Prescriptive Programs*, June 2008.

² Ontario Regulations 350/06, 2006 Building Code

³ Rothman, Lorne, SAS® Analysis for Enbridge Gas Distribution Incorporated: Estimating the impact of Low Flow Showerhead Installation, March 16, 2009

The study used two classes of statistical method for estimating savings (1) Paired T-tests and (2) Longitudinal Mixed models.

1. Three iterations of the paired t-test method were estimated and of these, the report recommends the one which makes use of the entire data-set. This model yielded savings estimates of an average of 0.24 m³/day, for an extrapolated annual savings of 89 m³.
2. Two longitudinal mixed models were also estimated, one relatively simple linear model controlling for a variety of household factors, the other still linear, but with more parameters to be estimated (all additional parameters being the products of two previously estimated parameters) in order to study interaction effects. This model yielded savings estimates of an average of 0.18 m³/day for pre-existing showerhead flow rates of 2.0 to 2.5 GPM and 0.32 m³/day for pre-existing showerhead flow rates greater than 2.5 GPM. Extrapolation of these results for annual savings is approximately 66 m³ and 116 m³, respectively.

Navigant Consulting agrees with the report which recommends the simpler of the longitudinal mixed to be used for planning purposes, since it is the more robust of the two analyses. Therefore, the natural gas savings are estimated to be as follows:

| Baseline Flow rate (GPM) | Energy Efficient Flow Rate (GPM) | Change in GPM | Annual Natural Gas Savings (m ³) | Annual Natural Gas Savings (m ³ per GPM) |
|--------------------------|----------------------------------|---------------|--|---|
| 2.25 ⁴ | 1.25 | 1.0 | 66 | 66 |
| 3 ⁵ | 1.25 | 1.75 | 116 | 66 |

Therefore, using an average baseline flow rate of 2.2 GPM and Union Gas' low flow showerhead of 1.5 GPM, the natural gas savings are estimated to be (2.2 – 1.5 GPM) x 66 m³/GPM = 46 m³.

It should be noted that the period of the sample in which the effects of the new showerheads might be observed is relatively short (e.g, between 74 days and 141 days, or roughly 15%-30% of the sample period). The report acknowledge this and recommend that the analysis be repeated when one year of post-installation data is available. Navigant agrees with the recommendation that a deemed saving for this measure be re-appraised when more post-installation data becomes available.

| | |
|-----------------------------------|----------------|
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 6,334 L |

Since the SAS report did not look at water savings, Navigant Consulting proposes the following method for calculating resulting water savings:

Assumptions and inputs:

- As-used flow rate with base equipment: 1.89 GPM⁶
- Average household size: 3.1 persons⁷
- Showers per capita per day: 0.75⁸
- Proportion of showering affected by measure (i.e. percentage of the time the low-flow showerhead used) : 76%⁹

⁴ Average of 2.0 GPM and 2.5 GPM

⁵ Assumed average low flow showerhead which is greater than 2.5 GPM.

⁶ As-used flow is calculated as a function of "full-on" or label flow: as-used flow = min{ 0.691+0.542*full-on flow, full-on flow}. Proctor, J. Gavelis, B. and Miller, B. *Savings and Showers: It's All in the Head*, (PGE) Home Energy Magazine, July/Aug 1994. Cited in Summit Blue (2008).

⁷ Summit Blue (2008).

⁸ Ibid, based on data from: Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007

- Average showering time per capita per day with base equipment: 7.32 minutes
- Average showering time per capita per day with new technology: 7.5 minutes¹⁰

Annual water savings calculated as follows:

$$Savings = Ppl * Sh * 365 * Pr * (T_{base} * Fl_{base} - T_{eff} * Fl_{eff})$$

Where:

Ppl = Number of people per household

Sh = Showers per capita per day

365 = Days per year

T_{base} = Showering time with base equipment (minutes)

T_{eff} = Showering time with efficient equipment (minutes)

Fl_{base} = As-used flow rate with base equipment (GPM)

Fl_{eff} = As-used flow rate with efficient equipment (GPM)

Pr = Percentage of showers where efficient equipment used

Water savings were determined to be 14% over base technology:

$$Percent Savings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water consumed by showers with efficient equipment, 38,138 litres (10,073 gallons)

W_{base} = Annual water consumed by showers with base equipment: 44,472 litres (11,746 gallons)

⁹ Survey of participants, 116 from Enbridge, 111 from Union, Summit Blue (2008)

¹⁰ Relationship modeled as: Average shower length = 8.17 – 0.448 * as-used GPM. From Energy Center of Wisconsin Analysis of data from Resource Management Strategies, Inc., *Regional Municipality of York Water Efficiency Master Plan Update*, April 2007. Cited in Summit Blue (2008)

Other Input Assumptions

| | |
|---|-------------------|
| Effective Useful Life (EUL) | 10 Years |
| Summit Blue (2008) suggests an EUL of 10 years based on a survey of five studies of showerheads in other jurisdictions (California – two studies, New England, Vermont, Arkansas). | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 6\$ |
| Incremental cost based on a survey of online retailers ¹¹ . This does not include installation costs. | |
| Customer Payback Period (Natural Gas Only)¹² | 0.25 Years |
| Using a 5-year average commodity cost (avoided cost) ¹³ of \$0.38 / m ³ and an average residential distribution cost ¹⁴ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 0.25 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$6/ (46 m ³ /year * \$0.52 / m ³) = 0.25 years | |
| Market Penetration | 65% |
| Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of low-flow showerheads of all flow rates across all sectors to be 65% ¹⁵ . | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Flex Your Power ¹⁶ | 72 | 10 | N/A | N/A |
| Comments Based on switching from a 2.2 GPM to a 1.5 GPM showerhead. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁷ | 71 | 10 | US\$ 36 | 75% |
| Comments Based on switching from a 4 GPM to a 2.5 GPM showerhead. Measure saves 13.9% of 514 m ³ required for water heating. | | | | |

¹¹ Whedon Products 1.5 GPM Ultra Saver Showerhead. http://www.antonline.com/p_USB3C-GP_398829.htm

¹² Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹³ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁴ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁵ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

¹⁶ http://www.fypower.org/res/tools/products_results.html?id=100160

¹⁷ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

14. Low-Flow Showerhead (1.25 GPM, Residential, UG ESK, per Household)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Low-flow Showerhead (1.25 GPM) – distributed to participants under Union Gas' ESK program.

Base Equipment and Technologies Description

Average existing stock (2.2 GPM)¹.

| Decision Type | Target Market(s) | End Use |
|---------------|------------------------|---------------|
| Retrofit | Residential (Existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)² requires shower heads to have a maximum flow of 2.5 GPM (9.5 L/min)

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|----------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 63 | 0 | 10,570 | 13 | 0 |
| 2 | 63 | 0 | 10,570 | 0 | 0 |
| 3 | 63 | 0 | 10,570 | 0 | 0 |
| 4 | 63 | 0 | 10,570 | 0 | 0 |
| 5 | 63 | 0 | 10,570 | 0 | 0 |
| 6 | 63 | 0 | 10,570 | 0 | 0 |
| 7 | 63 | 0 | 10,570 | 0 | 0 |
| 8 | 63 | 0 | 10,570 | 0 | 0 |
| 9 | 63 | 0 | 10,570 | 0 | 0 |
| 10 | 63 | 0 | 10,570 | 0 | 0 |
| TOTALS | 630 | 0 | 105,700 | 13 | 0 |

Resource Savings Assumptions

Annual Natural Gas Savings

63 m³

Enbridge Gas commissioned a study by the SAS Institute (Canada)³ to estimate natural gas savings for low-flow showerheads using a sample of 69 households in Enbridge territory between August 31 2007 to December 31, 2008. Replacement low-flow showerheads were installed between August 13, 2008 and October 18, 2008.

¹ Shower-heads distributed under Union Gas's ESK program are installed by homeowners rather than Union contractors. No observation is made of the base equipment's GPM. It is therefore assumed to be the full-on flow rate corresponding to the as-used flow from York Region monitoring study calculated using the equation cited below. Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007. Cited by: Summit Blue, *Resource Savings Values in Selected Residential DSM Prescriptive Programs*, June 2008.

² Ontario Regulations 350/06, 2006 Building Code

³ Rothman, Lorne, SAS® Analysis for Enbridge Gas Distribution Incorporated: Estimating the impact of Low Flow Showerhead Installation, March 16, 2009

The study used two classes of statistical method for estimating savings (1) Paired T-tests and (2) Longitudinal Mixed models.

1. Three iterations of the paired t-test method were estimated and of these, the report recommends the one which makes use of the entire data-set. This model yielded savings estimates of an average of 0.24 m³/day, for an extrapolated annual savings of 89 m³.
2. Two longitudinal mixed models were also estimated, one relatively simple linear model controlling for a variety of household factors, the other still linear, but with more parameters to be estimated (all additional parameters being the products of two previously estimated parameters) in order to study interaction effects. This model yielded savings estimates of an average of 0.18 m³/day for pre-existing showerhead flow rates of 2.0 to 2.5 GPM and 0.32 m³/day for pre-existing showerhead flow rates greater than 2.5 GPM. Extrapolation of these results for annual savings is approximately 66 m³ and 116 m³, respectively

Navigant Consulting agrees with the report which recommends the simpler of the longitudinal mixed to be used for planning purposes, since it is the more robust of the two analyses. Therefore, the natural gas savings are estimated to be as follows:

| Baseline Flow rate (GPM) | Energy Efficient Flow Rate (GPM) | Change in GPM | Annual Natural Gas Savings (m ³) | Annual Natural Gas Savings (m ³ per GPM) |
|--------------------------|----------------------------------|---------------|--|---|
| 2.25 ⁴ | 1.25 | 1.0 | 66 | 66 |
| 3 ⁵ | 1.25 | 1.75 | 116 | 66 |

Therefore, using an average baseline flow rate of 2.2 GPM, the natural gas savings are estimated to be (2.2 – 1.25 GPM) x 66 m³/GPM = 63 m³.

It should be noted that the period of the sample in which the effects of the new showerheads might be observed is relatively short (e.g, between 74 days and 141 days, or roughly 15%-30% of the sample period). The report acknowledge this and recommend that the analysis be repeated when one year of post-installation data is available. Navigant agrees with the recommendation that a deemed saving for this measure be re-appraised when more post-installation data becomes available.

| | |
|-----------------------------------|-----------------|
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 10,570 L |

Since the SAS report did not look at water savings, Navigant Consulting proposes the following method for calculating resulting water savings:

Assumptions and inputs:

- As-used flow rate with base equipment: 1.89 GPM⁶
- Average household size: 3.1 persons⁷
- Showers per capita per day: 0.75⁸
- Proportion of showering affected by measure (i.e. percentage of the time the low-flow showerhead used) : 76%⁹

⁴ Average of 2.0 GPM and 2.5 GPM

⁵ Assumed average low flow showerhead which is greater than 2.5 GPM.

⁶ As-used flow is calculated as a function of "full-on" or label flow: as-used flow = min{ 0.691+0.542*full-on flow, full-on flow}. Proctor, J. Gavelis, B. and Miller, B. *Savings and Showers: It's All in the Head*, (PGE) Home Energy Magazine, July/Aug 1994. Cited in Summit Blue (2008).

⁷ Summit Blue (2008).

⁸ Ibid, based on data from: Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007

- Average showering time per capita per day with base equipment: 7.32 minutes
- Average showering time per capita per day with new technology: 7.61 minutes¹⁰

Annual water savings calculated as follows:

$$Savings = Ppl * Sh * 365 * Pr * (T_{base} * Fl_{base} - T_{eff} * Fl_{eff})$$

Where:

Ppl = Number of people per household

Sh = Showers per capita per day

365 = Days per year

T_{base} = Showering time with base equipment (minutes)

T_{eff} = Showering time with efficient equipment (minutes)

Fl_{base} = As-used flow rate with base equipment (GPM)

Fl_{eff} = As-used flow rate with efficient equipment (GPM)

Pr = Percentage of showers where efficient equipment used

Water savings were determined to be 24% over base equipment:

$$Percent Savings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water consumed by showers with efficient equipment,
33,902 litres (8,954 gallons)

W_{base} = Annual water consumed by showers with base equipment: 44,472
litres (11,746 gallons)

⁹ Survey of participants, 116 from Enbridge, 111 from Union, Summit Blue (2008)

¹⁰ Relationship modeled as: Average shower length = 8.17 – 0.448 * as-used GPM. From Energy Center of Wisconsin Analysis of data from Resource Management Strategies, Inc., *Regional Municipality of York Water Efficiency Master Plan Update*, April 2007. Cited in Summit Blue (2008)

Other Input Assumptions

| | |
|--|------------------|
| Effective Useful Life (EUL) | 10 Years |
| Summit Blue (2008) suggests an EUL of 10 years based on a survey of five studies of showerheads in other jurisdictions (California – two studies, New England, Vermont, Arkansas). | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 13\$ |
| Incremental cost based on a survey of online retailers ¹¹ . This does not include installation costs. | |
| Customer Payback Period (Natural Gas Only)¹² | 0.4 Years |
| Using a 5-year average commodity cost (avoided cost) ¹³ of \$0.38 / m ³ and an average residential distribution cost ¹⁴ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 0.4 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$13/ (63 m ³ /year * \$0.52 / m ³) = 0.4 years | |
| Market Penetration | 65% |
| Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of low-flow showerheads of all flow rates across all sectors to be 65% ¹⁵ . | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Flex Your Power ¹⁶ | 72 | 10 | N/A | N/A |
| Comments Based on switching from a 2.2 GPM to a 1.5 GPM showerhead. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁷ | 71 | 10 | US\$ 36 | 75% |
| Comments Based on switching from a 4 GPM to a 2.5 GPM showerhead. Measure saves 13.9% of 514 m ³ required for water heating. | | | | |

¹¹ Earth Massage Showerhead 1.25 GPM

http://cgi.ebay.com/Earth-Massage-Showerhead-Water-Saver-1-25-gpm-flow_W0QQitemZ130256063752QQihZ003QQcategoryZ71282QQcmdZViewItemQQ_trksidZp1742.m153.l1262

¹² Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹³ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁴ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁵ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

http://www.fypower.org/res/tools/products_results.html?id=100160

¹⁷ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

15. Low-Flow Showerhead (1.25 GPM, Residential, Enbridge TAPS, per Household)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Low-flow Showerhead (1.25 GPM) – Installed by Enbridge-designated contractors.

Base Equipment and Technologies Description

Average existing stock within one of three ranges.

Range mid-points used as point estimates:

- Scenario A – 2.25 GPM
- Scenario B – 3.0 GPM

When new showerheads are installed contractors use a bag-test to determine base equipment flow-rate.

| Decision Type | Target Market(s) | End Use |
|---------------|------------------------|---------------|
| Retrofit | Residential (Existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)¹ requires shower heads to have a maximum flow of 2.5 GPM (9.5 L/min)

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | A:66 B: 116 | 0 | A: 10,886 B: 17,168 | 13 | 0 |
| 2 | A:66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 3 | A:66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 4 | A:66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 5 | A:66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 6 | A:66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 7 | A:66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 8 | A:66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 9 | A:66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 10 | A:66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| TOTALS | A: 660 B: 1,160 | 0 | A: 108,860 B: 171,680 | 13 | 0 |

¹ Ontario Regulations 350/06, 2006 Building Code

Resource Savings Assumptions

Annual Natural Gas Savings

A: 66 m³
B: 4116 m³

Enbridge Gas commissioned a study by the SAS Institute (Canada)² to estimate natural gas savings for low-flow showerheads using a sample of 69 households in Enbridge territory between August 31 2007 to December 31, 2008. Replacement low-flow showerheads were installed between August 13, 2008 and October 18, 2008.

The study used two classes of statistical method for estimating savings (1) Paired T-tests and (2) Longitudinal Mixed models.

1. Three iterations of the paired t-test method were estimated and of these, the report recommends the one which makes use of the entire data-set. This model yielded savings estimates of an average of 0.24 m³/day, for an extrapolated annual savings of 89 m³.
2. Two longitudinal mixed models were also estimated, one relatively simple linear model controlling for a variety of household factors, the other still linear, but with more parameters to be estimated (all additional parameters being the products of two previously estimated parameters) in order to study interaction effects. This model yielded savings estimates of an average of 0.18 m³/day for pre-existing showerhead flow rates of 2.0 to 2.5 GPM and 0.32 m³/day for pre-existing showerhead flow rates greater than 2.5 GPM. Extrapolation of these results for annual savings is approximately 66 m³ and 116 m³, respectively

Navigant Consulting agrees with the report which recommends the simpler of the longitudinal mixed to be used for planning purposes, since it is the more robust of the two analyses. Therefore, the natural gas savings are estimated to be as follows:

| Baseline Flow rate (GPM) | Energy Efficient Flow Rate (GPM) | Change in GPM | Annual Natural Gas Savings (m ³) | Annual Natural Gas Savings (m ³ per GPM) |
|--------------------------|----------------------------------|---------------|--|---|
| 2.25 ³ | 1.25 | 1.0 | 66 | 66 |
| 3 ⁴ | 1.25 | 1.75 | 116 | 66 |

It should be noted that the period of the sample in which the effects of the new showerheads might be observed is relatively short (e.g, between 74 days and 141 days, or roughly 15%-30% of the sample period). The report acknowledge this and recommend that the analysis be repeated when one year of post-installation data is available. Navigant agrees with the recommendation that a deemed saving for this measure be re-appraised when more post-installation data becomes available.

Annual Electricity Savings

0 kWh

N/A

Annual Water Savings

A: 10,886 L
B: 17,168 L

Since the SAS report did not look at water savings, Navigant Consulting proposes the following method for calculating resulting water savings:

Assumptions and inputs:

² Rothman, Lorne, SAS® Analysis for Enbridge Gas Distribution Incorporated: Estimating the impact of Low Flow Showerhead Installation, March 16, 2009

³ Average of 2.0 GPM and 2.5 GPM

⁴ Assumed average low flow showerhead which is greater than 2.5 GPM.

- As-used flow rate with base equipment⁵:
Scenario **A**: 1.91 GPM
Scenario **C**: 2.32 GPM
- Average household size: 3.1 persons⁶
- Showers per capita per day: 0.75⁷
- Proportion of showering affected by measure (i.e. percentage of the time the low-flow showerhead used) : 76%⁸
- Average showering time per capita per day with base equipment:
Scenario **A**: 7.31 minutes
Scenario **B**: 7.13 minutes
- Average showering time per capita per day with new technology: 7.61 minutes⁹

Annual water savings calculated as follows:

$$Savings = Ppl * Sh * 365 * Pr * (T_{base} * Fl_{base} - T_{eff} * Fl_{eff})$$

Where:

Ppl = Number of people per household.

Sh = Showers per capita per day.

365 = Days per year.

T_{base} = Showering time with base equipment (minutes)

T_{eff} = Showering time with efficient equipment (minutes).

Fl_{base} = As-used flow rate with base equipment (GPM)

Fl_{eff} = As-used flow rate with efficient equipment (GPM)

Pr = Percentage of showers where efficient equipment used.

Scenario **A**: Water savings were determined to be 24% over base equipment

Scenario **B**: Water savings were determined to be 32% over base equipment

$$Percent Savings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water consumed by showers with efficient equipment,

Scenario **A**: 34,002 litres (8,980 gallons)

Scenario **B**: 35,986 litres (9,504 gallons)

W_{base} = Annual water consumed by showers with base equipment:

Scenario **A**: 44,888 litres (11,856 gallons)

Scenario **B**: 53,154 litres (14,039 gallons)

⁵ As-used flow is calculated as a function of "full-on" or label flow: as-used flow = min{ 0.691+0.542*full-on flow, full-on flow}.
Proctor, J. Gavelis, B. and Miller, B. *Savings and Showers: It's All in the Head*, (PGE) Home Energy Magazine, July/Aug 1994. Cited in Summit Blue (2008)..

⁶ Summit Blue (2008).

⁷ Ibid, based on data from: Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007

⁸ Survey of participants, 116 from Enbridge, 111 from Union, Summit Blue (2008)

⁹ Relationship modeled as: Average shower length = 8.17 – 0.448 * as-used GPM. From Energy Center of Wisconsin Analysis of data from Resource Management Strategies, Inc., *Regional Municipality of York Water Efficiency Master Plan Update*, April 2007. Cited in Summit Blue (2008)

Other Input Assumptions

| | |
|---|--------------------------------------|
| Effective Useful Life (EUL) | 10 Years |
| Summit Blue (2008) suggests an EUL of 10 years based on a survey of five studies of showerheads in other jurisdictions (California – two studies, New England, Vermont, Arkansas). | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 13\$ |
| Incremental cost based on a survey of online retailers ¹⁰ . This does not include installation cost. | |
| Customer Payback Period (Natural Gas Only)¹¹ | A: 0.4 Years B: 0.2 Years |
| <p>Using a 5-year average commodity cost (avoided cost)¹² of \$0.38 / m³ and an average residential distribution cost¹³ of \$0.14 / m³, the payback period for natural gas savings is determined to be 0.4 years for Scenario A, and 0.2 years for Scenario B, based on the following:</p> <p>Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p>Scenario A = \$13/ (66 m³/year * \$0.52 / m³) = 0.4 years</p> <p>Scenario B = \$13/ (116 m³/year * \$0.52 / m³) = 0.2 years</p> | |
| Market Penetration | 65% |
| Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of low-flow showerheads of all flow rates across all sectors to be 65% ¹⁴ . | |

¹⁰ Earth Massage Showerhead 1.25 GPM

http://cgi.ebay.com/Earth-Massage-Showerhead-Water-Saver-1-25-gpm-flow_W0QQitemZ130256063752QQcategoryZ71282QQcmdZViewItemQQ_trksidZp1742.m153.l1262

¹¹ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹² 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹³ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁴ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Flex Your Power ¹⁵ | 72 | 10 | N/A | N/A |
| Comments | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁶ | 71 | 10 | US\$ 36 | 75% |
| Comments | | | | |
| Based on switching from a 4 GPM to a 2.5 GPM showerhead. Measure saves 13.9% of 514 m ³ required for water heating. | | | | |

¹⁵ http://www.fypower.org/res/tools/products_results.html?id=100160

¹⁶ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

16. Pipe Wrap (R-4)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Insulated hot water pipe for conventional gas storage tank-type hot water heater (R-4).

Base Equipment and Technologies Description

Conventional gas storage tank-type hot water heater without pipe wrap (R-1).

| Decision Type | Target Market(s) | End Use |
|---------------|------------------------|---------------|
| Retrofit | Residential (Existing) | Water heating |

Codes, Standards, and Regulations

N/A

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 18 | 0 | 0 | 2 | 0 |
| 2 | 18 | 0 | 0 | 0 | 0 |
| 3 | 18 | 0 | 0 | 0 | 0 |
| 4 | 18 | 0 | 0 | 0 | 0 |
| 5 | 18 | 0 | 0 | 0 | 0 |
| 6 | 18 | 0 | 0 | 0 | 0 |
| 7 | 18 | 0 | 0 | 0 | 0 |
| 8 | 18 | 0 | 0 | 0 | 0 |
| 9 | 18 | 0 | 0 | 0 | 0 |
| 10 | 18 | 0 | 0 | 0 | 0 |
| TOTALS | 180 | 0 | 0 | 2 | |

Resource Savings Assumptions

Annual Natural Gas Savings

18 m³

Assumptions and inputs:

- Gas savings calculated using method set out in 2006 Massachusetts study¹ except where noted.
- Average water heater recovery efficiency: 0.76²
- Average household size: 3.1 persons³
- Assumed diameter of pipe to be wrapped: 0.75 inches
- Length of pipe to be wrapped: 6 feet.
- Surface area of pipe to be wrapped: 1.18 square feet.
- Ambient temperature around pipes: 16 °C (60 °F)⁴
- Average water heater set point temperature: 54 °C (130 °F)⁵
- Hot water temperature in outlet pipe: 52 °C (125 °F)⁶

Annual gas savings calculated as follows:

$$Savings = \left(\frac{1}{R_{base}} - \frac{1}{R_{eff}} \right) * Sa * (T_{pipe} - T_{amb}) * 24 * 365 * \frac{1}{EF} * 10^{-6} * 27.8$$

Where:

R_{base} = R-value of base equipment
 R_{eff} = R-value of efficient equipment
 Sa = Surface area of outlet pipe (ft²)
 T_{pipe} = Temperature of water in outlet pipe (°F)
 T_{amb} = Ambient temperature around pipe (°F)
 24 = Hours per day
 365 = Days per year
 EF = Water heater energy factor
 10^{-6} = Factor to convert Btu to MMBtu
 27.8 = Factor to convert MMBtu to m³

Gas savings were determined to be 75% over base measure

$$Percent Savings = \frac{(G_{base} - G_{eff})}{G_{base}}$$

Where:

G_{eff} = Annual natural gas use with efficient equipment, 8 m³

¹ RLW Analytics, *Final Market Potential Report Of Massachusetts Owner Occupied 1-4 Unit Dwellings*, July 2006

http://www.cee1.org/eval/db_pdf/575.pdf

² Assumption used by Energy Center of Wisconsin, citing GAMA,

Pigg, Scott, *Water Heater Savings Calculator*, 2003, www.doa.state.wi.us/docs_view2.asp?docid=2249

³ Summit Blue, *Resource Savings Values in Selected Residential DSM Prescriptive Programs*, June 2008.

⁴ RLW Analytics (2006). Given geographic proximity, Massachusetts temperatures used unchanged for Ontario.

⁵ As suggested by NRCAN: <http://oee.nrcan.gc.ca/residential/personal/new-homes/water-conservation.cfm?attr=4>

⁶ From source: "It is common to find a 5 - 10 F temperature drop from the water heater to the furthest fixtures in the house."

Chinnery, G. *Policy recommendations for the HERS Community to consider*

regarding HERS scoring credit due to enhanced effective energy factors of water heaters resulting from volumetric hot water savings due to conservation devices/strategies, EPA Energy Star for Homes, Sept 2006

http://www.energystar.gov/ia/partners/bldrs_lenders_raters/downloads/Volumetric_Hot_Water_Savings_Guidelines.pdf

| | |
|---|--------------|
| G _{base} = Annual natural gas use with base equipment, 33 m ³ | |
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 0 L |
| Navigant has assumed that adopting the measure would not affect the quantity of water consumed. | |

Other Input Assumptions

| | |
|---|------------------|
| Effective Useful Life (EUL) | 10 Years |
| Based on the estimated measure lifetimes used in four other jurisdictions (Iowa - 15 years, Puget Sound Energy - 10 years, Efficiency Vermont – 10 years, and NYSERDA ⁷ – 10 years) Navigant recommends using an EUL of 10 years. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 2 \$ |
| Average equipment cost (for six feet of pipe wrap) based on communication with local hardware stores. This does not include installation costs. | |
| Customer Payback Period (Natural Gas Only)⁸ | 0.2 Years |
| Using an 5-year average commodity cost (avoided cost) ⁹ of \$0.38 / m ³ and an average residential distribution cost ¹⁰ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 0.2 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$2/ (18 m ³ /year * \$0.52 / m ³) = 0.2 years | |
| Market Penetration | 47% |
| Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of this measure to be 47% ¹¹ . | |

⁷ NYSERDA, New York Energy Smart Programs, *Deemed Savings Database*

⁸ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁹ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁰ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹¹ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| State of Iowa Utilities Board ¹² | 21 | 15 | 113 US\$ | 52% |
| Comments For addition of R-4 insulation to previously un-insulated pipes. Measure saves 4% of 514 m ³ required for water heating. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Puget Sound Energy, 2007 ¹³ | 8 | 10 | 8 US\$ | 38% |
| Comments For addition of R-4 insulation to previously un-insulated pipes. Measure saves 1% of 759 m ³ required for water heating. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Midwest Energy Efficiency Alliance, 2003 ¹⁴ | 36 | N/A | N/A | 10.4% |
| Comments No indication given of percentage savings or base natural gas consumption for water heating. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Efficiency Vermont, 2006 ¹⁵ | N/A | 10 | 15 US\$ | N/A |
| Comments Only electricity savings reported (33 kWh) for an electric hot water system. Insulation upgrade not specified. No indication given of percentage savings or base natural gas consumption for water heating. | | | | |

¹² Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

¹³ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁴ Midwest Energy Efficiency Alliance, *Illinois Residential Market Analysis, Final Report*, May 12, 2003.

¹⁵ http://www.cee1.org/eval/db_pdf/390.pdf

¹⁵ Efficiency Vermont, *Technical Reference User Manual (TRM)*, February 2006

17. Solar Pool Heaters

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Swimming pools heated by solar heating systems

Base Equipment and Technologies Description

Swimming pools heated by conventional gas-fired heating systems (50% seasonal efficiency)

| Decision Type | Target Market(s) | End Use |
|-----------------|----------------------------|---------------|
| New/Replacement | Residential (New/Existing) | Water Heating |

Codes, Standards, and Regulations

- Although currently there are no codes that define minimum values for the solar collector thermal efficiency, the following two standards define the thermal performance testing procedures applying to a single isolated collector: 1) CAN/CSA-F378-87 (R2004)¹, 2) Florida Solar Energy Centre (FSEC) standard test, FSEC-GP-5-80².

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 493 | -57 | 0 | 3,450 | 2,000 |
| 2 | 493 | -57 | 0 | 0 | 0 |
| 3 | 493 | -57 | 0 | 0 | 0 |
| 4 | 493 | -57 | 0 | 0 | 0 |
| 5 | 493 | -57 | 0 | 0 | 0 |
| 6 | 493 | -57 | 0 | 0 | 0 |
| 7 | 493 | -57 | 0 | 0 | 0 |
| 8 | 493 | -57 | 0 | 0 | 0 |
| 9 | 493 | -57 | 0 | 0 | 0 |
| 10 | 493 | -57 | 0 | 0 | 0 |
| 11 | 493 | -57 | 0 | 0 | 0 |
| 12 | 493 | -57 | 0 | 0 | 0 |
| 13 | 493 | -57 | 0 | 0 | 0 |
| 14 | 493 | -57 | 0 | 0 | 0 |
| 15 | 493 | -57 | 0 | 0 | 0 |
| 16 | 493 | -57 | 0 | 0 | 0 |
| 17 | 493 | -57 | 0 | 0 | 0 |
| 18 | 493 | -57 | 0 | 0 | 0 |
| 19 | 493 | -57 | 0 | 0 | 0 |
| 20 | 493 | -57 | 0 | 0 | 0 |
| TOTALS | 9,860 | -1,140 | 0 | 3,450 | 2,000 |

¹ CAN/CSA Solar Collector Standard, <http://www.csa-intl.org/onlinestore/GetCatalogItemDetails.asp?mat=2000426&Parent=173>

² FSEC Solar Collector Standard, <http://www.fsec.ucf.edu/en/industry/testing/STcollectors/standards/FSEC-GP-5-80.html>

Resource Savings Assumptions

Annual Natural Gas Savings

493 m³

- Navigant Consulting used RETScreen® software³ to model the energy savings resulting from a solar pool heater for a typical residential swimming pool in Ontario. The following system characteristics are assumed for both London and Sudbury, representing typical Southern and Northern Ontario climate zones:

| Variable Names | Value | Source |
|---|------------------------------|--------|
| Collector type | Unglazed | NCI |
| Gross area of one collector | 4.37 m ² | NCI |
| Aperture area of one collector | 4.37 m ² | NCI |
| Fr (tau alpha) coefficient ⁽¹⁾ | 82% | NCI |
| Fr UL coefficient ⁽²⁾ | 15.76 (W/m ²)/°C | NCI |
| Number of collectors | 5 | NCI |
| Heat exchanger/antifreeze protection | Yes | NCI |
| Heat exchanger effectiveness | 80% | NCI |
| Pipe diameter | 38 mm | NCI |
| Pumping power per collector area | 3 W/m ² | NCI |
| Piping and solar tank losses | 0.01% | NCI |
| Losses due to snow and/or dirt | 0.03% | NCI |
| Horz. dist. from mech. room to collector | 5 m | NCI |
| # of floors from mech. room to collector | 2 | NCI |

Notes⁴:

(1) Fr (tau alpha) coefficient is a dimensionless parameter used to characterise the collector's optical efficiency.

(2) Fr UL coefficient is a parameter used to characterize the collector's thermal losses [(W/m²)/°C]

- The RETScreen® software takes into account the local weather data, annual solar radiation, annual average temperature, annual average wind speed, desired load temperature and other system characteristics specific for both the London and Sudbury area.
- The following table summarizes the output of the model and the weighted average natural gas savings is calculated by assigning 70% to London and 30% to Sudbury based on the customer population service territory used by Union Gas:

| Annual Natural Gas Savings | Renewable Energy Delivered (GJ) | Natural Gas Displaced (m ³) | Weight | Weighted Average (m ³) |
|----------------------------|---------------------------------|---|--------|------------------------------------|
| Northern Ontario (Sudbury) | 16.4 | 442 | 30% | 493 |
| Southern Ontario (London) | 19.1 | 515 | 70% | |

- Since the solar power replaces the need for natural gas, it is assumed that the percentage of natural gas savings is 100%.

Annual Electricity Savings

- 57 kWh

- The electricity required for pumping the water through the collector system is calculated to be 0.057 MWh/year (57 kWh) based on the assumptions presented above, i.e., pumping power per collector area of 3 W/m² and piping and solar tank losses of 0.01%. This amount of electricity is considered incremental in comparison to a conventional natural gas heater.
- Using the same weighted average for both London and Sudbury, the incremental electricity is summarized below:

³ NRCAN, RETScreen ® http://canmetenergy-canmetenergie.nrcan-rncan.gc.ca/eng/software_tools/retscreen.html

⁴ NRCAN, RETScreen ® Software Online User Manual, 2005

| Annual Electricity Consumption | Renewable Energy Delivered (MWh) | Weight | Weighted Average (kWh) |
|--------------------------------|----------------------------------|--------|------------------------|
| Northern Ontario (Sudbury) | 0.05 | 30% | 57 |
| Southern Ontario (London) | 0.06 | 70% | |
| Annual Water Savings | | | 0 L |
| N/A | | | |

Other Input Assumptions

| | |
|---|------------------|
| Effective Useful Life (EUL) | 20 Years |
| According to NRCAN, solar pool heating systems are durable and last approximately 20 years ⁵ . Florida Solar Energy Centre estimates an effective useful life of 15 years ⁶ considering the longer swimming heating season in Florida. Therefore, Navigant Consulting estimates an EUL of 20 years for a solar pool heating system in Ontario. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$1,450 |
| The cost of a solar pool heater is dependent on the size of the swimming pool. Based on communication with local contractors ⁷ , the average installed cost is \$69 per m ² . Given a medium-sized pool of 50 m ² , the installed cost is determined to be \$3,450. The average cost for a conventional residential pool gas-fired heating system is \$2,000 ⁸ . Therefore, the incremental cost for solar pool heater is determined to be \$1,450. | |
| Customer Payback Period (Natural Gas Only)⁹ | 5.7 Years |
| Using a 5-year average commodity cost (avoided cost) ¹⁰ of \$0.38 / m ³ and an average residential distribution cost ¹¹ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 5.7 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$1,450 / (493 m ³ /year x \$0.52 / m ³) = 5.7 years | |
| Market Share¹² | Medium |
| Based on NRCAN report ¹³ and communication with local contractors, approximately 60% of in-ground pools are heated across Canada, most commonly by natural gas heaters or electric air-source heat pumps. Roughly 10% of heated pools currently use solar heaters. Therefore, Navigant Consulting estimates the market share of solar pool heaters in Ontario to be medium. | |

⁵ NRCAN, An Introduction to Solar Pool Heating Systems,

<http://www.energyalternatives.ca/PDF/An%20Introduction%20to%20Solar%20Pool%20Heating%20Systems.pdf>

⁶ FESC, Q&A for Solar Pool Heating, http://www.fsec.ucf.edu/en/consumer/solar_hot_water/pools/q_and_a/index.htm#Long

⁷ For example, Ottawa Solar Power, <http://ottawasolarpower.com/osp2008/poolheatingcost.html>

⁸ NRCAN, RETScreen ® Software Online User Manual, 2005

⁹ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹⁰ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹¹ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹² Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹³ NRCAN, Residential Solar Pool Heating Systems: A Buyer's Guide, 2001.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|--|-------------------------------|-----------------------|--------------------------|
| Florida Solar Energy Centre (FSEC), 2008 ¹⁴ | 2,332 | 15 | 3,500 | N/A |
| Comments Assuming a 470 ft ² collector located in central Florida and 12 months of swimming season (effectively 210 days of heating), the annual solar energy delivered is 87 MMBtu, which is equivalent to 2,332 m ³ natural gas savings. The effective useful life is estimated to be 15 years according to FSEC ¹⁵ . | | | | |

¹⁴ FSEC, Solar Swimming Pool Heating in Florida, http://www.fsec.ucf.edu/en/consumer/solar_hot_water/pools/sizing.htm

¹⁵ FSEC, Q&A for Solar Pool Heating, http://www.fsec.ucf.edu/en/consumer/solar_hot_water/pools/q_and_a/index.htm#Long

18. Tankless Gas Water Heater

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Tankless Gas Water Heater (EF = 0.82)

Base Equipment and Technologies Description

Conventional gas 50 gallon storage tank water heater (EF = 0.575)

| Decision Type | Target Market(s) | End Use |
|-------------------|---|---------------|
| New / Replacement | Residential (Existing and New Construction) | Water heating |

Codes, Standards, and Regulations

Ontario's Energy Efficiency Act¹ requires that gas-fired water storage heaters with nominal inputs of 75,000 Btu or less capable of storing between 20 and 100 US gallons have a minimum energy factor of 0.67 - (0.0019*X)

Where X is the capacity (in gallons) of the storage tank.

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 130 | 0 | 0 | \$1,500 | \$750 |
| 2 | 130 | 0 | 0 | 0 | 0 |
| 3 | 130 | 0 | 0 | 0 | 0 |
| 4 | 130 | 0 | 0 | 0 | 0 |
| 5 | 130 | 0 | 0 | 0 | 0 |
| 6 | 130 | 0 | 0 | 0 | 0 |
| 7 | 130 | 0 | 0 | 0 | 0 |
| 8 | 130 | 0 | 0 | 0 | 0 |
| 9 | 130 | 0 | 0 | 0 | 0 |
| 10 | 130 | 0 | 0 | 0 | 0 |
| 11 | 130 | 0 | 0 | 0 | 0 |
| 12 | 130 | 0 | 0 | 0 | 0 |
| 13 | 130 | 0 | 0 | 0 | 0 |
| 14 | 130 | 0 | 0 | 0 | 0 |
| 15 | 130 | 0 | 0 | 0 | 0 |
| 16 | 130 | 0 | 0 | 0 | 0 |
| 17 | 130 | 0 | 0 | 0 | 0 |
| 18 | 130 | 0 | 0 | 0 | 0 |
| TOTALS | 2,340 | 0 | 0 | \$1,500 | \$750 |

¹ <http://www.energy.gov.on.ca/english/pdf/conservation/2006%20-%20EEA%20Guide%20C%20-%20Water%20Heaters.pdf>

Resource Savings Assumptions

| Annual Natural Gas Savings | 130 m ³ |
|--|--------------------|
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> Following a 2006 recommendation to the California Energy Commission that the Alternative Calculation Method (ACM) be amended to recognise the disparity between the nominal Energy Factor of tankless water heaters drawing less than 11 gallons and the actual energy efficiency, savings are calculated using an energy factor degraded by 8.8%² Adjusted energy factor³: 0.77 Daily average household hot water use: 179 litres (47 gallons)⁴ Average water inlet temperature: 9.33 C (48.8 F)⁵ Average water heater set point temperature: 54 C (130 F)⁶ <p>Annual gas savings calculated as follows:</p> $Savings = W * 8.33 * (T_{out} - T_{in}) * \left(\frac{1}{EF_{base}} - \frac{1}{EF_{eff}} \right) * 10^{-6} * 27.8$ <p>Where:</p> <p>W = Annual hot water use (gallons) 8.33 = Energy content of water (Btu/gallon/°F) T_{out} = Water heater set point temperature (°F) T_{in} = Water inlet temperature (°F) EF_{base} = Energy factor of base equipment EF_{eff} = Adjusted energy factor of efficient equipment 10⁻⁶ = Factor to convert Btu to MMBtu 27.8 = Factor to convert MMBtu to metres cubed</p> <p>Gas savings 23% over base measure:</p> $PercentSavings = \frac{(G_{base} - G_{eff})}{G_{base}}$ <p>Where:</p> <p>G_{eff} = Annual natural gas use with efficient equipment, 434 m³ G_{base} = Annual natural gas use with base equipment, 564 m³</p> | |
| Annual Electricity Savings | 0 kWh |
| N/A | |

² Davis Energy Group, *Measure Information Template: Tankless Gas Water Heaters*, April 2008

http://www.energy.ca.gov/title24/2008standards/prerulemaking/documents/2006-05-18_workshop/2006-05-11_GAS_WATER.PDF

³ It should be noted that an alternative study, by Exelon Services for Okaloosa Gas, conducted carefully controlled tests to determine the thermal efficiency of a tankless and a storage tank gas water heater. This study found that the listed energy factor *underestimated* the tankless water heater's true thermal efficiency. This result is not reflected in this substantiation sheet due to the more recent findings cited above, based on a larger sample than the Okaloosa study.

Exelon Services and Okaloosa Gas District, *Performance Comparison of Residential Water Heating Systems*, December 2002

⁴ From sample of 150 Enbridge customers whose gas consumption is monitored by Enbridge. Correspondence with Enbridge.

⁵ Chinnery, Glen. *Policy Recommendations for the HERS Community to Consider regarding HERS point credit for Waste Water Heat Recovery Devices*, EPA, Energy Star for homes, March 2004

http://www.energystar.gov/ia/partners/bldrs_lenders_raters/downloads/Waste_Water_Heat_Recovery_Guidelines.pdf

⁶ As suggested by NRCAN: <http://oee.nrcan.gc.ca/residential/personal/new-homes/water-conservation.cfm?attr=4>

| | |
|---|------------|
| Annual Water Savings | 0 L |
| Navigant has assumed that adopting the measure would not affect the quantity of water consumed. | |

Other Input Assumptions

| | |
|--|-----------------|
| Effective Useful Life (EUL) | 18 Years |
| Navigant Consulting recommends using an EUL of 18 years, the mean of estimated measure lifetimes used two other jurisdictions (Iowa ⁷ , 20 years, and Puget Sound Energy ⁸ , 13 years) and that quoted by an academic paper ⁹ (20 years). | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 750 \$ |
| Cost of tankless water heater determined to be \$1,500 ¹⁰ . Average price for a 50 gallon conventional storage tank water heater \$750 ¹¹ . | |
| Customer Payback Period (Natural Gas Only)¹² | 11 Years |
| Using a 5-year average commodity cost (avoided cost) ¹³ of \$0.38 / m ³ and an average residential distribution cost ¹⁴ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 11 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$750/ (130 m ³ /year * \$0.52 / m ³) = 10.5 years | |
| Market Penetration¹⁵ | Low |
| Based on the observation of low penetration in two other jurisdictions (Washington State ¹⁶ – 10%, Iowa ¹⁷ – 1%) and communications with local contractors, Navigant Consulting estimates the penetration in Ontario to be low. | |

⁷ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

⁸ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

⁹ Aguilar, C., White, D.J., and Ryan, David L. *Domestic Water Heating and Water Heater Energy Consumption in Canada*, April 2005

¹⁰ Based on online prices from Home Depot for a Paloma Whole Home 7.4 GPM, www.homedepot.ca

¹¹ Based on average prices from Home Depot, www.homedepot.ca

¹² Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹³ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁴ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁵ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁶ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁷ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy, 2007 ¹⁸ | 152 | 13 | 350 US\$ | 10% |
| Comments Assuming base equipment to be a conventional water tank with an EF=0.64. Measure saves 20% of 759 m ³ required for water heating. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁹ | 207 | 20 | 685 US\$ | 1% |
| Comments Assuming base equipment to be a conventional water tank with an EF = 0.59. Measure saves 40.2% of 514 m ³ required for water heating. | | | | |

¹⁸ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁹ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

LOW INCOME SPACE HEATING

19. Programmable Thermostat (LIA)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Programmable thermostat.

Base Equipment and Technologies Description

Standard thermostat.

| Decision Type | Target Market(s) | End Use |
|---------------|----------------------------|---------------|
| Retrofit | Residential existing homes | Space Heating |

Codes, Standards, and Regulations

- For a programmable thermostat to receive Energy Star® qualification, it must meet specific criteria such as having at least two different programming periods (for weekday and weekend programming), at least four possible temperature settings and allow for temporary overriding by the user.
- In Canada, applicable CSA standards can be found in CSA C828-99- CAN/CSA Performance Requirements for Thermostats used with Individual Room Electric Space Heating Devices.

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 53 | 54 | 0 | 25 | 0 |
| 2 | 53 | 54 | 0 | 0 | 0 |
| 3 | 53 | 54 | 0 | 0 | 0 |
| 4 | 53 | 54 | 0 | 0 | 0 |
| 5 | 53 | 54 | 0 | 0 | 0 |
| 6 | 53 | 54 | 0 | 0 | 0 |
| 7 | 53 | 54 | 0 | 0 | 0 |
| 8 | 53 | 54 | 0 | 0 | 0 |
| 9 | 53 | 54 | 0 | 0 | 0 |
| 10 | 53 | 54 | 0 | 0 | 0 |
| 11 | 53 | 54 | 0 | 0 | 0 |
| 12 | 53 | 54 | 0 | 0 | 0 |
| 13 | 53 | 54 | 0 | 0 | 0 |
| 14 | 53 | 54 | 0 | 0 | 0 |
| 15 | 53 | 54 | 0 | 0 | 0 |
| TOTALS | 2,190 | 2,730 | 0 | 25 | 0 |

Resource Savings Assumptions

Annual Natural Gas Savings

53 m³

- Two utility studies¹ are used to determine savings resulting from residential programmable thermostats on natural gas consumptions.
 - In the **GasNetworks** study², 4,061 mail-in surveys and bills were analyzed. Results were normalized for temperature and the energy impacts were determined through a multivariate regression analysis. The study found that programmable thermostat saved 6 % of total household annual natural gas use. GasNetworks is proposing 75 ccf (212 m³) natural gas savings based on a Non-Programmable Thermostat annual consumption of 1,253 ccf (3,548 m³) natural gas.
 - In the **Enbridge Billing Analysis**³, 911 customers' natural gas consumption was analyzed in 2005. Enbridge determined an average savings of 159 m³ for a house using 2,878 m³ of natural gas.
- Canadian Centre for Housing Technology (CCHT) also conducted a study in 2005 on programmable thermostat natural gas savings⁴. The study was done in two identical research homes located in Ottawa to allow direct comparison of changes in operating conditions in a home. It reports a 6.5% predicted savings for 18°C night setback.
- Based on these three studies, Navigant Consulting is assuming an average saving at 6% for natural gas consumptions for full temperature set back.

| Studies | Baseline Gas Consumption (m ³) | Gas Savings (m ³) | Gas Savings% |
|--------------------|--|-------------------------------|--------------|
| GasNetworks (2007) | 3,548 | 212 | 6.0% |
| Enbridge (2005) | 2,878 | 159 | 5.5% |
| CCHT (2005) | - | - | 6.5% |
| NCI Average | | | 6.0% |

Taking into account behavioural changes:

- Based on a recent Statistics Canada report⁵, approximately 41% of Ontario households with non-programmable or non-programmed thermostats manually set back their thermostat at night (19% lowered by 3 or more degrees, 21% lowered by 1 or 2 degrees) in the winter season, where as 59% did not lower their thermostat before going to sleep.
- Similar values were found based on a recent evaluation Ontario Power Authority's 2007 Hot and Cool Savings Program conservation program. A household survey determined that of the 59% of Ontario households with non-programmable thermostats who manually set back their thermostat, after installing their new programmable thermostat, 68% stated they continued with the same set back behaviour (no change), while 32% increased their set back temperature (19% by 3 or more degrees, 81% by 1 or 2 degrees)⁶.
- Furthermore, Navigant Consulting also determined from the survey that of the 41% of households who previously did not have a programmable thermostat and did not lower their thermostat at night, 67% of households changed their behaviour by programming their thermostat to lower the

¹ "Resource Savings Values in Selected Residential DSM Prescriptive Programs", Summit Blue Consulting, June 2008.

² RLW Analytics, Validating the impact of programmable thermostats: final report. Prepared for GasNetworks by RLW Analytics. Middletown, CT, January 2007.

³ "Resource Savings Values in Selected Residential DSM Prescriptive Programs", Summit Blue Consulting, June 2008.

⁴ The Effects of Thermostat Setting on Seasonal Energy Consumption at the CCHT Research Facility, Manning, Swinton, Szadkowski, Gusdorf, Ruest, February 14, 2005, <http://irc.nrc-cnrc.gc.ca/pubs/rr/rr191/rr191.pdf>

⁵ Statistics Canada, Household and Environment Survey, 2006

⁶ Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

temperature at night when they sleep (44% by 3 or more degrees, 56% by 1 or 2 degrees).

- Therefore, using Statistics Canada values for typical winter behaviour of non-programmable thermostat households and Navigant Consulting findings for post installation of a programmable thermostat, the following natural gas savings should be attributed for each installed programmable thermostat:

| <i>Savings</i> | <i>Distribution of Households</i> | <i>Natural Gas Savings</i> |
|--|-----------------------------------|----------------------------|
| No change in behaviour or no set back | 47% | 0% |
| Full change in behaviour - 3 + degrees set back | 20% | 6% |
| Partial change in behaviour: 1 -2 degrees set back | 33% | 3% |

Using Enbridge's baseline natural gas consumption of 2,436 m³ for mid-efficiency furnaces, NCI estimates the following natural gas savings from the installation of programmable thermostats:

$$2,436 \text{ m}^3 \times (47\% \times 0\% + 20\% \times 6\% + 33\% \times 3\%) = 53 \text{ m}^3$$

- This represents an overall savings of 2% over the baseline ($53 \text{ m}^3 / 2436 \text{ m}^3 = 2\%$)

Annual Electricity Savings

54 kWh

Heating Season Savings (Furnace fan)

- The following table is based on the CCHT study analysing furnace fan consumption in relation to set back temperatures from programmable thermostats⁷.

| <i>Temp Set Back</i> | <i>Total Winter Furnace Electricity Consumption (kWh)</i> | <i>Seasonal Savings (%)</i> |
|--------------------------------------|---|-----------------------------|
| None (22C) | 2,314 | 0 % |
| 18 C night time set back | 2,295 | 0.8% |
| 18 C daytime and night time set back | 2,270 | 1.9% |

- Using the CCHT study results from a full night-time set back of 4 degrees:
Approximate savings is expected for the winter season⁸ = $2,314 - 2,295 = 19 \text{ kWh/year}$
- Applying the same behaviour changes as presented above (natural gas savings), furnace fan savings during the heating season are estimated to be as follows:
 $47\% \times 0 \text{ kWh} + 20\% \times 19 \text{ kWh} + 33\% \times 9.5 \text{ kWh} = 7 \text{ kWh}$

Cooling Season Savings

- A side-by-side housing study conducted by the CCHT⁹ determined seasonal energy savings for a residential unit from a programmable thermostat as follows:

CAC:**

| <i>Temp Set Back</i> | <i>Total Summer Furnace and CAC Electricity Consumption (kWh)</i> | <i>Seasonal Savings (%)</i> |
|-----------------------|---|-----------------------------|
| None (22C) | 3,099 | 0 |
| 25 C daytime set back | 2,767 | 11 |
| 24 C daytime set back | 2,376 | 23 |

** 12 SEER , 2 ton capacity CAC, 362 cooling degree days (18C)

⁷ The Effects of Thermostat Setting on Seasonal Energy Consumption at the CCHT Research Facility, Manning, Swinton, Szadkowski, Gusdorf, Ruest, February 14, 2005, <http://irc.nrc-cnrc.gc.ca/pubs/rr/rr191/rr191.pdf>

⁸ Although furnace fan consumption is significantly higher than reported by other studies, the change in electricity consumption by using a programmable thermostat is assumed to be appropriate for this analysis.

⁹ The Effects of Thermostat Setting on Seasonal Energy Consumption at the CCHT Research Facility, Manning, Swinton, Szadkowski, Gusdorf, Ruest, February 14, 2005, <http://irc.nrc-cnrc.gc.ca/pubs/rr/rr191/rr191.pdf>

- A BC Hydro study¹⁰ reports savings between 10% and 15% for 4°C set back during night and unoccupied periods, Energy Star Calculator¹¹ reports 6% saving per degree (Fahrenheit) for *cooling season*.
- Assuming that baseline house is equipped with a SEER 10, 2.5 ton A/C unit¹² and is used 500 hours per year¹³, this implies that:

$$\text{Base A/C electricity use} = 500 \text{ (cooling hours)} \times [30,000 \text{ (Btu/hr)} / (10 \text{ (SEER)} \times 1,000)] = 1,500 \text{ kWh}$$

Taking into Account Changes in Behaviour (Cooling Season)

- Based on the same program evaluation survey for the OPA¹⁴, NCI determined that of the households who previously had non-programmable thermostats and did not manually adjust the thermostat to increase when they were away from home, 46% of respondents indicated they changed their behaviour when they installed a programmable thermostat by raising the temperature of their home when they were away (55% by 3 or more degrees, 45% by 1 or 2 degrees).
- Of the households who previously had non-programmable thermostats and manually adjusted their thermostat in the summer when they were away, 32% indicated they have increased their thermostats setting¹⁵, where as 68% of respondents indicated they had no change in temperature settings.
- Therefore, using Statistics Canada values for typical summer behaviour of non-programmable thermostat households and Navigant Consulting findings for post installation of a programmable thermostat, the following electricity savings should be attributed to each installed programmable thermostat:

| <i>Savings</i> | <i>Distribution of Households</i> | <i>Natural Gas Savings</i> |
|--|-----------------------------------|----------------------------|
| No change in behaviour or no set back | 60% | 0% |
| Full change in behaviour - 3 + degrees set back | 17% | 11% |
| Partial change in behaviour: 1 -2 degrees set back | 23% | 5.5% |

- Assuming that baseline house is equipped with a SEER 10, 2.5 ton¹⁶ A/C unit and is used 500 hours per year¹⁷, this implies that:

$$\text{Base A/C electricity use} = 500 \text{ (cooling hours)} \times [30,000 \text{ (Btu/hr)} / (10 \text{ (SEER)} \times 1,000)] = 1,500 \text{ kWh}$$
- NCI estimates the following cooling season electricity savings for each programmable thermostat installed in households with central air conditioning:

$$1,500 \text{ kWh} \times (60\% \times 0\% + 17\% \times 11\% + 23\% \times 5.5\%) = 47 \text{ kWh}$$
- However, assuming a penetration rate of central air conditioners in Ontario = 57%¹⁸, NCI estimates that the average home in Ontario will save the following in electricity during the cooling savings:

$$57\% \times 47 \text{ kWh} = 26.8 \text{ kWh}$$

¹⁰ Marbek Resource Consultants, The Sheltair Group Inc., BC Hydro BC Hydro Conservation Potential Review 2002, Residential Sector Report (Base Year: Fiscal 2000/01) (Revision 1) Submitted to: BC Hydro, June 2003

¹¹ US EPA (EPA Energy Star® Simple Savings Calculator – Programmable Thermostat), http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/CalculatorProgrammableThermostat.xls

¹² Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, referenced from: Heating, Refrigeration and Air Conditioning Institute of Canada (HRAI), 2006 Cool Savings Rebate Program, Prepared for the Ontario Power Authority, April 2007.

¹³ US EPA (EPA Energy Star® Simple Savings Calculator – Programmable Thermostat), http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/CalculatorProgrammableThermostat.xls

¹⁴ Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

¹⁵ Although the survey results did not indicate the change in degree-value in temperature for summer behaviour, Navigant Consulting is assuming it is the same as the winter change in behaviour (e.g., 19% by 3 or more degrees, 81% by 1-2 degrees).

¹⁶ Implying input of 30,000 Btu/hr, Energy Star Savings Calculator, http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Calc_CAC.xls

¹⁷ Number of full-load cooling hours provided by <http://energyexperts.org/ac%5Fcalc/> and based on the assumption that Ontario's climate is sufficiently similar to that of the north-eastern U.S.

¹⁸ Natural Resource Canada, Survey of Household Energy Use (SHEU), December 2005

- Total electricity savings for both heating (furnace fan) and cooling savings for an average Ontario home are estimated to be 54 kWh (7 kWh + 47 kWh = 54 kWh).

Annual Water Savings

0 L

N/A

Other Input Assumptions

Effective Useful Life (EUL)

15 Years

Navigant Consulting is estimating 15 years as the effective useful life based on the average lifetime of programmable thermostat from Energy Star ® website.

Base & Incremental Conservation Measure Equipment and O&M Costs

\$ 25

Average incremental cost of programmable thermostats determined to be \$25 based on average cost of non-programmable and programmable thermostats from Home Depot and Canadian Tire website in 2008.

Customer Payback Period (Natural Gas Only)¹⁹

0.9 Years

Using an 5-year average commodity cost (avoided cost)²⁰ of \$0.38 / m³ and an average residential distribution cost²¹ of \$0.14 / m³, the payback period for natural gas savings is determined to be 0.9 years, based on the following:

$$\begin{aligned}\text{Payback Period} &= \text{Incremental cost} / (\text{natural gas savings} \times \text{natural gas cost}) \\ &= \$25 / (53 \text{ m}^3/\text{year} \times \$0.52 / \text{m}^3) \\ &= 0.9 \text{ years}\end{aligned}$$

Market Penetration

65%

Due to the number of conservation programs in Ontario currently offering programmable thermostats and based on previous research conducted for the OPA²², Navigant Consulting estimates the penetration of programmable thermostats amongst single family residents in Ontario to be 65%.

¹⁹ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

²⁰ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

²¹ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

²² Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| State of Iowa Utilities Board ²³ | 276 | 15 | \$25 | 46% (single family) |
| Comments Measure provides savings of 11.5% over 2,399 m ³ required for space heating with base equipment. Behavioural adjustments were not included in results. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Ontario Power Authority ²⁴ | 182 | 15 | \$140 | N/A |
| Comments Based on gas savings from Canadian Centre for Housing Technology study for an 80% AFUE gas furnace using standard PCS motor and furnace size of 67,500 BTU/hr, using 4761 heating degree hours. Behavioural adjustments were not included in results. | | | | |

²³ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

²⁴ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008

20. Weatherization (LIA)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Weatherization includes: draft proofing (caulking and weather stripping) and increased insulation.

Base Equipment and Technologies Description

No weatherization.

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------------------|---------------|
| Retrofit | Low-income Residential (Existing) | Space Heating |

Codes, Standards, and Regulations

N/A

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 1,134 | 165 | 0 | 2,284 | 0 |
| 2 | 1,134 | 165 | 0 | 0 | 0 |
| 3 | 1,134 | 165 | 0 | 0 | 0 |
| 4 | 1,134 | 165 | 0 | 0 | 0 |
| 5 | 1,134 | 165 | 0 | 0 | 0 |
| 6 | 1,134 | 165 | 0 | 0 | 0 |
| 7 | 1,134 | 165 | 0 | 0 | 0 |
| 8 | 1,134 | 165 | 0 | 0 | 0 |
| 9 | 1,134 | 165 | 0 | 0 | 0 |
| 10 | 1,134 | 165 | 0 | 0 | 0 |
| 11 | 1,134 | 165 | 0 | 0 | 0 |
| 12 | 1,134 | 165 | 0 | 0 | 0 |
| 13 | 1,134 | 165 | 0 | 0 | 0 |
| 14 | 1,134 | 165 | 0 | 0 | 0 |
| 15 | 1,134 | 165 | 0 | 0 | 0 |
| 16 | 1,134 | 165 | 0 | 0 | 0 |
| 17 | 1,134 | 165 | 0 | 0 | 0 |
| 18 | 1,134 | 165 | 0 | 0 | 0 |
| 19 | 1,134 | 165 | 0 | 0 | 0 |
| 20 | 1,134 | 165 | 0 | 0 | 0 |
| 21 | 1,134 | 165 | 0 | 0 | 0 |
| 22 | 1,134 | 165 | 0 | 0 | 0 |
| 23 | 1,134 | 165 | 0 | 0 | 0 |
| TOTALS | 26.082 | 3,795 | 0 | 2,284 | 0 |

Resource Savings Assumptions

| Annual Natural Gas Savings | | | 1,134 m ³ |
|---|---|---|------------------------------|
| <ul style="list-style-type: none"> According to a low income weatherization research report¹ prepared by GreenSaver on behalf of Enbridge Gas, a total of 61 homes were retrofitted in the 2007 Enbridge pilot program. Home audits were conducted. Audits were completed on selected homes (inspection of the attic, wall and foundation insulation, windows, heating systems, water heaters and ventilation systems). The air tightness of each home was measured using a Blower Door device. Potential retrofit upgrades were modeled and if the total feasible improvements were projected at 15% or more of their current energy use, the home was recommended for retrofit work (including draft proofing² and attic and/or wall insulation³). After completion of the energy retrofit work, a second audit was conducted followed by an inspection verifying that the completed work met the specifications provided, and allowing for full assessment of the project results. Based on program data supplied by Enbridge and audited by GreenSaver, program savings results are summarized below: | | | |
| | Baseline NG Consumption (m ³) | Retrofit NG Consumption (m ³) | NG Savings (m ³) |
| Total | 310,168 | 247,804 | 62,364 |
| Average | 5,639 | 4,506 | 1,134 |
| <ul style="list-style-type: none"> Baseline estimates of natural gas consumption = 5,639 m³. Natural Gas Savings % = 1,134 m³ / 5,639 m³ = 20 % | | | |
| Annual Electricity Savings | | | 165 kWh |
| <ul style="list-style-type: none"> Electricity savings are modelled using HOT2000 after retrofit. Assumptions and Inputs: <ul style="list-style-type: none"> Four occupants per house (2 adults, 2 children), occupied 50% of the time Temperature set-point of 21 °C for the main floor walls and 19 °C for the basement Consumption of 225 litres of DWH per day Electrical consumption (lights and appliances) of 24 kWh per day Weather data file is based on the analysis of periods from 1971 - 2000 A/C is not factored into electrical savings Based on program data supplied by Enbridge and audited by GreenSaver, program savings results are summarized below: | | | |
| | Baseline Electricity Consumption (kWh) | Retrofit Electricity Consumption (kWh) | Electricity Savings (kWh) |
| Total | 512,822 | 502,773 | 10,050 |
| Average | 8,407 | 8,242 | 165 |
| <ul style="list-style-type: none"> Baseline estimates of electricity consumption = 8,407kWh. Electricity Savings % = 165 kWh / 8407 kWh = 2 % | | | |
| Annual Water Savings | | | 0 L |
| N/A | | | |

¹ GreenSaver, Low Income Weatherization Research Summary, prepared for Enbridge Gas, December 2007.

² Draft proofing included: caulking and weather stripping around doors and door frames, around window casing, around headers and baseboards and attic hatches

³ Insulation included blowing cellulose insulation into wood framed wall cavities and crawlspaces, adding or blowing insulation into attics and crawlspaces and adding insulation to the whole length of basement walls

Other Input Assumptions

| | |
|---|------------------|
| Effective Useful Life (EUL) | 23 Years |
| Based on average measure life of installed measures for 61 participant homes in GreenSaver study ⁴ . Measures included attic insulation, wall insulation, door and weather stripping and caulking. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$ 2,284 |
| Based on average actual cost (2007) for the 61 program participants in the pilot study ⁵ . | |
| Customer Payback Period (Natural Gas Only)⁶ | 3.9 Years |
| Using a 5-year average commodity cost (avoided cost) ⁷ of \$0.38 / m ³ and an average residential distribution cost ⁸ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 3.9 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$2,284 / (1,134 m ³ /year * \$0.52 / m ³) = 3.9 years | |
| Market Penetration⁹ | Medium |
| Based on communication with local contractors, the increased promotions and retrofit programs available to homeowners, Navigant Consulting is estimating the market penetration of weatherization to be medium. | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Iowa Sate Low-income Weatherization Program (2003) ¹⁰ | 767.3 | 1,031 | 5,064 | N/A |
| Comments On average, the 1,813 participants in this program saved 1031 kWh of electricity and 276 therms (767.3 m ³) of natural gas. | | | | |

⁴ GreenSaver, Low Income Weatherization Research Summary, prepared for Enbridge Gas, December 2007.

⁵ Ibid.

⁶ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁷ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁸ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

⁹ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁰ http://www.dcaa.iowa.gov/bureau_weath/pdfs/CY03ExecSummary.pdf

LOW INCOME WATER HEATING

21. Faucet Aerator (Bathroom) (LIA)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Faucet Aerator (Bathroom) (1.5 GPM)

Base Equipment and Technologies Description

Average existing stock (2.2 GPM)¹

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------------------|---------------|
| Retrofit | Low-Income Residential (existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)² requires bathroom and kitchen faucets to have a maximum flow of 2.2 GPM (8.35 L/min).

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|---------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 6 | 0 | 2,004 | 2 | 0 |
| 2 | 6 | 0 | 2,004 | 0 | 0 |
| 3 | 6 | 0 | 2,004 | 0 | 0 |
| 4 | 6 | 0 | 2,004 | 0 | 0 |
| 5 | 6 | 0 | 2,004 | 0 | 0 |
| 6 | 6 | 0 | 2,004 | 0 | 0 |
| 7 | 6 | 0 | 2,004 | 0 | 0 |
| 8 | 6 | 0 | 2,004 | 0 | 0 |
| 9 | 6 | 0 | 2,004 | 0 | 0 |
| 10 | 6 | 0 | 2,004 | 0 | 0 |
| TOTALS | 60 | 0 | 20,040 | 2 | 0 |

¹ From on-site audit data. Resource Management Strategies, Inc. *Regional Municipality of York Water Efficiency Master Plan Update*, 2007. Cited in: Summit Blue, *Resource Savings Values in Selected Residential DSM Prescriptive Programs*, June 2008.

² Ontario Regulations 350/06, 2006 Building Code

Resource Savings Assumptions

| Annual Natural Gas Savings | 6 m ³ |
|--|------------------|
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> Lacking any conclusive empirical data to suggest otherwise, Navigant Consulting has applied the same behavioural and base/efficient equipment assumptions to the Low-Income sector as to the Residential sector. Average faucet water temperature: 30 °C (86 °F)³ Average water inlet temperature: 9.33 °C (48.8 °F)⁴ Average water heater energy factor: 0.76⁵ <p>Annual gas savings calculated as follows:</p> $Savings = W * 8.33 * (T_{out} - T_{in}) * \frac{1}{EF} * 10^{-6} * 27.8$ <p>Where:</p> <p>W = Water savings (gallons) 8.33 = Energy content of water (Btu/gallon/°F) T_{out} = Faucet water temperature (°F) T_{in} = Water inlet temperature (°F) EF = Water heater recovery efficiency 10⁻⁶ = Factor to convert Btu to MMBtu 27.8 = Factor to convert MMBtu to m³</p> <p>Gas savings were determined to be 22% over base case:</p> $Percent\ Savings = \frac{(G_{base} - G_{new})}{G_{base}}$ <p>Where:</p> <p>G_{eff} = Annual natural gas use with efficient equipment, 27 m³ G_{base} = Annual natural gas use with base equipment, 21 m³</p> | |
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 2,004 L |
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> Average household size: 3.1 persons⁶ Baseline faucet use (all faucets) per capita per day: 53 litres (14 gallons)⁷ Bathroom faucet use as a percentage of total faucet use: 15%⁸ | |

³ Average of findings in two studies, adjusted for Toronto water inlet temperature. Mayer, P. W. et al, *Residential Indoor Water Conservation Study: Evaluation of High Efficiency Indoor Plumbing Fixture Retrofits in Single-Family Homes in East Bay Municipal Utility District Service Area*, 2003 and Skeel, T. and Hill, S. *Evaluation of Savings from Seattle's "Home Water Saver" Apartment/Condominium Program*, 1994. Both cited in: Summit Blue (2008).

⁴ Cited in the following as personal communication with City of Toronto Works Dept. VEIC, *Comments on Navigant's Draft Gas Measure Characterizations*, March 2009

⁵ Assumption used by Energy Center of Wisconsin, citing GAMA, Pigg, Scott. *Water Heater Savings Calculator*, 2003
www.doa.state.wi.us/docs_view2.asp?docid=2249

⁶ Summit Blue (2008).

⁷ Ibid.

⁸ DeOreo, W. and P. Mayer, *The End Uses of Hot Water in Single Family Homes from Flow Trace Analysis*, 1999 cited in Summit Blue (2008).

- Point estimate of quantity of water that goes straight down the drain: 70%⁹

Annual water savings calculated as follows:

$$Savings = Fu * Ppl * 365 * Ba * \left(\frac{Fl_{base} - Fl_{eff}}{Fl_{base}} \right) * Dr$$

Where:

Fu = Faucet use per capita (gallons)
Ppl = Number of people per household
365 = Days per year
Dr = Percentage of water that goes straight down the drain
Ba = Individual bathroom faucet use as a percentage of total faucet use
Fl_{base} = Flow rate of base equipment (GPM)
Fl_{eff} = Flow rate of efficient equipment (GPM)

Water savings was determined to be 22% over base case:

$$Percent Savings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water use with efficient equipment: 6,993 litres (1,847 gallons)
W_{base} = Annual water use with base equipment: 8,997 litres (2,376 gallons)

Other Input Assumptions

| | |
|---|------------------|
| Effective Useful Life (EUL) | 10 Years |
| The U.S. DOE assumes a 10 year life for faucet aerators ¹⁰ . | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 2 \$ |
| Average equipment cost based on communication with local hardware stores. This does not include installation costs. | |
| Customer Payback Period (Natural Gas Only)¹¹ | 0.6 Years |
| Using a 5-year average commodity cost (avoided cost) ¹² of \$0.38 / m ³ and an average residential distribution cost ¹³ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 0.6 years, based on the following: | |
| Payback Period = Incremental cost / (natural gas savings x natural gas cost) | |

⁹ Summit Blue (2008).

¹⁰ U.S. Department of Energy, Federal Energy Management Program, *FEMP Designated Product: Lavatory Faucets* http://www1.eere.energy.gov/femp/procurement/eeep_faucets.html

¹¹ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹² 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹³ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

$$= \$2 / (6 \text{ m}^3/\text{year} * \$0.52 / \text{m}^3)$$

$$= 0.6 \text{ years}$$

Market Penetration¹⁴

90%

Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of faucet aerators (bathroom and kitchen) across all sectors to be 90%¹⁵.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy ¹⁶ | 8 | 5 | N/A | 45% |
| Comments For a switch from a 2.5 GPM to a 1.8 GPM aerator. Measure saves 1% of 759 m ³ required for water heating. Note that no distinction is made, in this study, between kitchen and bathroom faucet use. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁷ | 36 | 9 | 20 US\$ | 90% |
| Comments For a switch from a 3.0 GPM to a 1.5 GPM aerator for the Low-Income sector. Measure saves 6.2% of 584 m ³ required for water heating. Note that no distinction is made, in this study, between kitchen and bathroom faucet use. Note also that the flow rate reduction in this jurisdiction is more than twice that of the measure addressed by this substantiation sheet. | | | | |

¹⁴ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁵ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

¹⁶ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁷ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

22. Faucet Aerator (Kitchen) (LIA)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Faucet Aerator (kitchen) (1.5 GPM)

Base Equipment and Technologies Description

Average existing stock (2.5 GPM)¹

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------------------|---------------|
| Retrofit | Low-Income Residential (existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)² requires bathroom and kitchen faucets to have a maximum flow of 2.2 GPM (8.35 L/min).

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|---------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 23 | 0 | 7,797 | 2 | 0 |
| 2 | 23 | 0 | 7,797 | 0 | 0 |
| 3 | 23 | 0 | 7,797 | 0 | 0 |
| 4 | 23 | 0 | 7,797 | 0 | 0 |
| 5 | 23 | 0 | 7,797 | 0 | 0 |
| 6 | 23 | 0 | 7,797 | 0 | 0 |
| 7 | 23 | 0 | 7,797 | 0 | 0 |
| 8 | 23 | 0 | 7,797 | 0 | 0 |
| 9 | 23 | 0 | 7,797 | 0 | 0 |
| 10 | 23 | 0 | 7,797 | 0 | 0 |
| TOTALS | 230 | 0 | 77,970 | 2 | 0 |

¹ From on-site audit data. Resource Management Strategies, Inc. *Regional Municipality of York Water Efficiency Master Plan Update*, 2007. Cited in: Summit Blue, *Resource Savings Values in Selected Residential DSM Prescriptive Programs*, June 2008.

² Ontario Regulations 350/06, 2006 Building Code

Resource Savings Assumptions

| | |
|---|-------------------------|
| Annual Natural Gas Savings | 23 m³ |
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> Lacking any conclusive empirical data to suggest otherwise, Navigant Consulting has applied the same behavioural and base/efficient equipment assumptions to the Low-Income sector as to the Residential sector. Average faucet water temperature: 30 °C (86 F)³ Average water inlet temperature: 9.33 °C (48.8 F)⁴ Average water heater energy factor: 0.76⁵ <p>Annual gas savings calculated as follows:</p> $Savings = W * 8.33 * (T_{out} - T_{in}) * \frac{1}{EF} * 10^{-6} * 27.8$ <p>Where:</p> <p>W = Water savings (gallons) 8.33 = Energy content of water (Btu/gallon/°F) T_{out} = Faucet water temperature (°F) T_{in} = Water inlet temperature (°F) EF = Water heater recovery efficiency 10⁻⁶ = Factor to convert Btu to MMBtu 27.8 = Factor to convert MMBtu to m³</p> <p>Gas savings were determined to be 20% over base case:</p> $Percent\ Savings = \frac{(G_{base} - G_{new})}{G_{base}}$ <p>Where:</p> <p>G_{eff} = Annual natural gas use with efficient equipment, 94 m³ G_{base} = Annual natural gas use with base equipment, 117 m³</p> | |
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 7,797 L |
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> Average household size: 3.1 persons⁶ Baseline faucet use (all faucets) per capita per day: 53 litres (14 gallons)⁷ Kitchen faucet use as a percentage of total faucet use: 65%⁸ | |

³ Average of findings in two studies, adjusted for Toronto water inlet temperature. Mayer, P. W. et al, *Residential Indoor Water Conservation Study: Evaluation of High Efficiency Indoor Plumbing Fixture Retrofits in Single-Family Homes in East Bay Municipal Utility District Service Area*, 2003 and Skeeel, T. and Hill, S. *Evaluation of Savings from Seattle's "Home Water Saver" Apartment/Condominium Program*, 1994. Both cited in:

Summit Blue (2008).

⁴ Cited in the following as personal communication with City of Toronto Works Dept. VEIC, *Comments on Navigant's Draft Gas Measure Characterizations*, March 2009

⁵ Assumption used by Energy Center of Wisconsin, citing GAMA, Pigg, Scott, *Water Heater Savings Calculator* 2003.

www.doa.state.wi.us/docs_view2.asp?docid=2249

⁶ Summit Blue (2008).

⁷ Ibid.

⁸ DeOreo, W. and P. Mayer, *The End Uses of Hot Water in Single Family Homes from Flow Trace Analysis*, 1999 cited in Summit Blue (2008).

- Point estimate of quantity of water that goes straight down the drain: 50%⁹

Annual water savings calculated as follows:

$$Savings = Fu * Ppl * 365 * Ba * \left(\frac{Fl_{base} - Fl_{eff}}{Fl_{base}} \right) * Dr$$

Where:

Fu = Faucet use per capita (gallons)
Ppl = Number of people per household
365 = Days per year
Dr = Percentage of water that goes straight down the drain
Ki = Kitchen faucet use as a percentage of total faucet use
Fl_{base} = Flow rate of base equipment (GPM)
Fl_{eff} = Flow rate of efficient equipment (GPM)

Water savings was determined to be 20% over base case:

$$Percent Savings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water use with efficient equipment: 38,986 litres (10,297 gallons)
W_{base} = Annual water use with base equipment: 31,188 litres (8,237 gallons)

Other Input Assumptions

| | |
|--|-------------------|
| Effective Useful Life (EUL) | 10 Years |
| The U.S. DOE assumes a 10 year life for faucet aerators ¹⁰ . | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 2 \$ |
| Average equipment cost based on communication with local hardware stores. This does not include installation costs. | |
| Customer Payback Period (Natural Gas Only)¹¹ | 0.17 Years |
| Using a 5-year average commodity cost (avoided cost) ¹² of \$0.38 / m ³ and an average residential distribution cost ¹³ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 0.17 years, based on the following: | |

⁹ Summit Blue (2008).

¹⁰ U.S. Department of Energy, Federal Energy Management Program, *FEMP Designated Product: Lavatory Faucets*
http://www1.eere.energy.gov/femp/procurement/eeep_faucets.html

¹¹ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹² 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹³ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

Payback Period = Incremental cost / (natural gas savings x natural gas cost)
 = \$2/ (23 m³/year * \$0.52 / m³)
 = 0.17 years

Market Penetration

90%

Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of faucet aerators (bathroom and kitchen) across all sectors to be 90%¹⁴.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy ¹⁵ | 8 | 5 | N/A | 45% |
| Comments For a switch from a 2.5 GPM to a 1.8 GPM aerator. Measure saves 1% of 759 m ³ required for water heating. Note that no distinction is made, in this study, between kitchen and bathroom faucet use. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁶ | 36 | 9 | 20 US\$ | 90% |
| Comments For a switch from a 3.0 GPM to a 1.5 GPM aerator for the Low-Income sector. Measure saves 6.2% of 584 m ³ required for water heating. Note that no distinction is made, in this study, between kitchen and bathroom faucet use. Note also that the flow reduction in this jurisdiction is more than twice that of the measure addressed by this substantiation sheet. | | | | |

¹⁴ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

¹⁵ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁶ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

23. Low-Flow Showerhead (1.5 Gpm, UG ESK, LIA, per Household)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Low-flow Showerhead (1.5 GPM) – distributed to participants under Union Gas' ESK program.

Base Equipment and Technologies Description

Average existing stock (2.2 GPM)¹.

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------------------|---------------|
| Retrofit | Low-Income Residential (Existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)² requires shower heads to have a maximum flow of 2.5 GPM (9.5 L/min).

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|---------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 46 | 0 | 6,334 | 6 | 0 |
| 2 | 46 | 0 | 6,334 | 0 | 0 |
| 3 | 46 | 0 | 6,334 | 0 | 0 |
| 4 | 46 | 0 | 6,334 | 0 | 0 |
| 5 | 46 | 0 | 6,334 | 0 | 0 |
| 6 | 46 | 0 | 6,334 | 0 | 0 |
| 7 | 46 | 0 | 6,334 | 0 | 0 |
| 8 | 46 | 0 | 6,334 | 0 | 0 |
| 9 | 46 | 0 | 6,334 | 0 | 0 |
| 10 | 46 | 0 | 6,334 | 0 | 0 |
| TOTALS | 460 | 0 | 63,340 | 6 | 0 |

Resource Savings Assumptions

| Annual Natural Gas Savings | 46 m ³ |
|--|-------------------|
| Enbridge Gas commissioned a study by the SAS Institute (Canada) ³ to estimate natural gas savings for low-flow showerheads using a sample of 69 households in Enbridge territory between August 31 2007 to December 31, 2008. Replacement low-flow showerheads were installed between August 13, 2008 and October 18, 2008. | |

¹ Shower-heads distributed under Union Gas's ESK program are installed by homeowners rather than Union contractors. No observation is made of the base equipment's GPM. It is therefore assumed to be the full-on flow rate corresponding to the as-used flow from York Region monitoring study calculated using the equation cited below.

Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007. Cited by: Summit Blue, *Resource Savings Values in Selected Residential DSM Prescriptive Programs*, June 2008.

² Ontario Regulations 350/06, 2006 Building Code

³ Rothman, Lorne, SAS® Analysis for Enbridge Gas Distribution Incorporated: Estimating the impact of Low Flow Showerhead Installation, March 16, 2009

The study used two classes of statistical method for estimating savings (1) Paired T-tests and (2) Longitudinal Mixed models.

1. Three iterations of the paired t-test method were estimated and of these, the report recommends the one which makes use of the entire data-set. This model yielded savings estimates of an average of 0.24 m³/day, for an extrapolated annual savings of 89 m³.
2. Two longitudinal mixed models were also estimated, one relatively simple linear model controlling for a variety of household factors, the other still linear, but with more parameters to be estimated (all additional parameters being the products of two previously estimated parameters) in order to study interaction effects. This model yielded savings estimates of an average of 0.18 m³/day for pre-existing showerhead flow rates of 2.0 to 2.5 GPM and 0.32 m³/day for pre-existing showerhead flow rates greater than 2.5 GPM. Extrapolation of these results for annual savings is approximately 66 m³ and 116 m³, respectively.

Navigant Consulting agrees with the report which recommends the simpler of the longitudinal mixed to be used for planning purposes, since it is the more robust of the two analyses. Therefore, the natural gas savings are estimated to be as follows:

| Baseline Flow rate (GPM) | Energy Efficient Flow Rate (GPM) | Change in GPM | Annual Natural Gas Savings (m3) | Annual Natural Gas Savings (m3 per GPM) |
|--------------------------|----------------------------------|---------------|---------------------------------|---|
| 2.25 ⁴ | 1.25 | 1.0 | 66 | 66 |
| 3 ⁵ | 1.25 | 1.75 | 116 | 66 |

Therefore, using an average baseline flow rate of 2.2 GPM and Union Gas' low flow showerhead of 1.5 GPM, the natural gas savings are estimated to be (2.2 – 1.5 GPM) x 66 m³/GPM = 46 m³.

It should be noted that the period of the sample in which the effects of the new showerheads might be observed is relatively short (e.g, between 74 days and 141 days, or roughly 15%-30% of the sample period). The report acknowledge this and recommend that the analysis be repeated when one year of post-installation data is available. Navigant agrees with the recommendation that a deemed saving for this measure be re-appraised when more post-installation data becomes available.

| | |
|-----------------------------------|----------------|
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 6,334 L |

Since the SAS report did not look at water savings, Navigant Consulting proposes the following method for calculating resulting water savings:

Assumptions and inputs:

- As-used flow rate with base equipment: 1.89 GPM⁶
- Average household size: 3.1 persons⁷
- Showers per capita per day: 0.75⁸
- Proportion of showering affected by measure (i.e. percentage of the time the low-flow showerhead

⁴ Average of 2.0 GPM and 2.5 GPM

⁵ Assumed average low flow showerhead which is greater than 2.5 GPM.

⁶ As-used flow is calculated as a function of "full-on" or label flow: as-used flow = min{ 0.691+0.542*full-on flow, full-on flow}. Proctor, J. Gavelis, B. and Miller, B. *Savings and Showers: It's All in the Head*, (PGE) Home Energy Magazine, July/Aug 1994. Cited in Summit Blue (2008).

⁷ Summit Blue (2008).

⁸ Ibid, based on data from: Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007

used) : 76%⁹

- Average showering time per capita per day with base equipment: 7.32 minutes
- Average showering time per capita per day with new technology: 7.5 minutes¹⁰

Annual water savings calculated as follows:

$$Savings = Ppl * Sh * 365 * Pr * (T_{base} * Fl_{base} - T_{eff} * Fl_{eff})$$

Where:

Ppl = Number of people per household

Sh = Showers per capita per day

365 = Days per year

T_{base} = Showering time with base equipment (minutes)

T_{eff} = Showering time with efficient equipment (minutes)

Fl_{base} = As-used flow rate with base equipment (GPM)

Fl_{eff} = As-used flow rate with efficient equipment (GPM)

Pr = Percentage of showers where efficient equipment used

Water savings were determined to be 14% over base technology:

$$Percent Savings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water consumed by showers with efficient equipment, 38,138 litres (10,073 gallons)

W_{base} = Annual water consumed by showers with base equipment: 44,472 litres (11,746 gallons)

⁹ Survey of participants, 116 from Enbridge, 111 from Union, Summit Blue (2008)

¹⁰ Relationship modeled as: Average shower length = 8.17 – 0.448 * as-used GPM. From Energy Center of Wisconsin Analysis of data from Resource Management Strategies, Inc., *Regional Municipality of York Water Efficiency Master Plan Update*, April 2007. Cited in Summit Blue (2008)

Other Input Assumptions

| | |
|---|-------------------|
| Effective Useful Life (EUL) | 10 Years |
| Summit Blue (2008) suggests an EUL of 10 years based on a survey of five studies of showerheads in other jurisdictions (California – two studies, New England, Vermont, Arkansas). | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 6\$ |
| Incremental cost based on a survey of online retailers ¹¹ . This does not include installation costs. | |
| Customer Payback Period (Natural Gas Only)¹² | 0.25 Years |
| Using a 5-year average commodity cost (avoided cost) ¹³ of \$0.38 / m ³ and an average residential distribution cost ¹⁴ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 0.25 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$6/ (46 m ³ /year * \$0.52 / m ³) = 0.25 years | |
| Market Penetration | 65% |
| Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of low-flow showerheads of all flow rates across all sectors to be 65% ¹⁵ . | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Flex Your Power ¹⁶ | 72 | 10 | N/A | N/A |
| Comments Based on switching from a 2.2 GPM to a 1.5 GPM showerhead. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁷ | 71 | 10 | US\$ 36 | 75% |
| Comments Based on switching from a 4 GPM to a 2.5 GPM showerhead. Measure saves 13.9% of 514 m ³ required for water heating. | | | | |

¹¹ Whedon Products 1.5 GPM Ultra Saver Showerhead. http://www.antonline.com/p_USB3C-GP_398829.htm

¹² Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹³ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁴ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁵ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

¹⁶ http://www.fypower.org/res/tools/products_results.html?id=100160

¹⁷ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

24. Low-Flow Showerhead (1.25 GPM, LIA, UG ESK, per Household)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Low-flow Showerhead (1.25 GPM) – distributed to participants under Union Gas' ESK program.

Base Equipment and Technologies Description

Average existing stock (2.2 GPM)¹.

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------------------|---------------|
| Retrofit | Low Income Residential (Existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)² requires shower heads to have a maximum flow of 2.5 GPM (9.5 L/min)

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|----------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 63 | 0 | 10,570 | 13 | 0 |
| 2 | 63 | 0 | 10,570 | 0 | 0 |
| 3 | 63 | 0 | 10,570 | 0 | 0 |
| 4 | 63 | 0 | 10,570 | 0 | 0 |
| 5 | 63 | 0 | 10,570 | 0 | 0 |
| 6 | 63 | 0 | 10,570 | 0 | 0 |
| 7 | 63 | 0 | 10,570 | 0 | 0 |
| 8 | 63 | 0 | 10,570 | 0 | 0 |
| 9 | 63 | 0 | 10,570 | 0 | 0 |
| 10 | 63 | 0 | 10,570 | 0 | 0 |
| TOTALS | 630 | 0 | 105,700 | 13 | 0 |

Resource Savings Assumptions

| Annual Natural Gas Savings | 63 m ³ |
|--|-------------------|
| Enbridge Gas commissioned a study by the SAS Institute (Canada) ³ to estimate natural gas savings for low-flow showerheads using a sample of 69 households in Enbridge territory between August 31 2007 to December 31, 2008. Replacement low-flow showerheads were installed between August 13, 2008 and October 18, 2008. | |

¹ Shower-heads distributed under Union Gas's ESK program are installed by homeowners rather than Union contractors. No observation is made of the base equipment's GPM. It is therefore assumed to be the full-on flow rate corresponding to the as-used flow from York Region monitoring study calculated using the equation cited below. Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007. Cited by: Summit Blue, *Resource Savings Values in Selected Residential DSM Prescriptive Programs*, June 2008.

² Ontario Regulations 350/06, 2006 Building Code

³ Rothman, Lorne, SAS® Analysis for Enbridge Gas Distribution Incorporated: Estimating the impact of Low Flow Showerhead Installation, March 16, 2009

The study used two classes of statistical method for estimating savings (1) Paired T-tests and (2) Longitudinal Mixed models.

3. Three iterations of the paired t-test method were estimated and of these, the report recommends the one which makes use of the entire data-set. This model yielded savings estimates of an average of 0.24 m³/day, for an extrapolated annual savings of 89 m³.
4. Two longitudinal mixed models were also estimated, one relatively simple linear model controlling for a variety of household factors, the other still linear, but with more parameters to be estimated (all additional parameters being the products of two previously estimated parameters) in order to study interaction effects. This model yielded savings estimates of an average of 0.18 m³/day for pre-existing showerhead flow rates of 2.0 to 2.5 GPM and 0.32 m³/day for pre-existing showerhead flow rates greater than 2.5 GPM. Extrapolation of these results for annual savings is approximately 66 m³ and 116 m³, respectively

Navigant Consulting agrees with the report which recommends the simpler of the longitudinal mixed to be used for planning purposes, since it is the more robust of the two analyses. Therefore, the natural gas savings are estimated to be as follows:

| Baseline Flow rate (GPM) | Energy Efficient Flow Rate (GPM) | Change in GPM | Annual Natural Gas Savings (m ³) | Annual Natural Gas Savings (m ³ per GPM) |
|--------------------------|----------------------------------|---------------|--|---|
| 2.25 ⁴ | 1.25 | 1.0 | 66 | 66 |
| 3 ⁵ | 1.25 | 1.75 | 116 | 66 |

Therefore, using an average baseline flow rate of 2.2 GPM, the natural gas savings are estimated to be (2.2 – 1.25 GPM) x 66 m³/GPM = 63 m³.

It should be noted that the period of the sample in which the effects of the new showerheads might be observed is relatively short (e.g, between 74 days and 141 days, or roughly 15%-30% of the sample period). The report acknowledge this and recommend that the analysis be repeated when one year of post-installation data is available. Navigant agrees with the recommendation that a deemed saving for this measure be re-appraised when more post-installation data becomes available.

⁴ Average of 2.0 GPM and 2.5 GPM

⁵ Assumed average low flow showerhead which is greater than 2.5 GPM.

| | |
|--|-----------------|
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 10,570 L |
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> As-used flow rate with base equipment: 1.89 GPM⁶ Average household size: 3.1 persons⁷ Showers per capita per day: 0.75⁸ Proportion of showering affected by measure (i.e. percentage of the time the low-flow showerhead used) : 76%⁹ Average showering time per capita per day with base equipment: 7.32 minutes Average showering time per capita per day with new technology: 7.61 minutes¹⁰ <p>Annual water savings calculated as follows:</p> $Savings = Ppl * Sh * 365 * Pr * (T_{base} * Fl_{base} - T_{eff} * Fl_{eff})$ <p>Where:</p> <p>Ppl = Number of people per household Sh = Showers per capita per day 365 = Days per year T_{base} = Showering time with base equipment (minutes) T_{eff} = Showering time with efficient equipment (minutes) Fl_{base} = As-used flow rate with base equipment (GPM) Fl_{eff} = As-used flow rate with efficient equipment (GPM) Pr = Percentage of showers where efficient equipment used</p> <p>Water savings were determined to be 24% over base equipment:</p> $PercentSavings = \frac{(W_{base} - W_{eff})}{W_{base}}$ <p>Where:</p> <p>W_{eff} = Annual water consumed by showers with efficient equipment, 33,902 litres (8,954 gallons) W_{base} = Annual water consumed by showers with base equipment: 44,472 litres (11,746 gallons)</p> | |

Other Input Assumptions

| | |
|--|-----------------|
| Effective Useful Life (EUL) | 10 Years |
| Summit Blue (2008) suggests an EUL of 10 years based on a survey of five studies of showerheads in other jurisdictions (California – two studies, New England, Vermont, Arkansas). | |

⁶ As-used flow is calculated as a function of “full-on” or label flow: as-used flow = min{ 0.691+0.542*full-on flow, full-on flow}. Proctor, J. Gavelis, B. and Miller, B. *Savings and Showers: It's All in the Head*, (PGE) Home Energy Magazine, July/Aug 1994. Cited in Summit Blue (2008).

⁷ Summit Blue (2008).

⁸ Ibid, based on data from: Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007

⁹ Survey of participants, 116 from Enbridge, 111 from Union, Summit Blue (2008)

¹⁰ Relationship modeled as: Average shower length = 8.17 – 0.448 * as-used GPM. From Energy Center of Wisconsin Analysis of data from Resource Management Strategies, Inc., *Regional Municipality of York Water Efficiency Master Plan Update*, April 2007. Cited in Summit Blue (2008)

| | |
|--|------------------|
| Base & Incremental Conservation Measure Equipment and O&M Costs | 13\$ |
| Incremental cost based on a survey of online retailers ¹¹ . This does not include installation costs. | |
| Customer Payback Period (Natural Gas Only)¹² | 0.4 Years |
| Using a 5-year average commodity cost (avoided cost) ¹³ of \$0.38 / m ³ and an average residential distribution cost ¹⁴ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 0.4 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$13/ (63 m ³ /year * \$0.52 / m ³) = 0.4 years | |
| Market Penetration | 65% |
| Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of low-flow showerheads of all flow rates across all sectors to be 65% ¹⁵ . | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Flex Your Power ¹⁶ | 72 | 10 | N/A | N/A |
| Comments Based on switching from a 2.2 GPM to a 1.5 GPM showerhead. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁷ | 71 | 10 | US\$ 36 | 75% |
| Comments Based on switching from a 4 GPM to a 2.5 GPM showerhead. Measure saves 13.9% of 514 m ³ required for water heating. | | | | |

¹¹ Earth Massage Showerhead 1.25 GPM

http://cgi.ebay.com/Earth-Massage-Showerhead-Water-Saver-1-25-gpm-flow_W0QQitemZ130256063752QQihZ003QQcategoryZ71282QQcmdZViewItemQQ_trksidZp1742.m153.l1262

¹² Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹³ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁴ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁵ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

http://www.fypower.org/res/tools/products_results.html?id=100160

¹⁷ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

25. Low-Flow Showerhead (1.25 Gpm, LIA, Enbridge TAPS, per Household)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Low-flow Showerhead (1.25 Gpm) – Installed by Enbridge-designated contractors.

Base Equipment and Technologies Description

Average existing stock within one of three ranges.

Range mid-points used as point estimates:

- Scenario A – 2.25 GPM
- Scenario B – 3.0 GPM

When new showerheads are installed contractors use a bag-test to determine base equipment flow-rate.

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------------------|---------------|
| Retrofit | Low Income Residential (Existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)¹ requires shower heads to have a maximum flow of 2.5 GPM (9.5 L/min)

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|----------------------------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | A: 66 B: 116 | 0 | A: 10,886 B: 17,168 | 13 | 0 |
| 2 | A: 66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 3 | A: 66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 4 | A: 66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 5 | A: 66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 6 | A: 66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 7 | A: 66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 8 | A: 66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 9 | A: 66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| 10 | A: 66 B: 116 | 0 | A: 10,886 B: 17,168 | 0 | 0 |
| TOTALS | A: 660 B: 1,160 | 0 | A: 108,860 B: 171,680 | 13 | 0 |

¹ Ontario Regulations 350/06, 2006 Building Code

Resource Savings Assumptions

Annual Natural Gas Savings

A: 66 m³
B: 116 m³

Enbridge Gas commissioned a study by the SAS Institute (Canada)² to estimate natural gas savings for low-flow showerheads using a sample of 69 households in Enbridge territory between August 31 2007 to December 31, 2008. Replacement low-flow showerheads were installed between August 13, 2008 and October 18, 2008.

The study used two classes of statistical method for estimating savings (1) Paired T-tests and (2) Longitudinal Mixed models.

1. Three iterations of the paired t-test method were estimated and of these, the report recommends the one which makes use of the entire data-set. This model yielded savings estimates of an average of 0.24 m³/day, for an extrapolated annual savings of 89 m³.
2. Two longitudinal mixed models were also estimated, one relatively simple linear model controlling for a variety of household factors, the other still linear, but with more parameters to be estimated (all additional parameters being the products of two previously estimated parameters) in order to study interaction effects. This model yielded savings estimates of an average of 0.18 m³/day for pre-existing showerhead flow rates of 2.0 to 2.5 GPM and 0.32 m³/day for pre-existing showerhead flow rates greater than 2.5 GPM. Extrapolation of these results for annual savings is approximately 66 m³ and 116 m³, respectively

Navigant Consulting agrees with the report which recommends the simpler of the longitudinal mixed to be used for planning purposes, since it is the more robust of the two analyses. Therefore, the natural gas savings are estimated to be as follows:

| Baseline Flow rate (GPM) | Energy Efficient Flow Rate (GPM) | Change in GPM | Annual Natural Gas Savings (m ³) | Annual Natural Gas Savings (m ³ per GPM) |
|--------------------------|----------------------------------|---------------|--|---|
| 2.25 ³ | 1.25 | 1.0 | 66 | 66 |
| 3 ⁴ | 1.25 | 1.75 | 116 | 66 |

It should be noted that the period of the sample in which the effects of the new showerheads might be observed is relatively short (e.g, between 74 days and 141 days, or roughly 15%-30% of the sample period).The report acknowledge this and recommend that the analysis be repeated when one year of post-installation data is available. Navigant agrees with the recommendation that a deemed saving for this measure be re-appraised when more post-installation data becomes available.

Annual Electricity Savings

0 kWh

N/A

Annual Water Savings

A: 10,886 L
B: 17,168 L

Since the SAS report did not look at water savings, Navigant Consulting proposes the following method for calculating resulting water savings:

² Rothman, Lorne, SAS® Analysis for Enbridge Gas Distribution Incorporated: Estimating the impact of Low Flow Showerhead Installation, March 16, 2009

³ Average of 2.0 GPM and 2.5 GPM

⁴ Assumed average low flow showerhead which is greater than 2.5 GPM.

Assumptions and inputs:

- As-used flow rate with base equipment⁵:
Scenario **A**: 1.91 GPM
Scenario **B**: 2.32 GPM
- Average household size: 3.1 persons⁶
- Showers per capita per day: 0.75⁷
- Proportion of showering affected by measure (i.e. percentage of the time the low-flow showerhead used) : 76%⁸
- Average showering time per capita per day with base equipment:
Scenario **A**: 7.31 minutes
Scenario **B**: 7.13 minutes
- Average showering time per capita per day with new technology: 7.61 minutes⁹

Annual water savings calculated as follows:

$$Savings = Ppl * Sh * 365 * Pr * (T_{base} * Fl_{base} - T_{eff} * Fl_{eff})$$

Where:

Ppl = Number of people per household.

Sh = Showers per capita per day.

365 = Days per year.

T_{base} = Showering time with base equipment (minutes)

T_{eff} = Showering time with efficient equipment (minutes).

Fl_{base} = As-used flow rate with base equipment (GPM)

Fl_{eff} = As-used flow rate with efficient equipment (GPM)

Pr = Percentage of showers where efficient equipment used.

Scenario **A**: Water savings were determined to be 24% over base equipment

Scenario **B**: Water savings were determined to be 32% over base equipment

$$PercentSavings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water consumed by showers with efficient equipment,

Scenario **A**: 34,002 litres (8,980 gallons)

Scenario **B**: 35,986 litres (9,504 gallons)

W_{base} = Annual water consumed by showers with base equipment:

Scenario **A**: 44,888 litres (11,856 gallons)

Scenario **B**: 53,154 litres (14,039 gallons)

⁵ As-used flow is calculated as a function of "full-on" or label flow: as-used flow = min{ 0.691+0.542*full-on flow, full-on flow}. Proctor, J. Gavelis, B. and Miller, B. *Savings and Showers: It's All in the Head*, (PGE) Home Energy Magazine, July/Aug 1994. Cited in Summit Blue (2008).

⁶ Summit Blue (2008).

⁷ Ibid, based on data from: Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007

⁸ Survey of participants, 116 from Enbridge, 111 from Union, Summit Blue (2008)

⁹ Relationship modeled as: Average shower length = 8.17 – 0.448 * as-used GPM. From Energy Center of Wisconsin Analysis of data from Resource Management Strategies, Inc., *Regional Municipality of York Water Efficiency Master Plan Update*, April 2007. Cited in Summit Blue (2008)

Other Input Assumptions

| | |
|---|--------------------------------------|
| Effective Useful Life (EUL) | 10 Years |
| Summit Blue (2008) suggests an EUL of 10 years based on a survey of five studies of showerheads in other jurisdictions (California – two studies, New England, Vermont, Arkansas). | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 13\$ |
| Incremental cost based on a survey of online retailers ¹⁰ . This does not include installation cost. | |
| Customer Payback Period (Natural Gas Only)¹¹ | A: 0.4 Years B: 0.2 Years |
| <p>Using a 5-year average commodity cost (avoided cost)¹² of \$0.38 / m³ and an average residential distribution cost¹³ of \$0.14 / m³, the payback period for natural gas savings is determined to be 0.4 years for Scenario A, and 0.2 years for Scenario B, based on the following:</p> <p>Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p>Scenario A = \$13/ (66 m³/year * \$0.52 / m³) = 0.4 years</p> <p>Scenario B = \$13/ (116 m³/year * \$0.52 / m³) = 0.2 years</p> | |
| Market Penetration | 65% |
| Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of low-flow showerheads of all flow rates across all sectors to be 65% ¹⁴ . | |

¹⁰ Earth Massage Showerhead 1.25 GPM

http://cgi.ebay.com/Earth-Massage-Showerhead-Water-Saver-1-25-gpm-flow_W0QQitemZ130256063752QQihZ003QQcategoryZ71282QQcmdZViewItemQQ_trksidZp1742.m153.l1262

¹¹ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹² 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹³ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁴ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Flex Your Power ¹⁵ | 72 | 10 | N/A | N/A |
| Comments Based on switching from a 2.2 GPM to a 1.5 GPM showerhead. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁶ | 71 | 10 | US\$ 36 | 75% |
| Comments Based on switching from a 4 GPM to a 2.5 GPM showerhead. Measure saves 13.9% of 514 m ³ required for water heating. | | | | |

¹⁵ http://www.fypower.org/res/tools/products_results.html?id=100160

¹⁶ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

26. Pipe Wrap – R4 (LIA)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Insulated hot water pipe for conventional gas storage tank-type hot water heater (R-4).

Base Equipment and Technologies Description

Conventional gas storage tank-type hot water heater without pipe wrap (R-1).

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------------------|---------------|
| Retrofit | Low-Income Residential (Existing) | Water heating |

Codes, Standards, and Regulations

N/A

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 18 | 0 | 0 | 2 | 0 |
| 2 | 18 | 0 | 0 | 0 | 0 |
| 3 | 18 | 0 | 0 | 0 | 0 |
| 4 | 18 | 0 | 0 | 0 | 0 |
| 5 | 18 | 0 | 0 | 0 | 0 |
| 6 | 18 | 0 | 0 | 0 | 0 |
| 7 | 18 | 0 | 0 | 0 | 0 |
| 8 | 18 | 0 | 0 | 0 | 0 |
| 9 | 18 | 0 | 0 | 0 | 0 |
| 10 | 18 | 0 | 0 | 0 | 0 |
| TOTALS | 180 | 0 | 0 | 2 | 0 |

Resource Savings Assumptions

Annual Natural Gas Savings

18 m³

Assumptions and inputs:

- Lacking any conclusive empirical data to suggest otherwise, Navigant Consulting has applied the same behavioural and base/efficient equipment assumptions to the Low-Income sector as to the Residential sector.
- Gas savings calculated using method set out in 2006 Massachusetts study¹ except where noted.
- Average water heater recovery efficiency: 0.76²
- Average household size: 3.1 persons³
- Assumed diameter of pipe to be wrapped: 0.75 inches
- Length of pipe to be wrapped: 6 feet.
- Surface area of pipe to be wrapped: 1.18 square feet.
- Ambient temperature around pipes: 16 °C (60 °F)⁴
- Average water heater set point temperature: 54 °C (130 °F)⁵
- Hot water temperature in outlet pipe: 52 °C (125 °F)⁶

Annual gas savings calculated as follows:

$$Savings = \left(\frac{1}{R_{base}} - \frac{1}{R_{eff}} \right) * Sa * (T_{pipe} - T_{amb}) * 24 * 365 * \frac{1}{EF} * 10^{-6} * 27.8$$

Where:

R_{base} = R-value of base equipment
 R_{eff} = R-value of efficient equipment
 Sa = Surface area of outlet pipe (ft²)
 T_{pipe} = Temperature of water in outlet pipe (°F)
 T_{amb} = Ambient temperature around pipe (°F)
 24 = Hours per day
 365 = Days per year
 EF = Water heater energy factor
 10^{-6} = Factor to convert Btu to MMBtu
 27.8 = Factor to convert MMBtu to m³

Gas savings were determined to be 75% over base measure

$$Percent Savings = \frac{(G_{base} - G_{eff})}{G_{base}}$$

¹ RLW Analytics, *Final Market Potential Report Of Massachusetts Owner Occupied 1-4 Unit Dwellings*, July 2006
http://www.cee1.org/eval/db_pdf/575.pdf

² Assumption used by Energy Center of Wisconsin, citing GAMA, Pigg, Scott, *Water Heater Savings Calculator*, 2003
www.doa.state.wi.us/docs_view2.asp?docid=2249

³ Summit Blue, *Resource Savings Values in Selected Residential DSM Prescriptive Programs*, June 2008.

⁴ RLW Analytics (2006). Given geographic proximity, Massachusetts temperatures used unchanged for Ontario.

⁵ As suggested by NRCAN: <http://oee.nrcan.gc.ca/residential/personal/new-homes/water-conservation.cfm?attr=4>

⁶ From source: "It is common to find a 5 - 10 F temperature drop from the water heater to the furthest fixtures in the house."
 Chinnery, G. *Policy recommendations for the HERS Community to consider regarding HERS scoring credit due to enhanced effective energy factors of water heaters resulting from volumetric hot water savings due to conservation devices/strategies*, EPA Energy Star for Homes, Sept 2006
http://www.energystar.gov/ia/partners/bldrs_lenders_raters/downloads/Volumetric_Hot_Water_Savings_Guidelines.pdf

| | |
|---|--------------|
| Where: | |
| G_{eff} = Annual natural gas use with efficient equipment, 8 m ³ G_{base} = Annual natural gas use with base equipment, 33 m ³ | |
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 0 L |
| Navigant has assumed that adopting the measure would not affect the quantity of water consumed. | |

Other Input Assumptions

| | |
|--|------------------|
| Effective Useful Life (EUL) | 10 Years |
| Based on the estimated measure lifetimes used in four other jurisdictions (Iowa - 15 years, Puget Sound Energy - 10 years, Efficiency Vermont – 10 years, and NYSERDA ⁷ – 10 years) Navigant recommends using an EUL of 10 years. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 2 \$ |
| Average equipment cost (for six feet of pipe wrap) based on communication with local hardware stores. | |
| Customer Payback Period (Natural Gas Only)⁸ | 0.2 Years |
| <p>Using an 5-year average commodity cost (avoided cost)⁹ of \$0.38 / m³ and an average residential distribution cost¹⁰ of \$0.14 / m³, the payback period for natural gas savings is determined to be 0.2 years, based on the following:</p> <p>Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="padding-left: 40px;">= \$2 / (18 m³/year * \$0.52 / m³)</p> <p style="padding-left: 40px;">= 0.2 years</p> | |
| Market Penetration | 47% |
| Based on previous research conducted for the OPA, Navigant Consulting estimates the market penetration of this measure to be 47% ¹¹ . | |

⁷ NYSERDA, New York Energy Smart Programs, *Deemed Savings Database*

⁸ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁹ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁰ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹¹ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| State of Iowa Utilities Board ¹² | 23 | 15 | 115 US\$ | 41% |
| Comments For addition of R-4 insulation to previously un-insulated pipes in the Low-Income sector. Measure saves 4% of 584 m ³ required for water heating. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Puget Sound Energy, 2007 ¹³ | 8 | 10 | 8 US\$ | 38% |
| Comments For addition of R-4 insulation to previously un-insulated pipes. Measure saves 1% of 759 m ³ required for water heating. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Midwest Energy Efficiency Alliance, 2003 ¹⁴ | 36 | N/A | N/A | 10.4% |
| Comments No indication given of percentage savings or base natural gas consumption for water heating. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Efficiency Vermont, 2006 ¹⁵ | N/A | 10 | 15 US\$ | N/A |
| Comments Only electricity savings reported (33 kWh) for an electric hot water system. Insulation upgrade not specified. No indication given of percentage savings or base natural gas consumption for water heating. | | | | |

¹² Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

¹³ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁴ Midwest Energy Efficiency Alliance, *Illinois Residential Market Analysis, Final Report*, May 12, 2003.

¹⁵ http://www.cee1.org/eval/db_pdf/390.pdf

¹⁵ Efficiency Vermont, *Technical Reference User Manual (TRM)*, February 2006

COMMERCIAL COOKING

27. Energy Star Commercial Fryer

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Energy Star commercial fryer (50% cooking efficiency¹)

Base Equipment and Technologies Description

Standard commercial fryer (35% cooking efficiency)

| Decision Type | Target Market(s) | End Use |
|-----------------|--|---------|
| New/Replacement | New/Existing Commercial buildings (Restaurant) | Cooking |

Codes, Standards, and Regulations

In order to be a certified Energy Star deep fryer, the fryer must have a minimum cooking efficiency of 50%, and a maximum idle energy rate of 9,000 Btu/hr². NRCan's Office of Energy Efficiency does not regulate commercial fryers.

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$/kBtu/hour) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|---|----------------------|--------------|--|--|
| | Natural Gas (m ³ /Btu/hour) | Electricity (kWh) | Water (L) | | |
| 1 | 913 | 0 | 0 | \$6,871 | \$4,223 |
| 2 | 913 | 0 | 0 | 0 | 0 |
| 3 | 913 | 0 | 0 | 0 | 0 |
| 4 | 913 | 0 | 0 | 0 | 0 |
| 5 | 913 | 0 | 0 | 0 | 0 |
| 6 | 913 | 0 | 0 | 0 | 0 |
| 7 | 913 | 0 | 0 | 0 | 0 |
| 8 | 913 | 0 | 0 | 0 | 0 |
| 9 | 913 | 0 | 0 | 0 | 0 |
| 10 | 913 | 0 | 0 | 0 | 0 |
| 11 | 913 | 0 | 0 | 0 | 0 |
| 12 | 913 | 0 | 0 | 0 | 0 |
| TOTALS | 10,956 | 0 | 0 | \$6,871 | \$4,223 |

¹ Cooking energy efficiency is defined as the quantity of energy input to the food products expressed as a percentage of the quantity of energy input to the appliance.

² Energy Star, *Commercial Fryers*, http://www.energystar.gov/index.cfm?c=fryers.pr_fryers

Resource Savings Assumptions

Annual Natural Gas Savings

913 m³

Assumptions and inputs used by Energy Star to calculate savings³:

- Input assumptions are listed below:

| Category | Value | Unit | Data Source |
|--|---------|-------------|-----------------------------------|
| Energy Star Qualified Unit | | | |
| Initial Cost | 6,871 | | FSTC [†] 2007, Union Gas |
| Cooking Energy Efficiency | 1 | | Energy Star Specification |
| Cooking Energy | 114,000 | Btu | Calculated |
| Production Capacity | 65 | lb/hour | FSTC 2004 |
| Idle Energy Rate | 9,000 | Btu/hour | Energy Star Specification |
| Total Idle Time | 9 | hour | Calculated |
| Idle Energy | 83,354 | Btu | Calculated |
| Energy to Food | 570 | Btu/lb | FSTC 2004 |
| Heavy Load | 3 | lb | FSTC 2004 |
| Preheat Energy | 15,500 | Btu | FSTC 2004 |
| Preheat Time | 15 | minutes | FSTC 2007 |
| Total Energy | 212,854 | Btu/day | Calculated |
| Lifetime | 12 | years | FSTC 2007 |
| Conventional Unit | | | |
| Initial Cost | 4,223 | | Union Gas, NCI* Estimate |
| Cooking Energy Efficiency | 0 | | FSTC 2004 |
| Cooking Energy | 162,857 | Btu | Calculated |
| Production Capacity | 60 | lb/hour | FSTC 2007 |
| Idle Energy Rate | 14,000 | Btu/hour | FSTC 2004 |
| Total Idle Time | 9 | hour | Calculated |
| Idle Energy | 127,867 | Btu | Calculated |
| Energy to Food | 570 | Btu/lb | FSTC 2004 |
| Heavy Load | 3 | lb | FSTC 2004 |
| Preheat Energy | 16,000 | Btu | FSTC 2004 |
| Preheat Time | 15 | minutes | FSTC 2007 |
| Total Energy | 306,724 | Btu/day | Calculated |
| Lifetime | 12 | years | FSTC 2007 |
| Maintenance | | | |
| Labor cost (per hour) | 20 | | EPA 2004 |
| Labor time (hours) | 0 | | EPA 2004 |
| Usage | | | |
| Average number of operating hours per day | 11 | hours/day | Union Gas |
| Average number of operating hours per year | 3,832 | hours/year | Calculated |
| Number of Days of operation | 347 | days/year | Union Gas |
| Number of Preheats per day | 1 | preheat/day | FSTC 2004 |
| Pounds of Food Cooked per day | 100 | lb/day | Union Gas |

[†] Food Service Technology Center

* Navigant Consulting, Inc.

- Natural gas consumption is calculated as the total gas required for cooking energy, idle energy and pre-heat energy. Based on the assumptions above the Energy Star savings calculator provides the following values for base and efficient equipment.

$$\text{Gas use (base)} = 1,064 \text{ (therms / year)} \times 2.8 \text{ m}^3/\text{therm} = 2,979.2 \text{ m}^3$$

³ Energy Star Savings Calculator for commercial gas fryers. Unless otherwise noted all assumptions and inputs that follow are drawn from this source: http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Commercial_Gas_Fryers.xls

| | |
|--|--------------|
| <p>Gas use (efficient) = $738 \text{ m}^3/\text{year} \times 2.8 \text{ m}^3/\text{therm} = 2,066.4 \text{ m}^3$</p> <ul style="list-style-type: none"> Gas savings were determined to be $2,979.2 \text{ m}^3 - 2,066.4 \text{ m}^3 = 912.8 \text{ m}^3$ or 30% over the base equipment. | |
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 0 L |
| N/A | |

Other Input Assumptions

| | |
|--|------------------|
| Effective Useful Life (EUL) | 12 Years |
| <p>The Minnesota Department of Commerce⁴ and Puget Sound Energy⁵ both estimate the EUL of this measure to be 15 years. The Consortium for Energy Efficiency⁶ and the State of Iowa Utilities Board⁷ both estimate the EUL of this measure to be 8 years. Union Gas reported⁸ 7 years in based on contacts with local contractors. Given the range of estimates, and given Energy Star's estimate of an EUL of 12 years for this measure, Navigant Consulting also estimates the EUL of this measure to be 12 years.</p> | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$2,648 |
| <ul style="list-style-type: none"> The incremental cost for an Energy Star fryer purchased from Garland Canada⁹ is \$5,000. The Consortium for Energy Efficiency reports an incremental cost¹⁰ of \$1,240 and the Minnesota Department of Commerce reports an incremental cost of \$2,125. Union Gas reported \$2,240 for the conventional fryers and \$3,740 for Energy Star fryers based on contacts with local contractors. Energy Star reported \$10,001 for Energy Star fryers and \$6206 for conventional fryers. Navigant Consulting estimates the incremental cost to be the average incremental costs reported by Union Gas and Energy Star, or approximately \$2,648. | |
| Customer Payback Period (Natural Gas Only)¹¹ | 5.8 Years |
| <p>Using a 5-year average commodity cost (avoided cost)¹² of $\\$0.38 / \text{m}^3$ and an average commercial distribution cost¹³ of $\\$0.12 / \text{m}^3$, the payback period for natural gas savings is determined to be 5.8 years, based on the following:</p> <p>Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="margin-left: 40px;">= $\\$2,648 / (913 \text{ m}^3/\text{year} \times \\$0.5 / \text{m}^3)$</p> <p style="margin-left: 40px;">= 5.8 years</p> | |
| Market Penetration¹⁴ | Medium |
| Based on the observation of medium penetration in two other jurisdictions (Washington State ¹⁵ – 15%, | |

⁴ Minnesota Department of Commerce, *Minnesota Deemed Savings Database*, Docket No. E,999/CIP-08-272

<https://www.edockets.state.mn.us/EFiling/ShowFile.do?DocNumber=4991781>

⁵ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

⁶ Erickson, K. et al, *Cooking Up a New Approach for Program Design II: A Recipe for Success*, Consortium for Energy Efficiency, 2008 <http://www.cee1.org/com/com-kit/files/CookingUpaNewApproachII.pdf>

⁷ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

⁸ Union Gas, Response to Navigant Consulting MEASURES AND ASSUMPTIONS FOR DEMAND SIDE MANAGEMENT (DSM) PLANNING, MARCH 13, 2009

⁹ Energy Star fryer: FPH-55, \$7,500, Base equipment: GF14, \$2,500

http://www.enodisusa.com/docs/uploaded/eno/ca/price_lists/Frymaster%20PL%202008.pdf

¹⁰ Where incremental cost was reported in U.S. dollars it has been converted to Canadian dollars using the exchange rate from February 2, 2009, or 1.24 Canadian dollars to the U.S. dollar.

¹¹ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹² 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹³ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁴ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%,

Iowa¹⁶ – 35%) and communication with a local distributor, Navigant Consulting estimates the penetration in Ontario to be medium.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|--|-------------------------------|----------------------------|--------------------------|
| State of Iowa Utilities Board ¹⁷ | 0.3 per ft ² (restaurant) | 8 | \$2,300 | 35% |
| Comments Energy Star fryer with 50% cooking efficiency replacing base equipment with 35% cooking efficiency. Measure saves 6.2% of 4.8 m ³ (1.73 therms) of gas per ft ² required for cooking. | | | | |
| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Puget Sound Energy ¹⁸ | 0.103 per ft ² (restaurant) | 15 | \$0.79 per ft ² | 15% |
| Comments Efficient equipment is a “power burner” fryer. No indication of base or efficient equipment cooking efficiencies is provided. Measure saves 4% of 2.6 m ³ (0.93 therms) of gas per ft ² required for cooking. | | | | |
| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Minnesota Department of Commerce ¹⁹ | 1,004 | 15 | \$1,714 | N/A |
| Comments The deemed savings database reports a standard fryer (122,000 BTUH) using 291.28 MMBtu/year and energy efficient fryer as using 255.16 MMBtu/year, equating to 36.12 MMBtu/year, or 1,004 m ³ . | | | | |

¹⁵ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁶ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

¹⁷ Ibid.

¹⁸ Quantec, *Comprehensive Demand-Side Management Resource Assessment*, Prepared for Puget Sound Energy, May 2007

¹⁹ Minnesota Department of Commerce, *Minnesota Deemed Savings Database*, Docket No. E,999/CIP-08-272

<https://www.edockets.state.mn.us/EFiling/ShowFile.do?DocNumber=4991781>

28. High Efficiency Commercial Griddle

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

High efficiency commercial griddle (40% cooking efficiency with heavy load¹)

Base Equipment and Technologies Description

Standard commercial griddle (32% cooking efficiency)

| Decision Type | Target Market(s) | End Use |
|---------------|--|---------|
| Retrofit/New | New/Existing Commercial buildings (Restaurant) | Cooking |

Codes, Standards, and Regulations

An Energy Star specification for commercial griddles is due to be launched in April 2009².
NRCAN's Office of Energy Efficiency does not regulate commercial griddles.

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$/kBtu/hour) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|---|----------------------|--------------|--|--|
| | Natural Gas (m ³ /Btu/hour) | Electricity (kWh) | Water (L) | | |
| 1 | 503 | 0 | 0 | \$8,570 | \$7,000 |
| 2 | 503 | 0 | 0 | 0 | 0 |
| 3 | 503 | 0 | 0 | 0 | 0 |
| 4 | 503 | 0 | 0 | 0 | 0 |
| 5 | 503 | 0 | 0 | 0 | 0 |
| 6 | 503 | 0 | 0 | 0 | 0 |
| 7 | 503 | 0 | 0 | 0 | 0 |
| 8 | 503 | 0 | 0 | 0 | 0 |
| 9 | 503 | 0 | 0 | 0 | 0 |
| 10 | 503 | 0 | 0 | 0 | 0 |
| 11 | 503 | 0 | 0 | 0 | 0 |
| 12 | 503 | 0 | 0 | 0 | 0 |
| TOTALS | 6,036 | 0 | 0 | \$8,570 | \$7,000 |

¹ Cooking energy efficiency is defined as the quantity of energy input to the food products expressed as a percentage of the quantity of energy input to the appliance.

² EPA update on Draft 1 Development , Nov 19, 2008,

[http://www.energystar.gov/ia/partners/prod_development/new_specs/downloads/comm_griddles/Griddle_Draft1_Status_Update.p
df](http://www.energystar.gov/ia/partners/prod_development/new_specs/downloads/comm_griddles/Griddle_Draft1_Status_Update.pdf)

Resource Savings Assumptions

| | |
|---|--------------------------|
| Annual Natural Gas Savings | 503 m³ |
| <p>Assumptions and inputs used by Pacific Gas and Electric's (PG&E) Food Service Technology Center (FSTC) to calculate savings³:</p> <ul style="list-style-type: none"> The FSTC calculator's default assumption is that the griddle is used 12 hours a day. Energy Star⁴ and the Federal Energy Management Program (FEMP)⁵ both also assume that 12 hours of operation per day. An FSTC report on a specific model of griddle, however, found that in a production-test kitchen serving two meals per day the griddle was in operation an average of eight hours per day⁶. To account for restaurants operating with extended hours or serving three (griddle-prepared) meals per day, Navigant Consulting has assumed 10 hours (the average of both reported values) of operation per day. The FSTC calculator assumes a production capacity of 25 lbs/hour for the base griddle and 44 lbs/hour for the high efficiency griddle. Navigant Consulting has therefore modified the base production capacity to match that of the high efficiency griddle to more accurately compare gas use. The base equipment is assumed to have an idle energy rate of 18,000 Btu/hr and a pre-heat energy rate of 20,000 Btu/hr (FSTC and Energy Star default assumption). The efficient equipment is assumed to adhere to FEMP guidelines and have an idle energy rate of 16,000 Btu/hr and a pre-heat energy rate of 15,000 Btu/hr. <p>Natural gas use with base equipment, given assumptions and inputs detailed above: 3,061 m³ (1,101 therms).</p> <p>Natural gas use with efficient equipment, given assumptions and inputs detailed above: 2,558 m³ (920 therms).</p> <ul style="list-style-type: none"> Annual gas savings were determined to be 503 m³ or approximately 16% over the base equipment. | |
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 0 L |
| N/A | |

³ Gas Griddle Life-Cycle Cost Calculator, default assumptions are used except where otherwise noted.

<http://www.foodservicetechnologycenter.com/saveenergy/tools/calculators/ggridcalc.php>

Note that the savings calculated for the two default (base and high efficiency) cases are identical to those presented in the Energy Star Commercial Food Service – Energy and Water Performance Upgrades available in the Commercial Best Practices section of the Energy Star web-site, http://www.energystar.gov/ia/products/commercial_food_service/CFS_Full_Service.xls

⁴ Energy Star Commercial Food Service – Energy and Water Performance Upgrades available in the Commercial Best Practices section of the Energy Star web-site, http://www.energystar.gov/ia/products/commercial_food_service/CFS_Full_Service.xls

⁵ U.S. DOE, FEMP, *FEMP designated product: Griddles*

http://www1.eere.energy.gov/femp/procurement/eeep_gas_griddles.html#buyertips

⁶ Cadotte, B. and D. Zabrowski, *Toastmaster Accu-Miser Model AM36SS Electric Griddle: In-Kitchen Appliance Performance Report*, Food Service Technology Center, January 1999.

http://www.fishnick.com/publications/appliancereports/griddles/Toastmaster_AM36SS_Griddle_in_kitchen.pdf

Other Input Assumptions

| | |
|--|------------------|
| Effective Useful Life (EUL) | 12 Years |
| The Minnesota Department of Commerce ⁷ estimates the EUL of this measure to be 15 years. The State of Iowa Utilities Board ⁸ , Energy Star and FEMP all estimate the EUL of this measure to be 12 years. Given that the majority of the agencies recommend using 12 years and given their relative expertise, Navigant Consulting also estimates the EUL of this measure to be 12 years. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$1,570 |
| Energy Star ⁹ estimates the cost of base equipment to be \$2,480 (\$US 2,000) and the cost of the efficient equipment to be \$3,925 (\$US 3,165) ¹⁰ for an incremental cost of \$1,445. The Garland CG-36R 01 (heavy-load cooking efficiency- 40.7%, production capacity – 46.2 lbs/hour, rated input – 90 kBtu/hour) has a dealer-recommended price of \$9,490 ¹¹ . The FSTC assessment of a Lang griddle (heavy-load cooking efficiency – 31.7%, production capacity – 43.2 lbs/hour, rated input – 81kBtu/hour) does not specify a model number, however the specifications listed appear to match those of the Lang 236T which has a suggested price of \$7,795 (\$US 6,286) ¹² . This implies an incremental cost of \$1,695. Navigant Consulting estimates the incremental price as the average of these figures, or \$1,570 | |
| Customer Payback Period (Natural Gas Only)¹³ | 6.2 Years |
| Using a 5-year average commodity cost (avoided cost) ¹⁴ of \$0.38 / m ³ and an average commercial distribution cost ¹⁵ of \$0.12 / m ³ , the payback period for natural gas savings is determined to be 6.2 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$1,570 / (503 m ³ /year * \$0.5 / m ³) = 6.2 years | |
| Market Penetration¹⁶ | Medium |
| Based on the observation of medium penetration in another jurisdiction (Iowa ¹⁷ – 25%) and on the observation that a large percentage of griddles tested by the FSTC are high efficiency, Navigant Consulting estimates the penetration in Ontario to be medium. | |

⁷ Minnesota Department of Commerce, *Minnesota Deemed Savings Database*, Docket No. E,999/CIP-08-272

<https://www.edockets.state.mn.us/EFiling/ShowFile.do?DocNumber=4991781>

⁸ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

⁹ Energy Star Commercial Food Service – Energy and Water Performance Upgrades available in the Commercial Best Practices section of the Energy Star web-site, http://www.energystar.gov/ia/products/commercial_food_service/CFS_Full_Service.xls

¹⁰ Cowen, D. and D. Zabrowski, *Garland CG-36R Gas Griddle Performance Test*, Food Service Technology Center, 2002.

http://www.fishnick.com/publications/appliancereports/griddles/Garland_CG-36R_Griddle.pdf

¹¹ Garland, *Price List Canada, 2008*

http://www.enodisusa.com/docs/uploaded/eno/ca/price_lists/Gar%20USRange%20PL%202008.pdf

¹² Lang, 2009 Price List, <http://www.langworld.com/Content/PriceLists/PriceListLangComm2009.pdf>

¹³ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹⁴ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁵ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁶ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁷ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|--|-------------------------------|-----------------------|--------------------------|
| State of Iowa Utilities Board ¹⁸ | 0.024 per ft ² (restaurant) | 12 | \$2,538 | 25% |
| Comments High efficiency griddle with 40% cooking efficiency replacing base equipment with 32% cooking efficiency. Measure saves 0.5% of 4.8 m ³ (1.73 therms) of gas per ft ² required for cooking. | | | | |
| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Energy Star Commercial Best Practices ¹⁹ | 170 | 12 | \$1,444 | N/A |
| Comments High efficiency griddle with 40% cooking efficiency replacing base equipment with 32% cooking efficiency. | | | | |
| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| New York Energy \$mart – Deemed Savings Database ²⁰ | 806 | 10 | \$1,240 | N/A |
| Comments High efficiency griddle with 45% cooking efficiency replacing base equipment with 30% cooking efficiency. | | | | |

¹⁸ Ibid.

¹⁹ Energy Star Commercial Food Service – Energy and Water Performance Upgrades, http://www.energystar.gov/ia/products/commercial_food_service/CFS_Full_Service.xls

²⁰ NYSERDA Deemed Savings Database, revision 12, 2008.

COMMERCIAL SPACE HEATING

29. Air Curtains – Single Door (8' x 6')

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Air curtains in retail, office and institutional buildings are used to reduce infiltration of cold outside air through doorways. A reduction in air infiltration means a reduction in natural gas heating during heating season and a reduction in air conditioning during the summer season.

Base Equipment and Technologies Description

Retail, office and institutional buildings without air curtains.

| Decision Type | Target Market(s) | End Use |
|---------------|--|---------------|
| Retrofit | Retail, Office and Institutional Buildings | Space Heating |

Codes, Standards, and Regulations

N/A

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 667 | 172 | 0 | 1,650 | 0 |
| 2 | 667 | 172 | 0 | 0 | 0 |
| 3 | 667 | 172 | 0 | 0 | 0 |
| 4 | 667 | 172 | 0 | 0 | 0 |
| 5 | 667 | 172 | 0 | 0 | 0 |
| 6 | 667 | 172 | 0 | 0 | 0 |
| 7 | 667 | 172 | 0 | 0 | 0 |
| 8 | 667 | 172 | 0 | 0 | 0 |
| 9 | 667 | 172 | 0 | 0 | 0 |
| 10 | 667 | 172 | 0 | 0 | 0 |
| 11 | 667 | 172 | 0 | 0 | 0 |
| 12 | 667 | 172 | 0 | 0 | 0 |
| 13 | 667 | 172 | 0 | 0 | 0 |
| 14 | 667 | 172 | 0 | 0 | 0 |
| 15 | 667 | 172 | 0 | 0 | 0 |
| TOTALS | 10,005 | 2,580 | 0 | 1,650 | 0 |

Resource Savings Assumptions

Annual Natural Gas Savings

667 m³

Natural gas savings reflect reduced heating load; less outside cold air passes through doors. Savings are estimated based on the following assumptions:

| Variable Names | Symbol | Value | Source |
|---|------------------|----------------------|--------------|
| Inside Temperature for heating season | T _{IH} | 68 °F | NCI estimate |
| Inside Temperature for cooling season | T _{IC} | 72 °F | NCI estimate |
| Average outside temperature in heating season | T _{OH} | 29.27 °F | NCI estimate |
| Average outside temperature in cooling season | T _{OC} | 77.00 °F | NCI estimate |
| Hours per day that door is open | HR | 1 hour | NCI estimate |
| Days per week that door is in use | DPW | 7 Days | NCI estimate |
| Door Height | H | 8 feet | NCI estimate |
| Door Width | W | 6 feet | NCI estimate |
| Total horsepower of air curtain | HP | 0.5 hp | NCI estimate |
| Air curtain cfm at nozzle | Q ₀ | 1005 cfm | NCI estimate |
| Air curtain nozzle depth | NZ | 2.75 inches | NCI estimate |
| Door coefficient | DC | 0.3 | NCI estimate |
| Days per heating season | DPS _H | 120 Days | NCI estimate |
| Days per cooling season | DPS _C | 100 Days | NCI estimate |
| Average wind velocity for heating season | V _{WH} | 2.6 mph ¹ | NCI estimate |
| Average wind velocity for cooling season | V _{WC} | 2.1 mph | NCI estimate |
| Energy Efficiency Ratio for A/C Unit | EER | 12 Btu/Watt-hour | NCI estimate |

During Heating Season

Doorway Calculations Without Air Curtain for Heating Season:

- Air entering doorway due to wind², $Q_W = V_{WH} \times H \times W \times DC \times 88 \text{ fpm/mph} = 3,295 \text{ cfm}$
- Air entering doorway due to inside/outside temperature difference, $Q_{TD} = [68.094 + 0.4256(T_i - T_{OH})] \times H \times W \times \sqrt{H(T_i - T_{OH})} / (T_i + 460) = 3,110 \text{ cfm}$
- Total air entering doorway, $Q_T = Q_W + Q_{TD} = 6,405 \text{ cfm}$
- Heat lost at doorway without air curtain $q_D = 1.1 \times Q_T \times (T_i - T_{OH}) = 272,856 \text{ Btu/hr}$

Doorway Calculations With Air Curtain for Heating Season:

- Total air flow rate at the door, $Q_E = 0.4704 Q_0 (\sqrt{H}/NZ) - Q_0 = 1,788 \text{ cfm}$
- Heat lost at doorway using air curtain, $q_{AC} = 1.1 \times Q_E \times (T_i - T_{OH}) = 76,183 \text{ Btu/hr}$

Heat Loss Prevented Per Year Using Air Curtain for Heating Season:

- $q_s = (q_D - q_{AC}) \times HR \times DPS_H \times (DPW/7) = 23.60 \text{ MMBtu} = 667 \text{ m}^3 \text{ natural gas.}$
- Baseline estimates of natural gas consumption: heat lost at doorway without air curtains = $q_D \times HR \times DPS_H \times (DPW/7) = 32.74 \text{ MMBtu} = 925 \text{ m}^3$.
- Natural Gas Savings % = 72.1%

Annual Electricity Savings

172 kWh

- Electricity savings are a result of the following factors:

¹ An average daily wind speed of 17 km/h for winter season and 14 km/h for summer season for Pearson Airport was estimated based on Environment Canada monitoring data (Environment Canada, http://www.climate.weatheroffice.ec.gc.ca/climateData/hourlydata_e.html?timeframe=1&Prov=ON&StationID=5097&Year=2009&Month=3&Day=29). To adjust for the appropriate height and geographic characteristics for a regular building door in Greater Toronto Area, a 25% factor is applied to estimate a typical urban wind speed

² ASHRAE Handbook 2001 Fundamentals Ch.26

| | |
|--|------------|
| <ul style="list-style-type: none"> - Reduced AC load - Increased electricity use to operate air curtain. • Based on the Enbridge 2007 DSM program Air Door projects for various small commercial sites, electricity savings were calculated using Agviro Air Door Calculator. Based on their reported results, the average savings is determined to be 172 kWh. | |
| Annual Water Savings | 0 L |
| N/A | |

Other Input Assumptions

| | |
|---|-----------------|
| Effective Useful Life (EUL) | 15 Years |
| This EUL was developed in conjunction with equipment manufacturers by Union Gas. It is also confirmed by SEED Program Guidelines ³ . | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$ 1,650 |
| This O&M cost was developed with conjunction with equipment manufacturers by Union Gas. | |
| Customer Payback Period (Natural Gas Only)⁴ | 5 Years |
| <p>Using a 5-year average commodity cost (avoided cost)⁵ of \$0.38 / m³ and an average commercial distribution cost⁶ of \$0.12 / m³, the payback period for natural gas savings is determined to be 5 years, based on the following:</p> <p>Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="margin-left: 40px;">= \$1,650 / (667 m³/year * \$0.5 / m³)</p> <p style="margin-left: 40px;">≈ 5 years</p> | |
| Market Penetration⁷ | Medium |
| Based on communication with local contractors, Navigant Consulting estimates a medium market penetration in Ontario. | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Berner Energy Calculator ⁸ | 2,092 | N/A | 2,000 | N/A |
| Comments This is a typical application during winter months. Based on the same assumptions stated above in the Annual Electricity Savings table, the saved annual natural gas is 74 MMBtu, which is equivalent to 2,092 m ³ . | | | | |

³ Cost Effectiveness Analysis, SEED Program Guidelines. <http://www.oregon.gov/ENERGY/CONS/SEED/docs/AppendixJ.pdf>

⁴ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁵ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁶ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

⁷ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

⁸ Berner Calculator, <http://www.berner.com/sales/energy.php5>

30. Air Curtains – Double Door (2 x 8' x 6')

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Air curtains in retail, office and institutional buildings are used to reduce infiltration of cold outside air through doorways. A reduction in air infiltration means a reduction in natural gas heating during heating season and a reduction in air conditioning during the summer season.

Base Equipment and Technologies Description

Retail, office and institutional buildings without air curtains.

| Decision Type | Target Market(s) | End Use |
|---------------|--|---------------|
| Retrofit | Retail, Office and Institutional Buildings | Space Heating |

Codes, Standards, and Regulations

N/A

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 1,529 | 1,023 | 0 | 2,500 | 0 |
| 2 | 1,529 | 1,023 | 0 | 0 | 0 |
| 3 | 1,529 | 1,023 | 0 | 0 | 0 |
| 4 | 1,529 | 1,023 | 0 | 0 | 0 |
| 5 | 1,529 | 1,023 | 0 | 0 | 0 |
| 6 | 1,529 | 1,023 | 0 | 0 | 0 |
| 7 | 1,529 | 1,023 | 0 | 0 | 0 |
| 8 | 1,529 | 1,023 | 0 | 0 | 0 |
| 9 | 1,529 | 1,023 | 0 | 0 | 0 |
| 10 | 1,529 | 1,023 | 0 | 0 | 0 |
| 11 | 1,529 | 1,023 | 0 | 0 | 0 |
| 12 | 1,529 | 1,023 | 0 | 0 | 0 |
| 13 | 1,529 | 1,023 | 0 | 0 | 0 |
| 14 | 1,529 | 1,023 | 0 | 0 | 0 |
| 15 | 1,529 | 1,023 | 0 | 0 | 0 |
| TOTALS | 22,935 | 15,345 | 0 | 2,500 | 0 |

Resource Savings Assumptions

Annual Natural Gas Savings

1,529 m³

Natural gas savings reflect reduced heating load; less outside cold air passes through. Savings are estimated based on the following assumptions:

| Variable Names | Symbol | Value | Source |
|---|------------------|----------------------|--------------|
| Inside Temperature for heating season | T _{IH} | 68 °F | NCI estimate |
| Inside Temperature for cooling season | T _{IC} | 72 °F | NCI estimate |
| Average outside temperature in heating season | T _{OH} | 29.27 °F | NCI estimate |
| Average outside temperature in cooling season | T _{OC} | 77.00 °F | NCI estimate |
| Hours per day that door is open | HR | 1 hour | NCI estimate |
| Days per week that door is in use | DPW | 7 Days | NCI estimate |
| Door Height | H | 8 ' | NCI estimate |
| Door Width | W | 2 x 6 ' | NCI estimate |
| Total horsepower of air curtain | HP | 0.5 hp | NCI estimate |
| Air curtain cfm at nozzle | Q ₀ | 1005 cfm | NCI estimate |
| Air curtain nozzle depth | NZ | 2.75 " | NCI estimate |
| Door coefficient | DC | 0.3 | NCI estimate |
| Days per heating season | DPS _H | 120 Days | NCI estimate |
| Days per cooling season | DPS _C | 100 Days | NCI estimate |
| Average wind velocity for heating season | V _{WH} | 2.6 mph ¹ | NCI estimate |
| Average wind velocity for cooling season | V _{WC} | 2.1 mph | NCI estimate |
| Energy Efficiency Ratio for A/C Unit | EER | 12 Btu/Watt-hour | NCI estimate |

During Heating Season

Doorway Calculations Without Air Curtain for Heating Season:

- Air entering doorway due to wind², $Q_W = V_{WH} \times H \times W \times DC \times 88 \text{ fpm/mph} = 6,589 \text{ cfm}$
- Air entering doorway due to inside/outside temperature difference, $Q_{TD} = [68.094 + 0.4256(T_{IH} - T_{OH})] \times H \times W \times \sqrt{H(T_{IH} - T_{OH})} / (T_{IH} + 460) = 6,220 \text{ cfm}$
- Total air entering doorway, $Q_T = Q_W + Q_{TD} = 12,809 \text{ cfm}$
- Heat lost at doorway without air curtain $q_D = 1.1 \times Q_T \times (T_{IH} - T_{OH}) = 545,713 \text{ Btu/hr}$

Doorway Calculations With Air Curtain for Heating Season:

- Total air flow rate at the door, $Q_E = 0.4704 Q_0 (\sqrt{H/NZ}) - Q_0 = 1,788 \text{ cfm}$
- Heat lost at doorway using air curtain, $q_{AC} = 1.1 \times Q_E \times (T_{IH} - T_{OH}) = 76,183 \text{ Btu/hr}$

Heat Loss Prevented Per Year Using Air Curtain for Heating Season:

- $q_s = (q_D - q_{AC}) \times HR \times DPS_H \times (DPW/7) = 56.34 \text{ MMBtu} = 1,592 \text{ m}^3 \text{ natural gas.}$
- Baseline estimates of natural gas consumption: heat lost at doorway without air curtains = $q_D \times HR \times DPS_H \times (DPW/7) = 65.49 \text{ MMBtu} = 1,851 \text{ m}^3$.
- Natural Gas Savings % = $1,529 \text{ m}^3 / 1,851 \text{ m}^3 = 86\%$

Annual Electricity Savings

1,023 kWh

- Electricity savings are a result of the following factors:

¹ An average daily wind speed of 17 km/h for winter season and 14 km/h for summer season for Pearson Airport was estimated based on Environment Canada monitoring data (Environment Canada, http://www.climate.weatheroffice.ec.gc.ca/climateData/hourlydata_e.html?timeframe=1&Prov=ON&StationID=5097&Year=2009&Month=3&Day=29). To adjust for the appropriate height and geographic characteristics for a regular building door in Greater Toronto Area, a 25% factor is applied to estimate a typical urban wind speed

² ASHRAE Handbook 2001 Fundamentals Ch.26

| | |
|--|------------|
| <ul style="list-style-type: none"> - Reduced AC load - Increased electricity use to operate air curtain. • Based on the Enbridge 2007 DSM program Air Door projects at various small commercial sites, electricity savings were calculated using Agviro air door calculator. The average result is estimated to be 1,023 kWh. | |
| Annual Water Savings | 0 L |
| N/A | |

Other Input Assumptions

| | |
|--|------------------|
| Effective Useful Life (EUL) | 15 Years |
| This EUL was developed in conjunction with equipment manufacturers by Union Gas. It is also confirmed by SEED Program Guidelines ³ . | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$ 2,500 |
| This O&M cost was developed in conjunction with equipment manufacturers by Union Gas. | |
| Customer Payback Period (Natural Gas Only)⁴ | 3.3 Years |
| <p>Using a 5-year average commodity cost (avoided cost)⁵ of \$0.38 / m³ and an average commercial distribution cost⁶ of \$0.12 / m³, the payback period for natural gas savings is determined to be 3.3 years, based on the following:</p> <p>Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="margin-left: 40px;">= \$2500 / (1,529 m³/year * \$0.5 / m³)</p> <p style="margin-left: 40px;">= 3.3 years</p> | |
| Market Penetration⁷ | Medium |
| Based on communication with local contractors, Navigant Consulting estimates a medium market penetration in Ontario. | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Berner Energy Calculator ⁸ | 4,946 | N/A | 2,500 | N/A |
| Comments Based on the same assumptions used above, for a typical application during the winter season, the annual natural gas savings are determined to be 175 MMBtu, or 4,946 m ³ . | | | | |

³ Cost Effectiveness Analysis, SEED Program Guidelines. <http://www.oregon.gov/ENERGY/CONS/SEED/docs/AppendixJ.pdf>

⁴ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁵ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁶ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

⁷ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

⁸ Berner Calculator, <http://www.berner.com/sales/energy.php5>

31. Condensing Boilers

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Condensing boiler with 88% estimated seasonal efficiency

Base Equipment and Technologies Description

Non-condensing boiler with 76% estimated seasonal efficiency

| Decision Type | Target Market(s) | End Use |
|---------------|-------------------------------|---------------|
| Retrofit | Existing Commercial buildings | Space Heating |

Codes, Standards, and Regulations

- ASHRAE Standard 155P: test and calculation procedures result in an application-specific seasonal efficiency of commercial space heating boiler systems.
- ASHRAE Standard 90.1-2004: minimum boiler efficiencies for buildings except low-rise residential buildings.

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$/kBtu/hour) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|---|----------------------|--------------|--|--|
| | Natural Gas (m ³ /Btu/hour) | Electricity (kWh) | Water (L) | | |
| 1 | 0.01 | 0 | 0 | 12 | 0 |
| 2 | 0.01 | 0 | 0 | 0 | 0 |
| 3 | 0.01 | 0 | 0 | 0 | 0 |
| 4 | 0.01 | 0 | 0 | 0 | 0 |
| 5 | 0.01 | 0 | 0 | 0 | 0 |
| 6 | 0.01 | 0 | 0 | 0 | 0 |
| 7 | 0.01 | 0 | 0 | 0 | 0 |
| 8 | 0.01 | 0 | 0 | 0 | 0 |
| 9 | 0.01 | 0 | 0 | 0 | 0 |
| 10 | 0.01 | 0 | 0 | 0 | 0 |
| 11 | 0.01 | 0 | 0 | 0 | 0 |
| 12 | 0.01 | 0 | 0 | 0 | 0 |
| 13 | 0.01 | 0 | 0 | 0 | 0 |
| 14 | 0.01 | 0 | 0 | 0 | 0 |
| 15 | 0.01 | 0 | 0 | 0 | 0 |
| 16 | 0.01 | 0 | 0 | 0 | 0 |
| 17 | 0.01 | 0 | 0 | 0 | 0 |
| 18 | 0.01 | 0 | 0 | 0 | 0 |
| 19 | 0.01 | 0 | 0 | 0 | 0 |
| 20 | 0.01 | 0 | 0 | 0 | 0 |
| 21 | 0.01 | 0 | 0 | 0 | 0 |
| 22 | 0.01 | 0 | 0 | 0 | 0 |
| 23 | 0.01 | 0 | 0 | 0 | 0 |
| 24 | 0.01 | 0 | 0 | 0 | 0 |
| 25 | 0.01 | 0 | 0 | 0 | 0 |
| TOTALS | 0.25 | 0 | 0 | 12 | 0 |

Resource Savings Assumptions

Annual Natural Gas Savings

0.0104 m³/Btu/hr

- The natural gas savings are based on the reduction in space heating gas consumption from using a condensing boiler instead of a non-condensing boiler.
- For condensing and non-condensing boilers, Fuel Consumption = Design Heat Loss (Btu/year) / Boiler efficiency / Natural Gas Low Heating Value¹ (Btu/m³)
- Estimated seasonal efficiency is 76% for non-condensing boilers and 88% for condensing boilers².
- Design Heat Loss is calculated using degree days analysis (full year) for London, ON and Sudbury, ON. The single saving number is weighted average of Union Gas South (London, 70%) and Union Gas North (Sudbury, 30%) based on the customer population of Union Gas service territories.

Example: a 300,000 Btu/hr condensing boiler located in London or Sudbury

Assuming the following specifications for a condensing boiler located in London, ON

| Variables | Values |
|-------------------------|---------|
| Boiler Input (Btu/hr) | 300,000 |
| Oversizing | 1.2 |
| Boiler Operating Factor | 90% |

- Heat Loss = (Boiler Input x Boiler Operating Factor) / Oversizing = 225,000 Btu/hr
- In general, Natural Gas Low Heating Value = 35,310 Btu/m³
- Historically, London experiences 42 hours/year at -5°F. Design Heat Loss per Year at this temperature = 225,000 Btu/hr x 42 hours = 9,450,000 Btu
- For conventional boilers (76% efficiency), natural gas consumption at -5°F = 9,450,000 Btu / 76% / Natural Gas Low Heating Value = 352 m³/year.
- For condensing boilers (88% efficiency), natural gas consumption at -5°F = 9,450,000 Btu / 76% / Natural Gas Low Heating Value = 304 m³/year.
- Design Heat Losses at different temperatures (t) are extrapolated based on assumed linear relationship with 225,000 Btu/hr (@-5°F) using 225,000 Btu/hr x (65-t)/[65-(-5)]
- The following tables are constructed to calculate the natural gas consumptions at all temperatures for a whole year.

¹ Natural gas lower heating value – the lower heating value (also known as net calorific value, net CV, or LHV) of a fuel is defined as the amount of heat released by combusting a specified quantity (initially at 25 °C or another reference state) and returning the temperature of the combustion products to 150 °C, given as 35,310 Btu/m³.

² Seasonal efficiencies are estimates based on "Boiler System Efficiency", Thomas H. Durkin, ASHRAE Journal, July 2006

| | | | | | Fuel Consumption | |
|-----------------------|-------|--------|------------------|--------------------|---------------------|--------------------|
| Temperature Intervals | | London | Design Heat Loss | | Conventional Boiler | Condensing Boiler |
| Temp (*F) | Range | Hours | Btu/hr | Btu/year | m ³ /yr | m ³ /yr |
| -20 | -15 | 4 | | | | |
| -15 | -10 | 8 | | | | |
| -10 | -5 | 17 | | | | |
| -5 | 0 | 42 | 225,000 | 9,450,000 | 352 | 304 |
| 0 | 5 | 87 | 208,929 | 18,176,786 | 677 | 585 |
| 5 | 10 | 152 | 192,857 | 29,314,286 | 1,092 | 943 |
| 10 | 15 | 281 | 176,786 | 49,676,786 | 1,851 | 1,599 |
| 15 | 20 | 337 | 160,714 | 54,160,714 | 2,018 | 1,743 |
| 20 | 25 | 435 | 144,643 | 62,919,643 | 2,345 | 2,025 |
| 25 | 30 | 584 | 128,571 | 75,085,714 | 2,798 | 2,416 |
| 30 | 35 | 948 | 112,500 | 106,650,000 | 3,974 | 3,432 |
| 35 | 40 | 735 | 96,429 | 70,875,000 | 2,641 | 2,281 |
| 40 | 45 | 634 | 80,357 | 50,946,429 | 1,898 | 1,640 |
| 45 | 50 | 622 | 64,286 | 39,985,714 | 1,490 | 1,287 |
| 50 | 55 | 643 | 48,214 | 31,001,786 | 1,155 | 998 |
| 55 | 60 | | 32,143 | 0 | 0 | 0 |
| 60 | 65 | | 16,071 | 0 | 0 | 0 |
| Total | | | | 598,242,857 | 22,293 | 19,253 |

- The operating hours for boilers in London are based on the Union Gas program record.
- Natural Gas savings for condensing boilers in London = $22,293 \text{ m}^3 - 19,253 \text{ m}^3 = 3,040 \text{ m}^3$
- The same calculation is repeated for a 300,000 Btu/hr boiler in Sudbury as below:

| | | | | | Fuel Consumption | |
|-----------------------|-------|---------|------------------|--------------------|---------------------|--------------------|
| Temperature Intervals | | Sudbury | Design Heat Loss | | Conventional Boiler | Condensing Boiler |
| Temp (*F) | Range | Hours | Btu/hr | Btu/year | m ³ /yr | m ³ /yr |
| -35 | -30 | 2 | | | | |
| -30 | -25 | 7 | | | | |
| -25 | -20 | 20 | | | | |
| -20 | -15 | 46 | 225000 | 10350000 | 386 | 333 |
| -15 | -10 | 99 | 211765 | 20964705.88 | 781 | 675 |
| -10 | -5 | 159 | 198529 | 31566176.47 | 1176 | 1016 |
| -5 | 0 | 221 | 185,294 | 40,950,000 | 1,526 | 1,318 |
| 0 | 5 | 272 | 172,059 | 46,800,000 | 1,744 | 1,506 |
| 5 | 10 | 345 | 158,824 | 54,794,118 | 2,042 | 1,763 |
| 10 | 15 | 380 | 145,588 | 55,323,529 | 2,062 | 1,780 |
| 15 | 20 | 437 | 132,353 | 57,838,235 | 2,155 | 1,861 |
| 20 | 25 | 502 | 119,118 | 59,797,059 | 2,228 | 1,924 |
| 25 | 30 | 658 | 105,882 | 69,670,588 | 2,596 | 2,242 |
| 30 | 35 | 748 | 92,647 | 69,300,000 | 2,582 | 2,230 |
| 35 | 40 | 584 | 79,412 | 46,376,471 | 1,728 | 1,493 |
| 40 | 45 | 537 | 66,176 | 35,536,765 | 1,324 | 1,144 |
| 45 | 50 | 605 | 52,941 | 32,029,412 | 1,194 | 1,031 |
| 50 | 55 | 665 | 39,706 | 26,404,412 | 984 | 850 |
| 55 | 60 | | 26,471 | 0 | 0 | 0 |
| 60 | 65 | | 13,235 | 0 | 0 | 0 |
| Total | | | | 657,701,471 | 24,509 | 21,166 |

- Natural Gas savings for condensing boilers in Sudbury = $24,509 \text{ m}^3 - 21,166 \text{ m}^3 = 3,342 \text{ m}^3$
- Based on 70% (London) and 30% (Sudbury) mix, the weighted average of natural gas savings = $70\% \times 3040 + 30\% \times 3342 = 3,131 \text{ m}^3$.
- Therefore, the natural gas savings = $3,131 \text{ m}^3$

| | |
|---|--------------|
| <ul style="list-style-type: none"> On a per Btu/hour basis, NG savings = $3,131 \text{ m}^3 / 300,000 \text{ Btu/hour} = 0.0104 \text{ m}^3/\text{Btu/hour}$. Baseline conventional boiler consumption = $70\% \times 22,293 + 30\% \times 24,509 = 22,958 \text{ m}^3$. Natural Gas Savings % = $3,131 \text{ m}^3 / 22,958 \text{ m}^3 = 13.6 \%$ | |
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 0 L |
| N/A | |

Other Input Assumptions

| | |
|---|--------------------------|
| Effective Useful Life (EUL) | 25 Years |
| Condensing boilers have an estimated service life of 25 years ³ . | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$ 12 / kBtu / hr |
| Local Canadian manufactures reported \$9,800 for 230,000 Btu/hour condensing boilers ⁴ , which is \$43 / kBtu/hour. Baseline cost (conventional boilers) is \$31/kBtu/hr. Incremental cost is \$12 kBtu/hour. | |
| Customer Payback Period (Natural Gas Only)⁵ | 2.3 Years |
| <p>Using a 5-year average commodity cost (avoided cost)⁶ of \$0.38 / m³ and an average commercial distribution cost⁷ of \$0.12 / m³, the payback period for natural gas savings is determined to be 2.3 years, based on the following:</p> <p>On a per Btu/hr basis,</p> <p>Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="margin-left: 40px;">= $\\$0.012 / (0.0104 \text{ m}^3/\text{year} * \\$0.5 / \text{m}^3)$</p> <p style="margin-left: 40px;">= 2.3 years</p> | |
| Market Share⁸ | High |
| Based on conversations with local contractors and the number of condensing boilers on the market, Navigant Consulting has determined that condensing boilers have a high market share in Ontario. | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|--|-------------------------------|---------------------------|--------------------------|
| State of Iowa Utilities Board ⁹ | 0.156 per ft ² | 20 | \$35.80 (Large Office) | N/A |
| Comments Base equipment has an 80% seasonal efficiency, efficient equipment has an 89% seasonal efficiency. Baseline usage reported on a square footage basis (eg 0.57 therms/sq.ft. for large offices). Estimated 10.2% savings over the baseline. Incremental costs are based on per 1,000 ft ² basis. Equivalent natural gas savings is $10.2\% \times 0.57 \text{ therms/sq.ft.} = 0.058 \text{ therms} = 0.156 \text{ m}^3 / \text{ft}^2$. | | | | |

³ ASHRAE Applications Handbook – 2003, Chapter 36 – Owning and Operating Costs, Table 3

⁴ Veissmann Group, <http://www.viessmann.ca/en>

⁵ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁶ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁷ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

⁸ Navigant Consulting is defining “Low” as below 5%, “Medium” as between 5-50%, and “High” as above 50%.

⁹ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|--|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy ¹⁰ | 0.063 per ft ² | 20 | \$0.10 (offices) | N/A |
| Comments Base equipment is a standard central boiler with 75% seasonal efficiency and efficient equipment is a condensing boiler with 85% seasonal efficiency. Baseline usage reported on a square footage basis (eg 0.19 therms/sq.ft. for offices). Estimated 12% savings over the baseline. Incremental costs are based on per sqft basis. Equivalent natural gas savings is 12% x 0.19 therms/sq.ft. = 0.0228 therms = 0.063 m ³ / ft ² . | | | | |

¹⁰ Quantec, Comprehensive Demand-Side Management Resource Assessment, Prepared for Puget Sound Energy, May 2007

32. Demand Control Kitchen Ventilation (DCKV – 5000 CFM)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Kitchen ventilation with DCKV hood exhaust (5000 CFM). Demand ventilation uses temperature and/or smoke sensing to adjust ventilation rates. This saves energy comparing with the traditional 100% on/off kitchen ventilation system.

Base Equipment and Technologies Description

Kitchen ventilation without DCKV.

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------------------|---------------|
| Retrofit | Existing Commercial (Restaurants) | Space Heating |

Codes, Standards, and Regulations

N/A

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 4,801 | 13,521 | 0 | 10,000 | 0 |
| 2 | 4,801 | 13,521 | 0 | 0 | 0 |
| 3 | 4,801 | 13,521 | 0 | 0 | 0 |
| 4 | 4,801 | 13,521 | 0 | 0 | 0 |
| 5 | 4,801 | 13,521 | 0 | 0 | 0 |
| 6 | 4,801 | 13,521 | 0 | 0 | 0 |
| 7 | 4,801 | 13,521 | 0 | 0 | 0 |
| 8 | 4,801 | 13,521 | 0 | 0 | 0 |
| 9 | 4,801 | 13,521 | 0 | 0 | 0 |
| 10 | 4,801 | 13,521 | 0 | 0 | 0 |
| 11 | 4,801 | 13,521 | 0 | 0 | 0 |
| 12 | 4,801 | 13,521 | 0 | 0 | 0 |
| 13 | 4,801 | 13,521 | 0 | 0 | 0 |
| 14 | 4,801 | 13,521 | 0 | 0 | 0 |
| 15 | 4,801 | 13,521 | 0 | 0 | 0 |
| TOTALS | 72,015 | 202,815 | 0 | 10,000 | 0 |

Resource Savings Assumptions

Annual Natural Gas Savings

4,801 m³

- The demand control kitchen ventilation savings were determined using the method described in the Melink Detailed Energy Savings Report¹.
- Assuming the DCKV system is operating 16 hours/day, 7 days/week, 52 weeks/year, at 80% heating efficiency.
- Using design weather data from the Outdoor Airload Calculator², baseline net heating loads for an exhaust volume of 5,000 CFM were determined for two locations: London (Union South) and North Bay (Union North): London = 624,111 kBtu; and North Bay = 803,266 kBtu.
- Heating savings for both locations (London and North Bay) were calculated by multiplying the individual baseline heating loads with $(1 - \text{estimated average make-up air RPM factor})$, which represents the percent savings when using Demand Control Kitchen Ventilation.
- Weighted average natural gas savings is calculated by assigning 70% to Union Gas South consumption and 30% to Union Gas North consumption based on the customer population of Union Gas service territories.

| NG Savings | Weight | Base Case Heating Load (kBtu) | Demand Ventilation Heating Load (kBtu) | Heating Savings (m ³) |
|-------------------------|--------|-------------------------------|--|-----------------------------------|
| Union South (London) | 70% | 624,111 | 464,963 | 4,421 |
| Union North (North Bay) | 30% | 803,266 | 598,433 | 5,690 |
| Weighted Average | | 677,858 | 505,004 | 4,801 |

- Baseline estimates of natural gas consumption = 677,858 kBtu = 18,829 m³
- Natural Gas Savings % = $4801 \text{ m}^3 / 677858 \text{ m}^3 = 26 \%$

Annual Electricity Savings

13,521 kWh

- Electricity savings consists two parts: fan motor savings and cooling load savings.
- Main assumption include: Motor capacity is 5 HP at 90% efficiency level, Cooling system COP = 3.
- Total Operating Time per Year (G) = 16 hrs/day x 7 days/week x 52 weeks/year = 5,824 hours
- Baseline fan motor electricity consumption = $0.746 \text{ kW/HP} \times G / 0.9 = 4,827.4 \text{ kWh/HP}$
- DCKV fan motor electricity consumption is calculated as below:

¹ Detailed Energy Savings Report, Melink Corporation, http://www.melinkcorp.com/Intellihood/Energy_Analysis.pdf

² This freeware is available at www.archenergy.com/ckv/oac/default.htm.

| % Rated RPM | % Run Time | Time HRS/YR | Output KW/HP | System Effic. | Input KW/HP | KWHR/ HP/YR |
|---------------------------------------|---------------|----------------|-----------------|------------------|----------------|------------------------|
| H | I | J=GxI | K | L | M=K/L | N=JxM |
| 100 | 5 | 291.2 | 0.746 | 0.9 | 0.829 | 241 |
| 90 | 20 | 1164.8 | 0.544 | 0.9 | 0.604 | 704 |
| 80 | 25 | 1456 | 0.382 | 0.9 | 0.424 | 618 |
| 70 | 25 | 1456 | 0.256 | 0.9 | 0.284 | 414 |
| 60 | 15 | 873.6 | 0.161 | 0.9 | 0.179 | 156 |
| 50 | 10 | 582.4 | 0.093 | 0.9 | 0.103 | 60 |
| 40 | 0 | 0 | 0.048 | 0.9 | 0.053 | 0 |
| 30 | 0 | 0 | 0.020 | 0.9 | 0.022 | 0 |
| 20 | 0 | 0 | 0.015 | 0.9 | 0.017 | 0 |
| 10 | 0 | 0 | 0.010 | 0.90 | 0.011 | 0 |
| O Total KWH/HP/YR (Total of Column N) | | | | | | 2,194 kWh/HP |

- The fan motor electricity savings = 5HP x (4,827.4 – 2,194) kWh/HP = 13,167.2 kWh.
- Cooling load savings are calculated using the same method as for heating load savings analysis. Baseline net cooling loads for London and North Bay are obtained using Outdoor Airload Calculator:
 - London = 17,801 kBtu; and
 - North Bay = 5,832 kBtu.
- Multiplying the baseline cooling loads by (1 – estimated average make-up air RPM factor), and then assigning 70% weight to London and 30% weight to North Bay, cooling load savings are calculated and shown below:

| Cooling Electricity Consumption | Weight | Base Case Cooling (kWh) | DCKV Cooling (kWh) | Cooling Savings (kWh) |
|---------------------------------|--------|----------------------------|--------------------|--------------------------|
| Union South (London) | 70% | 1,739 | 1,296 | 443 |
| Union North (North Bay) | 30% | 570 | 424 | 145 |
| Weighted Average | | 1,388 | 1,034 | 354 |

- Total electricity savings are calculated by combining the two components of electricity usages:

| Total Electricity Savings | Weight | Cooling Savings (kWh) | Exhaust Fan Motor Electricity Savings (kWh) | Total Savings (kWh) |
|---------------------------|--------|-----------------------|--|------------------------|
| Union South (London) | 70% | 443 | 13,167 | 13,611 |
| Union North (North Bay) | 30% | 145 | 13,167 | 13,313 |
| Weighted Average | | 354 | 13,167 | 13,521 |

- Baseline estimates of electricity consumption = 5HP x 4,827.4 kWh/HP + 1,388 kWh = 25,526 kWh.
- Electricity Savings % = 13,521 kWh / 25,526 kWh = 53 %

| | |
|-----------------------------|------------|
| Annual Water Savings | 0 L |
|-----------------------------|------------|

N/A

Other Input Assumptions

| | |
|--|------------------|
| Effective Useful Life (EUL) | 15 Years |
| Melink Canada representative George McGrath estimates their system life at 15 years ³ . | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$ 10,000 |
| Typical costing information was obtained from Melink Canada ⁴ . | |
| Customer Payback Period (Natural Gas Only)⁵ | 4.2 Years |
| <p>Using a 5-year average commodity cost (avoided cost)⁶ of \$0.38 / m³ and an average commercial distribution cost⁷ of \$0.12 / m³, the payback period for natural gas savings is determined to be 4.2 years, based on the following:</p> <p>Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="padding-left: 40px;">= \$10,000 / (4,801 m³/year * \$0.5 / m³)</p> <p style="padding-left: 40px;">= 4.2 years</p> | |
| Market Penetration⁸ | Low |
| Based on the penetration rates in another jurisdiction (5% for Puget Sound Energy) and communication with local contractors, Navigant Consulting estimates a low market penetration in Ontario. | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy ⁹ | 0.0385 per ft ² | 15 | 0.28 | 5% |
| <p>Comments</p> <p>Baseline therm reported on a square footage basis (eg 0.14 therms/sq.ft. for restaurant). Estimated 10% savings for new energy efficient technology is reported as a percent saving over the baseline. Incremental costs are also based on per sqft basis. Equivalent natural gas savings is 10% x 0.14 therms/sq.ft. = 0.014 therms/sq.ft. = 0.0385 m³ / sq.ft.</p> | | | | |

³ Melink Canada, February, 2009

⁴ Melink Canada, <http://melinkcanada.com/>

⁵ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁶ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁷ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

⁸ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

⁹ Quantec, Comprehensive Demand-Side Management Resource Assessment, Prepared for Puget Sound Energy, May 2007

33. Demand Control Kitchen Ventilation (DCKV – 10000 CFM)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Kitchen ventilation with DCKV hood exhaust (10000 CFM). Demand ventilation uses temperature and/or smoke sensing to adjust ventilation rates. This saves energy comparing with the traditional 100% on/off kitchen ventilation system.

Base Equipment and Technologies Description

Kitchen ventilation without DCKV.

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------------------|---------------|
| Retrofit | Existing Commercial (Restaurants) | Space Heating |

Codes, Standards, and Regulations

N/A

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 11,486 | 30,901 | 0 | 15,000 | 0 |
| 2 | 11,486 | 30,901 | 0 | 0 | 0 |
| 3 | 11,486 | 30,901 | 0 | 0 | 0 |
| 4 | 11,486 | 30,901 | 0 | 0 | 0 |
| 5 | 11,486 | 30,901 | 0 | 0 | 0 |
| 6 | 11,486 | 30,901 | 0 | 0 | 0 |
| 7 | 11,486 | 30,901 | 0 | 0 | 0 |
| 8 | 11,486 | 30,901 | 0 | 0 | 0 |
| 9 | 11,486 | 30,901 | 0 | 0 | 0 |
| 10 | 11,486 | 30,901 | 0 | 0 | 0 |
| 11 | 11,486 | 30,901 | 0 | 0 | 0 |
| 12 | 11,486 | 30,901 | 0 | 0 | 0 |
| 13 | 11,486 | 30,901 | 0 | 0 | 0 |
| 14 | 11,486 | 30,901 | 0 | 0 | 0 |
| 15 | 11,486 | 30,901 | 0 | 0 | 0 |
| TOTALS | 172,290 | 463,515 | 0 | 15,000 | 0 |

Resource Savings Assumptions

| Annual Natural Gas Savings | | | | 11,486 m ³ |
|--|--------|-------------------------------|--|-----------------------------------|
| <ul style="list-style-type: none"> The demand control kitchen ventilation savings were determined using the methodology described in the Melink Detailed Energy Savings Report¹. Assuming the DCKV system is operating 16 hours/day, 7 days/week, 52 weeks/year, at 80% heating efficiency. Using design weather data from the Outdoor Airload Calculator², baseline net heating loads for a exhaust volume of 10,000 CFM were determined for London (Union South) and North Bay (Union North). London: 1,248,221 kBTu, North Bay: 1,660,531 kBTu Heating savings for London and North Bay are calculated by multiplying the individual baseline heating loads with $(1 - \text{estimated average make-up air RPM factor})$, which represents the savings% when using Demand Control Kitchen Ventilation. Weighted average natural gas savings is calculated by assigning 70% to Union Gas South consumption and 30% to Union Gas North consumption based on the customer population of Union Gas service territories. | | | | |
| NG Savings | Weight | Base Case Heating Load (kBTu) | Demand Ventilation Heating Load (kBTu) | Heating Savings (m ³) |
| Union South (London) | 70% | 1,248,221 | 867,514 | 10,575 |
| Union North (North Bay) | 30% | 1,606,531 | 1,116,539 | 13,611 |
| Weighted Average | | 1,355,714 | 942,221 | 11,486 |
| <ul style="list-style-type: none"> Baseline estimates of natural gas consumption = 1,355,714 kBTu = 37,659 m³ Natural Gas Savings % = $11,486 \text{ m}^3 / 37,659 \text{ m}^3 = 31 \%$ | | | | |
| Annual Electricity Savings | | | | 30,901 kWh |
| <ul style="list-style-type: none"> Electricity savings consists two parts: fan motor savings and cooling load savings. Assuming the motor capacity is 10 HP at 90% efficiency level, cooling system COP = 3. Total Operating Time per Year (G) = 16 hrs/day x 7 days/week x 52 weeks/year = 5,824 hours Baseline fan motor electricity consumption = $0.746 \text{ kW/HP} \times G / 0.9 = 4,827.4 \text{ kWh/HP}$ DCKV fan motor electricity consumption is calculated as below: | | | | |

¹ Detailed Energy Savings Report, Melink Corporation, http://www.melinkcorp.com/Intellihood/Energy_Analysis.pdf

² This freeware is available at www.archenergy.com/ckv/oac/default.htm.

| % Rated RPM | % Run Time | Time HRS/YR | Output KW/HP | System Effic. | Input KW/HP | KWHR/ HP/YR |
|---------------------------------------|---------------|----------------|-----------------|------------------|----------------|------------------------|
| H | I | J=GxI | K | L | M=K/L | N=JxM |
| 100 | 5 | 291.2 | 0.746 | 0.9 | 0.829 | 241 |
| 90 | 10 | 582.4 | 0.544 | 0.9 | 0.604 | 352 |
| 80 | 20 | 1164.8 | 0.382 | 0.9 | 0.424 | 494 |
| 70 | 20 | 1164.8 | 0.256 | 0.9 | 0.284 | 331 |
| 60 | 30 | 1747.2 | 0.161 | 0.9 | 0.179 | 313 |
| 50 | 15 | 873.6 | 0.093 | 0.9 | 0.103 | 90 |
| 40 | 0 | 0 | 0.048 | 0.9 | 0.053 | 0 |
| 30 | 0 | 0 | 0.020 | 0.9 | 0.022 | 0 |
| 20 | 0 | 0 | 0.015 | 0.9 | 0.017 | 0 |
| 10 | 0 | 0 | 0.010 | 0.90 | 0.011 | 0 |
| O Total KWH/HP/YR (Total of Column N) | | | | | | 1,822 kWh/HP |

- The fan motor electricity savings = 10HP x (4,827.4 – 1,822) kWh/HP = 30,054 kWh.
- Cooling load savings are calculated using the same method as for heating load savings analysis. Baseline net cooling loads for London and North Bay are obtained using Outdoor Airload Calculator:
 - London = 35,603 kBtu
 - North Bay = 11,663 kBtu.
- Multiplying the baseline cooling loads by (1 – estimated average make-up air RPM factor), and then assigning 70% weight to London and 30% weight to North Bay, cooling load savings are calculated.

| Cooling Electricity Consumption | Weight | Base Case Cooling (kWh) | DCKV Cooling (kWh) | Cooling Savings (kWh) |
|---------------------------------|--------|----------------------------|--------------------|--------------------------|
| Union South (London) | 70% | 3,478 | 2,417 | 1,061 |
| Union North (North Bay) | 30% | 1,139 | 792 | 348 |
| Weighted Average | | 2,777 | 1,930 | 847 |

- Total electricity savings are calculated by combining the two components of electricity usages:

| Total Electricity Savings | Weight | Cooling Savings (kWh) | Exhaust Fan Motor Electricity Savings (kWh) | Total Savings (kWh) |
|---------------------------|--------|-----------------------|--|------------------------|
| Union South (London) | 70% | 1,061 | 30,054 | 31,115 |
| Union North (North Bay) | 30% | 348 | 30,054 | 30,402 |
| Weighted Average | | 847 | 30,054 | 30,901 |

- Baseline estimates of electricity consumption = 10HP x 4,817.4kWh/HP + 2,777 kWh = 51,051 kWh.
- Electricity Savings % = 30,901 kWh / 51,051 kWh = 61 %

| | |
|-----------------------------|------------|
| Annual Water Savings | 0 L |
|-----------------------------|------------|

N/A

Other Input Assumptions

| | |
|---|------------------|
| Effective Useful Life (EUL) | 15 Years |
| Melink Canada representative George McGrath estimates their system life at 15 years ³ . | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$ 15,000 |
| Typical costing information was provided by Melink Canada ⁴ . | |
| Customer Payback Period (Natural Gas Only)⁵ | 2.6 Years |
| <p>Using a 5-year average commodity cost (avoided cost)⁶ of \$0.38 / m³ and an average commercial distribution cost⁷ of \$0.12 / m³, the payback period for natural gas savings is determined to be 2.6 years, based on the following:</p> <p>Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="margin-left: 40px;">= \$15,000 / (11,486 m³/year * \$0.5 / m³)</p> <p style="margin-left: 40px;">= 2.6 years</p> | |
| Market Penetration⁸ | Low |
| Based on the penetration rate in another jurisdiction (5% for Puget Sound Energy) and communication with local contractors, Navigant Consulting estimates a low market penetration in Ontario. | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy ⁹ | 0.0385 / sqft | 15 | 0.28 | 5% |
| <p>Comments</p> <p>Baseline therm reported on a square footage basis (eg 0.14 therms/sq.ft. for restaurant). Estimated 10% savings for new energy efficient technology is reported as a percent saving over the baseline. Incremental costs are based on per sqft basis. Equivalent natural gas savings is 10% x 0.14 therms/sq.ft = 0.014 therms/sq.ft = 0.0385 m³/sq.ft</p> | | | | |

³ Melink Canada, February, 2009

⁴ Melink Canada, <http://melinkcanada.com/>

⁵ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁶ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁷ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

⁸ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

⁹ Quantec, Comprehensive Demand-Side Management Resource Assessment, Prepared for Puget Sound Energy, May 2007

34. Demand Control Kitchen Ventilation (DCKV – 15000 CFM)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Kitchen ventilation with DCKV hood exhaust (15000 CFM). Demand ventilation uses temperature and/or smoke sensing to adjust ventilation rates. This saves energy comparing with the traditional 100% on/off kitchen ventilation system.

Base Equipment and Technologies Description

Kitchen ventilation without DCKV.

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------------------|---------------|
| Retrofit | Existing Commercial (Restaurants) | Space Heating |

Codes, Standards, and Regulations

N/A

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 18,924 | 49,102 | 0 | 20,000 | 0 |
| 2 | 18,924 | 49,102 | 0 | 0 | 0 |
| 3 | 18,924 | 49,102 | 0 | 0 | 0 |
| 4 | 18,924 | 49,102 | 0 | 0 | 0 |
| 5 | 18,924 | 49,102 | 0 | 0 | 0 |
| 6 | 18,924 | 49,102 | 0 | 0 | 0 |
| 7 | 18,924 | 49,102 | 0 | 0 | 0 |
| 8 | 18,924 | 49,102 | 0 | 0 | 0 |
| 9 | 18,924 | 49,102 | 0 | 0 | 0 |
| 10 | 18,924 | 49,102 | 0 | 0 | 0 |
| 11 | 18,924 | 49,102 | 0 | 0 | 0 |
| 12 | 18,924 | 49,102 | 0 | 0 | 0 |
| 13 | 18,924 | 49,102 | 0 | 0 | 0 |
| 14 | 18,924 | 49,102 | 0 | 0 | 0 |
| 15 | 18,924 | 49,102 | 0 | 0 | 0 |
| TOTALS | 283,860 | 736,530 | 0 | 20,000 | 0 |

Resource Savings Assumptions

Annual Natural Gas Savings

18,924 m³

- The demand control kitchen ventilation savings were determined using the method described in the Melink Detailed Energy Savings Report¹.
- Assuming the DCKV system is operating 16 hours/day, 7 days/week, 52 weeks/year, at 80% heating efficiency.
- Using design weather data from the Outdoor Airload Calculator², baseline net heating loads for London (Union South) and North Bay (Union North) at 15000 CFM exhaust volume are obtained. They are 1,872,332 kBtu and 2,409,797 kBtu respectively.
- Heating savings for London and North Bay are calculated by multiplying the individual baseline heating loads with $(1 - \text{estimated average make-up air RPM factor})$, which represents the savings% when using Demand Control Kitchen Ventilation.
- Weighted average natural gas savings is calculated by assigning 70% to Union Gas South consumption and 30% to Union Gas North consumption based on the customer population of Union Gas service territories.

| NG Savings | Weight | Base Case Heating Load (kBtu) | Demand Ventilation Heating Load (kBtu) | Heating Savings (m ³) |
|-------------------------|--------|-------------------------------|--|-----------------------------------|
| Union South (London) | 70% | 1,872,332 | 1,245,101 | 17,423 |
| Union North (North Bay) | 30% | 2,409,797 | 1,602,515 | 22,424 |
| Weighted Average | | 2,033,572 | 1,352,325 | 18,924 |

- Baseline estimates of natural gas consumption = 2,033,572 kBtu = 56,488 m³
- Natural Gas Savings % = $18,924 \text{ m}^3 / 56,488 \text{ m}^3 = 34 \%$

Annual Electricity Savings

49,102 kWh

- Electricity savings consists two parts: fan motor savings and cooling load savings.
- Assuming the motor capacity is 15 HP at 90% efficiency level, cooling system COP = 3.
- Total Operating Time per Year (G) = 16 hrs/day x 7 days/week x 52 weeks/year = 5,824 hours
- Baseline fan motor electricity consumption = $0.746 \text{ kW/HP} \times G / 0.9 = 4,827.4 \text{ kWh/HP}$
- DCKV fan motor electricity consumption is calculated as below:

¹ Detailed Energy Savings Report, Melink Corporation, http://www.melinkcorp.com/Intellihood/Energy_Analysis.pdf

² This freeware is available at www.archenergy.com/ckv/oac/default.htm.

| % Rated RPM | % Run Time | Time HRS/YR | Output KW/HP | System Effic. | Input KW/HP | KWHR/HP/YR |
|---------------------------------------|------------|-------------|--------------|---------------|-------------|------------------------|
| H | I | J=GxI | K | L | M=K/L | N=JxM |
| 100 | 5 | 291.2 | 0.746 | 0.9 | 0.829 | 241 |
| 90 | 5 | 291.2 | 0.544 | 0.9 | 0.604 | 176 |
| 80 | 20 | 1164.8 | 0.382 | 0.9 | 0.424 | 494 |
| 70 | 20 | 1164.8 | 0.256 | 0.9 | 0.284 | 331 |
| 60 | 30 | 1747.2 | 0.161 | 0.9 | 0.179 | 313 |
| 50 | 10 | 582.4 | 0.093 | 0.9 | 0.103 | 60 |
| 40 | 10 | 582.4 | 0.048 | 0.9 | 0.053 | 31 |
| 30 | 0 | 0 | 0.020 | 0.9 | 0.022 | 0 |
| 20 | 0 | 0 | 0.015 | 0.9 | 0.017 | 0 |
| 10 | 0 | 0 | 0.010 | 0.90 | 0.011 | 0 |
| O Total KWH/HP/YR (Total of Column N) | | | | | | 1,647 kWh/HP |

- The fan motor electricity savings = 15HP x (4,827.4 – 1,647) kWh/HP = 47,707 kWh.
- Cooling load savings are calculated using the same method as for heating load savings analysis. Baseline net cooling loads for London and North Bay are obtained using Outdoor Airload Calculator:
 - London = 53,404 kBtu
 - North Bay = 17,495 kBtu
- Multiplying the baseline cooling loads by (1 – estimated average make-up air RPM factor), and then assigning 70% weight to London and 30% weight to North Bay, cooling load savings are calculated.

| Cooling Electricity Consumption | Weight | Base Case Cooling (kWh) | DCKV Cooling (kWh) | Cooling Savings (kWh) |
|---------------------------------|--------|-------------------------|--------------------|-----------------------|
| Union South (London) | 70% | 5,217 | 3,469 | 1,748 |
| Union North (North Bay) | 30% | 1,709 | 1,137 | 573 |
| Weighted Average | | 4,165 | 2,770 | 1,395 |

- Total electricity savings are calculated by combining the two components of electricity usages:

| Total Electricity Savings | Weight | Cooling Savings (kWh) | Exhaust Fan Motor Electricity Savings (kWh) | Total Savings (kWh) |
|---------------------------|--------|-----------------------|---|---------------------|
| Union South (London) | 70% | 1,748 | 47,707 | 49,455 |
| Union North (North Bay) | 30% | 573 | 47,707 | 48,279 |
| Weighted Average | | 1,395 | 47,707 | 49,102 |

- Baseline estimates of electricity consumption = 15HP x 4,827.4kWh/HP + 4,165 kWh = 76,577 kWh.
- Electricity Savings % = 49,102 kWh / 76,577 kWh = 64 %

| | |
|-----------------------------|------------|
| Annual Water Savings | 0 L |
| N/A | |

Other Input Assumptions

| | |
|---|------------------|
| Effective Useful Life (EUL) | 15 Years |
| Melink Canada representative George McGrath estimates their system life at 15 years ³ . | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$ 20,000 |
| Typical costing information was provided by Melink Corp. | |
| Customer Payback Period (Natural Gas Only)⁴ | 2.1 Years |
| <p>Using a 5-year average commodity cost (avoided cost)⁵ of \$0.38 / m³ and an average commercial distribution cost⁶ of \$0.12 / m³, the payback period for natural gas savings is determined to be 2.1 years, based on the following:</p> <p>Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="margin-left: 40px;">= \$20,000 / (18,924 m³/year * \$0.5 / m³)</p> <p style="margin-left: 40px;">= 2.1 years</p> | |
| Market Penetration⁷ | Low |
| Based on the penetration rate in another jurisdiction (5% for Puget Sound Energy) and communication with local contractors, Navigant Consulting estimates a low market penetration in Ontario. | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy ⁸ | 0.0385 per ft ² | 15 | 0.28 | 5% |
| <p>Comments</p> <p>Baseline therm reported on a square footage basis (eg 0.14 therms/sq.ft. for restaurant). Estimated 10% savings for new energy efficient technology is reported as a percent saving over the baseline. Incremental costs are based on per sqft basis. Equivalent natural gas savings is 10% x 0.14 therms/sq.ft. = 0.014 therms / sqft = 0.0385 m³ / sqft</p> | | | | |

³ Melink Canada, February, 2009

⁴ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁵ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁶ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

⁷ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

⁸ Quantec, Comprehensive Demand-Side Management Resource Assessment, Prepared for Puget Sound Energy, May 2007

35. Destratification Fan – New or Existing Commercial

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Destratification Fan. For fans of with minimum diameter of 20' located in warehousing, manufacturing, industrial or retail buildings¹ with forced air space heating, including unit heaters .

Base Equipment and Technologies Description

No destratification fan.

| Decision Type | Target Market(s) | End Use |
|------------------|------------------------------|---------------|
| New, Replacement | Commercial (New or Existing) | Space Heating |

Codes, Standards, and Regulations

N/A

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|---|---------------------------------------|--------------|--|--|
| | Natural Gas (m ³ /ft ²) | Electricity (kWh/ft ²) | Water (L) | | |
| 1 | 0.5 | -0.0034 | 0 | 7,021 | 0 |
| 2 | 0.5 | -0.0034 | 0 | 0 | 0 |
| 3 | 0.5 | -0.0034 | 0 | 0 | 0 |
| 4 | 0.5 | -0.0034 | 0 | 0 | 0 |
| 5 | 0.5 | -0.0034 | 0 | 0 | 0 |
| 6 | 0.5 | -0.0034 | 0 | 0 | 0 |
| 7 | 0.5 | -0.0034 | 0 | 0 | 0 |
| 8 | 0.5 | -0.0034 | 0 | 0 | 0 |
| 9 | 0.5 | -0.0034 | 0 | 0 | 0 |
| 10 | 0.5 | -0.0034 | 0 | 0 | 0 |
| 11 | 0.5 | -0.0034 | 0 | 0 | 0 |
| 12 | 0.5 | -0.0034 | 0 | 0 | 0 |
| 13 | 0.5 | -0.0034 | 0 | 0 | 0 |
| 14 | 0.5 | -0.0034 | 0 | 0 | 0 |
| 15 | 0.5 | -0.0034 | 0 | 0 | 0 |
| TOTALS | 7.5 | -0.068 | 0 | 7,021 | 0 |

¹ Buildings with a minimum of 25" ceilings.

Resource Savings Assumptions

Annual Natural Gas Savings

0.5 m³ / ft²

Estimation Based on Agviro Study for Enbridge

- Based on the Agviro's report², which was based largely on an analysis of energy savings due to destratification fans installed at the commercial manufacturing and warehousing facility of Hunter-Douglas during the winter of 2008³, the following key assumptions are used:

| Key Enbridge Input Assumptions | |
|--|--------|
| Effective destratification area (ft ²) | 13,270 |
| Ceiling Height (ft) | 30 |
| Heater Height (ft) | 20 |
| Electric Motor Nameplate HP | 1.5 |
| Annual Operation Hours | 5,186 |
| Fan Diameter | 24' |
| Thermostat Setpoint (°F) | 72 |
| Thermostat Reduction [after destratification] (°F) | 2 |

- The Hunter-Douglas monitoring results provided important input assumptions for modeling purposes using Enbridge's ETool. However, certain factors in the monitoring were below industry standard. For example, the destratification fan was operated at speed of 15 Hz on site, which is slower than the typical or average fan speed at 20 Hz. When modeling the gas savings using ETool, Enbridge considered this factor, and revised fan speed up to 20 Hz. The modeled gas savings results are presented as follows:

| Enbridge's ETool Modeling Results | |
|--|-------|
| Electricity Consumption (kWh) | 890 |
| Auxiliary Electrical Savings (kWh) | 767 |
| Natural Gas Savings (m ³) | 7,020 |

- However, due to Navigant Consulting's lack of access to ETool to verify the calculation process of natural gas savings, Navigant Consulting opted to use Union Gas destratification fan calculator based on Enbridge's input assumptions in the presented table.

Navigant Consulting Estimation Based on Union Gas Calculator

- Using the Destratification fan calculator provided by Union Gas and the same set of input assumptions used by Enbridge, natural gas savings are presented as follows:

| Navigant Estimated Gas Savings Results | |
|---|-------|
| Electricity Consumption (kWh) | 812 |
| Auxiliary Electrical Savings (kWh) | - |
| Natural Gas Savings (m ³) | 6,828 |

- On a per square footage basis, the natural gas savings = $6,828 \text{ m}^3 / 13,270 \text{ ft}^2 = 0.51 \text{ m}^3/\text{ft}^2$.

Annual Electricity Savings

– 0.0034 kWh / ft²

- The auxiliary electrical savings represents electrical savings through the reduced use of auxiliary heating equipment such as blower motors on space heating equipment⁴. Union Gas calculator does not include this savings impact in its calculation process. Enbridge developed an equation to correlate electrical power to unit heater input size based on specifications for commercial space heating equipments.
- Since the key input assumptions used in Union Gas calculator are based on the inputs provided by

² Prescriptive Destratification Fan Program – Prescriptive Savings Analysis, Agviro Inc., Feb 2, 2009

³ Cold Weather Destratification, Hunter Douglas Monitoring Results, Final Report, May 2008

⁴ Prescriptive Destratification Fan Program – Prescriptive Savings Analysis, Agviro Inc., Feb 2, 2009

Agviro report and the calculated electrical savings are within 10% of the reported Enbridge gas savings. Navigant Consulting assumes same amount of auxiliary electrical savings can be achieved by destratification fans in Union Gas service territories.

- Therefore, net electricity consumption (kWh) = electricity consumptions in electric motor (kWh) – auxiliary electrical saving (kWh) = 812 kWh – 767 kWh = 45 kWh
- On a per square footage basis, the electricity savings = – 45 kWh / 13,270 ft² = – 0.0034 kWh/ft².

Annual Water Savings

0 L

N/A

Other Input Assumptions

Effective Useful Life (EUL)

15 Years

The estimated equipment life for de-stratification fans is 15 years⁵. This value is also supported by ASHRAE⁶, which lists the service life for propeller fans as 15 years.

Base & Incremental Conservation Measure Equipment and O&M Costs

\$7,021

The weighted average costs are based on market shares described above and cost data⁷.

| Results | Fan Sizes | |
|----------------------------|--------------|--------------|
| | 24' diameter | 20' diameter |
| Incremental Cost for 1 Fan | \$7,088 | \$6,885 |
| Market Share | 55% | 27% |
| Weighted Average Cost | \$7,021 | |

According to Envira-North (a local Canadian manufacturer of destratification fans), the suggested retail price for a de-stratification fan with a 2' drop from the ceiling, 2 HP and stealth blade is \$6,000. For the 20' fan with 1' drop, 1 HP and a stellar blade, the price is \$5,200.

Customer Payback Period (Natural Gas Only)⁸

2.1 Years

Using a 5-year average commodity cost (avoided cost)⁹ of \$0.38 / m³ and an average commercial distribution cost¹⁰ of \$0.12 / m³, the payback period for natural gas savings is determined to be 2.1 years, based on the following:

$$\begin{aligned}
 \text{Payback Period} &= \text{Incremental cost} / (\text{natural gas savings} \times \text{natural gas cost}) \\
 &= \$7,021 / (6,828 \text{ m}^3/\text{year} \times \$0.5 / \text{m}^3) \\
 &= 2.1 \text{ years}
 \end{aligned}$$

Market Penetration¹¹

Low

Based on conversations with suppliers of destratification fans, Navigant Consulting estimates that fewer than 5% of buildings in Ontario capable of installing the technology currently have them installed. Although this is considered to be low market penetration, this technology is relatively new and the penetration is steadily growing.

⁵ SEED Program Guideline, J-20, December 2004, <http://www.oregon.gov/ENERGY/CONS/SEED/docs/AppendixJ.pdf>

⁶ ASHRAE Handbook, HVAC Applications SI Edition. Chapter 36 – Table 4. Pg.36.3, 2007.

⁷ Targeted Market Study. HVLS Fans on Wisconsin Dairy Farms. State of Wisconsin Department of Administration Division of Energy. June 12, 2006., RSMeans. Mechanical Cost Data – 29th Annual Edition. 2006, and communications with Manufacturers.

⁸ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁹ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁰ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹¹ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|------------------------|---------------------------------|-------------------------------|-----------------------|--------------------------|
| N/A | N/A | N/A | N/A | N/A |
| Comments N/A | | | | |

36. Energy Recovery Ventilator (ERV) – Existing Commercial

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Ventilation with Energy Recovery Ventilator (ERV)

Base Equipment and Technologies Description

Ventilation without Energy Recovery Ventilator (ERV)

| Decision Type | Target Market(s) | End Use |
|---------------|---------------------|---------------|
| Replacement | Existing Commercial | Space Heating |

Codes, Standards, and Regulations

N/A

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$/CFM) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³ /CFM) | Electricity (kWh) | Water (L) | | |
| 1 | 1.84 – 5.14 | 0 | 0 | 3 | 0 |
| 2 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 3 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 4 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 5 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 6 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 7 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 8 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 9 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 10 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 11 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 12 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 13 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 14 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 15 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 16 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 17 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 18 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 19 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| 20 | 1.84 – 5.14 | 0 | 0 | 0 | 0 |
| TOTALS | 36.8 – 102.8 | 0 | 0 | 3 | 0 |

Resource Savings Assumptions

Annual Natural Gas Savings

1.84 – 5.14 m³/CFM

- Natural gas savings are determined from engineering calculations utilizing inputs such as air flow, indoor/outdoor temperatures, indoor/outdoor and relative humidity.
- For example, input assumptions for a typical Ontario retail store are:

| Symbols | Variable Names | Values | Source |
|---------|--|-----------------|------------------|
| A | Supply air flow (cfm) | 500 | UG [†] |
| B | Exhaust air flow (cfm) | 500 | UG |
| C | Average indoor air temperature (°F) | 70 | UG |
| D | Average indoor relative humidity (%) | 30 | UG |
| E | Average outside air temperature (°F) | 31.5 | UG |
| F | Average outdoor relative humidity (%) | 70 | NCI ^Δ |
| G | Atmospheric pressure (psia) | 14.3 | UG |
| H | No. of hours in heating season (hrs) | 4,800 | UG |
| I1 | Demand Controlled Ventilation | no | UG |
| I2 | No. of hours of operation per week (hrs/wk) | 108 | UG |
| J | Make and Model of Heat Recovery Equipment | Eng A, HRW-2100 | UG |
| K | Effectiveness of Heat Recovery Equipment (%) | 60 | NCI |
| L | Sensible Heat Recovery Only | no | UG |
| M | Enthalpy (Btu/lba) & Humidity Ratio (lbw/lba) of INLET exhaust air | 22.0 | UG |
| N | Enthalpy (Btu/lba) & Humidity Ratio (lbw/lba) of INLET supply air | 10.4 | UG |
| O | Enthalpy (Btu/lba) & Humidity Ratio (lbw/lba) of OUTLET supply air | 17.3 | UG |
| P | Average Temperature of OUTLET supply air (°F) | 55 | UG |
| Q | Average Hourly Moisture Addition (lb/hr) | 2.6 | UG |
| R | Defrost Control Derating Factor (%) | 5 | UG |
| S | Average Hourly Heat Recovery (MBH) | 14.7 | UG |
| T | Seasonal Efficiency of Gas-Fired Equipment (%) | 82 | UG |
| U | Average annual gas reduction (m ³) | 1,571 | UG |
| V | Incremental natural gas rate (\$/m ³) | 0.3 | UG |
| W | Average annual gas savings (\$) | 471.3 | UG |

[†]UG: Union Gas

^ΔNCI: Navigant Consulting, Inc

- NG Savings** = # of Hours in Heating Season x (operating hours/168) x Average Hourly Heat Recovery / (35.3 m³/MJ) / (Seasonal Efficiency / 100%) **(A)**
 - 168 hour = 7 days/week x 24hours/day
 - Average Hourly Heat Recovery = Supply air flow x 60 x (Supply air flow – Inlet supply air)/Specific Supply Air Conditions Volume x (1 – Defrost Control De-rating Factor¹ %) **(B)**
- Operating hours for each sectors being considered are as the following

| Building Occupancy | Typical Hrs of Operation per week |
|--------------------|-----------------------------------|
| Hotel | 168 |
| Restaurant | 108 |
| Retail | 108 |
| Office | 60 |
| School | 84 |
| Health Care | 168 |
| Nursing Home | 168 |
| Warehouse | 168 |

¹ From Union Gas, all air-to-air heat recovery equipment requires frost control in colder climates to prevent freeze-up of exhaust air condensate on heat exchange components. Depending on the defrost control system, annual heat recovery estimates should be reduced by 5 to 15 %. Equipment manufacturers and suppliers can provide an estimated defrost derating factor given the operating conditions of the equipment.

- Based on the NG Savings formula (A) and input assumptions above, the natural gas savings for each of the commercial sectors are calculated, and a simple average is taken to be the general savings.

| Market Segment | ERV Capacity (CFM) | Existing Buildings | |
|------------------------------------|--------------------|------------------------------|--|
| | | NG Savings (m ³) | NG Savings per CFM (m ³ /CFM) |
| Hotel | 500 | 2,569 | 5.14 |
| Restaurant | 500 | 1,652 | 3.30 |
| Retail | 500 | 1,652 | 3.30 |
| Office | 500 | 918 | 1.84 |
| School | 500 | 1,285 | 2.57 |
| Health Care | 500 | 2,569 | 5.14 |
| Nursing Home | 500 | 2,569 | 5.14 |
| Warehouse | 500 | 2,569 | 5.14 |
| Average (m³/CFM) | | | 3.95 |

| | |
|-----------------------------------|----------------|
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 0 L/CFM |
| N/A | |

Other Input Assumptions

| | |
|---|------------------------|
| Effective Useful Life (EUL) | 20 Years |
| ERVs have an estimated service life of 15 years based on Jacques Whitford study ² . Questar Gas ³ and Puget Sound ⁴ both report 20 years as an ERV's effective useful life. Navigant Consulting estimates 20 years as an effective useful life for ERVs. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$3/CFM |
| The incremental costs are based on relative scaling of incremental costs \$2,500 / 1000 CFM ⁵ . Based on communication with local contractors, the incremental costs are \$3/CFM. | |
| Customer Payback Period (Natural Gas Only)⁶ | 1.2 – 3.3 Years |
| Using a 5-year average commodity cost (avoided cost) ⁷ of \$0.38 / m ³ and an average commercial distribution cost ⁸ of \$0.12 / m ³ , the payback period for natural gas savings is determined to be between 1.2 to 3.3 years, based on the following: On a per CFM basis, 1) For offices, Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$3 / (1.84 m ³ /year * \$0.5 / m ³) = 3.3 years 2) For hotels, warehouses and health care, etc., Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$3 / (5.14 m ³ /year * \$0.5 / m ³) = 1.2 years | |
| Market Penetration⁹ | Low |
| Based on Jacques Whitford report ¹⁰ (less than 5% market penetration) and communication with local contractors, Navigant Consulting estimates the market penetration of ERV to be low. | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy, 2007 ¹¹ | 0.105 per sqft | 20 | 1 | N/A |
| Comments Baseline therm reported on a square footage basis (e.g. 0.19 therms/sq.ft. for offices). Estimated 20% savings over the baseline. Incremental cost is reported on a per square footage basis. Equivalent savings is 0.19 therms/sq.ft x 2.75 m ³ /therms x 20% = 0.105 m ³ / sq.ft | | | | |

² "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., by Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000.

³ Questar Gas, DSM Market Characterization Report, by Nexant, August 9, 2006

⁴ Quantec — Puget Sound Energy Demand-Side Management Resource Assessment

⁵ "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., by Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000.

⁶ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁷ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁸ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

⁹ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁰ "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., by Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000.

¹¹ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

37. Energy Recovery Ventilator (ERV) – New Commercial

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Ventilation with ERV

Base Equipment and Technologies Description

Ventilation without ERV

| Decision Type | Target Market(s) | End Use |
|---------------|------------------|---------------|
| New | New Commercial | Space Heating |

Codes, Standards, and Regulations

- 1) Restriction for new building construction: This measure is not applicable to system $\geq 5,000$ CFM with $\geq 70\%$ OA ratio because energy recovery is required by Ontario Building Code 2006.
- 2) Restriction for new building construction: This measure is not applicable to systems serving health care spaces indicated in **Table 1** because heat recovery is required by CSA Z317.2-01

Table 1 - Health Care Spaces Not Eligible

| | | |
|----------------------------|----------------------|-----------------------------|
| Anaesthetic gas scavenging | Cart and can washers | Areas using hazardous gases |
| Animal facilities | Chemical storage | Isolation rooms |
| Autopsy suite | Cooking facilities | Perchloric hoods |
| Biohazard and fume hoods | Ethylene oxide | Radioisotope hoods |

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$/CFM) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³ /CFM) | Electricity (kWh) | Water (L) | | |
| 1 | 1.75 – 4.89 | 0 | 0 | 3 | 0 |
| 2 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 3 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 4 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 5 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 6 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 7 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 8 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 9 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 10 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 11 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 12 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 13 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 14 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 15 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 16 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 17 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 18 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 19 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| 20 | 1.75 – 4.89 | 0 | 0 | 0 | 0 |
| TOTALS | 35 – 97.8 | 0 | 0 | 3 | 0 |

Resource Savings Assumptions

Annual Natural Gas Savings

1.75 – 4.89 m³/CFM

- ERV gas savings in new buildings is determined in the same way as in the ERV gas savings in existing buildings except the balance point temperature of a building. The balance point temperature of a building is selected based on building's thermal characteristics (internal & solar heat gains, infiltration rates and indoor temperature settings). Generally, older buildings (pre-1970's) or buildings with low internal heat gains (residences, motels, supermarkets, warehouses) should consider using a base HDD65°F or HDD60°F value. New buildings built to current OBC standards or buildings with high internal heat gains (retail, restaurants, offices) should consider using base HDD55°F, HDD50°F or even lower balance point temperature. The balance point values listed represent climate data for the London area.
- Natural gas savings are determined from engineering calculations utilizing inputs such as air flow, indoor/outdoor temperatures, indoor/outdoor and relative humidity.
- For example, input assumptions for a typical Ontario retail store are:

| Symbols | Variable Names | Values | Source |
|---------|--|-----------------|------------------|
| A | Supply air flow (cfm) | 500 | UG [†] |
| B | Exhaust air flow (cfm) | 500 | UG |
| C | Average indoor air temperature (°F) | 70 | UG |
| D | Average indoor relative humidity (%) | 30 | UG |
| E | Average outside air temperature (°F) | 31.5 | UG |
| F | Average outdoor relative humidity (%) | 70 | NCI ^Δ |
| G | Atmospheric pressure (psia) | 14.3 | UG |
| H | No. of hours in heating season (hrs) | 4,800 | UG |
| I1 | Demand Controlled Ventilation | no | UG |
| I2 | No. of hours of operation per week (hrs/wk) | 108 | UG |
| J | Make and Model of Heat Recovery Equipment | Eng A, HRW-2100 | UG |
| K | Effectiveness of Heat Recovery Equipment (%) | 60 | NCI |
| L | Sensible Heat Recovery Only | no | UG |
| M | Enthalpy (Btu/lba) & Humidity Ratio (lbw/lba) of INLET exhaust air | 22.0 | UG |
| N | Enthalpy (Btu/lba) & Humidity Ratio (lbw/lba) of INLET supply air | 10.4 | UG |
| O | Enthalpy (Btu/lba) & Humidity Ratio (lbw/lba) of OUTLET supply air | 17.3 | UG |
| P | Average Temperature of OUTLET supply air (°F) | 55 | UG |
| Q | Average Hourly Moisture Addition (lb/hr) | 2.6 | UG |
| R | Defrost Control Derating Factor (%) | 5 | UG |
| S | Average Hourly Heat Recovery (MBH) | 14.7 | UG |
| T | Seasonal Efficiency of Gas-Fired Equipment (%) | 82 | UG |
| U | Average annual gas reduction (m ³) | 1,571 | UG |
| V | Incremental natural gas rate (\$/m ³) | 0.3 | UG |
| W | Average annual gas savings (\$) | 471.3 | UG |

[†]UG: Union Gas

^ΔNCI: Navigant Consulting, Inc

NG Savings = # of Hours in Heating Season x (operating hours/168) x Average Hourly Heat Recovery / (35.3 m³/MJ) / (Seasonal Efficiency / 100%) **(A)**

- 168 hour = 7 days/week x 24hours/day

Average Hourly Heat Recovery = Supply air flow x 60 x (Supply air flow – Inlet supply air)/Specific Supply Air Conditions Volume x (1 – Defrost Control De-rating Factor¹ %) **(B)**

- Operating hours for each sectors being considered are as the following

¹ From Union Gas, all air-to-air heat recovery equipment requires frost control in colder climates to prevent freeze-up of exhaust air condensate on heat exchange components. Depending on the defrost control system, annual heat recovery estimates should be reduced by 5 to 15 %. Equipment manufacturers and suppliers can provide an estimated defrost derating factor given the operating conditions of the equipment.

| Building Occupancy | Typical Hrs of Operation per week |
|--------------------|-----------------------------------|
| Hotel | 168 |
| Restaurant | 108 |
| Retail | 108 |
| Office | 60 |
| School | 84 |
| Health Care | 168 |
| Nursing Home | 168 |
| Warehouse | 168 |

- New buildings and existing buildings mainly differ in the enthalpy (BTU/LBa) that is used to calculate the Specific Supply Air Conditions Volume in formula **(B)**.
- Based on the NG Savings formula **(A)** and input assumptions above, the natural gas savings for each of the commercial sectors are calculated, and a simple average is taken to be the general savings.

| Market Segment | ERV Capacity (CFM) | New Buildings | |
|------------------------------------|--------------------|------------------------------|--|
| | | NG Savings (m ³) | NG Savings per CFM (m ³ /CFM) |
| Hotel | 500 | 2,444 | 4.89 |
| Restaurant | 500 | 1,571 | 3.14 |
| Retail | 500 | 1,571 | 3.14 |
| Office | 500 | 873 | 1.75 |
| School | 500 | 1,222 | 2.44 |
| Health Care | 500 | 2,444 | 4.89 |
| Nursing Home | 500 | 2,444 | 4.89 |
| Warehouse | 500 | 2,444 | 4.89 |
| Average (m³/CFM) | | | 3.75 |

Annual Electricity Savings

0 kWh

N/A

Annual Water Savings

0 L

N/A

Other Input Assumptions

Effective Useful Life (EUL)

20 Years

ERVs have an estimated service life of 15 years based on Jacques Whitford study². Questar Gas³ and Puget Sound⁴ both report 20 years as an ERV's effective useful life. Navigant Consulting estimates 20 years as an effective useful life for ERVs.

Base & Incremental Conservation Measure Equipment and O&M Costs

\$3 / CFM

The incremental costs are based on relative scaling of incremental costs \$2,500 / 1000 CFM⁵. Based on communication with local contractors, the incremental costs are \$3/CFM.

² "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., by Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000.

³ Questar Gas, DSM Market Characterization Report, by Nexant, August 9, 2006

⁴ Quantec — Puget Sound Energy Demand-Side Management Resource Assessment

| Customer Payback Period (Natural Gas Only) ⁶ | 1.2 – 3.4 Years |
|---|-----------------|
| <p>Using an 5-year average commodity cost (avoided cost)⁷ of \$0.38 / m³ and an average commercial distribution cost⁸ of \$0.12 / m³, the payback period for natural gas savings is determined to be between 1.2 and 3.4 years, based on the following:</p> <p>On a per CFM basis,</p> <ol style="list-style-type: none"> 1) For offices, Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$3 / (1.75 m³/year * \$0.5 / m³) = 3.4 years 2) For hotels, warehouses, and health care, etc., Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$3 / 4.89 m³/year * \$0.5 / m³) =1.2 years | |
| Market Penetration ⁹ | Low |
| <p>Based on Jacques Whitford report¹⁰ (less than 5% market penetration) and communication with local contractors, Navigant Consulting estimates the market penetration of ERV to be low.</p> | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy, 2007 ¹¹ | 0.105 per sqft | 20 | 1 | N/A |
| <p>Comments Baseline therm reported on a square footage basis (eg 0.19 therms/sq.ft. for offices). Estimated 20% savings over the baseline. Incremental cost is reported on a per square footage basis. Equivalent savings is 0.19 therms/sq.ft x 2.75 m³/therms x 20% = 0.105 m³ / sq.ft</p> | | | | |

⁵ Ibid.

⁶ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁷ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁸ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

⁹ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁰ "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., by Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000.

¹¹ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

38. Enhanced Furnace (Electronically Commutated Motor) – Existing Commercial

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

High efficiency gas furnace equipped with an electronically commutated motor (ECM)

Base Equipment and Technologies Description

High efficiency gas furnace with a permanent split capacitor (PSC) motor

| Decision Type | Target Market(s) | End Use |
|---------------|-------------------------------|---------------|
| Replace | Commercial Existing Buildings | Space Heating |

Codes, Standards, and Regulations

- Under Ontario's building code, all gas furnaces installed in new residential constructions must meet a minimum condensing efficiency level effective January 1, 2007¹.
- There is no minimum energy performance standard restricting the electricity consumption of furnace fan blowers.
- However, effective December 31, 2009, NRCan requires the minimum performance level, or the Annual Fuel Utilization Efficiency (AFUE), for residential gas-fired furnaces with an input rate not exceeding 65.92 kW (225 000 Btu/h) to be 90%².

¹ Ministry of Energy, "Heating and Cooling your Home: A Conservation Guide", Reproduced with the permission of Natural Resource Canada, 2004. http://www.energy.gov.on.ca/english/pdf/conservation/heating_and_cooling_your_home.pdf

² Office of Energy Efficiency, Canada's Energy Efficiency Regulations, Final Bulletin, December 2008. <http://oee.nrcan.gc.ca/regulations/bulletin/gas-furnaces-dec08.cfm?attr=0>

Resource Savings Table (for 2 different cases)

Continuous Fan Usage

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure ³ (\$) |
|-----------------|---|-----------------------------|--------------|---|---|
| | Natural Gas (m ³ /kBtu/h) | Electricity (kWh/kBtu/h) | Water (L) | | |
| 1 | -2.7 | 22.7 | 0 | 960 | 0 |
| 2 | -2.7 | 22.7 | 0 | 0 | 0 |
| 3 | -2.7 | 22.7 | 0 | 0 | 0 |
| 4 | -2.7 | 22.7 | 0 | 0 | 0 |
| 5 | -2.7 | 22.7 | 0 | 0 | 0 |
| 6 | -2.7 | 22.7 | 0 | 0 | 0 |
| 7 | -2.7 | 22.7 | 0 | 0 | 0 |
| 8 | -2.7 | 22.7 | 0 | 0 | 0 |
| 9 | -2.7 | 22.7 | 0 | 0 | 0 |
| 10 | -2.7 | 22.7 | 0 | 0 | 0 |
| 11 | -2.7 | 22.7 | 0 | 0 | 0 |
| 12 | -2.7 | 22.7 | 0 | 0 | 0 |
| 13 | -2.7 | 22.7 | 0 | 0 | 0 |
| 14 | -2.7 | 22.7 | 0 | 0 | 0 |
| 15 | -2.7 | 22.7 | 0 | 0 | 0 |
| TOTALS | -40.7 | 340.5 | 0 | 960 | 0 |

Resource Savings Assumptions

| Annual Natural Gas Savings | -2.7 m ³ / kBtu / h |
|--|--------------------------------|
| <p>Continuous fan usage and non-continuous fan usage is estimated to be 26% and 74%, respectively, based on Ontario customer survey results⁴. Navigant Consulting is assuming the same mix of furnace fan usage for commercial application.</p> <p>A study conducted by the Canadian Center for Housing Technologies determined that the annual gas use of a typical existing home with a continuous ECM actually <i>increases</i> by 180 m³ for high efficiency furnaces (AFUE 92)⁵. The increase in natural gas consumption is a result of the reduction of heat added to the home from the decrease in electricity usage by the furnace motor.</p> <p>According to the CCHT report⁶, the residential furnace capacity is 67,500 Btu/h. Assuming savings for an ECM used for commercial applications do not significantly differ from a residential furnace, the natural gas savings on a kBtu/h basis is -180 m³ / 67.5 kBtu/h = -2.7m³/kBtu/h.</p> | |
| Annual Electricity Savings | 22.7kWh / kBtu / h |
| <p>Based on the Ontario Power Authority's 2009 OPA Measure and Assumptions Lists⁷, the electricity savings for an existing home using an ECM are estimated to be 1,387 kWh/year for continuous furnace fan usage. This represents a saving of 72% over a conventional PSC motor.</p> <p>These results are based on the same CCHT study, which determined that annual electricity savings for an existing home using a gas furnace with a continuous ECM for heating only is 1,535 kWh for high efficiency furnaces (AFUE 92)⁸. Since it is unlikely that the furnace fan will run continuously during the</p> | |

³ US DOE Energy Star Furnace Calculator, "Assumptions" tab.

http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Calc_Furnaces.xls

⁴ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, based on Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

⁵ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

⁶ Ibid.

⁷ Ontario Power Authority, 2009 OPA Measures and Assumptions List (Mass Market), November 2008.

⁸ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

shoulder season, the OPA assumes that during the shoulder season the same electricity savings from a non-continuous ECM are applicable. Navigant Consulting is assuming the same electricity savings for residential furnaces are applicable for commercial applications.

According to the CCHT report⁹, the residential furnace capacity is 67,500 Btu/h. Assuming savings for an ECM used for commercial applications do not significantly differ from a residential furnace, the electricity savings on a kBTU/h basis are estimated to be 1,535 / 67.5 kBTU/h = 22.7kWh/kBTU/h

Annual Water Savings

0 L

N/A

Non-Continuous Fan Usage

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure ¹⁰ (\$) |
|-----------------|---|-----------------------------|--------------|---|--|
| | Natural Gas (m ³ /kBTU/h) | Electricity (kWh/kBTU/h) | Water (L) | | |
| 1 | -0.4 | 4.8 | 0 | 960 | 0 |
| 2 | -0.4 | 4.8 | 0 | 0 | 0 |
| 3 | -0.4 | 4.8 | 0 | 0 | 0 |
| 4 | -0.4 | 4.8 | 0 | 0 | 0 |
| 5 | -0.4 | 4.8 | 0 | 0 | 0 |
| 6 | -0.4 | 4.8 | 0 | 0 | 0 |
| 7 | -0.4 | 4.8 | 0 | 0 | 0 |
| 8 | -0.4 | 4.8 | 0 | 0 | 0 |
| 9 | -0.4 | 4.8 | 0 | 0 | 0 |
| 10 | -0.4 | 4.8 | 0 | 0 | 0 |
| 11 | -0.4 | 4.8 | 0 | 0 | 0 |
| 12 | -0.4 | 4.8 | 0 | 0 | 0 |
| 13 | -0.4 | 4.8 | 0 | 0 | 0 |
| 14 | -0.4 | 4.8 | 0 | 0 | 0 |
| 15 | -0.4 | 4.8 | 0 | 0 | 0 |
| TOTALS | -5.3 | 72 | 0 | 960 | 0 |

Resource Savings Assumptions

Annual Natural Gas Savings

-0.4 m³ / kBTU / h

Continuous fan usage and non-continuous fan usage is estimated to be 26% and 74%, respectively, based on Ontario customer survey results¹¹. Navigant Consulting is assuming the same mix of furnace fan usage for commercial application.

A study conducted by the Canadian Center for Housing Technologies determined that the annual gas use of a typical existing home with a non-continuous ECM actually *increases* by 26 m³ for high efficiency furnaces (AFUE 92)¹². The increase in natural gas consumption is a result of the reduction of heat added to the home from the decrease in electricity usage by the furnace motor.

⁹ Ibid.

¹⁰ US DOE Energy Star Furnace Calculator, "Assumptions" tab.

http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Calc_Furnaces.xls

¹¹ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, based on Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

¹² The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

According to the CCHT report¹³, the residential furnace capacity is 67,500 Btu/h. Assuming savings for an ECM used for commercial applications do not significantly differ from a residential furnace, the natural gas savings on a kBTU/h basis is $-26 \text{ m}^3 / 67.5 \text{ kBTU/h} = -0.4 \text{ m}^3/\text{kBTU/h}$.

Annual Electricity Savings

4.8 kWh / kBTU / h

Based on the Ontario Power Authority's 2009 OPA Measure and Assumptions List¹⁴, the electricity savings for a new home using an ECM are estimated to be 324 kWh/year for non-continuous furnace fan use. This represents a saving of 40% over a conventional PSC motor.

These results are based on the same CCHT study, which determined that annual electricity savings for a new home using a gas furnace with an ECM for heating only is 324 kWh for high efficiency furnaces (AFUE 92)¹⁵. Navigant Consulting is assuming the same electricity savings for residential furnaces are applicable for commercial applications.

According to the CCHT report¹⁶, the residential furnace capacity is 67,500 Btu/h. Assuming savings for an ECM used for commercial applications do not significantly differ from a residential furnace, the electricity savings on a kBTU/h basis is estimated to be $324 / 67.5 \text{ kBTU/h} = 4.8 \text{ kWh/kBTU/h}$.

Annual Water Savings

0 L

N/A

Other Input Assumptions

Effective Useful Life (EUL)

15 Years

An OPA commissioned study by Seeline Group Inc. suggests a useful life of 15 years. Furthermore, a June 2007 study by GDS Associates, Inc.¹⁷ for New England State Program Working Group (SPWG) also suggests 15 years. Finally, Iowa Utilities¹⁸ also uses 15 years as an effective useful life for an ECM.

Base & Incremental Conservation Measure Equipment and O&M Costs

\$960

Based on the average of a survey of prices from HVAC contractors in Ontario¹⁹, the incremental cost for residential ECM's are estimated to be \$960. This incremental cost is assumed to be the same for commercial furnaces. Incremental costs were confirmed through communication with additional HVAC contractors.

Customer Payback Period (Natural Gas Only)²⁰

**Continuous = 10 years
Non-Continuous = 31 years**

Since natural gas usage increases with an ECM, Navigant Consulting has used both natural gas and electricity savings to calculate the customer payback period.

For Natural Gas Usage:

Combining a 5-year average commodity cost (avoided cost)²¹ of $\$0.38 / \text{m}^3$ and an average commercial distribution cost²² of $\$0.12 / \text{m}^3$, the total cost of natural gas for typical commercial customers is determined to be \$0.50.

¹³ Ibid.

¹⁴ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008.

¹⁵ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

¹⁶ Ibid.

¹⁷ GDS Associates Inc, Measure Life Report: Residential and Commercial/Industrial Lighting and HVAC Measures, Prepared for The New England State Program Working Group (SPWG) For use as an Energy Efficiency Measures/Programs Reference Document for the ISO Forward Capacity Market (FCM), June 2007.

¹⁸ Joint Assessment Study, MidAmerican Energy Company, Appendix C. State of Iowa Utilities Board Docket No. EEP-08-2, 2008, C-131

¹⁹ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, based on Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

²⁰ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

²¹ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

For Electricity Savings:

An average commodity and distribution cost of \$0.09 / kWh is assumed for commercial customers.

For customer payback calculations, Navigant Consulting is assuming a commercial furnace which to be double the size of a residential furnace, or 135 kBtu/h (67,500 Btu/h x 2 = 135,000 Btu/h or 135 kBTU/hr).

The payback period incorporating both natural gas usage and electricity savings is determined to be 10 years for continuous usage and 31 years for non-continuous furnace fan usage, based on the following:

$$\text{Payback Period} = \text{Incremental cost} / [(\text{natural gas savings} \times \text{natural gas cost}) + (\text{electricity savings} \times \text{electricity cost})]$$

Continuous Fan Usage:

$$\begin{aligned} &= \$960 / [135 \text{ kBtu/hr} \times ((-2.7 \text{ m}^3 / \text{kBtu/h} / \text{year} \times \$0.50 / \text{m}^3) + (22.7 \text{ kWh} / \text{kBtu/h} / \text{year} \times \$0.09 / \text{kWh}))] \\ &= 10.3 \text{ years} \end{aligned}$$

Non-Continuous Fan Usage:

$$\begin{aligned} &= \$960 / [135 \text{ kBtu/hr} \times ((-0.4 \text{ m}^3 / \text{kBtu/h} / \text{year} \times \$0.50 / \text{m}^3) + (4.8 \text{ kWh} / \text{kBtu/h} / \text{year} \times \$0.09 / \text{kWh}))] \\ &= 31 \text{ years} \end{aligned}$$

Market Share²³

Low

Although the benefits of electronically commutated motors are increasingly being promoted by the industry, the overall market share still remains low in the commercial retrofit market, as seen in another jurisdiction (Iowa reports a 5% market penetration for commercial buildings²⁴). Therefore, Navigant Consulting estimates the market share in Ontario to be low.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/ Market Share |
|--|---|-------------------------------|-----------------------|---------------------------|
| 2009 OPA Measures and Assumptions List ²⁵ | -80.1m ³ (continuous) 22.6m ³ (non-continuous) | 15 | \$960 | N/A |
| Comments Assumptions made in the OPA Measures and Assumptions List are the same assumptions that are made in the above tables. | | | | |

²² Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

²³ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

²⁴ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

²⁵ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008.

39. Enhanced Furnace (Electronically Commutated Motor) – New Commercial

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Gas furnace equipped with an electronically commutated motor (ECM)

Base Equipment and Technologies Description

Gas furnace with a permanent split capacitor (PSC) motor

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------------|---------------|
| New | Commercial New Construction | Space Heating |

Codes, Standards, and Regulations

- Under Ontario's building code, all gas furnaces installed in new residential constructions must meet a minimum condensing efficiency level effective January 1, 2007¹.
- There is no minimum energy performance standard restricting the electricity consumption of furnace fan blowers.

However, effective December 31, 2009, NRCAN requires the minimum performance level, or the Annual Fuel Utilization Efficiency (AFUE), for residential gas-fired furnaces with an input rate not exceeding 65.92 kW (225 000 Btu/h) to be 90%².

Resource Savings Table (for 2 different cases)

Continuous Fan Usage

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|---|-----------------------------|--------------|---|--|
| | Natural Gas (m ³ /kBtu/h) | Electricity (kWh/kBtu/h) | Water (L) | | |
| 1 | -2.4 | 23.2 | 0 | 960 | 0 |
| 2 | -2.4 | 23.2 | 0 | 0 | 0 |
| 3 | -2.4 | 23.2 | 0 | 0 | 0 |
| 4 | -2.4 | 23.2 | 0 | 0 | 0 |
| 5 | -2.4 | 23.2 | 0 | 0 | 0 |
| 6 | -2.4 | 23.2 | 0 | 0 | 0 |
| 7 | -2.4 | 23.2 | 0 | 0 | 0 |
| 8 | -2.4 | 23.2 | 0 | 0 | 0 |
| 9 | -2.4 | 23.2 | 0 | 0 | 0 |
| 10 | -2.4 | 23.2 | 0 | 0 | 0 |
| 11 | -2.4 | 23.2 | 0 | 0 | 0 |
| 12 | -2.4 | 23.2 | 0 | 0 | 0 |
| 13 | -2.4 | 23.2 | 0 | 0 | 0 |
| 14 | -2.4 | 23.2 | 0 | 0 | 0 |
| 15 | -2.4 | 23.2 | 0 | 0 | 0 |
| TOTALS | -36 | 348 | 0 | 960 | 0 |

¹ Ministry of Energy, "Heating and Cooling your Home: A Conservation Guide." Reproduced with the permission of Natural Resource Canada, 2004. http://www.energy.gov.on.ca/english/pdf/conservation/heating_and_cooling_your_home.pdf

² Office of Energy Efficiency, Canada's Energy Efficiency Regulations, Final Bulletin, December 2008. <http://oee.nrcan.gc.ca/regulations/bulletin/gas-furnaces-dec08.cfm?attr=0>

Resource Savings Assumptions

| Annual Natural Gas Savings | -2.4 m³ / kBtu / h |
|--|--------------------------------------|
| <p>Continuous fan usage and non-continuous fan usage is estimated to be 26% and 74%, respectively, based on Ontario customer survey results³. Navigant Consulting is assuming the same mix of furnace fan usage for commercial application.</p> <p>A study conducted by the Canadian Center for Housing Technologies determined that a the annual gas use of a typical new home with a continuous ECM actually <i>increases</i> by 164m³ for high efficiency furnaces (AFUE 92)⁴. The increase in natural gas consumption is a result of the reduction of heat added to the home from the decrease in electricity usage by the furnace motor. NCI assumes that 12% of new furnaces are mid-efficiency and 88% of furnaces are high efficiency based on recent survey results for residential furnaces⁵, resulting in an average increase of 166.4m³. Navigant Consulting is assuming the same mix of furnace fan usage for commercial application.</p> <p>According to the CCHT report⁶, the residential furnace capacity is 67,500 Btu/h. Assuming savings for an ECM used for commercial applications do not significantly differ from a residential furnace, the natural gas savings on a kBtu/h basis is $-164 \text{ m}^3 / 67.5 \text{ kBtu/h} = -2.4 \text{ m}^3/\text{kBtu/h}$.</p> | |

³ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, based on Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

⁴ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

⁵ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, based on Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

⁶ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

| Annual Electricity Savings | 23.2kWh / kBtu / h |
|---|--------------------|
| <p>Based on the Ontario Power Authority's 2009 OPA Measure and Assumptions Lists⁷, the electricity savings for a new home using an ECM are estimated to be 1,403 kWh/year for continuous furnace fan use. This represents a savings of 78% over a conventional PSC motor.</p> <p>These results are based on the same CCHT study, which determined that annual electricity savings for a new home using a gas furnace with an ECM for heating only is 1,569 kWh for high efficiency furnaces (AFUE 92)⁸. Since it is unlikely that the furnace fan will run continuously during the shoulder season, the OPA assumes that during the shoulder season the same electricity savings from a non-continuous ECM are applicable. Navigant Consulting is assuming the same electricity savings for residential furnaces are applicable for commercial applications.</p> <p>According to the CCHT report⁹, the residential furnace capacity is 67,500 Btu/h. Assuming savings for an ECM used for commercial applications do not significantly differ from a residential furnace, the electricity savings on a kBtu/h basis are estimated to be 1,569 / 67.5 kBtu/h = 23.2 kWh/kBtu/h.</p> | |
| Annual Water Savings | 0 L |
| N/A | |

Non-Continuous Fan Usage

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure ¹⁰ (\$) ¹¹ |
|-----------------|---|-----------------------------|--------------|---|--|
| | Natural Gas (m ³ /kBtu/h) | Electricity (kWh/kBtu/h) | Water (L) | | |
| 1 | -0.3 | 3.1 | 0 | 960 | 0 |
| 2 | -0.3 | 3.1 | 0 | 0 | 0 |
| 3 | -0.3 | 3.1 | 0 | 0 | 0 |
| 4 | -0.3 | 3.1 | 0 | 0 | 0 |
| 5 | -0.3 | 3.1 | 0 | 0 | 0 |
| 6 | -0.3 | 3.1 | 0 | 0 | 0 |
| 7 | -0.3 | 3.1 | 0 | 0 | 0 |
| 8 | -0.3 | 3.1 | 0 | 0 | 0 |
| 9 | -0.3 | 3.1 | 0 | 0 | 0 |
| 10 | -0.3 | 3.1 | 0 | 0 | 0 |
| 11 | -0.3 | 3.1 | 0 | 0 | 0 |
| 12 | -0.3 | 3.1 | 0 | 0 | 0 |
| 13 | -0.3 | 3.1 | 0 | 0 | 0 |
| 14 | -0.3 | 3.1 | 0 | 0 | 0 |
| 15 | -0.3 | 3.1 | 0 | 0 | 0 |
| TOTALS | -4.5 | 46 | 0 | 960 | 0 |

Resource Savings Assumptions

| Annual Natural Gas Savings | -0.3 m ³ / kBtu / h |
|---|--------------------------------|
| <p>Continuous fan usage and non-continuous fan usage is estimated to be 26% and 74%, respectively, based on Ontario customer survey results¹². Navigant Consulting is assuming the same mix of furnace fan usage for commercial application.</p> | |

⁷ Ontario Power Authority, 2009 OPA Measures and Assumptions List (Mass Market), November 2008.

⁸ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

⁹ Ibid.

¹⁰ USDOE Energy Star Furnace Calculator, "Assumptions" tab.
http://www.energystar.gov/ia/business/bulk_purchasing/bpsavings_calc/Calc_Furnaces.xls

¹¹ The 2007 average exchange rate from US dollar to Canadian dollar is US\$1 = CA\$1.07. This rate is used to convert USDOE base furnace cost to Canadian dollars. <http://www.x-rates.com/d/CAD/USD/hist2007.html>

¹² Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, based on Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

A study conducted by the Canadian Center for Housing Technologies determined that the annual gas use of a typical new home with a non-continuous ECM actually *increases* by 18 m³ for high efficiency furnaces (AFUE 92)¹³. The increase in natural gas consumption is a result of the reduction of heat added to the home from the decrease in electricity usage by the furnace motor.

According to the CCHT report¹⁴, the residential furnace capacity is 67,500 Btu/h. Assuming savings for an ECM used for commercial applications do not significantly differ from a residential furnace, the natural gas savings on a kBTU/h basis is $-18 \text{ m}^3 / 67.5 \text{ kBTU/h} = -0.3 \text{ m}^3/\text{kBTU/h}$.

Annual Electricity Savings

3.1 kWh / kBTU / h

Based on the Ontario Power Authority's 2009 OPA Measure and Assumptions List¹⁵, the electricity savings for a new home using an ECM are estimated to be 207 kWh/year for non-continuous furnace fan use. This represents a savings of 40% over a conventional PSC motor.

These results are based on the same CCHT study, which determined that annual electricity savings for a new home using a gas furnace with an ECM for heating is 207 kWh for high efficiency furnaces (AFUE 92)¹⁶. Navigant Consulting is assuming the same electricity savings for residential furnaces are applicable for commercial applications.

According to the CCHT report¹⁷, the residential furnace capacity is 67,500 Btu/h. Assuming savings for an ECM used for commercial applications do not significantly differ from a residential furnace, the electricity savings on a kBTU/h basis is estimated to be $207 / 67.5 \text{ kBTU/h} = 3.1 \text{ kWh/kBTU/h}$.

Annual Water Savings

0 L

N/A

Other Input Assumptions

Effective Useful Life (EUL)

15 Years

An OPA commissioned study by Seeline Group Inc. suggests a useful life of 15 years. Furthermore, a June 2007 study by GDS Associates, Inc.¹⁸ for New England State Program Working Group (SPWG) also suggests 15 years. Finally, Iowa Utilities¹⁹ also uses 15 years as an effective useful life for an ECM.

Base & Incremental Conservation Measure Equipment and O&M Costs

\$960

Based on the average of a survey of prices from HVAC contractors in Ontario²⁰, the incremental cost is estimated to be \$960. Incremental costs were confirmed through communication with additional HVAC contractors.

Customer Payback Period (Natural Gas and Electricity)

**Continuous = 10 years
Non-Continuous = 55 years**

Since natural gas usage increases with an ECM, Navigant Consulting has used both natural gas and electricity savings to calculate the customer payback period.

¹³ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

¹⁴ Ibid.

¹⁵ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008.

¹⁶ The Canadian Center for Housing Technologies, "Final Report on the Effects of ECM Furnace Motors on Electricity and Gas Use: Results from the CCHT Research Facility and Projections" <http://irc.nrcnrc.gc.ca/pubs/fulltext/nrcc38500/nrcc38500.pdf>

¹⁷ Ibid.

¹⁸ GDS Associates Inc, Measure Life Report: Residential and Commercial/Industrial Lighting and HVAC Measures, Prepared for The New England State Program Working Group (SPWG) For use as an Energy Efficiency Measures/Programs Reference Document for the ISO Forward Capacity Market (FCM), June 2007.

¹⁹ Joint Assessment Study, MidAmerican Energy Company, Appendix C. State of Iowa Utilities Board Docket No. EEP-08-2, 2008, C-131

²⁰ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008, based on Navigant Consulting, Evaluation Report: 2007 Hot and Cool Savings Programs, prepared for the Ontario Power Authority (OPA), July 2008.

For Natural Gas Usage:

Combining a 5-year average commodity cost (avoided cost)²¹ of \$0.38 / m³ and an average commercial distribution cost²² of \$0.12 / m³, the total cost of natural gas for typical commercial customers is determined to be \$0.50.

For Electricity Savings:

An average commodity and distribution cost of \$0.09 / kWh is assumed for commercial customers.

For customer payback calculations, Navigant Consulting is assuming a commercial furnace to be double the size of a residential furnace, or 135 kBtu/h (67,500 Btu/h x 2 = 135,000 Btu/h or 135 kBTU/hr).

The payback period incorporating both natural gas usage and electricity savings is determined to be 10 years for continuous usage and 55 years for non-continuous furnace fan usage, based on the following:

Payback Period = Incremental cost / [(natural gas savings x natural gas cost) + (electricity savings x electricity cost)]

Continuous Fan Usage:

$$\begin{aligned} &= \$960 / [135 \text{ kBtu/hr} \times ((-2.4 \text{ m}^3 / \text{kBtu/h} / \text{year} \times \$0.50 / \text{m}^3) + (23.2 \text{ kWh} / \text{kBtu/h} / \text{year} \times \$0.09 / \text{kWh}))] \\ &= 10 \text{ years} \end{aligned}$$

Non-Continuous Fan Usage:

$$\begin{aligned} &= \$960 / [135 \text{ kBtu/hr} \times ((-0.3 \text{ m}^3 / \text{kBtu/h} / \text{year} \times \$0.50 / \text{m}^3) + (3.1 \text{ kWh} / \text{kBtu/h} / \text{year} \times \$0.09 / \text{kWh}))] \\ &= 55 \text{ years} \end{aligned}$$

Market Share²³

Low

Although the benefits of electronically commutated motors are increasingly being promoted by the industry, the overall market share still remains low in the commercial retrofit market, as seen in another jurisdictions (Iowa reports a 5% market penetration for commercial buildings²⁴). Therefore, Navigant Consulting estimates the market share in Ontario to be low.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/ Market Share |
|---|---------------------------------|-------------------------------|-----------------------|---------------------------|
| Efficiency Vermont Technical Resources ²⁵ | 0 | 18 | \$200 (USD) | NA |
| Comments A furnace meeting minimum Federal efficiency standards using a low-efficiency permanent split capacitor (PSC) fan motor is replaced with a high efficiency an ENERGY STAR® qualified furnace with a high-efficiency ECM. Vermont suggests electricity savings of 393 kWh/yr for space heating. | | | | |

²¹ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

²² Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

²³ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

²⁴ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

²⁵ Efficiency Vermont. Residential Master Technical Reference Manual. Number 2005-37 Measure Savings Algorithms and Cost Assumptions. February 2006.

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/ Market Share |
|---|---|-------------------------------|-----------------------|---------------------------|
| 2009 OPA Measures and Assumptions List ²⁶ | -66.8 m ³ (continuous usage) 30.6m ³ (non-continuous) | 15 | \$960 | NA |
| Comments Assumptions made in the OPA Measures and Assumptions Lists are the same assumptions that are made in the above tables. | | | | |

²⁶ Ontario Power Authority, 2009 OPA Measures and Assumptions Lists (Mass Market), November 2008.

40. Heat Recovery Ventilator (HRV) – Existing Commercial

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Ventilation with HRV

Base Equipment and Technologies Description

Ventilation without HRV

| Decision Type | Target Market(s) | End Use |
|---------------|---------------------|---------------|
| Retrofit | Existing Commercial | Space Heating |

Codes, Standards, and Regulations

N/A

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$/CFM) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³ /CFM) | Electricity (kWh) | Water (L) | | |
| 1 | 1.75 – 4.90 | 0 | 0 | 3.4 | 0 |
| 2 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 3 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 4 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 5 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 6 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 7 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 8 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 9 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 10 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 11 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 12 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 13 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 14 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 15 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 16 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 17 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 18 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 19 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| 20 | 1.75 – 4.90 | 0 | 0 | 0 | 0 |
| TOTALS | 35 – 98 | 0 | 0 | 3.4 | 0 |

Resource Savings Assumptions

| Annual Natural Gas Savings | | | 1.75 – 4.90 m ³ / CFM |
|--|--|-----------------|----------------------------------|
| <ul style="list-style-type: none"> Natural gas savings are determined from engineering calculations utilizing inputs such as air flow, indoor/outdoor temperatures, indoor/outdoor and relative humidity. For example, input assumptions for a typical Ontario retail store are: | | | |
| Symbols | Variable Names | Values | Source |
| A | Supply air flow (cfm) | 500 | UG [†] |
| B | Exhaust air flow (cfm) | 500 | UG |
| C | Average indoor air temperature (°F) | 70 | UG |
| D | Average indoor relative humidity (%) | 30 | UG |
| E | Average outside air temperature (°F) | 31.5 | UG |
| F | Average outdoor relative humidity (%) | 70 | NCI ^Δ |
| G | Atmospheric pressure (psia) | 14.3 | UG |
| H | No. of hours in heating season (hrs) | 4,800 | UG |
| I1 | Demand Controlled Ventilation | no | UG |
| I2 | No. of hours of operation per week (hrs/wk) | 108 | UG |
| J | Make and Model of Heat Recovery Equipment | Eng A, HRW-2100 | UG |
| K | Effectiveness of Heat Recovery Equipment (%) | 70 | NCI |
| L | Sensible Heat Recovery Only | yes | UG |
| M | Enthalpy (Btu/lba) & Humidity Ratio (lbw/lba) of INLET exhaust air | 22.0 | UG |
| N | Enthalpy (Btu/lba) & Humidity Ratio (lbw/lba) of INLET supply air | 10.4 | UG |
| O | Enthalpy (Btu/lba) & Humidity Ratio (lbw/lba) of OUTLET supply air | 16.9 | UG |
| P | Average Temperature of OUTLET supply air (°F) | 58 | UG |
| Q | Average Hourly Moisture Addition (lb/hr) | 0.0 | UG |
| R | Defrost Control Derating Factor (%) | 5 | UG |
| S | Average Hourly Heat Recovery (MBH) | 13.7 | UG |
| T | Seasonal Efficiency of Gas-Fired Equipment (%) | 82 | UG |
| U | Average annual gas reduction (m ³) | 1,461 | UG |
| V | Incremental natural gas rate (\$/m ³) | 0.3 | UG |
| W | Average annual gas savings (\$) | 438.4 | UG |

[†]UG: Union Gas

^ΔNCI: Navigant Consulting, Inc

- NG Savings** = # of Hours in Heating Season x (operating hours/168) x Average Hourly Heat Recovery / (35.3 m³/MJ) / (Seasonal Efficiency / 100%) **(A)**
 - 168 hour = 7 days/week x 24hours/day
 - Average Hourly Heat Recovery = Supply air flow x 60 x (Supply air flow – Inlet supply air)/Specific Supply Air Conditions Volume x (1 – Defrost Control De-rating Factor¹ %) **(B)**
- Operating hours for each sectors being considered are as the following

| Building Occupancy | Typical Hrs of Operation per week |
|--------------------|-----------------------------------|
| Hotel | 168 |
| Restaurant | 108 |
| Retail | 108 |
| Office | 60 |
| School | 84 |
| Health Care | 168 |
| Nursing Home | 168 |
| Warehouse | 168 |

¹ From Union Gas, all air-to-air heat recovery equipment requires frost control in colder climates to prevent freeze-up of exhaust air condensate on heat exchange components. Depending on the defrost control system, annual heat recovery estimates should be reduced by 5 to 15 %. Equipment manufacturers and suppliers can provide an estimated defrost derating factor given the operating conditions of the equipment.

- New buildings and existing buildings mainly differ in enthalpy (BTU/LBa) that is used to calculate the Specific Supply Air Conditions Volume in formula **(B)**.
- Based on the NG Savings formula **(A)** and input assumptions above, the natural gas savings for each of the commercial sectors are calculated, and a simple average is taken to be the general savings.

| Market Segment | HRV Capacity (CFM) | Existing Buildings | |
|------------------------------------|--------------------|------------------------------|--|
| | | NG Savings (m ³) | NG Savings per CFM (m ³ /CFM) |
| Hotel | 500 | 2,452 | 4.90 |
| Restaurant | 500 | 1,576 | 3.15 |
| Retail | 500 | 1,576 | 3.15 |
| Office | 500 | 876 | 1.75 |
| School | 500 | 1,226 | 2.45 |
| Health Care | 500 | 2,452 | 4.90 |
| Nursing Home | 500 | 2,452 | 4.90 |
| Warehouse | 500 | 2,452 | 4.90 |
| Average (m³/CFM) | | | 3.77 |

| | |
|-----------------------------------|------------------|
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 0 L / CFM |
| N/A | |

Other Input Assumptions

| | |
|---|------------------------|
| Effective Useful Life (EUL) | 20 Years |
| HRVs have an estimated service life of 15 years based on Jacques Whitford study ² . Since Questar Gas ³ and Puget Sound ⁴ both report 20 years as its effective useful life, Navigant also estimates the EUL to be 20 years. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$3.4 / CFM |
| The incremental costs are based on relative scaling of incremental costs \$1,700 / 500 CFM ⁵ . | |
| Customer Payback Period (Natural Gas Only)⁶ | 1.4 – 3.9 Years |
| Using an 5-year average commodity cost (avoided cost) ⁷ of \$0.38 / m ³ and an average commercial distribution cost ⁸ of \$0.12 / m ³ , the payback period for natural gas savings is determined to be between 1.4 and 3.9 years, based on the following: | |
| On a per CFM basis, | |
| 1) For offices, Payback Period = Incremental cost / (natural gas savings x natural gas cost) | |
| = \$3.4 / (1.75 m ³ /year * \$0.5 / m ³) | |
| = 3.9 years | |

² "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., by Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000.

³ Questar Gas, DSM Market Characterization Report, by Nexant, August 9, 2006

⁴ Quantec — Puget Sound Energy Demand-Side Management Resource Assessment

⁵ "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., by Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000.

⁶ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁷ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁸ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

- 2) For hotels, warehouses, and health care, etc., Payback Period = Incremental cost / (natural gas savings x natural gas cost)
 $= \$3.4 / (4.90 \text{ m}^3/\text{year} * \$0.5 / \text{m}^3)$
 $= 1.4 \text{ years}$

Market Penetration⁹

Low

Based on Jacques Whitford report¹⁰ (less than 5% market penetration) and communication with local contractors, Navigant Consulting estimates the market penetration of HRV to be low.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Questar Gas ¹¹ | 670 | 20 | 1,785 | N/A |
| Comments Specifications for HRVs are not provided in the report, nor the baseline assumptions. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Puget Sound Energy ¹² | 0.1045 per ft ² | 20 | 1 | N/A |
| Comments Baseline therm reported on a square footage basis (eg 0.19 therms/sq.ft. for offices). Estimated 20% savings for new energy efficient technology is reported as a percent saving over the baseline. Incremental cost is reported on a per square footage basis. Equivalent savings is 0.19 therms/sq.ft. x 2.75 m ³ /therms x 20% = 0.1045 m ³ | | | | |

⁹ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁰ "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., by Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000.

¹¹ Questar Gas, DSM Market Characterization Report, by Nexant, August 9, 2006

¹² Quantec, Comprehensive Demand-Side Management Resource Assessment, Prepared for Puget Sound Energy, May 2007
C-184

41. Heat Recovery Ventilator (HRV) – New Commercial

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Ventilation with HRV

Base Equipment and Technologies Description

Ventilation without HRV

| Decision Type | Target Market(s) | End Use |
|---------------|------------------|---------------|
| New | Commercial | Space Heating |

Codes, Standards, and Regulations

- Restriction for New Building Construction: This measure is not applicable to system $\geq 5,000$ CFM with $\geq 70\%$ OA ratio because energy recovery is required by Ontario Building Code 2006.
- Restriction for New Building Construction: This measure is not applicable to systems serving health care spaces indicated in **Table 1** because heat recovery is required by CSA Z317.2-01

Table 1 - Health Care Spaces Not Eligible

| | | |
|----------------------------|----------------------|-----------------------------|
| Anaesthetic gas scavenging | Cart and can washers | Areas using hazardous gases |
| Animal facilities | Chemical storage | Isolation rooms |
| Autopsy suite | Cooking facilities | Perchloric hoods |
| Biohazard and fume hoods | Ethylene oxide | Radioisotope hoods |

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$/CFM) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³ /CFM) | Electricity (kWh) | Water (L) | | |
| 1 | 1.62 – 4.55 | 0 | 0 | 3.4 | 0 |
| 2 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 3 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 4 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 5 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 6 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 7 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 8 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 9 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 10 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 11 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 12 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 13 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 14 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 15 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 16 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 17 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 18 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 19 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| 20 | 1.62 – 4.55 | 0 | 0 | 0 | 0 |
| TOTALS | 32.4 – 91 | 0 | 0 | 3.4 | 0 |

Resource Savings Assumptions

| Annual Natural Gas Savings | | | 1.62 – 4.55 m ³ /CFM |
|---|--|-----------------|---------------------------------|
| <ul style="list-style-type: none"> • HRV gas savings in new buildings is determined in the same way as in the HRV gas savings in existing buildings except the balance point temperature of a building. The balance point temperature of a building is selected based on building's thermal characteristics (internal & solar heat gains, infiltration rates and indoor temperature settings). Generally, older buildings (pre-1970's) or buildings with low internal heat gains (residences, motels, supermarkets, warehouses) should consider using a base HDD65oF or HDD60oF value. New buildings built to current OBC standards or buildings with high internal heat gains (retail, restaurants, offices) should consider using base HDD55oF, HDD50oF or even lower balance point temperature. The balance point values listed represent climate data for the London area. • Natural gas savings are determined from engineering calculations utilizing inputs such as air flow, indoor/outdoor temperatures, indoor/outdoor and relative humidity. • For example, input assumptions for a typical Ontario retail store are: | | | |
| Symbols | Variable Names | Values | Source |
| A | Supply air flow (cfm) | 500 | UG [†] |
| B | Exhaust air flow (cfm) | 500 | UG |
| C | Average indoor air temperature (°F) | 70 | UG |
| D | Average indoor relative humidity (%) | 30 | UG |
| E | Average outside air temperature (°F) | 31.5 | UG |
| F | Average outdoor relative humidity (%) | 70 | NCI ^Δ |
| G | Atmospheric pressure (psia) | 14.3 | UG |
| H | No. of hours in heating season (hrs) | 4,800 | UG |
| I1 | Demand Controlled Ventilation | no | UG |
| I2 | No. of hours of operation per week (hrs/wk) | 108 | UG |
| J | Make and Model of Heat Recovery Equipment | Eng A, HRW-2100 | UG |
| K | Effectiveness of Heat Recovery Equipment (%) | 70 | NCI |
| L | Sensible Heat Recovery Only | yes | UG |
| M | Enthalpy (Btu/lba) & Humidity Ratio (lbw/lba) of INLET exhaust air | 22.0 | UG |
| N | Enthalpy (Btu/lba) & Humidity Ratio (lbw/lba) of INLET supply air | 10.4 | UG |
| O | Enthalpy (Btu/lba) & Humidity Ratio (lbw/lba) of OUTLET supply air | 16.9 | UG |
| P | Average Temperature of OUTLET supply air (°F) | 58 | UG |
| Q | Average Hourly Moisture Addition (lb/hr) | 0.0 | UG |
| R | Defrost Control Derating Factor (%) | 5 | UG |
| S | Average Hourly Heat Recovery (MBH) | 13.7 | UG |
| T | Seasonal Efficiency of Gas-Fired Equipment (%) | 82 | UG |
| U | Average annual gas reduction (m ³) | 1,461 | UG |
| V | Incremental natural gas rate (\$/m ³) | 0.3 | UG |
| W | Average annual gas savings (\$) | 438.4 | UG |
| [†] UG: Union Gas ^Δ NCI: Navigant Consulting, Inc | | | |
| <ul style="list-style-type: none"> • NG Savings = # of Hours in Heating Season x (operating hours/168) x Average Hourly Heat Recovery / (35.3 m³/MJ) / (Seasonal Efficiency / 100%) (A) <ul style="list-style-type: none"> – 168 hour = 7 days/week x 24hours/day – Average Hourly Heat Recovery = Supply air flow x 60 x (Supply air flow – Inlet supply air)/Specific Supply Air Conditions Volume x (1 – Defrost Control De-rating Factor¹ %) (B) | | | |

¹ From Union Gas, all air-to-air heat recovery equipment requires frost control in colder climates to prevent freeze-up of exhaust air condensate on heat exchange components. Depending on the defrost control system, annual heat recovery estimates should be reduced by 5 to 15 %. Equipment manufacturers and suppliers can provide an estimated defrost derating factor given the operating conditions of the equipment.

- Operating hours for each sectors being considered are as the following

| Building Occupancy | Typical Hrs of Operation per week |
|--------------------|-----------------------------------|
| Hotel | 168 |
| Restaurant | 108 |
| Retail | 108 |
| Office | 60 |
| School | 84 |
| Health Care | 168 |
| Nursing Home | 168 |
| Warehouse | 168 |

- New buildings and existing buildings mainly differ in enthalpy (BTU/LBa) that is used to calculate the Specific Supply Air Conditions Volume in formula **(B)**.
- Based on the NG Savings formula **(A)** and input assumptions above, the natural gas savings for each of the commercial sectors are calculated, and a simple average is taken to be the general savings.

| Market Segment | HRV Capacity (CFM) | New Buildings | |
|------------------------------------|--------------------|------------------------------|--|
| | | NG Savings (m ³) | NG Savings per CFM (m ³ /CFM) |
| Hotel | 500 | 2,273 | 4.55 |
| Restaurant | 500 | 1,461 | 2.92 |
| Retail | 500 | 1,461 | 2.92 |
| Office | 500 | 812 | 1.62 |
| School | 500 | 1,137 | 2.27 |
| Health Care | 500 | 2,273 | 4.55 |
| Nursing Home | 500 | 2,273 | 4.55 |
| Warehouse | 500 | 2,273 | 4.55 |
| Average (m³/CFM) | | | 3.49 |

Annual Electricity Savings

0 kWh

N/A

Annual Water Savings

0 L/CFM

N/A

Other Input Assumptions

Effective Useful Life (EUL)

20 Years

HRVs have an estimated service life of 15 years based on Jacques Whitford study². Since Questar Gas³ and Puget Sound⁴ both report 20 years as its effective useful life, Navigant also estimates the EUL to be 20 years.

Base & Incremental Conservation Measure Equipment and O&M Costs

\$3.4 / CFM

The incremental costs are based on relative scaling of incremental costs \$1,700 / 500 CFM⁵.

² "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., by Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000.

³ Questar Gas, DSM Market Characterization Report, by Nexant, August 9, 2006

⁴ Quantec — Puget Sound Energy Demand-Side Management Resource Assessment

⁵ "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., by Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000.

| Customer Payback Period (Natural Gas Only) ⁶ | 1.5 – 4.2 Years |
|---|-----------------|
| <p>Using an 5-year average commodity cost (avoided cost)⁷ of \$0.38 / m³ and an average commercial distribution cost⁸ of \$0.12 / m³, the payback period for natural gas savings is determined to be between 1.5 and 4.2 years, based on the following:</p> <p>On a per CFM basis,</p> <ol style="list-style-type: none"> 1) For offices, Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$3.4 / (1.62 m³/year * \$0.5 / m³) = 4.2 years 2) For hotels, warehouses, health care, etc., Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$3.4 / (4.55 m³/year * \$0.5 / m³) = 1.5 years | |
| Market Penetration ⁹ | Low |
| <p>Based on Jacques Whitford report¹⁰ (less than 5% market penetration) and communication with local contractors, Navigant Consulting is estimating the market penetration of HRV to be low.</p> | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Questar Gas ¹¹ | 670 | 20 | 1,785 | N/A |
| Comments Specifications for HRVs are not provided in the report, nor the baseline assumptions. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Puget Sound Energy ¹² | 0.1045 per ft ² | 20 | 1 | N/A |
| Comments Baseline therm reported on a square footage basis (eg 0.19 therms/sq.ft. for offices). Estimated 20% savings for new energy efficient technology is reported as a percent saving over the baseline. Incremental cost is reported on a per square footage basis. Equivalent savings is 0.19 therms/sq.ft. x 2.75 m ³ /therms x 20% = 0.1045 m ³ | | | | |

⁶ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁷ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁸ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

⁹ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁰ "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., by Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000.

¹¹ Questar Gas, DSM Market Characterization Report, by Nexant, August 9, 2006

¹² Quantec, Comprehensive Demand-Side Management Resource Assessment, Prepared for Puget Sound Energy, May 2007
C-188

42. High Efficiency (Condensing) Furnace - Commercial

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

High-efficiency condensing furnace with regular PSC motor – AFUE 96.

Base Equipment and Technologies Description

Mid-efficiency furnace AFUE 90.

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------------|---------------|
| New, Retrofit | Commercial office buildings | Space Heating |

Codes, Standards, and Regulations

- Under Ontario's building code, all gas furnaces installed in new residential construction must meet a minimum condensing efficiency level effective January 1, 2007¹.
- However, effective December 31, 2009, NRCan requires the minimum performance level, or the Annual Fuel Utilization Efficiency (AFUE), for residential gas-fired furnaces with an input rate not exceeding 65.92 kW (225 000 Btu/h) to be 90%².

Resource Savings Table

AFUE 96

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$/kBtu/hr) | Equipment & O&M Costs of Base Measure (\$/kBtu/hr) |
|-----------------|---|----------------------|--------------|---|--|
| | Natural Gas (m ³ /kBtu/h) | Electricity (kWh) | Water (L) | | |
| 1 | 1.7 | 0 | 0 | 30.6 | 22.2 |
| 2 | 1.7 | 0 | 0 | 0 | 0 |
| 3 | 1.7 | 0 | 0 | 0 | 0 |
| 4 | 1.7 | 0 | 0 | 0 | 0 |
| 5 | 1.7 | 0 | 0 | 0 | 0 |
| 6 | 1.7 | 0 | 0 | 0 | 0 |
| 7 | 1.7 | 0 | 0 | 0 | 0 |
| 8 | 1.7 | 0 | 0 | 0 | 0 |
| 9 | 1.7 | 0 | 0 | 0 | 0 |
| 10 | 1.7 | 0 | 0 | 0 | 0 |
| 11 | 1.7 | 0 | 0 | 0 | 0 |
| 12 | 1.7 | 0 | 0 | 0 | 0 |
| 13 | 1.7 | 0 | 0 | 0 | 0 |
| 14 | 1.7 | 0 | 0 | 0 | 0 |
| 15 | 1.7 | 0 | 0 | 0 | 0 |
| 16 | 1.7 | 0 | 0 | 0 | 0 |
| 17 | 1.7 | 0 | 0 | 0 | 0 |
| 18 | 1.7 | 0 | 0 | 0 | 0 |
| TOTALS | 30.6 | 0 | 0 | 30.6 | 22.2 |

¹ Ministry of Energy, "Heating and Cooling your Home: A Conservation Guide." Reproduced with the permission of Natural Resource Canada, 2004. http://www.energy.gov.on.ca/english/pdf/conservation/heating_and_cooling_your_home.pdf

² Office of Energy Efficiency, Canada's Energy Efficiency Regulations, Final Bulletin, December 2008. <http://oee.nrcan.gc.ca/regulations/bulletin/gas-furnaces-dec08.cfm?attr=0>

Resource Savings Assumptions

| | |
|--|------------------------------------|
| Annual Natural Gas Savings | 1.7m³ / kBtu / h |
| <ul style="list-style-type: none"> Gas savings associated with upgrading from a mid-efficiency furnace to a high efficiency furnace are based on the following formula: Annual Savings = $1 - \text{Base Technology AFUE} / \text{Efficient Equipment AFUE}$ $= 1 - 90/96$ $= 6.3\%$ The US DOE reports a 4.91% gas savings for an AFUE 96 furnace (based on an AFUE90 baseline).³ Natural gas savings are based on Enbridge research⁴ indicates the average consumption for a high-efficiency furnace⁵ is 2,045m³. Using the calculated percent savings (6.3%) multiplied by the base energy consumption (2,045 m³) the annual gas savings are estimated to be 129 m³. Assuming a typical commercial furnace input of 75,000 BTU/h, natural gas savings on a per thousand BTU/h basis are 129 m³ / 75 kBtu/h = 1.7 kBtu/h | |
| Annual Electricity Savings | 0 kWh |
| Electricity savings resulting from high efficiency furnaces are negligible. | |
| Annual Water Savings | 0 L |
| N/A | |

Other Input Assumptions

| | |
|--|------------------------|
| Effective Useful Life (EUL) | 18 Years |
| ACEEE ⁶ and State of Iowa ⁷ both estimate an effective useful life of 18 years. Puget Sound Energy ⁸ and New England State Program Working Group (SPWG) ⁹ also suggest 18 years for high efficiency furnaces. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$8.4/ kBtu / h |
| Average incremental cost is based on communication with local HVAC contractors. Navigant Consulting is assuming that the ratio of the incremental cost between a commercial AFUE 90 furnace and a commercial AFUE 96 furnace is the same as for residential market (38%). Therefore, using a baseline commercial AFUE 90 furnace of \$3,000, the incremental cost is estimated to be \$1,135 for a 135,000 Btu/hr furnace, or \$8.4.5/kBtu/hr. | |
| Customer Payback Period (Natural Gas Only)¹⁰ | 9.6 Years |
| Using an 5-year average commodity cost (avoided cost) ¹¹ of \$0.36/ m ³ and an average commercial distribution cost ¹² of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 9.6 years, based on the following: | |

³ US DOE Residential Furnaces and Boilers Technical Support Document Analytical Tools. Life Cycle Cost Results for Non-Weatherized Gas Furnaces. http://www1.eere.energy.gov/buildings/appliance_standards/residential/docs/lcc_nwgf_gt6000hdd.xls

⁴ Based on information provided by Enbridge Gas, based on Decision for the Enbridge 2006 DSM Plan (EB2005-0001).

⁵ Average commercial baseline consumption for a mid-efficiency furnace was not available from either of the Ontario gas utilities, therefore, residential baseline furnace consumption will be used and computed on a per thousand Btu/h basis.

⁶ Powerful Priorities: Updating Energy Efficiency Standards for Residential Furnaces, Commercial Air Conditioners, and Distribution Transformers. ACEEE, September 2004.

⁷ Joint Assessment Study, MidAmerican Energy Company, Appendix C. State of Iowa Utilities Board Docket No. EEP-08-2, 2008, C-131

⁸ Quantec, Comprehensive Demand-Side Management Resource Assessment, Prepared for Puget Sound Energy, May 2007

⁹ GDS Associates, Inc., Measure Life Report: Residential and Commercial/Industrial Lighting and HVAC Measures, Prepared for The New England State Program Working Group (SPWG), For use as an Energy Efficiency Measures/Programs Reference Document for the ISO Forward Capacity Market (FCM), June 2007

¹⁰ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹¹ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

Payback Period = Incremental cost / (natural gas savings x natural gas cost)
 = \$8.4/kBtu/hr / (1.7m³/kBtu/hr/year* \$0.50 / m³)
 = 9.6 Years

Market Share¹³

Medium

Based on market share information for residential furnaces¹⁴, Navigant Consulting is assuming a similar trend for the commercial sector. Therefore, Navigant Consulting estimates the market share in Ontario to be medium.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Questar Gas, 2006 ¹⁵ | 841.5 | 20 | 487.5 | N/A |
| Comments Questar Gas reported 30.6 DTH annual natural gas savings, which translates to 841.5 m ³ . | | | | |
| Puget Sound Energy ¹⁶ | 0.0396 m ³ /sq.ft. | 20 | \$0.1/sq.ft. | N/A |
| Comments Puget Sound reports 12% savings based on a baseline gas furnace of AFUE 75 and energy efficient furnace of AFUE 85. Baseline usage is 0.12 therms/sq.ft., therefore savings is 12% x 0.12 therms/sq.ft. x 2.75 m ³ /therm = 0.0396 m ³ /sq.ft. | | | | |

¹² Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹³ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁴ NRCAN, Office of Energy Efficiency, Comprehensive Energy Use Database: Table 22: Single detached heating system stock by heating system type, http://oee.nrcan.gc.ca/corporate/statistics/neud/dpa/trends_res_on.cfm, updated September 2008.

¹⁵ Nexant, Questar Gas DSM Market Characterization Report, 2006

¹⁶ Quantec, Comprehensive Demand-Side Management Resource Assessment, Prepared for Puget Sound Energy, May 2007

43. Infrared Heaters

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Infrared heater (up to 300,000 Btu/hour)

Base Equipment and Technologies Description

Regular unit heater

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------------------|---------------|
| New/Retrofit | New/Existing Commercial buildings | Space Heating |

Codes, Standards, and Regulations

The old code CAN 1-2.16-M81 (R1996) has been withdrawn.

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$/Btu/hour) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|---|-----------------------|--------------|---|--|
| | Natural Gas (m ³ /Btu/hour) | Electricity (kWh) | Water (L) | | |
| 1 | 0.015 | 245 ~ 870 | 0 | 0.0122 | 0 |
| 2 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 3 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 4 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 5 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 6 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 7 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 8 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 9 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 10 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 11 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 12 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 13 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 14 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 15 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 16 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 17 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 18 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 19 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| 20 | 0.015 | 245 ~ 870 | 0 | 0 | 0 |
| TOTALS | 0.3 | 4,900 ~ 17,400 | 0 | 0.0122 | 0 |

Resource Savings Assumptions

Annual Natural Gas Savings

0.015 m³ / Btu/ h

- The infrared heater gas savings were based on the analysis procedures previously created by Agviro Inc. for Union Gas¹. The analysis was supplemented by adding 20% oversizing factor for the equipment, based on recommendations by Union Gas.

| Location | Heater Range (Btu/h) | Annual Gas Savings (m ³ /year) | | |
|----------|----------------------|---|---------|----------------|
| | | Single Stage | 2-Stage | High Intensity |
| London | 0 - 75,000 | 898 | 1,508 | 898 |
| | 76,000 - 150,000 | 1,786 | 3,017 | 1,786 |
| | 151,000 - 300,000 | 3,591 | 6,033 | 3,591 |
| Sudbury | 0 - 75,000 | 971 | 1,631 | 971 |
| | 76,000 - 150,000 | 1,942 | 3,262 | 1,942 |
| | 151,000 - 300,000 | 3,883 | 6,524 | 3,883 |

- An average rate of savings of 0.015 m³/Btu/hour was determined by taking a weighted average of the savings from both locations: 70% of Union Gas South (London) and 30% of Union Gas North (Sudbury) based on customer population distribution in Union Gas service territories.

| Weighted Average | | | | |
|----------------------|--|---------------------------------------|--|--------------------------------------|
| Heater Range (Btu/h) | Single Stage (m ³ /year) | 2-Stage (m ³ /year) | High Intensity (m ³ /year) | Average (m ³ /year) |
| 0 - 75,000 | 920 | 1,545 | 920 | 1,128 |
| 76,000 - 150,000 | 1,833 | 3,091 | 1,833 | 2,252 |
| 151,000 - 300,000 | 3,679 | 6,180 | 3,679 | 4,513 |
| Heater Range (Btu/h) | Single Stage (m ³ /Btu/hr/year) | 2-Stage (m ³ /Btu/hr/year) | High Intensity (m ³ /Btu/hr/year) | Average (m ³ /Btu/h/year) |
| 0 - 75,000 | 0.0123 | 0.0206 | 0.0123 | 0.015 |
| 76,000 - 150,000 | 0.0122 | 0.0206 | 0.0122 | 0.015 |
| 151,000 - 300,000 | 0.0123 | 0.0206 | 0.0123 | 0.015 |

- Baseline estimates of natural gas consumption²:

| Heater Range (Btu/h) | Annual Gas Use (m ³ /year) |
|----------------------|---------------------------------------|
| 0 - 75,000 | 6,131 |
| 76,000 - 150,000 | 12,262 |
| 151,000 - 300,000 | 24,525 |

- Percentage of natural gas savings = Average Savings / Baseline Gas Consumption = 18.4%

Annual Electricity Savings

245 ~ 870 kWh

- Electricity savings are determined by taking the difference in electricity consumption for infrared heater and a comparable unit heater.

¹ Assessment of Average Infrared Heater Savings, Agviro, December 1, 2004

² "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., Prepared by: Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000.

- Electricity savings are based on Solaronics models that use a 1/24 hp motor³.

| Capacity | Capacities | | Operating Hours | | Electricity Savings (kWh) | Baseline Consumption (kWh) | Savings% |
|-----------------|------------------|---------------|-----------------|----------|---------------------------|----------------------------|----------|
| | Unit Heater (kW) | Infrared (kW) | Unit Heater | Infrared | | | |
| < 50,000 Btu/hr | 0.124 | 0.031 | 2,509 | 2,133 | 245 | 311 | 79% |
| <165,000 Btu/hr | 0.249 | 0.031 | 2,509 | 2,133 | 559 | 625 | 89% |
| >165,000 Btu/hr | 0.373 | 0.031 | 2,509 | 2,133 | 870 | 936 | 93% |

- Electricity savings = Unit heater capacity x operating hours – Infrared Capacity x operating hours, the savings are summarised above for three ranges of capacities.
- Electricity savings % = Electricity savings (kWh) / Baseline Consumption (kWh)

Annual Water Savings

0 L

N/A

Other Input Assumptions

Effective Useful Life (EUL)

20 Years

Infrared heaters have an estimated service life of 20 years⁴.

Base & Incremental Conservation Measure Equipment and O&M Costs

\$ 0.0122 / Btu / h

An incremental cost of \$350 was used based on past input assumptions filed by Union⁵. Local retailers reported an average of \$0.009 / Btu/hr incremental cost. Navigant Consulting therefore is estimating an average of \$0.0122 / Btu/hour.

Customer Payback Period (Natural Gas Only)⁶

1.6 Years

Using an 5-year average commodity cost (avoided cost)⁷ of \$0.38 / m³ and an average commercial distribution cost⁸ of \$0.12 / m³, the payback period for natural gas savings is determined to be 1.6 years, based on the following:

On a per Btu/hour basis,

$$\begin{aligned}
 \text{Payback Period} &= \text{Incremental cost} / (\text{natural gas savings} \times \text{natural gas cost}) \\
 &= \$0.0122 / (0.015 \text{ m}^3/\text{year} \times \$0.5 / \text{m}^3) \\
 &= 1.6 \text{ years}
 \end{aligned}$$

³ Solaronics specification sheet, http://solaronics.thomasnet.com/Asset/SSTG-SSTU-GB_200010_Spec_Sheet.pdf

⁴ "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., Prepared by: Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000.

⁵ EB-2005-0211, Union Gas Settlement Agreement, April 7, 2005

⁶ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁷ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁸ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

| Market Penetration ⁹ | Medium |
|---|--------|
| Based on communication with local contractors, Navigant Consulting is estimating a medium market penetration in Ontario. Infrared systems are currently used in approximately 5% of existing heating applications and 10% and 25% of new space heating applications ¹⁰ . | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Questar Gas ¹¹ | 32.64 | 17 | 1,391 | N/A |
| Comments Specifications for infrared heaters are not provided in the report or the baseline assumptions. | | | | |

⁹ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁰ "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., Prepared by: Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000. Union Gas Heating Product Database.

¹¹ Questar Gas, DSM Market Characterization Report, by Nexant, August 9, 2006

44. Gas-fired Rooftop Unit

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Two-stage rooftop units (5 ton per unit)

Base Equipment and Technologies Description

Single-stage rooftop units (5 ton per unit)

| Decision Type | Target Market(s) | End Use |
|---------------|----------------------|---------------|
| New | Commercial buildings | Space Heating |

Codes, Standards, and Regulations

- Residential gas furnaces are prescribed as regulated products under Canada's Energy Efficiency Regulations¹
- NRCAN proposes to increase the minimum performance level, Annual Fuel Utilization Efficiency (AFUE), for gas-fired furnaces with an input rate not exceeding 65.92 kW (225 000 Btu/h) to 90%. The amendment is intended to introduce new MEPS and associated reporting and compliance requirements for Commercial and industrial gas unit heaters.
- DOE currently has no regulation on AFUE level for commercial gas-fired rooftop units².

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 255 | 0 | 0 | 375 | 0 |
| 2 | 255 | 0 | 0 | 0 | 0 |
| 3 | 255 | 0 | 0 | 0 | 0 |
| 4 | 255 | 0 | 0 | 0 | 0 |
| 5 | 255 | 0 | 0 | 0 | 0 |
| 6 | 255 | 0 | 0 | 0 | 0 |
| 7 | 255 | 0 | 0 | 0 | 0 |
| 8 | 255 | 0 | 0 | 0 | 0 |
| 9 | 255 | 0 | 0 | 0 | 0 |
| 10 | 255 | 0 | 0 | 0 | 0 |
| 11 | 255 | 0 | 0 | 0 | 0 |
| 12 | 255 | 0 | 0 | 0 | 0 |
| 13 | 255 | 0 | 0 | 0 | 0 |
| 14 | 255 | 0 | 0 | 0 | 0 |
| 15 | 255 | 0 | 0 | 0 | 0 |
| TOTALS | 3,825 | 0 | 0 | 375 | 0 |

¹ Canada's Energy Efficiency Regulations (OEE), <http://oee.nrcan.gc.ca/regulations/bulletin/gas-furnace-jan2008.cfm?attr=0>

² U.S. Department of Energy, http://www1.eere.energy.gov/buildings/appliance_standards/commercial/ac_hp.html

Resource Savings Assumptions

| Annual Natural Gas Savings | | 255 m ³ | |
|---|---------------------------|--------------------|--|
| <ul style="list-style-type: none">• Baseline reference case is for a typical new 10,000 sq ft office building, occupant density of 200 sq ft per person. Ventilation is through the five 5 ton rooftop HVAC units using the unit fans³.• Energy efficiency option is five 5 ton units with 2 stage burners in the heating section.• Baseline estimates of natural gas consumption = 25,500 m³.• Natural Gas Savings % = 1,275 m³ / 25,500 m³ = 5%• OBC 2006 does not have more stringent efficiency requirements than OBC 1997 for the furnace section of rooftop units, so the energy savings from the Jacques Whitford study⁴ were not modified. | | | |
| Equipment Description | Incremental Cost Estimate | Efficiency | Gas Consumption (m ³ /year) |
| Single stage units | \$0 | 80% | 25,500 |
| 2-stage heating (5) | \$1,250 | 85% | 24,225 |
| Savings | | | 1,275 |
| <ul style="list-style-type: none">• Therefore, one 5 ton unit with 2 stage burners is estimated to save 1,275 m³ / 5 units = 255 m³. | | | |
| Annual Electricity Savings | | 0 kWh | |
| N/A | | | |
| Annual Water Savings | | 0 L | |
| N/A | | | |

Other Input Assumptions

| Effective Useful Life (EUL) | 15 Years |
|--|-----------|
| Estimated equipment life is 15 years ⁵ . | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | \$ 375 |
| The incremental cost of two-stage rooftop units compared single-stage units is \$1,250 for five units, which equates to \$250 per 5 ton unit ⁶ . Local Canadian manufacturer disclosed incremental cost of \$500 for 2-stage rooftop units comparing with single stage rooftop units. Therefore, an average cost of \$375 is assumed. | |
| Customer Payback Period (Natural Gas Only) ⁷ | 2.9 Years |
| Using an 5-year average commodity cost (avoided cost) ⁸ of \$0.38 / m ³ and an average commercial distribution cost ⁹ of \$0.12 / m ³ , the payback period for natural gas savings is determined to be 2.9 years, based on the following: | |

³ "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., Prepared by: Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000. A survey of manufacturers and distributors was conducted to solicit updated information as per Union Gas' Heating Product Database. Detailed lists were developed for each technology and integrated with the Heating Products Database.

⁴ Ibid.

⁵ ASHRAE Handbook, 2008

⁶ "Prescriptive Incentives for Selected Natural Gas Technologies", Prepared for Enbridge Consumers Gas and Union Gas Ltd., Prepared by: Jacques Whitford Environment Limited, Agviro Inc., and Engineering Interface Ltd., September 27, 2000. A survey of manufacturers and distributors was conducted to solicit updated information as per Union Gas' Heating Product Database. Detailed lists were developed for each technology and integrated with the Heating Products Database.

⁷ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁸ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁹ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

Payback Period = Incremental cost / (natural gas savings x natural gas cost)
 = \$375 / (255 m³/year * \$0.5 / m³)
 = 2.9 years

Market Penetration¹⁰

Medium

Based on communication with local contractors and manufacturers, 2-stage rooftop units are popular and more efficient technology for space heating. Therefore, Navigant Consulting is estimating a medium market penetration in Ontario.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|------------------------------|
| Emerging Technologies & Practice, ACEEE ¹¹ | 770 | 15 | 1,000 | N/A |
| Comments 28 MMBtu/year is approximately equal to 770 m ³ natural gas. | | | | |
| Equipment Description | | Incremental Cost Estimate | Efficiency | Gas Consumption (MMBtu/year) |
| 10 ton gas-fired rooftop unit | | \$0 | 0.80 | 178.5 |
| 10 ton gas-fired condensing rooftop unit | | \$1,000 | 0.95 | 150.3 |

¹⁰ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹¹ ACEEE, High Efficiency Gas-fired Rooftop Units, www.aceee.org/pubs/a042_h16.pdf

45. Programmable Thermostat - Commercial

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Programmable thermostat assuming full set back / forward¹.

Base Equipment and Technologies Description

Standard thermostat.

| Decision Type | Target Market(s) | End Use |
|---------------|----------------------|---------------|
| Retrofit | Commercial buildings | Space Heating |

Codes, Standards, and Regulations

- For a programmable thermostat to receive Energy Star® qualification, it must meet specific criteria such as having at least two different programming periods (for weekday and weekend programming), at least four possible temperature settings and allow for temporary overriding by the user.
- In Canada, applicable CSA standards can be found in CSA C828-99- CAN/CSA Performance Requirements for Thermostats used with Individual Room Electric Space Heating Devices.

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 82 - 538 | 63 - 266 | 0 | 110 | 0 |
| 2 | 82 - 538 | 63 - 266 | 0 | 0 | 0 |
| 3 | 82 - 538 | 63 - 266 | 0 | 0 | 0 |
| 4 | 82 - 538 | 63 - 266 | 0 | 0 | 0 |
| 5 | 82 - 538 | 63 - 266 | 0 | 0 | 0 |
| 6 | 82 - 538 | 63 - 266 | 0 | 0 | 0 |
| 7 | 82 - 538 | 63 - 266 | 0 | 0 | 0 |
| 8 | 82 - 538 | 63 - 266 | 0 | 0 | 0 |
| 9 | 82 - 538 | 63 - 266 | 0 | 0 | 0 |
| 10 | 82 - 538 | 63 - 266 | 0 | 0 | 0 |
| 11 | 82 - 538 | 63 - 266 | 0 | 0 | 0 |
| 12 | 82 - 538 | 63 - 266 | 0 | 0 | 0 |
| 13 | 82 - 538 | 63 - 266 | 0 | 0 | 0 |
| 14 | 82 - 538 | 63 - 266 | 0 | 0 | 0 |
| 15 | 82 - 538 | 63 - 266 | 0 | 0 | 0 |
| TOTALS | 1,230 – 8,070 | 945 – 3,990 | 0 | 110 | 0 |

¹Unlike residential programmable thermostat where data was available on the true behavior of the set back / forward pre and post installation of programmable thermostat, Navigant Consulting is assuming full set back / forward behavior for each commercial segment, as presented below.

Resource Savings Assumptions

| Annual Natural Gas Savings | | | | | | 82 - 538 m ³ |
|--|--|---------------|--|----------------------|---------------------------------|---|
| <ul style="list-style-type: none"> Energy use by market segment from space heating and space cooling were based on NRCan energy intensity data². The percentage of gas savings are based on the assumption of 3% savings per degree F setback as applied in the Energy Star setback calculator³ and Honeywell commercial calculator⁴, corrected for average outdoor heating season temperature to give a percentage savings of 2.4 % per degree F for London, and 2.05% per degree F for North Bay⁵ for space heating and 6% overall for space cooling. Setback duration was estimated for each market. The actual setback temperatures used in each market were estimated based on best available information (72 degrees F to 64 degrees F for heating and 74 degrees F to 78 degrees F for cooling). | | | | | | |
| NRCan Market Segment | Space Heating Energy Intensity (m ³ /ft ² /hr) | Gas Savings % | Space Cooling Energy Intensity (kWh/ft ² /yr) | Electrical Savings % | Space Cooling Market Saturation | Setback / Forward Duration |
| Wholesale Trade | 2.6 | 5.4% | 5.1 | 5.4% | 85% | 7 hrs/night |
| Retail Trade | 2.2 | 5.4% | 4.4 | 5.4% | 85% | 7 hrs/night |
| Transportation / Warehousing | 2.5 | 10.5% | 3.2 | 11.8% | 10% | 12 hrs/Mon-Sat Night + 24 hr Sunday |
| Information / Cultural Industries | 2.4 | 11.8% | 4.8 | 10.5% | 75% | 12 hrs/Weekday Night + 24 hrs Sat. & Sun. |
| Offices | 1.8 | 11.8% | 3.6 | 10.5% | 86% | 12 hrs/Weekday Night + 24 hrs Sat. & Sun. |
| Educational Services | 2.4 | 11.8% | 4.9 | 10.5% | 45% | 12 hrs/Weekday Night + 24 hrs Sat. & Sun. |
| Health Care and Social Assistance | 2.7 | 0.0% | 5.4 | 0% | 75% | 0 |
| Arts, Entertainment and Recreation | 3.7 | 5.4% | 7.5 | 5.4% | 87% | 7 hrs/night |
| Accommodation and Food Services | 3.5 | 5.4% | 7.0 | 5.4% | 70% | 7 hrs/night |
| Other Services | 2.2 | 5.4% | 4.3 | 5.4% | 69% | 7 hrs/night |
| <ul style="list-style-type: none"> For example, gas savings% for space heating for wholesale trade segment is calculated as follows: 2.3% x (72 - 64) degree F x 7/24 = 5.4%, where 2.3% is the weighted average of gas savings for Union Gas service territories assuming 70% weight for London and 30% weight for North Bay. The NRCan market segments were categorized according to Union Gas market segments, enabling Union Gas specific floor space (ft²) of thermostat zone areas to be used. Hospitals were not included because many of the rooms are occupied 24/7 and would not benefit from temperature setback. | | | | | | |

² NEUD database space heating / space cooling for 1990-2006, (as of January 2009)

³ Energy Star Programmable Thermostat Calculator, www.energystar.gov/index.cfm?c=thermostats.pr_thermostats

⁴ Honeywell Commercial, <http://acscorp.honeywell.com/Pages/default.aspx>

⁵ Union Gas Response to Navigant Consulting Measures and Assumptions For Demand Side Management Planning, March 13, 2009

| Union Gas Market Segments | Thermostat Zone Area (ft ²) | Intensity | Heating Savings |
|---------------------------|---|-----------|-----------------|
| Industrial | 3,000 | 2.4 | 7.1% |
| Warehouse | 3,000 | 2.5 | 10.5% |
| Multifamily | 1,200 | 3.5 | 5.4% |
| Office | 650 | 2.2 | 11.8% |
| Retail | 600 | 2.4 | 5.4% |
| Food Service | 1,175 | 3.5 | 5.4% |
| Hotels / Motels | 461 | 3.5 | 5.4% |
| Information and Cultural | 650 | 2.4 | 11.8% |
| Educational Services | 986 | 2.4 | 11.8% |
| Hospitals | - | 2.7 | 0.0% |
| Recreation | 2,500 | 3.7 | 5.4% |
| Agriculture | 3,000 | 2.2 | 5.4% |

- Navigant Consulting further consolidated the market segments are consolidated into similar segments based on three factors: 1) zone area size, 2) energy intensity levels, and 3) savings percentages.

| Navigant Consulting Market Segments | Gas Savings per Year (m ³) |
|--|--|
| Warehouse, Industrial, Recreation, Agriculture | 538 |
| Multifamily, Food Service | 223 |
| Office, Information and Cultural, Educational Services | 211 |
| Retail, Hotels / Motels | 82 |

Annual Electricity Savings

63 - 266 kWh

- The electricity savings is based on energy intensity from space cooling for different market segments as described in the previous gas savings section. Not all buildings have cooling; therefore the saturation of space cooling was included⁶. Otherwise, the electricity savings by segment type were calculated and grouped in the same way as the gas savings presented above.

| Union Gas Market Segments | Thermostat Zone Area (ft ²) | Intensity | Cooling Savings | Saturation |
|---------------------------|---|-----------|-----------------|------------|
| Industrial | 3,000 | 2.4 | 7.5% | 54.7% |
| Warehouse | 3,000 | 2.5 | 11.8% | 10.0% |
| Multifamily | 1,200 | 3.5 | 5.4% | 70.0% |
| Office | 650 | 2.2 | 10.5% | 68.7% |
| Retail | 600 | 2.4 | 5.4% | 85.0% |
| Food Service | 1,175 | 3.5 | 5.4% | 70.0% |
| Hotels / Motels | 461 | 3.5 | 5.4% | 70.0% |
| Information and Cultural | 650 | 2.4 | 10.5% | 75.0% |
| Educational Services | 986 | 2.4 | 10.5% | 45.0% |
| Hospitals | - | 2.7 | 0.0% | 75.0% |
| Recreation | 2,500 | 3.7 | 5.4% | 87.0% |
| Agriculture | 3,000 | 2.2 | 5.4% | 69.0% |

⁶ NEUD database space cooling for 1990-2006, (as of January 2009)

- Navigant Consulting further consolidated the market segments are consolidated into similar segments based on three factors: 1) zone area size, 2) energy intensity levels, and 3) savings percentages.

| Navigant Consulting Market Segments | Electricity Savings per Year (kWh) |
|--|------------------------------------|
| Warehouse, Industrial, Recreation, Agriculture | 266 |
| Multifamily, Food Service | 156 |
| Office, Information and Cultural, Educational Services | 112 |
| Retail, Hotels / Motels | 63 |

Annual Water Savings

0 L

N/A

Other Input Assumptions

Effective Useful Life (EUL)

15 Years

Navigant Consulting is estimating 15 years as the effective useful life based on the average lifetime of programmable thermostat from Energy Star ® website.

Base & Incremental Conservation Measure Equipment and O&M Costs

\$ 110

Local retail price for a commercial programmable thermostat is \$110. The incremental cost of \$109.00 was found based on average incremental cost for various commercial settings based on the Iowa Stated DSM study⁷.

Natural Gas Payback Period

0.4 – 3.5 Years

Using an 5-year average commodity cost (avoided cost)⁸ of \$0.38 / m³ and an average commercial distribution cost⁹ of \$0.12 / m³, the payback period for natural gas savings is determined to be between 0.4 – 3.5 years, based on the following:

- 1) For Warehouse, Industrial, Recreation and Agriculture segment:

$$\text{Payback Period} = \text{Incremental cost} / (\text{natural gas savings} \times \text{natural gas cost})$$

$$= \$110 / (538 \text{ m}^3/\text{year} \times \$0.5 / \text{m}^3)$$

$$= 0.4 \text{ years}$$
- 2) For Multi-family and Food Services segment:

$$\text{Payback Period} = \text{Incremental cost} / (\text{natural gas savings} \times \text{natural gas cost})$$

$$= \$110 / (223 \text{ m}^3/\text{year} \times \$0.5 / \text{m}^3)$$

$$= 1.0 \text{ years}$$
- 3) For Office, Information and Cultural, and Educational Services segment:

$$\text{Payback Period} = \text{Incremental cost} / (\text{natural gas savings} \times \text{natural gas cost})$$

$$= \$110 / (211 \text{ m}^3/\text{year} \times \$0.5 / \text{m}^3)$$

$$= 1.0 \text{ years}$$
- 4) For Retail, Hotel/Motel segment:

$$\text{Payback Period} = \text{Incremental cost} / (\text{natural gas savings} \times \text{natural gas cost})$$

$$= \$110 / (63 \text{ m}^3/\text{year} \times \$0.5 / \text{m}^3)$$

$$= 3.5 \text{ years}$$

⁷ Ibid.

⁸ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁹ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

| Market Penetration ¹⁰ | Medium |
|---|--------|
| Based on the observation of medium penetration in one jurisdiction (e.g., Puget Sound Energy) of low penetration in another (e.g., Iowa) and communication with local retailers, Navigant Consulting estimates the penetration in Ontario to be medium. | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|--|-------------------------------|---|--|
| Puget Sound Energy ¹¹ | 0.01045 per ft ² | 10 | \$0.01 per ft ² - (Office) | 48% |
| Comments Base equipment is a non-programmable thermostat. Baseline consumption is reported on a per square footage basis (e.g. 0.19 therms per ft ² for office). Estimated 2% savings for programmable thermostats are reported as a percent saving over the baseline. Equivalent natural gas savings is 2% x 0.19 therms/sq.ft. x 2.75 m ³ /therm = 0.01045 m ³ | | | | |
| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹² | 0.03383 | 15 | \$0.017 per ft ² (Large Office) - \$0.034 per ft ² (Small Office) | 13% (large office) 13% (small office) |
| Comments Base equipment is a non-programmable thermostat. Baseline consumption is reported on a square footage basis (e.g. 0.35 therms/sqft for large office, and 0.41 therms/sqft for small office). Estimated 3% savings for a programmable thermostat is reported as a percent saving over the baseline. Equivalent natural gas savings is 3% x 0.41 therms/sq.ft. x 2.75 m ³ /therm = 0.3383 m ³ | | | | |

¹⁰ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹¹ Quantec, Comprehensive Demand-Side Management Resource Assessment, Prepared for Puget Sound Energy, May 2007

¹² Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

46. Prescriptive Schools – Elementary

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Space heating, hydronic boiler with combustion efficiency of 83% or higher.

Base Equipment and Technologies Description

Space heating, hydronic boiler with combustion efficiency of 80% to 82%.

| Decision Type | Target Market(s) | End Use |
|---------------|-------------------------|---------------|
| Replacement | Institutional Buildings | Space Heating |

Codes, Standards, and Regulations

- ASHRAE Standard 155P: test and calculation procedures result in an application-specific seasonal efficiency of commercial space heating boiler systems¹.
- ASHRAE Standard 90.1-2004: minimum boiler efficiencies for buildings except low-rise residential buildings².

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 10,830 | 0 | 0 | 8,646 | 0 |
| 2 | 10,830 | 0 | 0 | 0 | 0 |
| 3 | 10,830 | 0 | 0 | 0 | 0 |
| 4 | 10,830 | 0 | 0 | 0 | 0 |
| 5 | 10,830 | 0 | 0 | 0 | 0 |
| 6 | 10,830 | 0 | 0 | 0 | 0 |
| 7 | 10,830 | 0 | 0 | 0 | 0 |
| 8 | 10,830 | 0 | 0 | 0 | 0 |
| 9 | 10,830 | 0 | 0 | 0 | 0 |
| 10 | 10,830 | 0 | 0 | 0 | 0 |
| 11 | 10,830 | 0 | 0 | 0 | 0 |
| 12 | 10,830 | 0 | 0 | 0 | 0 |
| 13 | 10,830 | 0 | 0 | 0 | 0 |
| 14 | 10,830 | 0 | 0 | 0 | 0 |
| 15 | 10,830 | 0 | 0 | 0 | 0 |
| 16 | 10,830 | 0 | 0 | 0 | 0 |
| 17 | 10,830 | 0 | 0 | 0 | 0 |
| 18 | 10,830 | 0 | 0 | 0 | 0 |
| 19 | 10,830 | 0 | 0 | 0 | 0 |
| 20 | 10,830 | 0 | 0 | 0 | 0 |
| 21 | 10,830 | 0 | 0 | 0 | 0 |
| 22 | 10,830 | 0 | 0 | 0 | 0 |
| 23 | 10,830 | 0 | 0 | 0 | 0 |
| 24 | 10,830 | 0 | 0 | 0 | 0 |
| 25 | 10,830 | 0 | 0 | 0 | 0 |
| TOTALS | 270,750 | 0 | 0 | 8,646 | 0 |

¹Boiler System Efficiency, ASHRAE Journal, July 2006

² Ibid.

Resource Savings Assumptions

| Annual Natural Gas Savings | | | 10,830 m ³ |
|--|--|--|---|
| <ul style="list-style-type: none">• The Agviro study³ analyzed the gas usage of 859 elementary school based on 2006 billing record. The analysis determined:<ul style="list-style-type: none">– The consumption and size of an average elementary school– The size of boiler required to heat the typical elementary school– The manufacturer’s suggested retail price for boilers based on the determined size– The savings of higher efficiency boilers versus a base case of 80 to 82% efficiency– Incremental cost associated with the higher efficiency boiler• Based on Enbridge project records⁴ the study found that 2 smaller boilers are typically installed (2 x 400 MBH boilers) for elementary schools. Also, based on project records, the study found that boiler upgrades will be weighted 89% towards the efficiency range of 85% to 88% and 11% towards boilers with combustion efficiencies ranging from 83% to 84%. | | | |
| | Estimated Annual Gas Consumption (m ³) | Estimated Annual Gas Savings (m ³) | Weighted Average NG Savings (m ³) |
| Base Case (81%) | 51,753 | | 10,830 |
| Mid Efficiency (83.5%) | 44,073 | 7,680 | |
| High Efficiency (86.5%) | 40,534 | 11,219 | |
| <p>Note: The gas savings are not solely contributed by energy efficiency level upgrade. The Agviro report does account for other significant drivers of the efficiency improvement, such as Maximum Supply Water Temperature. It went down from 14.4% loss in the base case to 5.24% loss in the mid efficiency case, and further to 2.88% loss in the high efficiency case. This substantially contributes to drive down the natural gas consumptions.</p> <ul style="list-style-type: none">• Baseline estimates of natural gas consumption = 51,753 m³.• Natural Gas Savings % = 10,830 m³ / 51,753 m³ = 21% | | | |
| Annual Electricity Savings | | | 0 kWh |
| N/A | | | |
| Annual Water Savings | | | 0 L |
| N/A | | | |

Other Input Assumptions

| Effective Useful Life (EUL) | | 25 Years | | | | | | | | | | | | | |
|--|------------------------|---|-----------------------------------|--|--|-----------------------|--------------|------------------|-----------------------|------------------------|---|---------------------------|------------------------|----------------------------|------------------------|
| Boilers have an estimated service life of 25 years according to ASHRAE ⁵ . | | | | | | | | | | | | | | | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | | \$ 8,646 | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th colspan="3">Average MSRP for 2x400 MBH Boiler</th></tr> <tr> <th>Combustion Efficiency</th><th>Average MSRP</th><th>Incremental Cost</th></tr> </thead> <tbody> <tr> <td>80 - 82 % [Base Case]</td><td>2 x \$5,500 = \$11,000</td><td rowspan="3">\$8,646 *including installation cost</td></tr> <tr> <td>83 - 84% [Mid Efficiency]</td><td>2 x \$7,700 = \$15,400</td></tr> <tr> <td>85 - 88% [High Efficiency]</td><td>2 x \$8,400 = \$16,800</td></tr> </tbody> </table> <p>Incremental costs are based on the weighted average of boiler types as noted above⁶.</p> | | | Average MSRP for 2x400 MBH Boiler | | | Combustion Efficiency | Average MSRP | Incremental Cost | 80 - 82 % [Base Case] | 2 x \$5,500 = \$11,000 | \$8,646 *including installation cost | 83 - 84% [Mid Efficiency] | 2 x \$7,700 = \$15,400 | 85 - 88% [High Efficiency] | 2 x \$8,400 = \$16,800 |
| Average MSRP for 2x400 MBH Boiler | | | | | | | | | | | | | | | |
| Combustion Efficiency | Average MSRP | Incremental Cost | | | | | | | | | | | | | |
| 80 - 82 % [Base Case] | 2 x \$5,500 = \$11,000 | \$8,646 *including installation cost | | | | | | | | | | | | | |
| 83 - 84% [Mid Efficiency] | 2 x \$7,700 = \$15,400 | | | | | | | | | | | | | | |
| 85 - 88% [High Efficiency] | 2 x \$8,400 = \$16,800 | | | | | | | | | | | | | | |

³ Agviro Inc, Elementary Schools Prescriptive Savings Analysis, November 23, 2007

⁴ Ibid.

⁵ ASHRAE Applications Handbook – 2003, Chapter 36 – Owning and Operating Costs, Table 3

⁶ Agviro Inc, Elementary Schools Prescriptive Savings Analysis, November 23, 2007

| | |
|--|------------------|
| Customer Payback Period (Natural Gas Only) | 1.6 Years |
| <p>Using an 5-year average commodity cost (avoided cost)⁷ of \$0.38 / m³ and an average commercial distribution cost⁸ of \$0.12 / m³, the payback period for natural gas savings is determined to be 1.6 years, based on the following:</p> <p>Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="padding-left: 40px;">= \$8,646/ (10,830 m³/year * \$0.5 / m³)</p> <p style="padding-left: 40px;">= 1.6 years</p> | |
| Market Penetration⁹ | Low |
| <p>Based on communication with local contractors and other jurisdiction penetration rates, the market penetration for high efficiency boilers in schools is low. Therefore, Navigant Consulting is estimating a low market penetration.</p> | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|----------------------------|--------------------------|
| Iowa State Utility Board Assessment Study ¹⁰ | 0.077 per ft ² | 20 | 24.589 per ft ² | 5% |
| Comments Greater than 300 kBTU/h, upgrade from 80% thermal baseline efficiency to 85% thermal efficiency. Baseline Therm reported on a square footage basis (eg 0.50 therms/sq.ft. for education sector). Estimated 5.6% savings for new energy efficient technology is reported as a percent saving over the baseline. Equivalent natural gas savings is 5.6% x 0.50 therms/sq.ft. = 0.028 therms = 0.077 m ³ | | | | |
| Iowa State Utility Board Assessment Study ¹¹ | 0.135 per ft ³ | 20 | 30.182 per ft ² | 5% |
| Comments Greater than 300 kBTU/h, upgrade from 80% thermal baseline efficiency to 89% thermal efficiency. y, Baseline Therm reported on a square footage basis (eg 0.50 therms/sq.ft. for education sector). Estimated 5.6% savings for new energy efficient technology is reported as a percent saving over the baseline. Equivalent natural gas savings is 9.8% x 0.50 therms/sq.ft. = 0.049 therms = 0.135 m ³ | | | | |

⁷ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁸ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

⁹ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁰ Joint Assessment Study, MidAmerican Energy Company, Appendix C. State of Iowa Utilities Board Docket No. EEP-08-2, 2008, C-131

¹¹ Ibid.

47. Prescriptive Schools – Secondary

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Space heating, hydronic boiler with combustion efficiency of 83% or higher.

Base Equipment and Technologies Description

Space heating, hydronic boiler with combustion efficiency of 80% to 82%.

| Decision Type | Target Market(s) | End Use |
|---------------|-------------------------|---------------|
| Retrofit | Institutional Buildings | Space Heating |

Codes, Standards, and Regulations

- ASHRAE Standard 155P: test and calculation procedures result in an application-specific seasonal efficiency of commercial space heating boiler systems¹.
- ASHRAE Standard 90.1-2004: minimum boiler efficiencies for buildings except low-rise residential buildings².

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|--|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 43,859 | 0 | 0 | 14,470 | 0 |
| 2 | 43,859 | 0 | 0 | 0 | 0 |
| 3 | 43,859 | 0 | 0 | 0 | 0 |
| 4 | 43,859 | 0 | 0 | 0 | 0 |
| 5 | 43,859 | 0 | 0 | 0 | 0 |
| 6 | 43,859 | 0 | 0 | 0 | 0 |
| 7 | 43,859 | 0 | 0 | 0 | 0 |
| 8 | 43,859 | 0 | 0 | 0 | 0 |
| 9 | 43,859 | 0 | 0 | 0 | 0 |
| 10 | 43,859 | 0 | 0 | 0 | 0 |
| 11 | 43,859 | 0 | 0 | 0 | 0 |
| 12 | 43,859 | 0 | 0 | 0 | 0 |
| 13 | 43,859 | 0 | 0 | 0 | 0 |
| 14 | 43,859 | 0 | 0 | 0 | 0 |
| 15 | 43,859 | 0 | 0 | 0 | 0 |
| 16 | 43,859 | 0 | 0 | 0 | 0 |
| 17 | 43,859 | 0 | 0 | 0 | 0 |
| 18 | 43,859 | 0 | 0 | 0 | 0 |
| 19 | 43,859 | 0 | 0 | 0 | 0 |
| 20 | 43,859 | 0 | 0 | 0 | 0 |
| 21 | 43,859 | 0 | 0 | 0 | 0 |
| 22 | 43,859 | 0 | 0 | 0 | 0 |
| 23 | 43,859 | 0 | 0 | 0 | 0 |
| 24 | 43,859 | 0 | 0 | 0 | 0 |
| 25 | 43,859 | 0 | 0 | 0 | 0 |
| TOTALS | 1,096,475 | 0 | 0 | 14,470 | 0 |

¹ Boiler System Efficiency, ASHRAE Journal, July 2006

² Ibid.

Resource Savings Assumptions

| Annual Natural Gas Savings | | | 43,859 m ³ |
|--|--|--|---|
| <ul style="list-style-type: none">• The Agviro study³ analyzed the gas usage of 147 elementary school based on 2006 billing record. The analysis determined:<ul style="list-style-type: none">- The consumption and size of an average elementary school- The size of boiler required to heat the typical elementary school- The manufacturer's suggested retail price for boilers based on the determined size- The savings of higher efficiency boilers versus a base case of 80 to 82% efficiency- Incremental cost associated with the higher efficiency boiler• Based on Enbridge project records the study found that 2 smaller boilers are typically installed (2 x 1500 MBH boilers for elementary schools). Also, based on project records, the study found that boiler upgrades will be weighted 89% towards the efficiency range of 85% to 88% and 11% towards boilers with combustion efficiencies ranging from 83% to 84%.• Baseline estimates of natural gas consumption = 209,596 m³. | | | |
| | Estimated Annual Gas Consumption (m ³) | Estimated Annual Gas Savings (m ³) | Weighted Average NG Savings (m ³) |
| Base Case (81%) | 209,596 | | |
| Mid Efficiency (83.5%) | 178,494 | 31,102 | 43,859 |
| High Efficiency (86.5%) | 164,160 | 45,436 | |
| <p>Note: The gas savings are not solely contributed by energy efficiency level upgrade. The Agviro report does account for other significant drivers of the efficiency improvement, such as Maximum Supply Water Temperature. It went down from 14.4% loss in the base case to 5.24% loss in the mid efficiency case, and further to 2.88% loss in the high efficiency case. This substantially contributes to drive down the natural gas consumptions.</p> | | | |
| <ul style="list-style-type: none">• Natural Gas Savings % = 43,859 m³ / 209,596 m³ = 21% | | | |
| Annual Electricity Savings | | | 0 kWh |
| N/A | | | |
| Annual Water Savings | | | 0 L |
| N/A | | | |

Other Input Assumptions

| Effective Useful Life (EUL) | | 25 Years | | | | | | | | | | | | | |
|--|-------------------------|--|-----------------------------------|--|--|-----------------------|--------------|------------------|-----------------------|-------------------------|--|---------------------------|-------------------------|----------------------------|-------------------------|
| Boilers have an estimated service life of 25 years according to ASHRAE ⁴ . | | | | | | | | | | | | | | | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | | \$ 14,470 | | | | | | | | | | | | | |
| <table border="1"> <thead> <tr> <th colspan="3">Average MSRP for 2x400 MBH Boiler</th></tr> <tr> <th>Combustion Efficiency</th><th>Average MSRP</th><th>Incremental Cost</th></tr> </thead> <tbody> <tr> <td>80 - 82 % [Base Case]</td><td>2 x \$18,100 = \$36,200</td><td rowspan="3">\$14,470 *including installation cost</td></tr> <tr> <td>83 - 84% [Mid Efficiency]</td><td>2 x \$21,000 = \$42,000</td></tr> <tr> <td>85 - 88% [High Efficiency]</td><td>2 x \$22,500 = \$45,000</td></tr> </tbody> </table> | | | Average MSRP for 2x400 MBH Boiler | | | Combustion Efficiency | Average MSRP | Incremental Cost | 80 - 82 % [Base Case] | 2 x \$18,100 = \$36,200 | \$14,470 *including installation cost | 83 - 84% [Mid Efficiency] | 2 x \$21,000 = \$42,000 | 85 - 88% [High Efficiency] | 2 x \$22,500 = \$45,000 |
| Average MSRP for 2x400 MBH Boiler | | | | | | | | | | | | | | | |
| Combustion Efficiency | Average MSRP | Incremental Cost | | | | | | | | | | | | | |
| 80 - 82 % [Base Case] | 2 x \$18,100 = \$36,200 | \$14,470 *including installation cost | | | | | | | | | | | | | |
| 83 - 84% [Mid Efficiency] | 2 x \$21,000 = \$42,000 | | | | | | | | | | | | | | |
| 85 - 88% [High Efficiency] | 2 x \$22,500 = \$45,000 | | | | | | | | | | | | | | |

³ Agviro Inc, Secondary Schools Prescriptive Savings Analysis, November 23, 2007

⁴ ASHRAE Applications Handbook – 2003, Chapter 36 – Owning and Operating Costs, Table 3

Incremental costs are based on the weighted average of boiler types as noted above⁵.

Customer Payback Period (Natural Gas Only)⁶

0.7 Years

Using an 5-year average commodity cost (avoided cost)⁷ of \$0.38 / m³ and an average commercial distribution cost⁸ of \$0.12 / m³, the payback period for natural gas savings is determined to be 0.74 years, based on the following:

$$\begin{aligned}\text{Payback Period} &= \text{Incremental cost} / (\text{natural gas savings} \times \text{natural gas cost}) \\ &= \$14,470 / (43,859 \text{ m}^3/\text{year} \times \$0.5 / \text{m}^3) \\ &= 0.7 \text{ years}\end{aligned}$$

Market Penetration⁹

Low

Based on communication with local contractors and other jurisdiction penetration rates, the market penetration for high efficiency boilers in schools is low. Therefore, Navigant Consulting is estimating a low market penetration.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m ³) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|--|-------------------------------|----------------------------|--------------------------|
| Iowa State Utility Board Assessment Study ¹⁰ | 0.077 per ft ² | 20 | 24.589 per ft ² | 5% |
| Comments Greater than 300 kBtu/h, upgrade from 80% thermal baseline efficiency to 85% thermal efficiency. Baseline Therm reported on a square footage basis (eg 0.50 therms/sq.ft.for education sector). Estimated 5.6% savings for new energy efficient technology is reported as a percent saving over the baseline. Equivalent natural gas savings is 5.6% x 0.50 therms/sq.ft. = 0.28 therms = 0.077 m ³ | | | | |
| Iowa State Utility Board Assessment Study ¹¹ | 0.135 per ft ² | 20 | 30.182 per ft ² | 5% |
| Comments Greater than 300 kBtu/h, upgrade from 80% thermal baseline efficiency to 89% thermal efficiency. Baseline Therm reported on a square footage basis (eg 0.50 therms/sq.ft.for education sector). Estimated 5.6% savings for new energy efficient technology is reported as a percent saving over the baseline. Equivalent natural gas savings is 9.8% x 0.50 therms/sq.ft = 0.049 therms = 0.135 m ³ | | | | |

⁵ Agviro Inc, Secondary Schools Prescriptive Savings Analysis, November 23, 2007

⁶ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

⁷ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

⁸ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

⁹ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁰ Joint Assessment Study, MidAmerican Energy Company, Appendix C. State of Iowa Utilities Board Docket No. EEP-08-2, 2008, C-131

¹¹ Ibid.

COMMERCIAL WATER HEATING

48. Condensing Gas Water Heater - Commercial

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Condensing Gas Water Heater¹ (95% thermal efficiency), 50 gallons.

Due to the variability in energy savings for commercial buildings resulting from the quantity of daily water use, resource savings were calculated for three scenarios of daily hot water use²:

Scenario A: 100 gallons (378 litres)

Scenario B: 500 gallons (1,893 litres)

Scenario C: 1,000 gallons (3,786 litres)

Base Equipment and Technologies Description

Conventional storage tank gas water heater³ (thermal efficiency⁴=80%), 91 gallons.

| Decision Type | Target Market(s) | End Use |
|---------------|---------------------------|---------------|
| New/Retrofit | Commercial (New/Existing) | Water heating |

Codes, Standards, and Regulations

Ontario's Energy Efficiency Act⁵ applies only to water heaters with an input rating of less than 75,000 Btu/hr.

¹ Locally available commercial condensing gas water heater, trade name: Polaris, model #: PC 199-50
http://www.johnwoodwaterheaters.com/pdfs/GSW_PolarisSpecSheet.pdf

² One of the input assumptions required for calculating resource savings for this measure is the stand-by heat loss of storage tank water heaters. Hourly stand-by losses are treated as constant using values drawn from GAMA's *Consumer Directory* (see citation below). This means that marginal percentage gas savings will fall as hot water use rises.

³ Locally available commercial conventional (non-condensing) gas water heater with the same input rating as the Polaris.
 Manufacturer: Rheem, model #: G91-200.

⁴ Although the required minimum thermal efficiency to be in compliance with ASHRAE 90.1 is 78%,
<http://www.energycodes.gov/comcheck/pdfs/404text.pdf>, only a very small percentage of commercial gas water heaters listed in the GAMA *Consumer's Directory of Certified Efficiency Ratings* had a thermal efficiency of less than 80%.

⁵ http://www.neo.ne.gov/neq_online/july2006/commgaswtrhr.pdf
<http://www.energy.gov.on.ca/english/pdf/conservation/2006%20-%20EEA%20Guide%20C%20-%20Water%20Heaters.pdf>

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | A: 332 B: 873 C: 1,551 | 0 | 0 | 5,880 | 3,650 |
| 2 | A: 332 B: 873 C: 1,551 | 0 | 0 | 0 | 0 |
| 3 | A: 332 B: 873 C: 1,551 | 0 | 0 | 0 | 0 |
| 4 | A: 332 B: 873 C: 1,551 | 0 | 0 | 0 | 0 |
| 5 | A: 332 B: 873 C: 1,551 | 0 | 0 | 0 | 0 |
| 6 | A: 332 B: 873 C: 1,551 | 0 | 0 | 0 | 0 |
| 7 | A: 332 B: 873 C: 1,551 | 0 | 0 | 0 | 0 |
| 8 | A: 332 B: 873 C: 1,551 | 0 | 0 | 0 | 0 |
| 9 | A: 332 B: 873 C: 1,551 | 0 | 0 | 0 | 0 |
| 10 | A: 332 B: 873 C: 1,551 | 0 | 0 | 0 | 0 |
| 11 | A: 332 B: 873 C: 1,551 | 0 | 0 | 0 | 0 |
| 12 | A: 332 B: 873 C: 1,551 | 0 | 0 | 0 | 0 |
| 13 | A: 332 B: 873 C: 1,551 | 0 | 0 | 0 | 0 |
| TOTALS | A: 4,316 B: 11,349 C: 20,163 | 0 | 0 | 5,880 | 3,650 |

Resource Savings Assumptions

| Annual Natural Gas Savings | A: 332 m ³ B: 873 m ³ C: 1,551 m ³ |
|--|---|
| Assumptions and inputs: <ul style="list-style-type: none"> Daily hot water draw: <ul style="list-style-type: none"> Scenario A: 100 gallons (378 litres) Scenario B: 500 gallons (1,893 litres) Scenario C: 1,000 gallons (3,786 litres) Input rating for efficient and base equipment: 199,000 Btu. | |

- Average water inlet temperature: 9.33 °C (48.8 °F)⁶
- Average water heater set point temperature: 54 °C (130 °F)⁷
- Stand-by loss of (condensing) Polaris PC 199-50 3NV: 244 Btu/hr⁸.
- Stand-by loss of (non-condensing) Rheem G91-200: 1,050 Btu/hr⁹.

Annual gas savings calculated as follows:

$$Savings = \left[W * 8.33 * (T_{out} - T_{in}) * \left(\frac{1}{Eff_{base}} - \frac{1}{Eff_{eff}} \right) + (Stby_{base} - Stby_{eff}) * 24 * 365 \right] * 10^{-6} * 27.8$$

Where:

W = Annual hot water use (gallons)
 8.33 = Energy content of water (Btu/gallon/°F)
 T_{out} = Water heater set point temperature (°F)
 T_{in} = Water inlet temperature (°F)
 Eff_{base} = Thermal efficiency of base equipment
 Eff_{eff} = Thermal efficiency of efficient equipment
 10⁻⁶ = Factor to convert Btu to MMBtu
 Stby_{base} = Stand-by loss per hour for base equipment (Btu)
 Stby_{eff} = Stand-by loss per hour for efficient equipment (Btu)
 24 = Hours per day
 365 = Days per year
 27.8 = Factor to convert MMBtu to m³

Scenario A: Gas savings were determined to be 29% over base measure

Scenario B: Gas savings were determined to be 19% over base measure

Scenario C: Gas savings were determined to be 17% over base measure

$$Percent Savings = \frac{(G_{base} - G_{eff})}{G_{base}}$$

G_{eff} = Annual natural gas use with efficient equipment,

Scenario A: 782 m³

Scenario B: 3,672 m³

Scenario C: 7,284 m³

G_{base} = Annual natural gas use with base equipment,

Scenario A: 1,114 m³

Scenario B: 4,545 m³

Scenario C: 8,835 m³

Annual Electricity Savings

0 kWh

N/A

⁶ Chinnery, Glen. *Policy Recommendations for the HERS Community to Consider regarding HERS point credit for Waste Water Heat Recovery Devices*, EPA, Energy Star for homes, March 2004

http://www.energystar.gov/ia/partners/bldrs_lenders_raters/downloads/Waste_Water_Heat_Recovery_Guidelines.pdf

⁷ As suggested by NRCAN: <http://oee.nrcan.gc.ca/residential/personal/new-homes/water-conservation.cfm?attr=4>

⁸ *Consumer's Directory of Certified Efficiency Ratings* http://www.neo.ne.gov/neq_online/july2006/commgaswtrhtr.pdf In this case stand-by losses are constant. Recalculating gas savings using the WHAM algorithm, in which stand-by losses are a function of water draw, results in less than 3% variation over the figures presented above. Lutz, J.D., C.D. Whitehead, A.B. Lekov, G.J. Rosenquist., and D.W. Winiarski. 1999. *WHAM: Simplified tool for calculating water heater energy use*. ASHRAE Transactions 105 (1): 1005-1015.

⁹ *Consumer's Directory of Certified Efficiency Ratings* http://www.neo.ne.gov/neq_online/july2006/commgaswtrhtr.pdf.

| | |
|---|------------|
| Annual Water Savings | 0 L |
| Navigant has assumed that adopting the measure would not affect the quantity of water consumed. | |

Other Input Assumptions

| | |
|---|--|
| Effective Useful Life (EUL) | 13 Years |
| Studies conducted in two different jurisdictions (Iowa ¹⁰ and Washington State ¹¹) use an EUL of 13 years, whereas one conducted for Enbridge and Union in 2000 ¹² uses an EUL of 15 years. Given that the two most recent studies both use 13 years, Navigant Consulting also recommends adopting 13 years. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 2,230 \$ |
| Incremental cost determined from communication with local distributor ¹³ | |
| Customer Payback Period (Natural Gas Only)¹⁴ | A: 13 Years B: 5 Years C: 2.8 Years |
| Using a 5-year average commodity cost (avoided cost) ¹⁵ of \$0.38 / m ³ and an average commercial distribution cost ¹⁶ of \$0.12 / m ³ , the payback period for natural gas savings is determined to be 13 years for Scenario A, 5 years for Scenario B and 2.8 years for Scenario C, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) Scenario A = \$2,230 / (332 m ³ /year * \$0.5 / m ³) = 13 years Scenario B = \$2,230 / (873 m ³ /year * \$0.5 / m ³) = 5 years Scenario C = \$2,230 / (1,614 m ³ /year * \$0.5 / m ³) = 2.8 years | |
| Market Penetration¹⁷ | Low |
| Based on the observation of low penetration in another jurisdiction (Washington State ¹⁸ – 5%), the paucity of distributors in Ontario and of the relatively high incremental cost, Navigant Consulting estimates the penetration in Ontario to be low. | |

¹⁰ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

¹¹ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹² Jacques Whitford Environment Ltd, *Prescriptive Incentives for Select Natural Gas Technologies*, Sept 2000

¹³ Rheem G91-200: \$3,650

Polaris PC 199-50: \$5,880

¹⁴ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹⁵ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁶ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁷ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁸ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Pacific Gas & Electric, April 2007 ¹⁹ | 2,107 | N/A | N/A | N/A |
| Comments Average daily hot water use 2,083 gallons per day, thermal efficiency of new technology (60 gallon tank), 95%, thermal efficiency of base measure (standard efficiency tankless water heater), 82%. Measure provides savings of 28% over 7,496 m ³ required for heating water used with base equipment. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Puget Sound Energy, 2007 ²⁰ | 0.78 per ft ² . | 13 | N/A | 5% |
| Comments Savings calculated for an existing restaurant. Measure saves 34% of 2.28 m ³ per square foot required for water heating. | | | | |

¹⁹ Karras, A. and D. Fisher, *Energy Efficiency Potential of Gas-Fired Water Heating Systems in a Quick Service Restaurant*. Pacific Gas & Electric, April 2007
http://www.fishnick.com/publications/appliancereports/special/Commercial_Water_Heating_Systems.pdf

²⁰ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy
 C-215

49. Pre-Rinse Spray Nozzle (1.6 GPM)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Low-flow pre-rinse spray nozzle/valve (1.6 GPM)

Due to the variability in energy savings resulting from variability in daily water use, resource savings were calculated for three types of commercial enterprise using this technology¹:

Scenario **A**: Full service restaurant

Scenario **B**: Limited service (fast food) restaurant

Scenario **C**: Other

Base Equipment and Technologies Description

Standard pre-rinse spray nozzle/valve (3.0 GPM)

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------|---------------|
| Retrofit | Commercial (existing) | Water heating |

Codes, Standards, and Regulations

N/A

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | A: 705 B: 151 C: 159 | 0 | A: 135,500 B: 29,000 C: 30,500 | 41 | 0 |
| 2 | A: 705 B: 151 C: 159 | 0 | A: 135,500 B: 29,000 C: 30,500 | 0 | 0 |
| 3 | A: 705 B: 151 C: 159 | 0 | A: 135,500 B: 29,000 C: 30,500 | 0 | 0 |
| 4 | A: 705 B: 151 C: 159 | 0 | A: 135,500 B: 29,000 C: 30,500 | 0 | 0 |
| 5 | A: 705 B: 151 C: 159 | 0 | A: 135,500 B: 29,000 C: 30,500 | 0 | 0 |
| TOTALS | A: 3,525 B: 755 C: 795 | 0 | A: 677,500 B: 145,000 C: 152,500 | 41 | 0 |

¹ These bins are chosen based on empirical research conducted by Energy Profiles Ltd on behalf of Union Gas Energy Profiles Ltd, *Deemed Savings for (Low Flow) Pre-Rinse Spray Nozzles*, January 2009

Resource Savings Assumptions

Annual Natural Gas Savings

A: 705 m³

B: 151 m³

C: 159 m³

Assumptions and inputs:

- Average water inlet temperature: 9.33 °C (48.8 °F)²
- Average food service water heater set point temperature: 63 °C (145 °F)³
- Water heater thermal efficiency: 0.78⁴
- Percentage of water used that is hot: 69%⁵

Annual gas savings calculated as follows:

$$Savings = Ws * Phot * 8.33 * (T_{out} - T_{in}) * \frac{1}{Eff} * 10^{-6} * 27.8$$

Where:

Ws = Water savings (gallons)
 Phot = Percentage of water used that is hot
 T_{out} = Water heater set point temperature (°F)
 T_{in} = Water inlet temperature (°F)
 Eff = Water heater thermal efficiency
 8.33 = Energy content of water (Btu/gallon/°F)
 10⁻⁶ = Factor to convert Btu to MMBtu
 27.8 = Factor to convert MMBtu to m³

Gas savings were determined to be 47% over base equipment:

$$PercentSavings = \frac{(G_{base} - G_{eff})}{G_{base}}$$

Where:

Full service restaurant:

G_{eff} = Annual natural gas use with efficient equipment, 805 m³

G_{base} = Annual natural gas use with base equipment, 1510 m³

Limited service restaurant:

G_{eff} = Annual natural gas use with efficient equipment, 173 m³

G_{base} = Annual natural gas use with base equipment, 323 m³

Other:

G_{eff} = Annual natural gas use with efficient equipment, 181 m³

² Cited in the following as personal communication with City of Toronto Works Dept. VEIC, *Comments on Navigant's Draft Gas Measure Characterizations*, March 2009

³ [Average](#) of temperatures found in a survey of restaurants in four Ontario municipalities. Energy Profiles Ltd, *Deemed Savings for (Low Flow) Pre-Rinse Spray Nozzles*, January 2009

⁴ Minimum thermal efficiency for compliance with ASHRAE 90.1 standard.

⁵ Average of ratio found in a survey of restaurants in four Ontario municipalities. Energy Profiles Ltd, *Deemed Savings for (Low Flow) Pre-Rinse Spray Nozzles*, January 2009

G_{base} = Annual natural gas use with base equipment, 340 m³

Annual Electricity Savings

0 kWh

N/A

Annual Water Savings

A: 135,500 L

B: 29,000 L

C: 30,500 L

Assumptions and inputs:

- Veritec's 2008 Calgary Study found a 6% increase in average daily use after the introduction of a low-flow valve, but did not test the significance of this change. Navigant Consulting is therefore assuming that daily water use remains the same after the introduction of the efficient equipment.

Annual water savings calculated as follows:

$$Savings = (Fl_{base} - Fl_{eff}) * 60 * Hr * 365$$

Where:

Fl_{base} = Flow rate of base equipment (GPM)
 Fl_{eff} = Flow rate of efficient equipment (GPM)
 60 = Minutes per hour
 Hr = Hours used per day
 365 = Days per year

Water savings were determined to be 47% over base equipment:

$$PercentSavings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

Full service restaurant:

W_{eff} = Annual water consumed with efficient equipment, 154,842 litres (40,896 gallons)

W_{base} = Annual water consumed by showers with base equipment: 290,329 litres (76,680 gallons)

Limited service restaurant:

W_{eff} = Annual water consumed with efficient equipment, 33,167 litres (8,760 gallons)

W_{base} = Annual water consumed by showers with base equipment: 62,189 litres (16,425 gallons)

Other:

W_{eff} = Annual water consumed with efficient equipment, 34,894 litres (9,216 gallons)

W_{base} = Annual water consumed by showers with base equipment: 65,426 litres (17,280 gallons)

Other Input Assumptions

| | |
|--|----------------------|
| Effective Useful Life (EUL) | 5 Years |
| Studies conducted for the City of Calgary ⁶ , the U.S. DOE's FEMP ⁷ and by Puget Sound Energy ⁸ all give EUL for this measure as five years. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 41 \$ |
| Incremental cost based on a survey of online retailers ⁹ . | |
| Customer Payback Period (Natural Gas Only)¹⁰ | 0.1-0.5 Years |
| Using a 5-year average commodity cost (avoided cost) ¹¹ of \$0.38 / m ³ and an average commercial distribution cost ¹² of \$0.12 / m ³ , the payback period for natural gas savings is determined to be between 0.1 and 0.5 years, based on the following: | |
| <p>Scenario A Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="padding-left: 40px;">= \$41/ (705 m³/year * \$0.50 / m³)</p> <p style="padding-left: 40px;">= 0.1 years</p> <p>Scenario B Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="padding-left: 40px;">= \$41/ (151 m³/year * \$0.50 / m³)</p> <p style="padding-left: 40px;">= 0.5 years</p> <p>Scenario C Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="padding-left: 40px;">= \$41/ (159 m³/year * \$0.50 / m³)</p> <p style="padding-left: 40px;">= 0.5 years</p> | |
| Market Penetration¹³ | Medium |
| Based on the observation of high penetration in one jurisdiction (Washington State ¹⁴ – 70%), of medium penetration in another (Iowa ¹⁵ – 45%) and of the relatively low cost/benefit ratio, Navigant Consulting estimates the penetration in Ontario to be medium. | |

⁶ Ibid.

⁷ U.S. DOE, Federal Energy Management Program, *How to Buy a Low-Flow Pre-Rinse Spray Valve*
<http://www1.eere.energy.gov/femp/pdfs/prerinsenozzle.pdf>

⁸ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

⁹ Niagara 1.6 GPM Pre-rinse Spray Valve N2180

<http://www.conservationsmart.com/p-301-niagara-16-gpm-prerinse-spray-valve-n2180.aspx>

¹⁰ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹¹ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹² Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹³ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁴ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁵ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| City of Calgary, 2008 ¹⁶ | 469 | 5 | 0 (City installed) | N/A |
| Comments Daily mean use estimated to be 47 minutes before measure installed and 50 minutes with the efficient measure installed. On-site water use data reveal an even mix of hot and cold water used. Average flow rate of base equipment was found to be 3 GPM, while the average flow rate after efficient equipment installed was found to be 1.1 GPM. No indication given of percentage savings or base natural gas consumption for water heating. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| U.S. Department of Energy, Federal Energy Management Program ¹⁷ | 2,021 | 5 | N/A | N/A |
| Comments Assumptions: four hours of use per day, switch from a 3.0 GPM pre-rinse spray valve to a 1.6 GPM pre-rinse spray valve. Measure provides savings of 47% over 4,340 m3 required for heating water used with base equipment. | | | | |

¹⁶ Veritec Consulting (2008)

http://www.calgary.ca/docgallery/bu/water_services/conservation/indoor/calgary_pre_rinse_report.pdf

¹⁷ U.S. DOE, Federal Energy Management Program, *How to Buy a Low-Flow Pre-Rinse Spray Valve*
<http://www1.eere.energy.gov/femp/pdfs/prerinsenozzle.pdf>

50. Pre-Rinse Spray Nozzle (1.24 GPM)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Low-flow pre-rinse spray nozzle/valve (1.24 GPM)

Due to the variability in energy savings resulting from variability in daily water use, resource savings were calculated for three types of commercial enterprise using this technology¹:

Scenario **A**: Full service restaurant

Scenario **B**: Limited service (fast food) restaurant

Scenario **C**: Other

Base Equipment and Technologies Description

Standard pre-rinse spray nozzle/valve (3.0 GPM)

| Decision Type | Target Market(s) | End Use |
|---------------|-----------------------|---------------|
| Retrofit | Commercial (existing) | Water heating |

Codes, Standards, and Regulations

N/A

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | A: 886 B: 190 C: 200 | 0 | A: 170,326 B: 36,484 C: 38,383 | 60 | 0 |
| 2 | A: 886 B: 190 C: 200 | 0 | A: 170,326 B: 36,484 C: 38,383 | 0 | 0 |
| 3 | A: 886 B: 190 C: 200 | 0 | A: 170,326 B: 36,484 C: 38,383 | 0 | 0 |
| 4 | A: 886 B: 190 C: 200 | 0 | A: 170,326 B: 36,484 C: 38,383 | 0 | 0 |
| 5 | A: 886 B: 190 C: 200 | 0 | A: 170,326 B: 36,484 C: 38,383 | 0 | 0 |
| TOTALS | A: 4,430 B: 950 C: 1,000 | 0 | A: 851,630 B: 182,420 C: 191,915 | 60 | 0 |

¹ These bins are chosen based on empirical research conducted by Energy Profiles Ltd on behalf of Union Gas Energy Profiles Ltd, *Deemed Savings for (Low Flow) Pre-Rinse Spray Nozzles*, January 2009

Resource Savings Assumptions

Annual Natural Gas Savings

A: 886 m³

B: 190 m³

C: 200 m³

Assumptions and inputs:

- Average water inlet temperature: 9.33 °C (48.8 °F)²
- Average water heater set point temperature: 63 °C (145 °F)³
- Water heater thermal efficiency: 0.78⁴
- Percentage of water used that is hot: 69%⁵

Annual gas savings calculated as follows:

$$Savings = Ws * Phot * 8.33 * (T_{out} - T_{in}) * \frac{1}{Eff} * 10^{-6} * 27.8$$

Where:

Ws = Water savings (gallons)

Phot = Percentage of water used that is hot

T_{out} = Water heater set point temperature (°F)

T_{in} = Water inlet temperature (°F)

Eff = Water heater thermal efficiency

8.33 = Energy content of water (Btu/gallon/°F)

10⁻⁶ = Factor to convert Btu to MMBtu

27.8 = Factor to convert MMBtu to m³

Gas savings were determined to be 59% over base equipment:

$$PercentSavings = \frac{(G_{base} - G_{eff})}{G_{base}}$$

Where:

Full service restaurant:

G_{eff} = Annual natural gas use with efficient equipment, 624 m³

G_{base} = Annual natural gas use with base equipment, 1510 m³

Limited service restaurant:

G_{eff} = Annual natural gas use with efficient equipment, 134 m³

G_{base} = Annual natural gas use with base equipment, 323 m³

Other:

G_{eff} = Annual natural gas use with efficient equipment, 141 m³

G_{base} = Annual natural gas use with base equipment, 340 m³

² Cited in the following as personal communication with City of Toronto Works Dept.

VEIC, *Comments on Navigant's Draft Gas Measure Characterizations*, March 2009

³ [Average](#) of temperatures found in a survey of restaurants in four Ontario municipalities.

Energy Profiles Ltd, *Deemed Savings for (Low Flow) Pre-Rinse Spray Nozzles*, January 2009

⁴ Minimum thermal efficiency for compliance with ASHRAE 90.1 standard.

⁵ Average of ratio found in a survey of restaurants in four Ontario municipalities.

Energy Profiles Ltd, *Deemed Savings for (Low Flow) Pre-Rinse Spray Nozzles*, January 2009

| | |
|--|---|
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | A: 170,326 m³ B: 36,484 m³ C: 38,383 m³ |
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> Veritec's 2008 Calgary Study found a 6% increase in average daily use after the introduction of a low-flow valve, but did not test the significance of this change. Navigant Consulting is therefore assuming that daily water use remains the same after the introduction of the efficient equipment. <p>Annual water savings calculated as follows:</p> $Savings = (Fl_{base} - Fl_{eff}) * 60 * Hr * 365$ <p>Where:</p> <p> Fl_{base} = Flow rate of base equipment (GPM) Fl_{eff} = Flow rate of efficient equipment (GPM) 60 = Minutes per hour Hr = Hours used per day 365 = Days per year </p> <p>Water savings were determined to be 59% over base equipment:</p> $Percent Savings = \frac{(W_{base} - W_{eff})}{W_{base}}$ <p>Where:</p> <p>Full service restaurant:</p> <p> W_{eff} = Annual water consumed with efficient equipment, 120,002 litres (31,694 gallons) W_{base} = Annual water consumed by showers with base equipment: 290,329 litres (76,680 gallons) </p> <p>Limited service restaurant:</p> <p> W_{eff} = Annual water consumed with efficient equipment, 25,705 litres (6,789 gallons) W_{base} = Annual water consumed by showers with base equipment: 62,189 litres (16,425 gallons) </p> <p>Other:</p> <p> W_{eff} = Annual water consumed with efficient equipment, 27,043 litres (7,142 gallons) W_{base} = Annual water consumed by showers with base equipment: 65,426 litres (17,280 gallons) </p> | |

Other Input Assumptions

| | |
|--|----------------------|
| Effective Useful Life (EUL) | 5 Years |
| Studies conducted for the City of Calgary ⁶ , the U.S. DOE's FEMP ⁷ and by Puget Sound Energy ⁸ all give EUL for this measure as five years. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 60 \$ |
| Incremental cost based on a survey of online retailers ⁹ . | |
| Customer Payback Period (Natural Gas Only)¹⁰ | 0.1-0.6 Years |
| Using a 5-year average commodity cost (avoided cost) ¹¹ of \$0.38 / m ³ and an average commercial distribution cost ¹² of \$0.12 / m ³ , the payback period for natural gas savings is determined to be between 0.1 and 0.6 years, based on the following: | |
| <p>Scenario A Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="padding-left: 40px;">= \$60/ (886 m³/year * \$0.50 / m³)</p> <p style="padding-left: 40px;">= 0.1 years</p> <p>Scenario B Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="padding-left: 40px;">= \$60/ (190 m³/year * \$0.50 / m³)</p> <p style="padding-left: 40px;">= 0.6 years</p> <p>Scenario C Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p style="padding-left: 40px;">= \$60/ (200 m³/year * \$0.50 / m³)</p> <p style="padding-left: 40px;">= 0.6 years</p> | |
| Market Penetration¹³ | Low |
| Although 1.6 GPM spray nozzles have a high penetration in one jurisdiction (Washington State ¹⁴ – 70%) and a medium penetration in another (Iowa ¹⁵ – 45%), no figures were uncovered for 1.24 GPM spray nozzles. Given the relative novelty of this newer, lower flow rate spray nozzle, Navigant Consulting estimates the penetration in Ontario to be low. | |

⁶ Ibid.

⁷ U.S. DOE, Federal Energy Management Program, *How to Buy a Low-Flow Pre-Rinse Spray Valve*
<http://www1.eere.energy.gov/femp/pdfs/prerinsenozzle.pdf>

⁸ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

⁹ T & S Brass (B-0107-C35) - JetSpray 1.24 GPM low flow spray valve <http://www.foodservicewarehouse.com/t-s-brass/b-0107-c35/p345921.aspx?source=googleps>

¹⁰ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹¹ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹² Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹³ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

¹⁴ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁵ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| City of Calgary, 2008 ¹⁶ | 469 | 5 | 0 (City installed) | N/A |
| Comments Daily mean use estimated to be 47 minutes before measure installed and 50 minutes with the efficient measure installed. On-site water use data reveal an even mix of hot and cold water used. Average flow rate of base equipment was found to be 3 GPM, while the average flow rate after efficient equipment installed was found to be 1.1 GPM. No indication given of percentage savings or base natural gas consumption for water heating. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| U.S. Department of Energy, Federal Energy Management Program ¹⁷ | 2,021 | 5 | N/A | N/A |
| Comments Assumptions: four hours of use per day, switch from a 3.0 GPM pre-rinse spray valve to a 1.6 GPM pre-rinse spray valve. Measure provides savings of 47% over 4,340 m3 required for heating water used with base equipment. | | | | |

¹⁶ Veritec Consulting (2008) http://www.calgary.ca/docgallery/bu/water_services/conservation/indoor/calgary_pre_rinse_report.pdf

¹⁷ U.S. DOE, Federal Energy Management Program, *How to Buy a Low-Flow Pre-Rinse Spray Valve*
<http://www1.eere.energy.gov/femp/pdfs/prerinsenozzle.pdf>

51. Tankless Water Heater - Commercial

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Gas Tankless Water Heater (Thermal efficiency = 84%).

Due to the variability in energy savings for commercial buildings resulting from the quantity of daily water use, resource savings were calculated for three scenarios of daily hot water use¹:

Scenario A: 100 gallons (378 litres)

Scenario B: 500 gallons (1,893 litres)

Scenario C: 1,000 gallons (3,786 litres)

Base Equipment and Technologies Description

For scenario A, a conventional storage tank gas water heater (Thermal efficiency = 80%), 35 gallons. For scenarios B and C, a conventional storage tank gas water heater (Thermal efficiency² = 80%), 91 gallons

| Decision Type | Target Market(s) | End Use |
|---------------|------------------|----------------|
| New | Commercial (New) | Water heating. |

Codes, Standards, and Regulations

Ontario's Energy Efficiency Act³ applies only to water heaters with an input rating of less than 75,000 Btu/hr.

¹ One of the input assumptions required for calculating resource savings for this measure is the stand-by heat loss of storage tank water heaters. Hourly stand-by losses are treated as constant using values drawn from GAMA's *Consumer Directory* (see citation below). This means that marginal percentage gas savings will fall as hot water use rises.

² Although the required minimum thermal efficiency to be in compliance with ASHRAE 90.1 is 78%, <http://www.energycodes.gov/comcheck/pdfs/404text.pdf>, only an very small percentage of commercial gas water heaters listed in the GAMA *Consumer's Directory of Certified Efficiency Ratings* had a thermal efficiency of less than 80%.

³ <http://www.energy.gov.on.ca/english/pdf/conservation/2006%20-%20EEA%20Guide%20C%20-%20Water%20Heaters.pdf>

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|--------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | A: 154 B: 66 C: -124 | 0 | 0 | A: \$2,080 B: \$4,160 C: \$6,240 | A: B: \$3,650 C: \$3,650 |
| 2 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 3 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 4 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 5 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 6 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 7 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 8 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 9 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 10 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 11 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 12 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 13 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 14 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 15 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 16 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 17 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| 18 | A: 154 B: 66 C: -124 | 0 | 0 | 0 | 0 |
| TOTALS | A: 2,772 B: 1,188 C: -2,232 | 0 | 0 | A: \$2,080 B: \$4,160 C: \$6,240 | A: B: \$3,650 C: \$3,650 |

Resource Savings Assumptions

Annual Natural Gas Savings

A: 154 m³
B: 66 m³
C: -124 m³

Assumptions and inputs:

- Following a recommendation made in 2006 to the California Energy Commission that the Alternative Calculation Method (ACM) be amended to recognise the disparity between the nominal recovery efficiency of tankless water heaters drawing less than 11 gallons and the actual energy efficiency, savings are calculated using an thermal efficiency degraded by 8.8%⁴
- Adjusted thermal efficiency⁵: 0.77.
- Input rating for new technology and base equipment: 199,000 Btu.
- Stand-by loss of Rheem G91-200: 1,050 Btu/hr⁶ (base measure, scenarios B,C).
- Stand-by loss of Rheem G37-200: 790 Btu/hr⁷ (base measure, scenario A)
- Daily hot water draw:
 - Scenario A: 100 gallons (378 litres)
 - Scenario B: 500 gallons (1,893 gallons)
 - Scenario C: 1,000 gallons (3,786 litres)
- Average water inlet temperature: 9.33 °C (48.8 °F)⁸
- Average water heater set point temperature: 54 °C (130 °F)⁹

Annual gas savings calculated as follows:

$$Savings = \left[W * 8.33 * (T_{out} - T_{in}) * \left(\frac{1}{Eff_{base}} - \frac{1}{Eff_{eff}} \right) + (Stby_{base} - Stby_{eff}) * 24 * 365 \right] * 10^{-6} * 27.8$$

Where:

W = Annual hot water use (gallons)
 8.33 = Energy content of water (Btu/gallon/°F)
 T_{out} = Water heater set point temperature (°F)
 T_{in} = Water inlet temperature (°F)
 Eff_{base} = Thermal efficiency of base equipment
 Eff_{eff} = Adjusted thermal efficiency of efficient equipment
 10⁻⁶ = Factor to convert Btu to MMBtu
 Stby_{base} = Stand-by loss per hour for base equipment (Btu)
 Stby_{eff} = Stand-by loss per hour for efficient equipment (Btu)
 24 = Hours per day
 365 = Days per year
 27.8 = Factor to convert MMBtu to m³

⁴ Davis Energy Group, *Measure Information Template: Tankless Gas Water Heaters*, April 2008

http://www.energy.ca.gov/title24/2008standards/prerulemaking/documents/2006-05-18_workshop/2006-05-11_GAS_WATER.PDF

⁵ It should be noted that an alternative study, by Exelon Services for Okaloosa Gas, conducted carefully controlled tests to determine the thermal efficiency of a tankless and a storage tank gas water heater. This study found that, in fact, the listed energy factor *underestimated* the tankless water heater's true thermal efficiency. This result is not reflected in this substantiation sheet due to the more recent findings cited above, arrived at with a larger sample than the Okaloosa study. Exelon Services and Okaloosa Gas District, *Performance Comparison of Residential Water Heating Systems*, December 2002

⁶ *Consumer's Directory of Certified Efficiency Ratings* http://www.neo.ne.gov/neq_online/july2006/commgaswtrhr.pdf

⁷ Ibid.

⁸ Chinnery, Glen. *Policy Recommendations for the HERS Community to Consider regarding HERS point credit for Waste Water Heat Recovery Devices*, EPA, Energy Star for homes, March 2004

http://www.energystar.gov/ia/partners/bldrs_lenders_raters/downloads/Waste_Water_Heat_Recovery_Guidelines.pdf

⁹ As suggested by NRCAN: <http://oee.nrcan.gc.ca/residential/personal/new-homes/water-conservation.cfm?attr=4>

Scenario A: Gas savings were determined to be 15% over base measure

Scenario B: Gas savings were determined to be 1% over base measure

Scenario C: Gas savings were determined to be -1% over base measure

$$\text{Percent Savings} = \frac{(G_{\text{base}} - G_{\text{eff}})}{G_{\text{base}}}$$

Where:

G_{eff} = Annual natural gas use with efficient equipment,

Scenario A: 896 m³

Scenario B: 4,480 m³

Scenario C: 8,959 m³

G_{base} = Annual natural gas use with base equipment,

Scenario A: 1,050 m³

Scenario B: 4,545 m³

Scenario C: 8,835 m³

Annual Electricity Savings

0 kWh

N/A

Annual Water Savings

0 L

Navigant has assumed that adopting the measure would not affect the quantity of water consumed.

Other Input Assumptions

Effective Useful Life (EUL)

18 Years

Navigant Consulting recommends using an EUL of 18 years, the mean of estimated measure lifetimes used two other jurisdictions (Iowa¹⁰, 20 years, and Puget Sound Energy¹¹, 13 years) and that quoted by an academic paper¹² (20 years).

Base & Incremental Conservation Measure Equipment and O&M Costs

A: -1,102\$

B: 510 \$

C: 2,590 \$

Commercial tankless water heaters are typically scaled up by unit - a commercial user would likely need several tankless water heaters to replace a single storage tank. The tankless model cited has a maximum flow rate of 4.7 – 7.4 GPM depending on temperature rise required. Any large commercial enterprise would likely require 2 – 3 tankless units to accommodate peak demand¹³.

Costs for the two systems were determined to be:

- WaiWela PH28CIFS tankless water heater and installation kit = \$2,080 ea¹⁴.
- Rheem G91-200 storage tank water heater = \$3,650¹⁵.
- Rheem G37-200 storage tank water heater = \$3,182¹⁶

¹⁰ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

¹¹ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹² Aguilar, C., White, D.J., and Ryan, David L. *Domestic Water Heating and Water Heater Energy Consumption in Canada*, April 2005,

¹³ A study for Pacific Gas and Electric of a chain casual dining restaurant found peak water draws of up to 20 GPM.

Wallace, C. and D. Fisher, *Energy Efficiency Potential of Gas-Fired Commercial Hot Water Heating Systems in Restaurants*. April 2007

¹⁴ <http://www.tanklesswaterheaters.ca/waiwelaph28ci.html>

¹⁵ From correspondence with local distributor.

¹⁶ Ibid

| | |
|--|--|
| Customer Payback Period (Natural Gas Only)¹⁷ | A: 0 B: 15 Years C: N/A |
| <p>Using a 5-year average commodity cost (avoided cost)¹⁸ of \$0.38 / m³ and an average commercial distribution cost¹⁹ of \$0.12 / m³, the payback period for natural gas savings is determined to be immediate for Scenario A and 17 years for Scenario B.</p> <p>For Scenario C, natural gas use increases, no natural gas payback is determined.</p> <p>Payback Period = Incremental cost / (natural gas savings x natural gas cost)</p> <p>Scenario A = Incremental cost is negative for this scenario; payback is immediate as efficient equipment costs less than base equipment.</p> <p>Scenario B = \$510/ (66 m³/year * \$0.50 / m³) = 15 years</p> | |
| Market Penetration²⁰ | Low |
| <p>Based on the observation of low penetration in two other jurisdictions (Washington State²¹ – 5%, Iowa²² – 0%), communications with local contractors and the logistical requirements for large commercial installations, Navigant Consulting estimates the penetration in Ontario to be low.</p> | |

¹⁷ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹⁸ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁹ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

²⁰ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

²¹ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

²² Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|------------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy, 2007 ²³ | 0.09 per ft ² (school) | 15 | N/A | 5% |
| Comments Assuming base equipment to be a conventional water tank with an EF=0.64. No indication that efficiency assumptions change from residential to commercial. Measure saves 27% of 0.33 m ³ per square foot required for water heating. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ²⁴ | 0.017 per ft ³ (school) | 20 | 9,167 US\$ | 0% |
| Comments Compare a tankless water heater with an EF = 0.82 against a conventional storage tank water heater with 80% thermal efficiency. Measure saves 30% of 0.56 m ³ per square foot required for water heating. | | | | |

²³ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

²⁴ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

MULTI-FAMILY WATER HEATING

52. Energy Star Front-Loading Clothes Washer

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Energy Star high efficiency front load washers for application in the Multi-Family sector (MEF¹=1.72 , WF²=8.0, tub size = 2.8 ft³)

Base Equipment and Technologies Description

Conventional top loading vertical axis washers (MEF = 1.26, WF=9.5, tub size = 2.8 ft³)

| Decision Type | Target Market(s) | End Use |
|-----------------|------------------|---------------|
| New/Replacement | Multi-Family | Water heating |

Codes, Standards, and Regulations

NRCan Federal Energy Efficiency Regulations require:

- Top loading washers are required to have a minimum MEF of 1.26 and a maximum tub size of 3.5 cubic feet.
- Front loading washers are required to have a minimum MEF of 1.26 and a maximum tub size of 4 cubic feet.

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|----------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 76 | 201 | 19,814 | \$1,000 | \$850 |
| 2 | 76 | 201 | 19,814 | 0 | 0 |
| 3 | 76 | 201 | 19,814 | 0 | 0 |
| 4 | 76 | 201 | 19,814 | 0 | 0 |
| 5 | 76 | 201 | 19,814 | 0 | 0 |
| 6 | 76 | 201 | 19,814 | 0 | 0 |
| 7 | 76 | 201 | 19,814 | 0 | 0 |
| 8 | 76 | 201 | 19,814 | 0 | 0 |
| 9 | 76 | 201 | 19,814 | 0 | 0 |
| 10 | 76 | 201 | 19,814 | 0 | 0 |
| 11 | 76 | 201 | 19,814 | 0 | 0 |
| TOTALS | 836 | 2,211 | 217,954 | \$1,000 | \$850 |

¹ Modified Energy Factor.

² Water Factor: the number of gallons per load cycle per cubic foot that the clothes washer uses. The lower the water factor, the more efficient the washer is.

Resource Savings Assumptions

Annual Natural Gas Savings

76 m³

Assumptions and inputs:

- Percentage of water used by base equipment which is hot water: 17%.
- Percentage of water used by efficient equipment which is hot water: 10%³
- Average water inlet temperature: 9.33 °C (48.8 °F)⁴
- Average water heater set point temperature: 54 °C (130 °F)⁵
- Water heater thermal efficiency: 0.78⁶
- Gas use per cycle⁷ for commercial gas dryer with base equipment: 0.138 m³
- Gas use per cycle for commercial gas dryer with Energy Star clothes washer: 0.117 m³
- Gas dryer penetration in Ontario Multi-Family market: 25.5%⁸
- Annual gas savings from reduced dryer use: 7 m³
- Annual gas savings from reduced hot water use: 73 m³

Annual gas savings calculated as follows:

$$Savings = \left[(W_{base} * Hot_{base} - W_{eff} * Hot_{eff}) * 8.33 * \frac{1}{Eff} * (T_{out} - T_{in}) + (Dr_{base} - Dr_{eff}) * Pene \right] * 10^{-6} * 27.8$$

Where:

W_{base} = Annual water use with base equipment (gallons)
 W_{eff} = Annual water use with efficient equipment (gallons)
 Hot_{base} = Percentage of water used that's hot with base equipment
 Hot_{eff} = Percentage of water used that's hot with efficient equipment
 8.33 = Energy content of water (Btu/gallon/°F)
 Eff = Water heater thermal efficiency
 T_{out} = Water heater set point temperature (°F)
 T_{in} = Water inlet temperature (°F)
 Dr_{base} = Annual dryer gas use with base equipment (Btu)
 Dr_{eff} = Annual dryer gas use with efficient equipment (Btu)
 $Pene$ = Penetration rate of natural gas powered clothes dryers in Ontario
 10^{-6} = Factor to convert Btu to MMBtu
 27.8 = Factor to convert MMBtu to m³

Gas savings were determined to be 43% over base equipment.

³ Base equipment uses 4.4 gallons of hot water per cycle, efficient equipment uses 2.3 gallons of hot water per cycle. U.S. DOE Federal Energy Management Program, Life-Cycle and Cost and Payback Period spreadsheet, http://www1.eere.energy.gov/buildings/appliance_standards/commercial/clothes_washers.html

⁴ Chinnery, Glen. *Policy Recommendations for the HERS Community to Consider regarding HERS point credit for Waste Water Heat Recovery Devices*, EPA, Energy Star for homes, March 2004 http://www.energystar.gov/ia/partners/bldrs_lenders_raters/downloads/Waste_Water_Heat_Recovery_Guidelines.pdf

⁵ As suggested by NRCAN: <http://oee.nrcan.gc.ca/residential/personal/new-homes/water-conservation.cfm?attr=4>

⁶ Minimum thermal efficiency for compliance with ASHRAE 90.1 standard.

⁷ U.S. DOE Federal Energy Management Program, National Energy Savings and Shipments spreadsheet http://www1.eere.energy.gov/buildings/appliance_standards/commercial/clothes_washers.html

⁸ Average residential penetration rate of gas dryers in Union and Enbridge territories. The commercial/Multi-Family clothes dryers is likely to be slightly higher. Enbridge Gas Distribution, *Enbridge Gas Distribution to the Ontario Power Authority in the matter of the province's energy supply mix*, August 26, 2005. http://www.energy.gov.on.ca/opareport/Part%20-%20Submissions%20and%20Presentations/5.1%20Written%20Submissions%20to%20the%20Supply%20Mix%20Project/Enbridge_Gas_Distribution_Supply_Mix_Submission_Aug_26_2005.pdf

$$Percent Savings = \frac{(G_{base} - G_{eff})}{G_{base}}$$

Where:

G_{eff} = Annual natural gas use with efficient equipment, 110 m³

G_{base} = Annual natural gas use with base equipment, 182 m³

Annual Electricity Savings

201 kWh

Assumptions and inputs:

- Water heated by natural gas (see above).
- Washer electricity use per cycle, base equipment: 0.13 kWh⁹.
- Washer electricity use per cycle, efficient equipment: 0.11 kWh.
- Dryer electricity use per cycle, base equipment: 1.3 kWh.
- Dryer electricity use per cycle, efficient equipment: 1.11 kWh.
- Average number of cycles per year for clothes washer serving Multi-Family: 1246 cycles¹⁰.

Annual electricity savings calculated as follows:

$$Savings = [(Wa_{base} - Wa_{eff}) + (Dr_{base} - Dr_{eff}) * (1 - Pene)] * Cyc$$

Where:

Wa_{base} = Washer electricity use per cycle, base equipment (kWh)

Wa_{eff} = Washer electricity use per cycle, efficient equipment (kWh)

Dr_{base} = Dryer electricity use per cycle, base equipment (kWh)

Dr_{eff} = Dry electricity use per cycle, efficient equipment (kWh)

$Pene$ = Penetration rate of natural gas powered clothes dryers in Ontario

Cyc = Average number of cycles per year machine is used

Electricity savings were determined to be 15% over base equipment:

$$Percent Savings = \frac{(Elec_{base} - Elec_{new})}{Elec_{base}}$$

Where:

$Elec_{eff}$ = Annual natural gas use with efficient equipment, 1,167 kWh

$Elec_{base}$ = Annual natural gas use with base equipment, 1,369 kWh

Annual Water Savings

19,814 L

Assumptions and inputs:

- Water use per cycle, base equipment: 101 litres (26.6 gallons).
- Water use per cycle, new technology: 85 litres (22.4 gallons).
- Average number of cycles per year for clothes washer serving Multi-Family: 1,246 cycles¹¹

⁹ U.S. DOE Federal Energy Management Program, Life-Cycle and Cost and Payback Period spreadsheet, http://www1.eere.energy.gov/buildings/appliance_standards/commercial/clothes_washers.html

¹⁰ U.S. DOE Federal Energy Management Program, National Energy Savings and Shipments spreadsheet http://www1.eere.energy.gov/buildings/appliance_standards/commercial/clothes_washers.html

¹¹ Ibid.

Annual water savings calculated as follows:

$$Savings = (W_{base} - W_{eff}) * Cyc$$

Where:

W_{base} = Annual water use with base equipment (gallons or litres)
 W_{eff} = Annual water use with efficient equipment (gallons or litres)
Cyc = Average number of cycles per year machine is used

Water savings were determined to be 16% over base measure:

$$Percent Savings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water consumed with efficient equipment, 105,675 litres (27,910 gallons).
 W_{base} = Annual water consumed by showers with base equipment: 125,489 litres (33,144 gallons).

Other Input Assumptions

| | |
|---|-----------------|
| Effective Useful Life (EUL) | 11 Years |
| The U.S. DOE's Federal Energy Management Program has determined that commercial/Multi-Family clothes washers have an average EUL of 11.25 years ¹² . Navigant Consulting recommends adopting an EUL of 11 years. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 150 \$ |
| Incremental cost based on prices offered online by a local retailer ¹³ . | |
| Customer Payback Period (Natural Gas Only)¹⁴ | 4 Years |
| Using a 5-year average commodity cost (avoided cost) ¹⁵ of \$0.38 / m ³ and an average commercial distribution cost ¹⁶ of \$0.12 / m ³ , the payback period for natural gas savings is determined to be 4 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$150 / (76 m ³ /year * \$0.50 / m ³) = 4 years | |
| Market Share¹⁷ | High |
| Based on the observation of high market penetration in two other jurisdictions (Washington State ¹⁸ – 48%, | |

¹² Ibid.

¹³ Base measure (3.5 cu/ft top loader, GE): \$850
New technology (3.5 cu/ft front loader, LG): \$1,000

www.homedepot.ca. Assuming the base equipment cost/ efficient equipment cost ratio of the two 3.5 cu/ft washers is equivalent to that of two 2.8 cu/ft washers.

¹⁴ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹⁵ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁶ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁷ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

Iowa¹⁹ – 72%) and of the fact that the majority of clothes washers offered for sale on the website of a major retailer are Energy Star, Navigant Consulting estimates the penetration in Ontario to be high.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy, 2007 ²⁰ | 70 | 14 | 600 | 48% |
| Comments No explicit assumptions made about base and efficient equipment for commercial clothes washers. For residential clothes washers, assumptions: base equipment, MEF = 1.0, efficient equipment, Energy Star Clothes Washer, MEF = 1.8. Measure saves 13% of 539 m ³ required for water heating. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Efficiency Vermont, 2005 ²¹ | 20 | 14 | \$750 | N/A |
| Comments Cost is reported as the full cost of the energy efficient equipment rather than the incremental cost. Savings calculated are per customer basis rather than a per machine basis. No indication given of percentage savings or base natural gas consumption for water heating. | | | | |

¹⁸ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁹ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

²⁰ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

²¹ Efficiency Vermont, Technical Reference User Manual (TRM) No. 2005 - 37

53. CEE Tier 2 Front-Loading Clothes Washer

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

CEE Tier 2 high efficiency front load washers for application in the Multi-Family sector (MEF¹=2.20 , WF²=5.1, tub size = 2.8 ft³)

Base Equipment and Technologies Description

Conventional top loading vertical axis washers (MEF = 1.26, WF=9.5, tub size = 2.8 ft³)

| Decision Type | Target Market(s) | End Use |
|-----------------|------------------|---------------|
| New/Replacement | Multi-Family | Water heating |

Codes, Standards, and Regulations

NRCan Federal Energy Efficiency Regulations require:

- Top loading washers are required to have a minimum MEF of 1.26 and a maximum tub size of 3.5 cubic feet.
- Front loading washers are required to have a minimum MEF of 1.26 and a maximum tub size of 4 cubic feet.

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|----------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 117 | 396 | 58,121 | \$1,450 | \$850 |
| 2 | 117 | 396 | 58,121 | 0 | 0 |
| 3 | 117 | 396 | 58,121 | 0 | 0 |
| 4 | 117 | 396 | 58,121 | 0 | 0 |
| 5 | 117 | 396 | 58,121 | 0 | 0 |
| 6 | 117 | 396 | 58,121 | 0 | 0 |
| 7 | 117 | 396 | 58,121 | 0 | 0 |
| 8 | 117 | 396 | 58,121 | 0 | 0 |
| 9 | 117 | 396 | 58,121 | 0 | 0 |
| 10 | 117 | 396 | 58,121 | 0 | 0 |
| 11 | 117 | 396 | 58,121 | 0 | 0 |
| TOTALS | 1,287 | 4,356 | 639,331 | \$1,450 | \$850 |

¹ Modified Energy Factor.

² Water Factor: the number of gallons per load cycle per cubic foot that the clothes washer uses. The lower the water factor, the more efficient the washer is.

Resource Savings Assumptions

Annual Natural Gas Savings

117 m³

Assumptions and inputs:

- Percentage of water used by base equipment which is hot water: 17%.
- Percentage of water used by efficient equipment which is hot water: 10%³
- Average water inlet temperature: 9.33 °C (48.8 °F)⁴
- Average water heater set point temperature: 54 °C (130 °F)⁵
- Water heater thermal efficiency: 0.78⁶
- Gas use per cycle⁷ for commercial gas dryer with base equipment: 0.138 m³
- Gas use per cycle for commercial gas dryer with CEE Tier 2 clothes washer: 0.96 m³
- Gas dryer penetration in Ontario Multi-Family market: 25.5%⁸
- Annual gas savings from reduced dryer use: 13 m³
- Annual gas savings from reduced hot water use: 103 m³

Annual gas savings calculated as follows:

$$Savings = \left[(W_{base} * Hot_{base} - W_{eff} * Hot_{eff}) * 8.33 * \frac{1}{Eff} * (T_{out} - T_{in}) + (Dr_{base} - Dr_{eff}) * Pene \right] * 10^{-6} * 27.8$$

Where:

W_{base} = Annual water use with base equipment (gallons)
 W_{eff} = Annual water use with efficient equipment (gallons)
 Hot_{base} = Percentage of water used that's hot with base equipment
 Hot_{eff} = Percentage of water used that's hot with efficient equipment
 8.33 = Energy content of water (Btu/gallon/°F)
 Eff = Water heater thermal efficiency
 T_{out} = Water heater set point temperature (°F)
 T_{in} = Water inlet temperature (°F)
 Dr_{base} = Annual dryer gas use with base equipment (Btu)
 Dr_{eff} = Annual dryer gas use with efficient equipment (Btu)
 $Pene$ = Penetration rate of natural gas powered clothes dryers in Ontario
 10^{-6} = Factor to convert Btu to MMBtu
 27.8 = Factor to convert MMBtu to m³

Gas savings were determined to be 66% over base equipment.

³ Base equipment uses 4.4 gallons of hot water per cycle, efficient equipment uses 1.4 gallons of hot water per cycle. U.S. DOE Federal Energy Management Program, Life-Cycle and Cost and Payback Period spreadsheet, http://www1.eere.energy.gov/buildings/appliance_standards/commercial/clothes_washers.html

⁴ Chinnery, Glen. *Policy Recommendations for the HERS Community to Consider regarding HERS point credit for Waste Water Heat Recovery Devices*, EPA, Energy Star for homes, March 2004
http://www.energystar.gov/ia/partners/bldrs_lenders_raters/downloads/Waste_Water_Heat_Recovery_Guidelines.pdf

⁵ As suggested by NRCAN: <http://oee.nrcan.gc.ca/residential/personal/new-homes/water-conservation.cfm?attr=4>

⁶ Minimum thermal efficiency for compliance with ASHRAE 90.1 standard.

⁷ U.S. DOE Federal Energy Management Program, National Energy Savings and Shipments spreadsheet
http://www1.eere.energy.gov/buildings/appliance_standards/commercial/clothes_washers.html

⁸ Average residential penetration rate of gas dryers in Union and Enbridge territories. The commercial/Multi-Family clothes dryers is likely to be slightly higher. Enbridge Gas Distribution, *Enbridge Gas Distribution to the Ontario Power Authority in the matter of the province's energy supply mix*, August 26, 2005.
http://www.energy.gov.on.ca/opareport/Part%205%20-%20Submissions%20and%20Presentations/5.1%20Written%20Submissions%20to%20the%20Supply%20Mix%20Project/Enbridge_Gas_Distribution_Supply_Mix_Submission_Aug_26_2005.pdf

$$\text{Percent Savings} = \frac{(G_{\text{base}} - G_{\text{eff}})}{G_{\text{base}}}$$

Where:

G_{eff} = Annual natural gas use with efficient equipment, 73 m³

G_{base} = Annual natural gas use with base equipment, 176 m³

Annual Electricity Savings

396 kWh

Assumptions and inputs:

- Water heated by natural gas (see above).
- Washer electricity use per cycle, base equipment: 0.13 kWh⁹.
- Washer electricity use per cycle, efficient equipment: 0.11 kWh.
- Dryer electricity use per cycle, base equipment: 1.3 kWh.
- Dryer electricity use per cycle, efficient equipment: 0.9 kWh.
- Average number of cycles per year for clothes washer serving Multi-Family: 1,246 cycles¹⁰.

Annual electricity savings calculated as follows:

$$\text{Savings} = [(Wa_{\text{base}} - Wa_{\text{eff}}) + (Dr_{\text{base}} - Dr_{\text{eff}}) * (1 - Pene)] * Cyc$$

Where:

Wa_{base} = Washer electricity use per cycle, base equipment (kWh)

Wa_{eff} = Washer electricity use per cycle, efficient equipment (kWh)

Dr_{base} = Dryer electricity use per cycle, base equipment (kWh)

Dr_{eff} = Dry electricity use per cycle, efficient equipment (kWh)

$Pene$ = Penetration rate of natural gas powered clothes dryers in Ontario

Cyc = Average number of cycles per year machine is used

Electricity savings were determined to be 29% over base equipment:

$$\text{Percent Savings} = \frac{(Elec_{\text{base}} - Elec_{\text{new}})}{Elec_{\text{base}}}$$

Where:

$Elec_{\text{eff}}$ = Annual natural gas use with efficient equipment, 973 kWh

$Elec_{\text{base}}$ = Annual natural gas use with base equipment, 1,369 kWh

Annual Water Savings

58,121 L

Assumptions and inputs:

- Water use per cycle, base equipment: 101 litres (26.6 gallons).
- Water use per cycle, new technology: 54 litres (14.3 gallons).
- Average number of cycles per year for clothes washer serving Multi-Family: 1,246 cycles¹¹

⁹ U.S. DOE Federal Energy Management Program, Life-Cycle and Cost and Payback Period spreadsheet, http://www1.eere.energy.gov/buildings/appliance_standards/commercial/clothes_washers.html

¹⁰ U.S. DOE Federal Energy Management Program, National Energy Savings and Shipments spreadsheet http://www1.eere.energy.gov/buildings/appliance_standards/commercial/clothes_washers.html

¹¹ Ibid.

Annual water savings calculated as follows:

$$Savings = (W_{base} - W_{eff}) * Cyc$$

Where:

W_{base} = Annual water use with base equipment (gallons or litres)
 W_{eff} = Annual water use with efficient equipment (gallons or litres)
Cyc = Average number of cycles per year machine is used

Water savings were determined to be 46% over base measure:

$$Percent Savings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water consumed with efficient equipment, 67,368 litres (17,793 gallons).
 W_{base} = Annual water consumed by showers with base equipment: 125,489 litres (33,144 gallons).

Other Input Assumptions

| | |
|--|-------------------|
| Effective Useful Life (EUL) | 11 Years |
| The U.S. DOE's Federal Energy Management Program has determined that commercial/Multi-Family clothes washers have an average EUL of 11.25 years ¹² . Navigant Consulting recommends adopting an EUL of 11 years. | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 600 \$ |
| Incremental cost based on prices offered online by a local retailer ¹³ and that given by Enbridge. | |
| Customer Payback Period (Natural Gas Only)¹⁴ | 10 Years |
| Using a 5-year average commodity cost (avoided cost) ¹⁵ of \$0.38 / m ³ and an average commercial distribution cost ¹⁶ of \$0.12 / m ³ , the payback period for natural gas savings is determined to be 10 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$600 / (117 m ³ /year * \$0.50 / m ³) = 10 years | |
| Market Share¹⁷ | Medium/Low |
| Based on the observation of high market penetration of Energy Star qualified washers in two other jurisdictions (Washington State ¹⁸ – 48%, Iowa ¹⁹ – 72%) but the paucity of washers available from online | |

¹² Ibid.

¹³ Base measure (3.5 cu/ft top loader, GE): \$850

www.homedepot.ca. Assuming the base equipment cost/ efficient equipment cost ratio of the two 3.5 cu/ft washers is equivalent to that of two 2.8 cu/ft washers.

¹⁴ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹⁵ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁶ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁷ Navigant Consulting is defining "Low" as below 5%, "Medium" as between 5-50%, and "High" as above 50%.

retailers with specifications sufficient to qualify for CEE Tier 2 Navigant Consulting estimates the penetration in Ontario to be medium to low.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy, 2007 ²⁰ | 70 | 14 | 600 | 48% |
| Comments No explicit assumptions made about base and efficient equipment for commercial clothes washers. For residential clothes washers, assumptions: base equipment, MEF = 1.0, efficient equipment, Energy Star Clothes Washer, MEF = 1.8. Measure saves 13% of 539 m ³ required for water heating. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| Efficiency Vermont, 2005 ²¹ | 20 | 14 | \$750 | N/A |
| Comments Cost is reported as the full cost of the energy efficient equipment rather than the incremental cost. Savings calculated are per customer basis rather than a per machine basis. No indication given of percentage savings or base natural gas consumption for water heating. | | | | |

¹⁸ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁹ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

²⁰ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

²¹ Efficiency Vermont, Technical Reference User Manual (TRM) No. 2005 - 37

54. Faucet Aerator (Multi-Family Bathroom)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Faucet Aerator (Bathroom) (1.5 GPM)

Base Equipment and Technologies Description

Average existing stock (2.2 GPM)¹

| Decision Type | Target Market(s) | End Use |
|---------------|-------------------------|---------------|
| Retrofit | Multi-Family (existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)² requires bathroom and kitchen faucets to have a maximum flow of 2.2 GPM (8.35 L/min).

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|---------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 4 | 0 | 1,382 | 2 | 0 |
| 2 | 4 | 0 | 1,382 | 0 | 0 |
| 3 | 4 | 0 | 1,382 | 0 | 0 |
| 4 | 4 | 0 | 1,382 | 0 | 0 |
| 5 | 4 | 0 | 1,382 | 0 | 0 |
| 6 | 4 | 0 | 1,382 | 0 | 0 |
| 7 | 4 | 0 | 1,382 | 0 | 0 |
| 8 | 4 | 0 | 1,382 | 0 | 0 |
| 9 | 4 | 0 | 1,382 | 0 | 0 |
| 10 | 4 | 0 | 1,382 | 0 | 0 |
| TOTALS | 40 | 0 | 13,820 | 2 | 0 |

¹ From on-site audit data. Resource Management Strategies, Inc. *Regional Municipality of York Water Efficiency Master Plan*

Update, 2007. Cited in: Summit Blue, *Resource Savings Values in Selected Residential DSM Prescriptive Programs*, June 2008.

² Ontario Regulations 350/06, 2006 Building Code

Resource Savings Assumptions

| Annual Natural Gas Savings | 4 m ³ |
|---|------------------|
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> • Average faucet water temperature: 30 °C (86 °F)³ • Average water inlet temperature: 9.33°C (48.8 °F)⁴ • Average water heater energy factor: 0.76⁵ <p>Annual gas savings calculated as follows:</p> $Savings = W * 8.33 * (T_{out} - T_{in}) * \frac{1}{EF} * 10^{-6} * 27.8$ <p>Where:</p> <p>W = Water savings (gallons) 8.33 = Energy content of water (Btu/gallon/°F) T_{out} = Faucet water temperature (°F) T_{in} = Water inlet temperature (°F) EF = Water heater recovery efficiency 10⁻⁶ = Factor to convert Btu to MMBtu 27.8 = Factor to convert MMBtu to m³</p> <p>Gas savings were determined to be 22% over base case:</p> $Percent\ Savings = \frac{(G_{base} - G_{new})}{G_{base}}$ <p>Where:</p> <p>G_{eff} = Annual natural gas use with efficient equipment, 18 m³ G_{base} = Annual natural gas use with base equipment, 14 m³</p> | |
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 1,382 L |
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> • Average household size: 2.14 persons⁶ • Baseline faucet use (all faucets) per capita per day: 53 litres (14 gallons)⁷ • Bathroom faucet use as a percentage of total faucet use: 15%⁸ • Point estimate of quantity of water that goes straight down the drain: 70%⁹ | |

³ Average of findings in two studies, adjusted for Toronto water inlet temperature. Mayer, P. W. et al, *Residential Indoor Water Conservation Study: Evaluation of High Efficiency Indoor Plumbing Fixture Retrofits in Single-Family Homes in East Bay Municipal Utility District Service Area*, 2003 and Skeel, T. and Hill, S. *Evaluation of Savings from Seattle's "Home Water Saver" Apartment/Condominium Program*, 1994. Both cited in: Summit Blue (2008).

⁴ Cited in the following as personal communication with City of Toronto Works Dept.
VEIC, *Comments on Navigant's Draft Gas Measure Characterizations*, March 2009

⁵ Assumption used by Energy Center of Wisconsin, citing GAMA, www.doa.state.wi.us/docs_view2.asp?docid=2249

⁶ Summit Blue (2008) and Census 2006. To maintain consistency with Summit Blue number but to reflect the fact that apartments are generally occupied by fewer people than houses, the Summit Blue number was degraded by the ratio of the average number of inhabitants per apartment in an Ontario building over five stories (2) to the average number of inhabitants of a fully detached house in Ontario (2.9).

⁷ Ibid.

⁸ DeOreo, W. and P. Mayer, *The End Uses of Hot Water in Single Family Homes from Flow Trace Analysis*, 1999 cited in Summit Blue (2008).

⁹ Summit Blue (2008).

Annual water savings calculated as follows:

$$Savings = Fu * Ppl * 365 * Ba * \left(\frac{Fl_{base} - Fl_{eff}}{Fl_{base}} \right) * Dr$$

Where:

Fu = Faucet use per capita (gallons)
Ppl = Number of people per household
365 = Days per year
Dr = Percentage of water that goes straight down the drain
Ba = Individual bathroom faucet use as a percentage of total faucet use
Fl_{base} = Flow rate of base equipment (GPM)
Fl_{eff} = Flow rate of efficient equipment (GPM)

Water savings was determined to be 22% over base case:

$$PercentSavings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water use with efficient equipment: 4,823 litres (1,274 gallons)
W_{base} = Annual water use with base equipment: 6,205 litres (1,639 gallons)

Other Input Assumptions

| | |
|--|-----------------|
| Effective Useful Life (EUL) | 10 Years |
| The U.S. DOE assumes a 10 year life for faucet aerators ¹⁰ . | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 2 \$ |
| Average equipment cost based on communication with local hardware stores. This does not include installation costs. | |
| Customer Payback Period (Natural Gas Only)¹¹ | 1 Year |
| Using a 5-year average commodity cost (avoided cost) ¹² of \$0.38 / m ³ and an average residential distribution cost ¹³ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 1 year, based on the following: | |
| Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$2/ (4 m ³ /year * \$0.52 / m ³) = 1 year | |

¹⁰ U.S. Department of Energy, Federal Energy Management Program, *FEMP Designated Product: Lavatory Faucets*
http://www1.eere.energy.gov/femp/procurement/eep_faucets.html

¹¹ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹² 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹³ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

| | |
|--|------------|
| Market Penetration | 90% |
| Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of faucet aerators (bathroom and kitchen) across all sectors to be 90% ¹⁴ . | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy ¹⁵ | 5 | 5 | N/A | 50% |
| Comments For a switch from a 2.5 GPM to a 1.8 GPM aerator. Measure saves 1% of 539 m ³ required for water heating. Note that no distinction is made, in this study, between kitchen and bathroom faucet use. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁶ | 27 | 9 | 14 US\$ | 90% |
| Comments For a switch from a 3.0 GPM to a 1.5 GPM aerator. Measure saves 8.5% of 320 m ³ required for water heating. Note that no distinction is made, in this study, between kitchen and bathroom faucet use. Note also that the flow rate reduction in this jurisdiction is more than twice that of the measure addressed by this substantiation sheet. | | | | |

¹⁴ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

¹⁵ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁶ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

55. Faucet Aerator (Multi-Family Kitchen)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Faucet Aerator (kitchen) (1.5 GPM)

Base Equipment and Technologies Description

Average existing stock (2.5 GPM)¹

| Decision Type | Target Market(s) | End Use |
|---------------|-------------------------|---------------|
| Retrofit | Multi-Family (existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)² requires bathroom and kitchen faucets to have a maximum flow of 2.2 GPM (8.35 L/min).

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|---------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 16 | 0 | 5,377 | 2 | 0 |
| 2 | 16 | 0 | 5,377 | 0 | 0 |
| 3 | 16 | 0 | 5,377 | 0 | 0 |
| 4 | 16 | 0 | 5,377 | 0 | 0 |
| 5 | 16 | 0 | 5,377 | 0 | 0 |
| 6 | 16 | 0 | 5,377 | 0 | 0 |
| 7 | 16 | 0 | 5,377 | 0 | 0 |
| 8 | 16 | 0 | 5,377 | 0 | 0 |
| 9 | 16 | 0 | 5,377 | 0 | 0 |
| 10 | 16 | 0 | 5,377 | 0 | 0 |
| TOTALS | 160 | 0 | 53,770 | 2 | 0 |

¹ From on-site audit data. Resource Management Strategies, Inc. *Regional Municipality of York Water Efficiency Master Plan Update*, 2007. Cited in: Summit Blue, *Resource Savings Values in Selected Residential DSM Prescriptive Programs*, June 2008.

² Ontario Regulations 350/06, 2006 Building Code

Resource Savings Assumptions

| Annual Natural Gas Savings | 16 m ³ |
|--|-------------------|
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> • Average faucet water temperature: 30 °C (86 F)³ • Average water inlet temperature: 9.33 °C (48.8 F)⁴ • Average water heater energy factor: 0.76⁵ <p>Annual gas savings calculated as follows:</p> $Savings = W * 8.33 * (T_{out} - T_{in}) * \frac{1}{EF} * 10^{-6} * 27.8$ <p>Where:</p> <p>W = Water savings (gallons) 8.33 = Energy content of water (Btu/gallon/°F) T_{out} = Faucet water temperature (°F) T_{in} = Water inlet temperature (°F) EF = Water heater recovery efficiency 10⁻⁶ = Factor to convert Btu to MMBtu 27.8 = Factor to convert MMBtu to m³</p> <p>Gas savings were determined to be 20% over base case:</p> $Percent\ Savings = \frac{(G_{base} - G_{new})}{G_{base}}$ <p>Where:</p> <p>G_{eff} = Annual natural gas use with efficient equipment, 64 m³ G_{base} = Annual natural gas use with base equipment, 80 m³</p> | |
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 5,377 L |
| <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> • Average household size: 2.14 persons⁶ • Baseline faucet use (all faucets) per capita per day: 53 litres (14 gallons)⁷ | |

³ Average of findings in two studies, adjusted for Toronto water inlet temperature. Mayer, P. W. et al, *Residential Indoor Water Conservation Study: Evaluation of High Efficiency Indoor Plumbing Fixture Retrofits in Single-Family Homes in East Bay Municipal Utility District Service Area*, 2003 and Skeel, T. and Hill, S. *Evaluation of Savings from Seattle's "Home Water Saver" Apartment/Condominium Program*, 1994. Both cited in: Summit Blue (2008).

⁴ Cited in the following as personal communication with City of Toronto Works Dept.
 VEIC, *Comments on Navigant's Draft Gas Measure Characterizations*, March 2009

⁵ Assumption used by Energy Center of Wisconsin, citing GAMA, www.doa.state.wi.us/docs_view2.asp?docid=2249

⁶ Summit Blue (2008) and Census 2006. To maintain consistency with Summit Blue number but to reflect the fact that apartments are generally occupied by fewer people than houses, the Summit Blue number was degraded by the ratio of the average number of inhabitants per apartment in an Ontario building over five stories (2) to the average number of inhabitants of a fully detached house in Ontario (2.9). Statistics Canada. No date. *Structural Type of Dwelling (10) and Household Size (9) for Occupied Private Dwellings of Canada, Provinces, Territories, Census Metropolitan Areas and Census Agglomerations, 2006 Census - 100% Data (Table) Census 2006*. Last updated Dec 6, 2008.

<http://www12.statcan.ca/english/census06/data/topics/RetrieveProductTable.cfm?ALEVEL=3&APATH=3&CATNO=&DETAIL=0&DIM=&DS=99&FL=0&FREE=0&GAL=0&GC=99&GID=837983&GK=NA&GRP=1&IPS=&METH=0&ORDER=1&PID=89071&PTY=88971&RL=0&S=1&SUB=0&ShowAll=No&StartRow=1&Temporal=2006&Theme=69&VID=0&VNAMEE=&VNAMEF=>

⁷ Ibid.

- Kitchen faucet use as a percentage of total faucet use: 65%⁸
- Point estimate of quantity of water that goes straight down the drain: 50%⁹

Annual water savings calculated as follows:

$$Savings = Fu * Ppl * 365 * Ba * \left(\frac{Fl_{base} - Fl_{eff}}{Fl_{base}} \right) * Dr$$

Where:

Fu = Faucet use per capita (gallons)
Ppl = Number of people per household
365 = Days per year
Dr = Percentage of water that goes straight down the drain
Ki = Kitchen faucet use as a percentage of total faucet use
Fl_{base} = Flow rate of base equipment (GPM)
Fl_{eff} = Flow rate of efficient equipment (GPM)

Water savings was determined to be 20% over base case:

$$Percent Savings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water use with efficient equipment: 21,509 litres (5,681 gallons)
W_{base} = Annual water use with base equipment: 26,887 litres (7,101 gallons)

Other Input Assumptions

| | |
|---|------------------|
| Effective Useful Life (EUL) | 10 Years |
| The U.S. DOE assumes a 10 year life for faucet aerators ¹⁰ . | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 2 \$ |
| Average equipment cost based on communication with local hardware stores. This does not include installation costs. | |
| Customer Payback Period (Natural Gas Only)¹¹ | 0.2 Years |
| Using a 5-year average commodity cost (avoided cost) ¹² of \$0.38 / m ³ and an average residential distribution cost ¹³ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 0.2 years, based on the following: | |

⁸ DeOreo, W. and P. Mayer, *The End Uses of Hot Water in Single Family Homes from Flow Trace Analysis*, 1999 cited in Summit Blue (2008).

⁹ Summit Blue (2008).

¹⁰ U.S. Department of Energy, Federal Energy Management Program, *FEMP Designated Product: Lavatory Faucets*
http://www1.eere.energy.gov/femp/procurement/eeep_faucets.html

¹¹ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹² 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

Payback Period = Incremental cost / (natural gas savings x natural gas cost)
 = \$2/ (16 m³/year * \$0.52 / m³)
 = 0.2 years

Market Penetration

90%

Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of faucet aerators (bathroom and kitchen) across all sectors to be 90%¹⁴.

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|--|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Puget Sound Energy ¹⁵ | 5 | 5 | N/A | 50% |
| Comments For a switch from a 2.5 GPM to a 1.8 GPM aerator. Measure saves 1% of 539 m ³ required for water heating. Note that no distinction is made, in this study, between kitchen and bathroom faucet use. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁶ | 27 | 9 | 14 US\$ | 90% |
| Comments For a switch from a 3.0 GPM to a 1.5 GPM aerator. Measure saves 8.5% of 320 m ³ required for water heating. Note that no distinction is made, in this study, between kitchen and bathroom faucet use. Note also that the flow rate reduction in this jurisdiction is more than twice that of the measure addressed by this substantiation sheet. | | | | |

¹³ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁴ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

¹⁵ Quantec *Comprehensive Assessment of Demand-Side Resource Potentials (2008-2027)* Prepared for Puget Sound Energy

¹⁶ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

56. Low-Flow Showerhead (1.5 GPM, Multi-Family, UG ESK, per Household)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Low-flow Showerhead (1.5 GPM) – distributed to participants under Union Gas' ESK program.

Base Equipment and Technologies Description

Average existing stock (2.2 GPM)¹.

| Decision Type | Target Market(s) | End Use |
|---------------|-------------------------|---------------|
| Retrofit | Multi-Family (Existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)² requires shower heads to have a maximum flow of 2.5 GPM (9.5 L/min)

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|---------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 33 | 0 | 5,228 | 6 | 0 |
| 2 | 33 | 0 | 5,228 | 0 | 0 |
| 3 | 33 | 0 | 5,228 | 0 | 0 |
| 4 | 33 | 0 | 5,228 | 0 | 0 |
| 5 | 33 | 0 | 5,228 | 0 | 0 |
| 6 | 33 | 0 | 5,228 | 0 | 0 |
| 7 | 33 | 0 | 5,228 | 0 | 0 |
| 8 | 33 | 0 | 5,228 | 0 | 0 |
| 9 | 33 | 0 | 5,228 | 0 | 0 |
| 10 | 33 | 0 | 5,228 | 0 | 0 |
| TOTALS | 330 | 0 | 52,280 | 6 | 0 |

Resource Savings Assumptions

| Annual Natural Gas Savings | 33 m ³ |
|--|-------------------|
| Enbridge Gas commissioned a study by the SAS Institute (Canada) ³ to estimate natural gas savings for low-flow showerheads using a sample of 69 households in Enbridge territory between August 31 2007 to December 31, 2008. Replacement low-flow showerheads were installed between August 13, 2008 and October 18, 2008. | |

¹ Shower-heads distributed under Union Gas's ESK program are installed by homeowners rather than Union contractors. No observation is made of the base equipment's GPM. It is therefore assumed to be the full-on flow rate corresponding to the as-used flow from York Region monitoring study calculated using the equation cited below.

Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007. Cited by: Summit Blue, *Resource Savings Values in Selected Residential DSM Prescriptive Programs*, June 2008.

² Ontario Regulations 350/06, 2006 Building Code

³ Rothman, Lorne, SAS® Analysis for Enbridge Gas Distribution Incorporated: Estimating the impact of Low Flow Showerhead Installation, March 16, 2009

The study used two classes of statistical method for estimating savings (1) Paired T-tests and (2) Longitudinal Mixed models.

1. Three iterations of the paired t-test method were estimated and of these, the report recommends the one which makes use of the entire data-set. This model yielded savings estimates of an average of 0.24 m³/day, for an extrapolated annual savings of 89 m³.
2. Two longitudinal mixed models were also estimated, one relatively simple linear model controlling for a variety of household factors, the other still linear, but with more parameters to be estimated (all additional parameters being the products of two previously estimated parameters) in order to study interaction effects. This model yielded savings estimates of an average of 0.18 m³/day for pre-existing showerhead flow rates of 2.0 to 2.5 GPM and 0.32 m³/day for pre-existing showerhead flow rates greater than 2.5 GPM. Extrapolation of these results for annual savings is approximately 66 m³ and 116 m³, respectively

Navigant Consulting agrees with the report which recommends the simpler of the longitudinal mixed to be used for planning purposes, since it is the more robust of the two analyses. Therefore, the natural gas savings are estimated to be as follows:

| Baseline Flow rate (GPM) | Energy Efficient Flow Rate (GPM) | Change in GPM | Annual Natural Gas Savings (m3) | Annual Natural Gas Savings (m3 per GPM) |
|--------------------------|----------------------------------|---------------|---------------------------------|---|
| 2.25 ⁴ | 1.25 | 1.0 | 66 | 66 |
| 3 ⁵ | 1.25 | 1.75 | 116 | 66 |

Therefore, using an average baseline flow rate of 2.2 GPM and Union Gas' low flow showerhead of 1.5 GPM, the natural gas savings are estimated to be (2.2 – 1.5 GPM) x 66 m³/GPM = 46 m³.

However, to reflect the fact that there are fewer occupants in apartments than in single family homes (average of 2.1 persons for apartments vs 2.9 persons for fully detached homes)⁶, Navigant has adjusted the savings as follows:

$$46 \text{ m}^3 \times (2.1 \text{ persons per household} / 2.9 \text{ persons per household}) = 46 \times 72\% = 33 \text{ m}^3$$

It should be noted that the period of the sample in which the effects of the new showerheads might be observed is relatively short (e.g, between 74 days and 141 days, or roughly 15%-30% of the sample period). The report acknowledges this and recommends that the analysis be repeated when one year of post-installation data is available. Navigant agrees with the recommendation that a deemed saving for this measure be re-appraised when more post-installation data becomes available.

Annual Electricity Savings

0 kWh

N/A

Annual Water Savings

5,228 L

Since the SAS report did not look at water savings, Navigant Consulting proposes the following method for calculating resulting water savings:

⁴ Average of 2.0 GPM and 2.5 GPM

⁵ Assumed average low flow showerhead which is greater than 2.5 GPM.

⁶ Statistics Canada. *Structural Type of Dwelling (10) and Household Size (9) for Occupied Private Dwellings of Canada, Provinces, Territories, Census Metropolitan Areas and Census Agglomerations, 2006 Census - 100% Data (Table) Census 2006*. Last updated Dec 6, 2008.

<http://www12.statcan.ca/english/census06/data/topics/RetrieveProductTable.cfm?ALEVEL=3&APATH=3&CATNO=&DETAIL=0&DI M=&DS=99&FL=0&FREE=0&GAL=0&GC=99&GID=837983&GK=NA&GRP=1&IPS=&METH=0&ORDER=1&PID=89071&PTYPE =88971&RL=0&S=1&SUB=0&ShowAll=No&StartRow=1&Temporal=2006&Theme=69&VID=0&VNAMEE=&VNAMEF=>

Assumptions and inputs:

- As-used flow rate with base equipment: 1.89 GPM⁷
- Average household size: 2.14 persons⁸
- Showers per capita per day: 0.75⁹
- Proportion of showering affected by measure (i.e. percentage of the time the low-flow showerhead used) : 92%¹⁰
- Average showering time per capita per day with base equipment: 7.32 minutes
- Average showering time per capita per day with new technology: 7.5 minutes¹¹

Annual water savings calculated as follows:

$$Savings = Ppl * Sh * 365 * (T_{base} * Fl_{base} - T_{eff} * Fl_{eff})$$

Where:

Ppl = Number of people per household

Sh = Showers per capita per day

365 = Days per year

T_{base} = Showering time with base equipment (minutes)

T_{eff} = Showering time with efficient equipment (minutes)

Fl_{base} = As-used flow rate with base equipment (GPM)

Fl_{eff} = As-used flow rate with efficient equipment (GPM)

Pr = Percentage of showers where efficient equipment used

Water savings were determined to be 17% over base technology:

$$PercentSavings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water consumed by showers with efficient equipment, 25,382 litres (6,704 gallons)

W_{base} = Annual water consumed by showers with base equipment: 30,671 litres (8,101 gallons)

⁷ As-used flow is calculated as a function of "full-on" or label flow: as-used flow = min{ 0.691+0.542*full-on flow, full-on flow}. Proctor, J. Gavelis, B. and Miller, B. *Savings and Showers: It's All in the Head*, (PGE) Home Energy Magazine, July/Aug 1994. Cited in Summit Blue (2008). Summit Blue uses the equation without assuming that it is a min function, implicitly assuming that participants will have the expertise or desire to make minor adjustments to the house water pressure to compensate for reduced shower flow.

⁸ To maintain consistency with Summit Blue number but to reflect the fact that apartments are generally occupied by fewer people than houses, the Summit Blue number was degraded by the ratio of the average number of inhabitants per apartment in an Ontario building over five stories (2) to the average number of inhabitants of a fully detached house in Ontario (2.9). Statistics Canada. No date. *Structural Type of Dwelling (10) and Household Size (9) for Occupied Private Dwellings of Canada, Provinces, Territories, Census Metropolitan Areas and Census Agglomerations, 2006 Census - 100% Data (Table) Census 2006*. Last updated Dec 6, 2008.

<http://www12.statcan.ca/english/census06/data/topics/RetrieveProductTable.cfm?ALEVEL=3&APATH=3&CATNO=&DETAIL=0&DIM=&DS=99&FL=0&FREE=0&GAL=0&GC=99&GID=837983&GK=NA&GRP=1&IPS=&METH=0&ORDER=1&PID=89071&PTYPE=88971&RL=0&S=1&SUB=0&ShowAll=No&StartRow=1&Temporal=2006&Theme=69&VID=0&VNAMEF=&VNAMEF=>

⁹ Ibid, based on data from: Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007

¹⁰ Survey of participants, 116 from Enbridge, 111 from Union, Summit Blue (2008)

¹¹ Relationship modeled as: Average shower length = 8.17 – 0.448 * as-used GPM. From Energy Center of Wisconsin Analysis of data from Resource Management Strategies, Inc., *Regional Municipality of York Water Efficiency Master Plan Update*, April 2007. Cited in Summit Blue (2008)

Other Input Assumptions

| | |
|---|------------------|
| Effective Useful Life (EUL) | 10 Years |
| Summit Blue (2008) suggests an EUL of 10 years based on a survey of five studies of showerheads in other jurisdictions (California – two studies, New England, Vermont, Arkansas). | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 6\$ |
| Incremental cost based on a survey of online retailers ¹² . This does not include installation costs | |
| Customer Payback Period (Natural Gas Only)¹³ | 0.3 Years |
| Using a 5-year average commodity cost (avoided cost) ¹⁴ of \$0.38 / m ³ and an average residential distribution cost ¹⁵ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 0.3 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$6/ (33 m ³ /year * \$0.52 / m ³) = 0.3 years | |
| Market Penetration | 65% |
| Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of low-flow showerheads of all flow rates across all sectors to be 65% ¹⁶ . | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Flex Your Power ¹⁷ | 72 | 10 | N/A | N/A |
| Comments Based on switching from a 2.2 GPM to a 1.5 GPM showerhead. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁸ | 48 | 10 | US\$ 36 | 75% |
| Comments Based on switching from a 4 GPM to a 2.5 GPM showerhead. Measure saves 15% of 320 m ³ required for water heating. | | | | |

¹² Whedon Products 1.5 GPM Ultra Saver Showerhead. http://www.antonline.com/p_USB3C-GP_398829.htm

¹³ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹⁴ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁵ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁶ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

¹⁷ http://www.fypower.org/res/tools/products_results.html?id=100160

¹⁸ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

57. Low-Flow Showerhead (1.25 GPM, Multi-Family, UG ESK, per Household)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Low-flow Showerhead (1.25 Gpm) – distributed to participants under Union Gas' ESK program.

Base Equipment and Technologies Description

Average existing stock (2.2 GPM)¹.

| Decision Type | Target Market(s) | End Use |
|---------------|-------------------------|---------------|
| Retrofit | Multi-Family (Existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)² requires shower heads to have a maximum flow of 2.5 GPM (9.5 L/min)

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|---------------|---|---|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | 45 | 0 | 8,824 | 13 | 0 |
| 2 | 45 | 0 | 8,824 | 0 | 0 |
| 3 | 45 | 0 | 8,824 | 0 | 0 |
| 4 | 45 | 0 | 8,824 | 0 | 0 |
| 5 | 45 | 0 | 8,824 | 0 | 0 |
| 6 | 45 | 0 | 8,824 | 0 | 0 |
| 7 | 45 | 0 | 8,824 | 0 | 0 |
| 8 | 45 | 0 | 8,824 | 0 | 0 |
| 9 | 45 | 0 | 8,824 | 0 | 0 |
| 10 | 45 | 0 | 8,824 | 0 | 0 |
| TOTALS | 450 | 0 | 88,240 | 13 | 0 |

Resource Savings Assumptions

| Annual Natural Gas Savings | 45 m ³ |
|--|-------------------|
| Enbridge Gas commissioned a study by the SAS Institute (Canada) ³ to estimate natural gas savings for low-flow showerheads using a sample of 69 households in Enbridge territory between August 31 2007 to December 31, 2008. Replacement low-flow showerheads were installed between August 13, 2008 and October 18, 2008. | |

¹ Shower-heads distributed under Union Gas's ESK program are installed by homeowners rather than Union contractors. No observation is made of the base equipment's GPM. It is therefore assumed to be the full-on flow rate corresponding to the as-used flow from York Region monitoring study calculated using the equation cited below. Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007. Cited by: Summit Blue, *Resource Savings Values in Selected Residential DSM Prescriptive Programs*, June 2008.

² Ontario Regulations 350/06, 2006 Building Code

³ Rothman, Lorne, SAS® Analysis for Enbridge Gas Distribution Incorporated: Estimating the impact of Low Flow Showerhead Installation, March 16, 2009

The study used two classes of statistical method for estimating savings (1) Paired T-tests and (2) Longitudinal Mixed models.

1. Three iterations of the paired t-test method were estimated and of these, the report recommends the one which makes use of the entire data-set. This model yielded savings estimates of an average of 0.24 m³/day, for an extrapolated annual savings of 89 m³.
2. Two longitudinal mixed models were also estimated, one relatively simple linear model controlling for a variety of household factors, the other still linear, but with more parameters to be estimated (all additional parameters being the products of two previously estimated parameters) in order to study interaction effects. This model yielded savings estimates of an average of 0.18 m³/day for pre-existing showerhead flow rates of 2.0 to 2.5 GPM and 0.32 m³/day for pre-existing showerhead flow rates greater than 2.5 GPM. Extrapolation of these results for annual savings is approximately 66 m³ and 116 m³, respectively

Navigant Consulting agrees with the report which recommends the simpler of the longitudinal mixed to be used for planning purposes, since it is the more robust of the two analyses. Therefore, the natural gas savings are estimated to be as follows:

| Baseline Flow rate (GPM) | Energy Efficient Flow Rate (GPM) | Change in GPM | Annual Natural Gas Savings (m ³) | Annual Natural Gas Savings (m ³ per GPM) |
|--------------------------|----------------------------------|---------------|--|---|
| 2.25 ⁴ | 1.25 | 1.0 | 66 | 66 |
| 3 ⁵ | 1.25 | 1.75 | 116 | 66 |

Therefore, using an average baseline flow rate of 2.2 GPM and Union Gas' low flow showerhead of 1.5 GPM, the natural gas savings are estimated to be (2.2 – 1.25 GPM) x 66 m³/GPM = 63 m³.

However, to reflect the fact that there are fewer occupants in apartments than in single family homes (average of 2.1 persons for apartments vs 2.9 persons for fully detached homes)⁶, Navigant has adjusted the savings as follows:

$$63 \text{ m}^3 \times (2.1 \text{ persons per household} / 2.9 \text{ persons per household}) = 63 \times 72\% = 45 \text{ m}^3$$

It should be noted that the period of the sample in which the effects of the new showerheads might be observed is relatively short (e.g, between 74 days and 141 days, or roughly 15%-30% of the sample period). The report acknowledge this and recommend that the analysis be repeated when one year of post-installation data is available. Navigant agrees with the recommendation that a deemed saving for this measure be re-appraised when more post-installation data becomes available.

| | |
|--|-----------------|
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | 78,824 L |
| Since the SAS report did not look at water savings, Navigant Consulting proposes the following | |

⁴ Average of 2.0 GPM and 2.5 GPM

⁵ Assumed average low flow showerhead which is greater than 2.5 GPM.

⁶ Statistics Canada. *Structural Type of Dwelling (10) and Household Size (9) for Occupied Private Dwellings of Canada, Provinces, Territories, Census Metropolitan Areas and Census Agglomerations, 2006 Census - 100% Data (Table) Census 2006*. Last updated Dec 6, 2008.
<http://www12.statcan.ca/english/census06/data/topics/RetrieveProductTable.cfm?ALEVEL=3&APATH=3&CATNO=&DETAIL=0&DIM=&DS=99&FL=0&FREE=0&GAL=0&GC=99&GID=837983&GK=NA&GRP=1&IPS=&METH=0&ORDER=1&PID=89071&PTYPE=88971&RL=0&S=1&SUB=0&ShowAll=No&StartRow=1&Temporal=2006&Theme=69&VID=0&VNAME=&VNAMEF=>

method for calculating resulting water savings:

Assumptions and inputs:

- As-used flow rate with base equipment: 1.89 GPM⁷
- Average household size: 2.14 persons⁸
- Showers per capita per day: 0.75⁹
- Proportion of showering affected by measure (i.e. percentage of the time the low-flow showerhead used) : 792%¹⁰
- Average showering time per capita per day with base equipment: 7.32 minutes
- Average showering time per capita per day with new technology: 7.61 minutes¹¹

Annual water savings calculated as follows:

$$Savings = Ppl * Sh * 365 * Pr * (T_{base} * Fl_{base} - T_{eff} * Fl_{eff})$$

Where:

Ppl = Number of people per household.

Sh = Showers per capita per day.

365 = Days per year.

T_{base} = Showering time with base equipment (minutes)

T_{eff} = Showering time with efficient equipment (minutes).

Fl_{base} = As-used flow rate with base equipment (GPM)

Fl_{eff} = As-used flow rate with efficient equipment (GPM)

Pr = Percentage of showers where efficient equipment used.

Water savings were determined to be 29% over base equipment:

$$PercentSavings = \frac{(W_{base} - W_{eff})}{W_{base}}$$

Where:

W_{eff} = Annual water consumed by showers with efficient equipment, 21,846 litres (5,770 gallons).

W_{base} = Annual water consumed by showers with base equipment: 30,671 litres (8,101 gallons).

⁷ As-used flow is calculated as a function of "full-on" or label flow: as-used flow = min{ 0.691+0.542*full-on flow, full-on flow}. Proctor, J. Gavelis, B. and Miller, B. *Savings and Showers: It's All in the Head*, (PGE) Home Energy Magazine, July/Aug 1994. Cited in Summit Blue (2008). Summit Blue uses the equation without assuming that it is a min function, implicitly assuming that participants will have the expertise or desire to make minor adjustments to the house water pressure to compensate for reduced shower flow.

⁸ To maintain consistency with Summit Blue number but to reflect the fact that apartments are generally occupied by fewer people than houses, the Summit Blue number was degraded by the ratio of the average number of inhabitants per apartment in an Ontario building over five stories (2) to the average number of inhabitants of a fully detached house in Ontario (2.9). Statistics Canada. No date. *Structural Type of Dwelling (10) and Household Size (9) for Occupied Private Dwellings of Canada, Provinces, Territories, Census Metropolitan Areas and Census Agglomerations, 2006 Census - 100% Data (Table) Census 2006*. Last updated Dec 6, 2008.

<http://www12.statcan.ca/english/census06/data/topics/RetrieveProductTable.cfm?ALEVEL=3&APATH=3&CATNO=&DETAIL=0&DIM=&DS=99&FL=0&FREE=0&GAL=0&GC=99&GID=837983&GK=NA&GRP=1&IPS=&METH=0&ORDER=1&PID=89071&PTYPE=88971&RL=0&S=1&SUB=0&ShowAll=No&StartRow=1&Temporal=2006&Theme=69&VID=0&VNAMEE=&VNAMEF=>

⁹ Ibid, based on data from: Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007

¹⁰ Survey of participants, 116 from Enbridge, 111 from Union, Summit Blue (2008)

¹¹ Relationship modeled as: Average shower length = 8.17 – 0.448 * as-used GPM. From Energy Center of Wisconsin Analysis of data from Resource Management Strategies, Inc., *Regional Municipality of York Water Efficiency Master Plan Update*, April 2007. Cited in Summit Blue (2008)

Other Input Assumptions

| | |
|--|------------------|
| Effective Useful Life (EUL) | 10 Years |
| Summit Blue (2008) suggests an EUL of 10 years based on a survey of five studies of showerheads in other jurisdictions (California – two studies, New England, Vermont, Arkansas). | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 13\$ |
| Incremental cost based on a survey of online retailers ¹² . | |
| Customer Payback Period (Natural Gas Only)¹³ | 0.6 Years |
| Using a 5-year average commodity cost (avoided cost) ¹⁴ of \$0.38 / m ³ and an average residential distribution cost ¹⁵ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 0.6 years, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) = \$13/ (45 m ³ /year * \$0.52 / m ³) = 0.6 years | |
| Market Penetration | 65% |
| Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of low-flow showerheads of all flow rates across all sectors to be 65% ¹⁶ . | |

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/ Market Share |
|--|---------------------------------|-------------------------------|-----------------------|---------------------------|
| U. S. Dept. of Energy, Federal Energy Management Program ¹⁷ | 108 | 10 | N/A | N/A |
| Comments Based on switching from a 2.2 GPM to a 1.5 GPM showerhead. Assumptions include: 10mins per shower, 2 showers per day, shower temperature of 106F, inlet water temp of 58F. Measure provides savings of 81% over 133 m ³ required for heating water used with base equipment. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/ Market Share |
| State of Iowa Utilities Board ¹⁸ | 48 | 10 | US\$ 36 | 75% |
| Comments Based on switching from a 4 GPM to a 2.5 GPM showerhead. Measure saves 15% of 320 m ³ required for water heating. | | | | |

¹² Earth Massage Showerhead 1.25 GPM http://cgi.ebay.com/Earth-Massage-Showerhead-Water-Saver-1-25-gpm-flow_W0QQitemZ130256063752QQihZ003QQcategoryZ71282QQcmdZViewItemQQ_trksidZp1742.m153.l1262

¹³ Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹⁴ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁵ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁶ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

¹⁷ U.S Department of Energy, Federal Energy Management Program, *FEMP Designated Product: Showerheads* http://www1.eere.energy.gov/femp/procurement/eeep_showerhead.html

¹⁸ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2

58. Low-Flow Showerhead (1.25 GPM, Multi-Family, Enbridge TAPS, per Household)

| Revision # | Description/Comment | Date Revised |
|------------|---------------------|--------------|
| | | |

Efficient Equipment and Technologies Description

Low-flow Showerhead (1.25 GPM) – Installed by Enbridge-designated contractors.

Base Equipment and Technologies Description

Average existing stock within one of three ranges.

Range mid-points used as point estimates:

- Scenario A – 2.25 GPM
- Scenario B – 3.0 GPM

When new showerheads are installed contractors use a bag-test to determine base equipment flow-rate.

| Decision Type | Target Market(s) | End Use |
|---------------|-------------------------|---------------|
| Retrofit | Multi-Family (Existing) | Water heating |

Codes, Standards, and Regulations

Ontario Building Code (2006)¹ requires shower heads to have a maximum flow of 2.5 GPM (9.5 L/min)

Resource Savings Table

| Year (EUL=) | Electricity and Other Resource Savings | | | Equipment & O&M Costs of Conservation Measure (\$) | Equipment & O&M Costs of Base Measure (\$) |
|-----------------|--|----------------------|-------------------------|---|--|
| | Natural Gas (m ³) | Electricity (kWh) | Water (L) | | |
| 1 | A: 48 B: 84 | 0 | A: 9,088 B: 14,333 | 13 | 0 |
| 2 | A: 48 B: 84 | 0 | A: 9,088 B: 14,333 | 0 | 0 |
| 3 | A: 48 B: 84 | 0 | A: 9,088 B: 14,333 | 0 | 0 |
| 4 | A: 48 B: 84 | 0 | A: 9,088 B: 14,333 | 0 | 0 |
| 5 | A: 48 B: 84 | 0 | A: 9,088 B: 14,333 | 0 | 0 |
| 6 | A: 48 B: 84 | 0 | A: 9,088 B: 14,333 | 0 | 0 |
| 7 | A: 48 B: 84 | 0 | A: 9,088 B: 14,333 | 0 | 0 |
| 8 | A: 48 B: 84 | 0 | A: 9,088 B: 14,333 | 0 | 0 |
| 9 | A: 48 B: 84 | 0 | A: 9,088 B: 14,333 | 0 | 0 |
| 10 | A: 48 B: 84 | 0 | A: 9,088 B: 14,333 | 0 | 0 |
| TOTALS | A: 480 B: 840 C: 600 | 0 | A: 90,880 B: 143,330 | 13 | 0 |

¹ Ontario Regulations 350/06, 2006 Building Code

Resource Savings Assumptions

Annual Natural Gas Savings

A: 48 m³
B: 84 m³

Enbridge Gas commissioned a study by the SAS Institute (Canada)² to estimate natural gas savings for low-flow showerheads using a sample of 69 households in Enbridge territory between August 31 2007 to December 31, 2008. Replacement low-flow showerheads were installed between August 13, 2008 and October 18, 2008.

The study used two classes of statistical method for estimating savings (1) Paired T-tests and (2) Longitudinal Mixed models.

1. Three iterations of the paired t-test method were estimated and of these, the report recommends the one which makes use of the entire data-set. This model yielded savings estimates of an average of 0.24 m³/day, for an extrapolated annual savings of 89 m³.
2. Two longitudinal mixed models were also estimated, one relatively simple linear model controlling for a variety of household factors, the other still linear, but with more parameters to be estimated (all additional parameters being the products of two previously estimated parameters) in order to study interaction effects. This model yielded savings estimates of an average of 0.18 m³/day for pre-existing showerhead flow rates of 2.0 to 2.5 GPM and 0.32 m³/day for pre-existing showerhead flow rates greater than 2.5 GPM. Extrapolation of these results for annual savings is approximately 66 m³ and 116 m³, respectively

Navigant Consulting agrees with the report which recommends the simpler of the longitudinal mixed to be used for planning purposes, since it is the more robust of the two analyses. Therefore, the natural gas savings are estimated to be as follows:

| Baseline Flow rate (GPM) | Energy Efficient Flow Rate (GPM) | Change in GPM | Annual Natural Gas Savings (m3) | Annual Natural Gas Savings (m3 per GPM) |
|--------------------------|----------------------------------|---------------|---------------------------------|---|
| 2.25 ³ | 1.25 | 1.0 | 66 | 66 |
| 3 ⁴ | 1.25 | 1.75 | 116 | 66 |

However, to reflect the fact that there are fewer occupants in apartments than in single family homes (average of 2.1 persons for apartments vs 2.9 persons for fully detached homes)⁵, Navigant has adjusted the savings as follows:

Scenario A: 66 m³ x (2.1 persons per household/2.9 persons per household) = 66 x 72% = 48 m³

Scenario B: 116 m³ x (2.1 persons per household/2.9 persons per household) = 116 x 72% = 84 m³

It should be noted that the period of the sample in which the effects of the new showerheads might be observed is relatively short (e.g, between 74 days and 141 days, or roughly 15%-30% of the sample period). The report acknowledge this and recommend that the analysis be repeated when one year of post-installation data is available. Navigant agrees with the recommendation that a deemed saving for this measure be re-appraised when more post-installation data becomes available.

² Rothman, Lorne, SAS® Analysis for Enbridge Gas Distribution Incorporated: Estimating the impact of Low Flow Showerhead Installation, March 16, 2009

³ Average of 2.0 GPM and 2.5 GPM

⁴ Assumed average low flow showerhead which is greater than 2.5 GPM.

⁵ Statistics Canada. *Structural Type of Dwelling (10) and Household Size (9) for Occupied Private Dwellings of Canada, Provinces, Territories, Census Metropolitan Areas and Census Agglomerations, 2006 Census - 100% Data (Table) Census 2006*. Last updated Dec 6, 2008.

<http://www12.statcan.ca/english/census06/data/topics/RetrieveProductTable.cfm?ALEVEL=3&APATH=3&CATNO=&DETAIL=0&DIM=&DS=99&FL=0&FREE=0&GAL=0&GC=99&GID=837983&GK=NA&GRP=1&IPS=&METH=0&ORDER=1&PID=89071&PTYPE=88971&RL=0&S=1&SUB=0&ShowAll=No&StartRow=1&Temporal=2006&Theme=69&VID=0&VNAME=&VNAMEF=>

| | |
|---|-----------------------------------|
| Annual Electricity Savings | 0 kWh |
| N/A | |
| Annual Water Savings | B: 9,088 L C: 14,333 L |
| <p>Since the SAS report did not look at water savings, Navigant Consulting proposes the following method for calculating resulting water savings:</p> <p>Assumptions and inputs:</p> <ul style="list-style-type: none"> As-used flow rate with base equipment⁶: Scenario A: 1.91 GPM Scenario B: 2.32 GPM Average household size: 2.14 persons⁷ Showers per capita per day: 0.75⁸ Proportion of showering affected by measure (i.e. percentage of the time the low-flow showerhead used): 92%⁹ Average showering time per capita per day with base equipment: Scenario A: 7.31 minutes Scenario B: 7.13 minutes Average showering time per capita per day with new technology: 7.61 minutes¹⁰ <p>Annual water savings calculated as follows:</p> $Savings = Ppl * Sh * 365 * Pr * (T_{base} * Fl_{base} - T_{eff} * Fl_{eff})$ <p>Where:</p> <p>Ppl = Number of people per household. Sh = Showers per capita per day. 365 = Days per year. T_{base} = Showering time with base equipment (minutes) T_{eff} = Showering time with efficient equipment (minutes). Fl_{base} = As-used flow rate with base equipment (GPM) Fl_{eff} = As-used flow rate with efficient equipment (GPM) Pr = Percentage of showers where efficient equipment used.</p> <p>Scenario A: Water savings were determined to be 29% over base equipment Scenario B: Water savings were determined to be 39% over base equipment</p> | |

⁶ As-used flow is calculated as a function of "full-on" or label flow: as-used flow = min{ 0.691+0.542*full-on flow, full-on flow } Proctor, J. Gavelis, B. and Miller, B. *Savings and Showers: It's All in the Head*, (PGE) Home Energy Magazine, July/Aug 1994. Cited in Summit Blue (2008).

⁷ To maintain consistency with Summit Blue number but to reflect the fact that apartments are generally occupied by fewer people than houses, the Summit Blue number was degraded by the ratio of the average number of inhabitants per apartment in an Ontario building over five stories (2) to the average number of inhabitants of a fully detached house in Ontario (2.9). Statistics Canada. No date. *Structural Type of Dwelling (10) and Household Size (9) for Occupied Private Dwellings of Canada, Provinces, Territories, Census Metropolitan Areas and Census Agglomerations, 2006 Census - 100% Data (Table) Census 2006*. Last updated Dec 6, 2008.

<http://www12.statcan.ca/english/census06/data/topics/RetrieveProductTable.cfm?ALEVEL=3&APATH=3&CATNO=&DETAIL=0&DIM=&DS=99&FL=0&FREE=0&GAL=0&GC=99&GID=837983&GK=NA&GRP=1&IPS=&METH=0&ORDER=1&PID=89071&PTYPE=88971&RL=0&S=1&SUB=0&ShowAll=No&StartRow=1&Temporal=2006&Theme=69&VID=0&VNAMEE=&VNAMEF=>

⁸ Ibid, based on data from: Resource Management Strategies, Inc., Regional Municipality of York Water Efficiency Master Plan Update, April 2007

⁹ Survey of participants, 116 from Enbridge, 111 from Union, Summit Blue (2008)

¹⁰ Relationship modeled as: Average shower length = 8.17 – 0.448 * as-used GPM. From Energy Center of Wisconsin Analysis of data from Resource Management Strategies, Inc., *Regional Municipality of York Water Efficiency Master Plan Update*, April 2007. Cited in Summit Blue (2008)

$$\text{Percent Savings} = \frac{(W_{\text{base}} - W_{\text{eff}})}{W_{\text{base}}}$$

Where:

W_{eff} = Annual water consumed by showers with efficient equipment,
Scenario **A**: 21,869 litres (5,776 gallons)

Scenario **B**: 22,325 litres (5,896 gallons)

W_{base} = Annual water consumed by showers with base equipment:

Scenario **A**: 30,957 litres (8,176 gallons)

Scenario **B**: 36,658 litres (9,682 gallons)

Other Input Assumptions

| | |
|---|--------------------------------------|
| Effective Useful Life (EUL) | 10 Years |
| Summit Blue (2008) suggests an EUL of 10 years based on a survey of five studies of showerheads in other jurisdictions (California – two studies, New England, Vermont, Arkansas). | |
| Base & Incremental Conservation Measure Equipment and O&M Costs | 13\$ |
| Incremental cost based on a survey of online retailers ¹¹ . This does not include the cost of installation | |
| Customer Payback Period (Natural Gas Only)¹² | A: 0.5 Years B: 0.4 Years |
| Using an 5-year average commodity cost (avoided cost) ¹³ of \$0.38 / m ³ and an average residential distribution cost ¹⁴ of \$0.14 / m ³ , the payback period for natural gas savings is determined to be 0.5 years for Scenario A, and 0.4 years for Scenario B, based on the following: Payback Period = Incremental cost / (natural gas savings x natural gas cost) Scenario A = \$13/ (48 m ³ /year * \$0.52 / m ³) = 0.5 years Scenario B = \$13/ (84 m ³ /year * \$0.52 / m ³) = 0.3 years | |
| Market Penetration | 65% |
| Based on previous research conducted for the OPA, Navigant Consulting estimates penetration of low-flow showerheads of all flow rates across all sectors to be 65% ¹⁵ . | |

¹¹ Earth Massage Showerhead 1.25 GPM http://cgi.ebay.com/Earth-Massage-Showerhead-Water-Saver-1-25-gpm-flow_W0QQitemZ130256063752QQihZ003QQcategoryZ71282QQcmdZViewItemQQ_trksidZp1742.m153.l1262

¹² Customer payback period has been calculated using natural gas savings only. Where applicable, payback period is expected to decrease when electricity and/or water savings are included.

¹³ 2009 Avoided gas cost provided by Union Gas. 5 year average avoided gas cost determined by taking average for baseload and weather sensitive avoided gas cost.

¹⁴ Average distribution cost taken calculated from both Union Gas website (<http://www.uniongas.com/residential/rates/>) and Enbridge Gas websites (<https://portal-plumprod.cgc.enbridge.com/portal/server.pt?open=512&objID=248&PageID=0&cached=true&mode=2&userID=2>).

¹⁵ Navigant Consulting, Inc. for the Ontario Power Authority, *Residential Rebate Program: Participation Forecast and Incentive Bundling Strategy – Key Findings Summary*, December 2008

Measure Assumptions Used by Other Jurisdictions

| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
|---|---------------------------------|-------------------------------|-----------------------|--------------------------|
| Flex Your Power ¹⁶ | 72 | 10 | N/A | N/A |
| Comments Based on switching from a 2.2 GPM to a 1.5 GPM showerhead. | | | | |
| Source | Annual Natural Gas Savings (m3) | Effective Useful Life (Years) | Incremental Cost (\$) | Penetration/Market Share |
| State of Iowa Utilities Board ¹⁷ | 48 | 10 | US\$ 36 | 65% |
| Comments Based on switching from a 4 GPM to a 2.5 GPM showerhead. Measure saves 15% of 320 m ³ required for water heating. | | | | |

¹⁶ http://www.fypower.org/res/tools/products_results.html?id=100160

¹⁷ Iowa Utilities Board. Docket No. EEP-08-02 MidAmerican Energy Company. Volume IV, Appendix D, Part 1 of 2