USL Load Data Study

February to May 2006

Background

This report documents a load study performed for various types of unmetered scattered loads (USL), involving a number of local distribution companies (LDC) in Ontario. The study was conducted to determine a load profile for the different types of USLs. The results of the study were then analyzed to determine if any suitable conclusions could be drawn and used in the OEB cost allocation model.

Because USL is by definition unmetered, prior to this study no data had been available as to the load shape of any type of USL. USL connections controlled by a photo sensor could be estimated as to load shape with some degree of confidence by reference to the daylight hours through the year. USL connections which are not photo sensor controlled were not well understood as to their load shape by the LDCs. Various estimation approaches are being used by different Ontario LDCs to estimate the monthly energy consumption of USL connections.

As part of the Ontario Energy Board's Cost Allocation Review process, a technical advisory group was asked to examine the issue of whether USL should be a separate class and if so, what rate structure is appropriate. In order to analyze USL as a separate customer class, load and load shape data specific to the class are required.

It was agreed among the participants, including representatives of customer groups that an attempt would be made to gather load shape data over a short period, and to develop an approach that would enable that data to be translated into a demand allocator for the cost allocation model with some degree of confidence.

Participation

All LDCs were asked if they would be interested in participating in the study. Over twenty-five LDCs indicated an interest. Fifteen agreed to install interval meters or electronic recording ammeters (ERA). In the end, only ten LDCs were able to provide readings. Results were obtained for:

- 55 cable TV power supplies (due to data limitation, 32 cables were used in the final analysis)
- 2 telephone booths
- 4 pipeline cathodic protection devices
- 3 billboards

The duration of the collected data ranged from one day to three months.

Rogers' Cable Communication Inc. (RCCI) provided detailed information on its equipment, its usage, and battery heater mats.

Collected Data

All gathered data has been forwarded to the Load Research group at Hydro One Networks Inc. (HONI) for analysis. During the collection process meetings were held between HONI Load Research staff, LDC representatives and RCCI to work through collection issues and initial interpretation of results.

The data files and results are held by HONI Load Research.

Initial Observations

Development of values for demand allocators (1 NCP, 4 NCP, 12 NCP, 1 CP, etc.) would require estimated load shapes for each type of USL, and an estimate of the total consumption which could then be allocated over the hours in the year according to the load shape. It is intended that the generic load shapes be developed by Hydro One, and then applied to an estimate of consumption data provided by the LDCs for each type of USL.

The following section discusses the issues with regard to development of both the load shape and consumption estimate for each of the major types of USL.

Cable TV Power Supplies

The load shape for cable TV USL connections includes the load shape for the power supply itself and the load shape of battery mats, if installed. Battery mats are not present in the service territory of all LDCs, and in LDCs where they are present, they are not present at all cable TV power supply connections. The basic power supply and the battery mat(s) where present can thus be regarded as separate components in terms of their consumption and load shape. Once a load level and load shape are established for the power supplies themselves, a load shape for the battery mat would be built on top to create the total load and load shape for cable TV USL connections in each LDC.

Where battery mats are not used in the LDC, only the basic power supply load shape would be needed. Battery mats were not in place anywhere in Ontario in 2004, which is the test year for 2006 rates for most LDCs. It was agreed by the working group that no LDC with a 2004 test year will therefore consider battery mats in its USL load shape for these informational filings. For those small numbers of LDCs using a 2006 test year and with battery mats in their service

territories, a load shape will be constructed based on operating data supplied by the cable company, and normalized for weather. The battery heater mat usage would be agreed upon by the LDC and the cable TV company, and estimated separately as part of the load data analysis. The battery heater mat usage is small in comparison to the amplifier annual usage, with many (if not most) LDCs having no battery heater mats in their service areas.

For determination of the demand allocator for the basic power supplies, the following options were considered as to the magnitude of the load:

Option 1 - Profile based on a percentage of the nameplate rating of the power supply.

Option 2 - Profile based on a percentage of the current kWh consumption estimate used by the LDC

Option 2 is the information that each LDC is currently using for billing purposes. It is recognized that the kWh being used for billing purposes is estimated, and that there are a variety of estimation approaches being applied in different LDCs.

Other USL Loads

Billboards – Since they have photosensitive devices, their usage should closely track the daylight hours with a load shape similar to the existing deemed streetlight profile.

Cathodic protection devices – The usage might vary by location, but the hourly profile should be relatively flat.

Telephone Booths (non-photosensitive) – The usage should be relatively flat.

Findings

Cable TV Power Supplies

- Based on monitored data, the cable loads are very flat (see Appendix A);
- Energy consumption level for cable TV equipment, however, varies substantially (see Appendix B);
- Nameplate information varies by equipment and this information is difficult to obtain;

Recommendation:

- Sample size under study is small and mostly contributed by one LDC, further monitoring and/or study is recommended if defensible estimates are required for rate submission;
- In the short-term, recommend to use current energy estimates provided by LDCs and Cable companies;
- LDCs and cable companies should work together in future study (such as monitoring and audits);
- There is a need to document how energy consumption estimates are established by Cable companies and LDCs;

Battery Heater Mats

- Data provided by RCCI shows significant correlation with hourly weather data;
- Weather normalized load shapes have successfully been generated (see Appendix C for sample load shapes on a weather normalized basis);
- Sample used for analysis is limited to selected areas, further analysis with a larger sample and other areas may improve the load shapes;

Recommendation:

- In the short-term, recommend to use the generated weather sensitive load shapes for informational filings to OEB;
- Further study with larger sample is recommended.

Other USL Loads

- The loads are relatively flat;
- Since the sample under study is very small, this finding may not be statistically significant;

Recommendation:

- In the short-term, recommend to use current energy profiles provided by LDCs;
- Further study with larger sample is recommended.

Appendix : A (i) Power Supply As A Percentage Of The Nameplate Rating

	Hydro One Nameplate rating = 0.900 kwh (15A, 60V)								
Meter number	1	2	3	4	5	6	7	8	9
Monitored consumption	0.25	0.33	0.37	0.61	0.14	0.36	0.68	1.27	0.66
Percentage of nameplate	28.0%	36.9%	41.4%	67.8%	16.0%	40.5%	75.1%	141.3%	73.3%

		Hydro One							
			Name	olate ratii	ng = 0.90	0 kwh (15	A, 60V)		
Meter number	10	11	12	13	14	15	16	17	18
Monitored consumption	0.77	0.51	0.22	0.41	0.40	0.75	0.24	0.54	0.43
Percentage of nameplate	85.3%	56.8%	24.8%	45.5%	43.9%	83.4%	26.2%	60.2%	47.8%

					Hydro Or	ne			
			Name	olate ratii	ng = 0.90	0 kwh (15	A, 60V)		
Meter number	19	20	21	22	23	24	25	26	27
Monitored consumption	0.34	0.33	0.18	0.77	0.16	0.52	0,42	0.62	0.59
Percentage of nameplate	37.4%	37.0%	20.4%	85.5%	17.8%	58.0%	46.5%	69.3%	65.3%

Appendix : A (ii) Power Supply As A Percentage Of The Nameplate Rating

	Chantam Kent -1				
N	lameplate = 15 A	60 V			
Monitored Kw	Frequency	% of Nameplate			
0.27	0.7%	30.0%			
0.28	0.8%	31.1%			
0.29	1.5%	32.2%			
0.55	9.2%	61.1%			
0.56	19.3%	62.2%			
0.57	22.2%	63.3%			
0.58	32.8%	64.4%			
0.59	9.4%	65.6%			
0.6	4.1%	66.7%			
1.14	0.1%	126.7%			

Chantam Kent -2						
N	Nameplate = 15 A 60 V					
Monitored Kw	Frequency	% of Nameplate				
0.34	0.1%	37.8%				
0.35	1.8%	38.9%				
0.36	1.0%	40.0%				
0.37	0.1%	41.1%				
0.66	0.2%	73.3%				
0.69	0.9%	76.7%				
0.7	21.5%	77.8%				
0.71	72.4%	78.9%				
0.72	1.9%	80.0%				
0.77	0.1%	85.6%				
0.78	0.1%	86.7%				

	Chantam Kent -3					
	Nameplate = 15 A 60 V					
Monitored Kw	Frequency	% of Nameplate				
0.37	1.2%	41.1%				
0.38	1.8%	42.2%				
0.66	0.1%	73.3%				
0.68	0.1%	75.6%				
0.73	0.1%	81.1%				
0.74	1.1%	82.2%				
0.75	49.9%	83.3%				
0.76	45.4%	84.4%				
0.78	0.1%	86.7%				
0.8	0.1%	88.9%				
0.81	0.1%	90.0%				

Chantam Kent -4					
Nameplate = 15 A 60 V					
Monitored Kw	Frequency	% of Nameplate			
0.33	0.6%	36.7%			
0.34	1.3%	37.8%			
0.35	0.8%	38.9%			
0.36	0.3%	40.0%			
0.66	5.8%	73.3%			
0.67	24.3%	74.4%			
0.68	36.8%	75.6%			
0.69	1.7%	76.7%			
0.7	7.0%	77.8%			
0.71	20.9%	78.9%			
0.72	0.2%	80.0%			
0.73	0.1%	81.1%			
1.35	0.1%	150.0%			
2.79	0.1%	310.0%			

	Chantam Kent -4				
Nameplate = 15 A 60 V					
Monitored Kw	Frequency	% of Nameplate			
0.29	0.5%	32.2%			
0.3	1.9%	33.3%			
0.31	0.4%	34.4%			
0.32	0.3%	35.6%			
0.57	0.1%	63.3%			
0.58	45.0%	64.4%			
0.59	20.1%	65.6%			
0.6	0.9%	66.7%			
0.61	1.1%	67.8%			
0.62	19.7%	68.9%			
0.63	10.1%	70.0%			

Gravenhurst -1					
Nam	eplate = 15 A 60 V				
Monitored Kw Frequency Nameplate					
0.53	0.1%	58.9%			
1.05	0.1%	116.7%			
1.08	2.9%	120.0%			
1.09	29.6%	121.1%			
1.1	55.7%	122.2%			
1.11	11.6%	123.3%			
1.12	0.1%	124.4%			

New Market 2					
Nameplate = 15 A 60 V					
Monitored Kw	Frequency	% of Nameplate			
0.06	0.2%	6.7%			
0.44	23.9%	48.9%			
0.46	74.7%	51.1%			
0.48	1.0%	53.3%			
0.52	0.2%	57.8%			

Gravenhurst -1				
Nam	eplate = 15 A 60 V			
Monitored Kw	Frequency	% of Nameplate		
0.48	0.1%	53.3%		
0.53	0.1%	58.9%		
0.67	0.1%	74.4%		
0.68	1.5%	75.6%		
0.69	28.8%	76.7%		
0.7	42.5%	77.8%		
0.71	22.3%	78.9%		
0.72	4.6%	80.0%		
0.73	0.1%	81.1%		

New Market 2				
N	ameplate = 15 /	\ 60 V		
Monitored Kw	Frequency	% of Nameplate		
0.48	0.0%	53.3%		
0.52	0.1%	57.8%		
0.88	0.0%	97.8%		
0.9	26.2%	100.0%		
0.92	63.2%	102.2%		
0.94	10.2%	104.4%		
0.96	0.1%	106.7%		
1	0.0%	111.1%		
1.12	0.0%	124.4%		

1	New Market 1	
Name	eplate = 15 A 60 V	
Monitored Kw	Frequency	% of Nameplate
0.32	0.2%	35.6%
0.42	22.0%	46.7%
0.44	76.3%	48.9%
0.46	1.0%	51.1%
0.48	0.2%	53.3%
0.5	0.2%	55.6%

	Whitby 1	
Namepl	ate = 0.417Kwh	(6.6A, 63.2)
Monitored Kw	Frequency	% of Nameplate
0.38	0.3%	91.1%
0.39	0.3%	93.5%
0.4	0.1%	95.9%
0.41	2.0%	98.3%
0.42	1.2%	100.7%
0.43	4.2%	103.1%
0.44	6.0%	105.5%
0.45	9.6%	107.9%
0.46	13.0%	110.3%
0.47	13.1%	112.7%
0.48	13.3%	115.1%
0.49	7.1%	117.5%
0.5	7.2%	119.9%
0.51	6.5%	122.3%
0.52	5.1%	124.7%
0.53	5.8%	127.1%
0.54	1.5%	129.5%
0.55	2.3%	131.9%
0.56	1.0%	134.3%

Appendix B : Power Supply As A Percentage Of The Current kWh Consumption Estimate Used By LDC

	COMPANY		Monthly billed Values	Measured Kw /	Average by cable
ACCOUNT NO.	NAME	Kw Measured	in Kw	Billing value.	company
HYDRO ONE					
1	Company A	0.25	0.18	138%	
2	Company A	0.33	0.26	129%	
3	Company A	0.37	0.59	63%	
4	Company A	0.61	0.65	94%	
5	Company A	0.14	0.47	31%	91%
6	Company B	0.51	0.44	116%	
7	Company B	0.22	0.18	128%	
8	Company B	0.41	0.76	54%	
9	Company B	0.40	0.47	85%	
10	Company B	0.75	0.77	97%	96%
11	Company C	0.24	0.23	102%	102.2%
12	Company D	0.54	0.63	86%	86.5%
13	Company E	0.43	0.33	130%	130.2%
14	Company F	0.34	0.39	85%	85.4%
15	Company G	0.33	0.40	83%	83.2%
16	Company H	0.18	0.23	80%	
17	Company H	0.77	0.79	97%	88%
18	Company I	0.16	0.07	235%	235%
19	Company J	0.52	0.19	272%	272%
20	Company K	0.42	0.47	89%	89%
21	Company L	0.62	0.24	261%	261%
22	Company M	0.59	0.82	71%	71%
 23	Company N	0.36	0.25	144%	
24	Company N	0.68	0.63	108%	
25	Company N	1.27	0.73	174%	
26	Company N	0.66	0.63	104%	
27	Company N	0.77	0.16	494%	205%
NEW MARKET					
1	Company N	0.44	0.44	101.0%	
2	Company N	0.92	1.22	75.1%	88.1%
WHITBY					
1	Company N	0.48	0.62	76.8%	76.8%
ı	Company N	0.40	0.02	7 0.0 70	70.070
WASAGA	_				
1	Company N	0.55	0.90	61.3%	
2	Company N	0.45	0.48	95.2%	143%
TOTAL		15.72	15.60		
Total measured	kw/Total billed kw	100.8%			

Appendix C: Battery Heater Mats Profile

Table 1

Unmetered Scattered Load, Battery Mats Count 1 - Monthly Electricity Consumption (Wh)

	lotai	4414	3535	1674	319	0	0	0	0	0	0	530	1381
5	74	96	86	45	10	0	0	0	0	0	0	9	40
6	3	113	66	20	7	0	0	0	0	0	0	8	44
8	7.7	116	100	51	7	0	0	0	0	0	0	18	44
Š	57	117	100	20	10	0	0	0	0	0	0	17	43
Ş	25	144	118	27	7	0	0	0	0	0	0	9	48
	<u> </u>	125	104	57	9	0	0	0	0	0	0	17	43
	18	130	107	25	10	0	0	0	0	0	0	17	44
1	1/	140	116	26	_	0	0	0	0	0	0	18	47
,	16	155	126	61	12	0	0	0	0	0	0	20	51
į	15	172	137	92	12	0	0	0	0	0	0	20	53
	14	188	148	69	<u>5</u>	0	0	0	0	0	0	21	56
	13	251	194	83	16	0	0	0	0	0	0	27	72
Hour													
	12	254	196	8	16	0	0	0	0	0	0	27	72
;	7	261	200	9	16	0	0	0	0	0	0	27	72
,	9	284	217	66	17	0	0	0	0	0	0	23	28
***************************************	თ	290	222	101	8	0	0	0	0	0	0	30	80
	∞	284	219	100	8	0	0	0	0	0	0	30	80
1	^	293	224	102	9	0	0	0	0	0	0	9	80
,	ဖ	246	193	88	16	0	0	0	0	0	0	27	72
	က	190	153	72	7	0	0	0	0	0	0	23	09
***************************************	4	159	132	64	5	0	0	0	0	0	0	21	54
***************************************	က	169	138	29	5	0	0	0	0	0	0	22	26
	7	124	107	53		0	0	0	0	0	0	8	46
	←	113	100	51	<u></u>	0	0	0	0	0	0	8	45
	Month	Jan	Feb	Mar	Apr	May	Jun	Juc	Aug	Sep	Oct	Nov	Dec

Note. All figures are weather-normal.

Appendix C: Battery Heater Mats Profile

Table 2

Unmetered Scattered Load, Battery Mats Count 2 - Monthly Electricity Consumption (Wh)

	Total	3833	3303	1713	342	0	0	0	0	0	0	269	1475
	24	137	125	99	4	0	0	0	0	0	0	24	26
	23	154	136	71	5	0	0	0	0	0	0	25	63
	22	138	122	64	13	0	0	0	0	0	0	22	56
	21	118	106	26	12	0	0	0	0	0	0	20	20
	20	108	6	27		0	0	0	0	0	0	<u>&</u>	45
	19	122	106	55	7	0	0	0	0	0	0	<u>6</u>	48
	18	95	84	45	10	0	0	0	0	0	0	16	9
	17	92	83	44	ග	0	0	0	0	0	0	16	39
	16	105	8	48	10	0	0	0	0	0	0	9	42
	15	92	84	44	6	0	0	0	0	0	0	16	38
	4-	124	107	56		0	0	0	0	0	0	19	48
=	13	123	109	22	12	0	0	0	0	0	0	20	52
Hour	12	186	155	79	5	0	0	0	0	0	0	25	29
	=	183	154	79	5	0	0	0	0	0	0	25	99
	10	197	166	85	16	0	0	0	0	0	0	27	72
	6	179	147	75	4	0	0	0	0	0	0	23	62
	8	231	188	95	17	0	0	0	0	0	0	28	78
	7	228	188	96	8	0	0	0	0	0	0	30	80
	9	241	199	101	<u>ნ</u>	0	0	0	0	0	0	<u>ب</u>	84
	ဌ	209	178	85	8	0	0	0	0	0	0	30	79
	4	201	170	87	17	0	0	0	0	0	0	78	74
	60	197	172	8	8	0	0	0	0	0	0	8	78
	2	205	179	93	9	0	0	0	0	0	0	32	8
	-	169	155	83	8	0	0	0	0	0	0	30	74
	Month	Jan	Feb	Mar	Apr	May)un	Jul	Aug	Sep	oct O	Nov	Dec

Note. All figures are weather-normal.

Appendix C: Battery Heater Mats Profile

Table 3

Unmetered Scattered Load, Battery Mats Count 3 - Monthly Electricity Consumption

	Total	6786	5709	3421	719	0	0	0	0	0	0	1548	3305
	24	211	207	150	37	0	0	0	0	0	0	84	165
	23	235	212	140	32	0	0	0	0	0	0	72	145
	22	234	191	109	22	0	0	0	0	0	0	46	101
	21	213	193	128	53	0	0	0	0	0	0	92	133
	20	239	221	151	36	0	0	0	0	0	0	80	160
	6	239	196	112	23	0	0	0	0	0	0	48	105
	18	342	281	162	33	0	0	0	0	0	0	69	152
	17	244	212	133	53	0	0	0	0	0	0	64	133
	16	312	262	156	32	0	0	0	0	0	0	2	150
	15	270	235	148	33	0	0	0	0	0	0	72	149
	41	343	296	183	4	0	0	0	0	0	0	87	182
Hour	13	391	347	224	57	0	0	0	0	0	0	112	229
ĭ	12	368	312	188	4	0	0	0	0	0	0	86	183
	77	346	276	152	53	0	0	0	0	0	0	90	137
	10	414	321	168	30	0	0	0	0	0	0	9	143
	ර	365	284	150	27	0	0	0	0	0	0	22	129
	∞	305	241	131	25	0	0	0	0	0	0	51	116
	7	386	287	138	22	0	0	0	0	0	0	41	107
	9	262	207	112	7	0	0	0	0	0	0	43	86
	53	264	222	132	28	0	0	0	0	0	0	29	127
	4	187	165	106	24	0	0	0	0	0	0	53	109
	3	220	185	112	24	0	0	0	0	0	0	51	108
	2	220	189	116	25	0	0	0	0	0	0	22	15
	Ψ	177	169	119	29	0	0	0	0	0	0	99	130
	Month	Jan	Feb	Mar	Apr	May	Jun	- In	Aug	Sep	Oct	Nov	Dec

Note. All figures are weather-normal.

Appendix C: Battery Heater Mats Profile

Unmetered Scattered Load, Battery Mats Count 6 - Monthly Electricity Consumption (Wh)

	Total	5346	4114	2051	170	0	0	0	0	0	0	438	1302
	24	129	93	28	ß	0	0	0	0	0	0	7	38
	23	143	117	61	Ŋ	0	0	0	0	0	0	4	39
	22	148	120	62	Ŋ	0	0	0	0	0	0	7	40
	21	162	129	99	ß	0	0	0	0	0	0	ភ	42
	20	146	200	61	വ	0	0	0	0	0	0	7	9
	19	156	125	64	Ω.	0	0	0	0	0	0	4	4
	18	169	135	69	ဖ	0	0	0	0	0	0	5	44
	17	180	140	7.1	ဖ	0	0	0	0	0	0	15	45
	16	199	154	11	ဖ	0	0	0	0	0	0	17	94
***************************************	15	206	159	80	7	0	0	0	0	0	0	17	51
	4	246	187	92	œ	0	0	0	0	0	0	6	28
Hour	13	290	220	108	0	0	0	0	0	0	0	23	88
	12	294	222	109	ග	0	0	0	0	0	0	23	69
	7	276	210	104	တ	0	0	0	0	0	0	22	99
	19	323	240	117	9	0	0	0	0	0	0	24	73
	6	323	240	116	19	0	0	0	0	0	0	24	73
	80	336	250	121	10	0	0	0	0	0	0	24	9/
	7	310	231	113	တ	0	0	0	0	0	0	23	70
	9	289	218	107	თ	0	0	0	0	0	0	22	29
	rs.	287	218	108	ග	0	0	0	0	0	0	23	99
	4	243	186	93	∞	0	0	0	0	0	0	20	29
	က	211	163	81	7	0	0	0	0	0	0	17	51
	2	152	122	63	5	0	0	0	0	0	0	14	4
	—	125	102	53	4	0	0	0	0	0	0	12	34
	Month	Jan	Feb	Mar	Apr	May	Jun	Ш	Aug	Sep	oct O	Nov	Dec

Note. All figures are weather-normal.