



Stephanie Allman
Regulatory Coordinator
Regulatory Affairs

tel 416 495 5499
Stephanie.allman@enbridge.com

Enbridge Gas Distribution
500 Consumers Road
North York, Ontario M2J 1P8
Canada

VIA RESS, EMAIL AND COURIER

December 14, 2015

Ms. Kirsten Walli
Ontario Energy Board
P.O. Box 2319
2300 Yonge Street, 26th Floor
Toronto, ON M4P 1E4

**Re: Enbridge Gas Distribution Inc. (“Enbridge”)
Ontario Energy Board (“Board”) File No.: EB-2015-0303
Application to Drill Wells in a Designated Storage Area - Affidavit of Service**

On December 1, 2015, the Board issued the Notice of Application and Letter of Direction for the above noted proceeding.

As directed by the Board, enclosed please find the Affidavit of Service which has been filed through the Board’s Regulatory Electronic Submission System.

Please contact the undersigned if you have any questions.

Sincerely,

(Original Signed)

Stephanie Allman
Regulatory Coordinator

ONTARIO ENERGY BOARD

IN THE MATTER OF the *Ontario Energy Board Act, 1998*, S.O. 1998, c. 15 (Schedule B);

AND IN THE MATTER OF an application by Enbridge Gas Distribution Inc. for permission to drill a natural gas well within the Corunna Designated Storage Area.

AFFIDAVIT OF SERVICE

I, Stephanie Allman, of the Town of Keswick, make oath and say as follows:

1. I am in the employ of Enbridge Gas Distribution Inc. ("Enbridge") and as such have knowledge of the matters hereinafter deposed to.
2. Pursuant to the December 1, 2015 Letter of Direction from the Ontario Energy Board (the "Board"), I caused to be served a copy of the Notice of Hearing ("Notice"), Enbridge's Application and Evidence to all of the following:
 - a) All landowners within the Designated Storage Area (DSA) of the storage pool that is the subject of this application
 - b) All owners and operators of rail lines, telecommunications (e.g. telephone) or other utilities affected by Enbridge's proposal
 - c) The Clerks of the Township of Moore and Lambton County
 - d) The Ministry of Natural Resources and Forestry, Petroleum Operations Section, London Ontario

3. Attached hereto and marked as Exhibit "A", and "B", are true copies of the aforesaid dated Notice, and Enbridge's Application, and Evidence.
4. Attached hereto and marked as Exhibit "C" is proof in the form of a courier receipt that the Notice, Application and Evidence was served on those parties as directed by the Ontario Energy Board in the Letter of Direction.
5. Pursuant to the Letter of Direction, I caused to provide a copy of the Notice to Enbridge Gas Distribution's website. Attached as Exhibit "D" is a screen shot of the Company's website page.

SWORN before me in the City of)
Toronto, this 14th day of)
December 2015)
)
)

(Original Signed)
Stephanie Allman

Original Commissioned by S.L. Spratt

ONTARIO ENERGY BOARD NOTICE

Enbridge Gas Distribution Inc. has applied for approval to drill a natural gas well.

Learn More. Have Your Say.

Enbridge Gas Distribution Inc. has applied to the Minister of Natural Resources and Forestry for approval to drill a natural gas injection/withdrawal well in its Corunna designated storage area located in the Township of Moore in Lambton County. The Minister of Natural Resources and Forestry referred the application to the Ontario Energy Board. The Ontario Energy Board is required to report to the Minister of Natural Resources and Forestry.

A map of the general location of the Corunna storage pool is provided below.

THE ONTARIO ENERGY BOARD IS HOLDING A PUBLIC HEARING

The Ontario Energy Board (OEB) will hold a public hearing to consider the application filed by Enbridge Gas. We will question Enbridge Gas on the case. We will also hear arguments from individuals and from groups that are interested in the case. At the end of this hearing, the OEB will report to the Minister of Natural Resources and Forestry on the application by Enbridge Gas for a well licence.

The OEB is an independent and impartial public agency. We make decisions that serve the public interest. Our goal is to promote a financially viable and efficient energy sector that provides you with reliable energy services at a reasonable cost.

BE INFORMED AND HAVE YOUR SAY

You have the right to information regarding this application and to be involved in the process.

- You can review the application filed by Enbridge Gas with the Ministry of Natural Resources and Forestry on the OEB's website now.
- You can file a letter with your comments, which will be considered during the hearing.
- You can become an active participant (called an intervenor). Apply by **December 18, 2015** or the hearing will go ahead without you and you will not receive any further notice of the proceeding.
- At the end of the process, you can review the OEB's decision and its reasons on our website.

LEARN MORE

Our file number for this case is **EB-2015-0303**. To learn more about how to participate in this hearing, including how to file a letter with your comments or how to become an intervenor, go to: www.ontarioenergyboard.ca/participate. From that OEB web page you can enter the file number **EB-2014-0378** to see all the documents related to this case. You can also phone our Consumer Relations Centre at 1-877-632-2727 with any questions.

ORAL VS. WRITTEN HEARINGS


There are two types of OEB hearings – oral and written. The OEB will determine at a later date whether to proceed by way of a written or oral hearing. If you think an oral hearing is needed, you can write to the OEB to explain why by **December 18, 2015**.

PRIVACY


If you write a letter of comment, your name and the content of your letter will be put on the public record and the OEB website. However, your personal telephone number, home address and email address will be removed. If you are a business, all your information will remain public. If you apply to become an intervenor, all information will be public.

This hearing will be held under section 40(1) of the Ontario Energy Board Act, 1998, S.O. 1998 c.15 (Schedule B).





LAMBTON COUNTY



LEGEND

PROPOSED LOCATION OF HORIZONTAL WELL



ZONE

DAWN

SARNIA

MOORE

SOMBRA

SARNIA

CORUNNA

CORUNNA DESIGNATED STORAGE AREA

BRIGDEN

WALLACEBURG

DRESDEN



Gas Storage Operations
3595 Tecumseh Road
Mooretown, ON N0N 1M0
(519) 862-1473
(519) 862-1168 Fax



November 6, 2015

Ministry of Natural Resources and Forestry
Petroleum Operations Section
659 Exeter Road
London, Ontario
N6E 1L3

Attention: Mr. Jug Manocha, Operations Engineer

**Subject: Submittal of Drilling Application for:
TC 9H (Horiz.#1) Moore 4-20-X**

Enclosed, please find the drilling application for a proposed gas storage well to be located in the Corunna Designated Storage Area. The application includes two copies of the Form 1, two copies of the Wellsite Survey, two copies of the Drilling Program and a cheque for the well application fee. It is our hope to start the drilling of the wells by April 1st, 2016. The Risk Assessment has been initiated and will be submitted to your office for confidential review. We would be pleased to meet with you to review or clarify any portion of the applications.

The proposed well is being drilled to replace deliverability lost due to the abandonment of two wells and the conversion of one injection well to an observation well. The two wells, TC 4 and TC 6, were abandoned in 2015 and 2011, respectively. TC 4 was an observation well that did not provide accurate data with respect to reef pressure during injection and withdrawal operations, the well was positioned in a poorer part of the reef and the observation well pressure always lagged behind the reef pressure by a few days. It was decided to abandon the TC 4 well and convert the TC 3 well to an observation well, removing the ability to use the TC 3 well as an injection well. The TC 6 well was abandoned in 2011 as it could not be repaired to meet the CSA Z341 Standard. By abandoning TC 6 and converting TC 3 to an observation well, approximately 23% of the deliverability of the Corunna Pool was lost, driving the need to replace the lost deliverability with a new well.

If approved, the TC 9H well will be drilled in Lot 20, Concession 10 on property owned by Mr. Richard Wellington. The well location was chosen based on 1.) Geological; 2.) Drilling operations concerns; and 3.) Minimal drainage disruption for the land, as follows:

1. Based on our past drilling experience, it has been found that to allow for the optimal placement of the production (219mm) casing, drilling must occur on the reef crest as opposed to landing the casing on the slope of the reef. There is a higher degree of uncertainty when picking the 219mm casing point, as the geology is extremely complicated off the crest of the reef and the formations – A-1 Carbonate, A-2 Anhydrite and Guelph – can interfinger further complicating the casing pick. Drilling on the crest of the Corunna reef allows the 219mm casing to be placed in the thickest part of the A-2

Anhydrite and at the point where the vertical section of the reef is at its maximum thickness.

2. Drilling on the reef crest is especially important in the Corunna reef as it is smaller in vertical section than normal and we need as much vertical section as possible to land the horizontal portion of the well in our target zone of -480m subsea. The more vertical section that we can utilize the smaller the dog legs in the build section and the lower the probability of drilling complications – such as becoming stuck in the hole or twisting off the drill string.
3. The proposed well is located at the end of an existing laneway. The field drainage tiles were previously re-located and re-routed around the driveway to allow proper drainage. Enbridge is continuing discussion with the landowner to understand if there are other potential issues which need to be addressed.


Enbridge has positioned the proposed well in a location that provides minimal disruption for the field tile drainage pattern, but still ensures that the well will be drilled in the most optimum location geologically and operationally. The well will be located approximately 21m from the Enbridge gathering line and as such, the drilling pad will be located over the pipeline – for the duration of the drilling activities, the pipeline pressure will be reduced to 0 psi and will be taken out of service.

An Environmental Screening has also been initiated and will be submitted to the Ontario Energy Board (OEB) and the MNRF upon completion, targeted by the end of this month.

It is our understanding that the drilling application will be forwarded to the OEB by your office and we are requesting your earliest attention to this application. For your information, Enbridge has also submitted a package containing the drilling applications to the OEB.

If any further information is required please contact the undersigned at 519-862-6025 or Kathy McConnell at 519-862-6032.

Yours truly,



Brian Black, P.Eng.
Director, Gas Storage Operations
3595 Tecumseh Road
Mooretown, Ontario
N0N 1M0

Enclosures



Exhibit B
Oil, Gas and Salt Resources Act
Application for a Well Licence

EB-2015-0303
EGDI Wells Application
Page 1 of 34

Form 1

To the Minister of Natural Resources

v.2013-10-04

The undersigned operator applies for a well licence under the Oil, Gas and Salt Resources Act and the Regulations thereunder and submits the following information, together with the application fee of \$100 + 13% HST. Make cheques payable to "Minister of Finance".

1. WELL NAME TC 9H (HORIZ#1) Moore 4-2-10 Target Formation Guelph

Purpose of Proposed Well (Well Type) Gas Storage

2. OPERATOR Enbridge Gas Distribution Inc. Tel # 519-862-1473 Fax # 519-862-1178

Street Address 3595 Tecumseh Road City Mooretown Prov. ON Postal Code N0N 1M0

Mailing Address 3595 Tecumseh Road City Mooretown Prov. ON Postal Code N0N 1M0

Contact Name Kathy McConnell Contact Tel # 519-862-6032

Email kathy.mcconnell@enbridge.com

3. LOCATION County Lambton Township Moore

Tract 4 Lot 20 Concession 10 Lake Erie: Block Tract Licence/Lease No.

Surface location, 532.7m m North South Latitude 42° 52' 57.285" Bottom-hole Lat. 42° 53' 07.100"

Lot Boundaries 139.2m m East West Longitude 82° 22' 44.769" Bottom-hole Long. 82° 22' 42.695"

Within 1.6 km of Designated Storage Area? Yes No Off-target? Yes No

4. WELL PARTICULARS Vertical Horizontal Directional Deepening Re-entry Lateral

Rig Type: Rotary Cable Well to be cored? Yes No Formation at TD Guelph

Ground Elevation 196.72 Proposed Depth 940.0 Proposed Depth TVD 681.00 Proposed Start Date 1-Apr-16

5. LANDOWNER [REDACTED] Tel # [REDACTED]

Street Address [REDACTED] City [REDACTED] Prov. [REDACTED] Postal Code [REDACTED]

The landowner hereby provides consent for the collection of their personal information, via the operator, as per Section 12 of this form. Landowner Signature: unavailable for signature, still attempting to contact

Pooling of the Spacing Unit or unitization of the Unit Area shown on the attached well location plan has been completed (see Ont. Reg. 245/97 definitions for "pooled spacing unit" and "unitize") Yes No

6. DRILLING CONTRACTOR TW Marsh Well Drilling & Servicing / Rotary Contractor - Unknown Tel # 519-695-6060 / Unknown

Address Box 53 / Unknown City Bothwell / Unknown Prov. ON Postal Code N0P 2C0

7. PROPOSED CASING AND CEMENTING PROGRAM

Hole Size (mm)	Casing O.D. (mm)	Weight (kg/m)	Grade	New Used or in-hole	Setting Depth TVD	Setting Depth Meas.	Setting Formation	CASING SETTING INFORMATION		
								How Set	Cement Type	Cement Top KB / RF
508	508	158.47	LS	New	46	46	Kettle Point	Driven	nil	nil
508	406	96.42	LS	New	61	61	Kettle Point	Cement	Class 'G'	surface
375	298	69.94	J55	New	405	405	F Unit	Cement	Class 'G'	surface
270	219	47.62	J55	New	649	663.6	A-2 Anhydrite	Cement	Class 'G'	surface

8. BLOW-OUT PREVENTION EQUIPMENT 16" 2M MSP Hydrill
11" 3M Annular Preventor and Double Gate (pipe and blind)

9. WELL SECURITY Name of Trustee Harrison Pensa LLP Total # Unplugged Wells 148 Current Balance \$70K

10. REMARKS Rotating Control Device 11" x 2M will be used for drilling in the reef

11. ENCLOSURES Fee Location Plan (Land wells only) Drilling Program

12. NOTICE OF COLLECTION

The Ministry of Natural Resources is collecting your personal information under the authority of the *Oil, Gas and Salt Resources Act*. Any personal information provided on this application will be used for licensing and law enforcement purposes only and will be protected in accordance with the Freedom of Information and Protection of Privacy Act.

If you have questions about use of your personal information, please contact the Policy and Program Officer, Petroleum Operations Section, Ministry of Natural Resources, 659 Exeter Road, London N6E1L3, 519-873-4638.

13. AUTHORITY

The undersigned certifies that the information provided herein is complete and accurate, the operator has the right to drill or operate a well in the above location, and he/she has authority to bind the operator.

Date (d/m/y)	<u>06.Nov.15</u>	Name	<u>Brian Black</u>	Signature	<u>[Signature]</u>
		Company	<u>Enbridge Gas Distribution Inc.</u>	Title	<u>Director, Storage Operations</u>

TC 9H (HORZ. #1) MOORE 4-20-X

DRILLING PROGRAM

Drilling Program
TC 9H (HORIZ. #1) MOORE 4-20-X

Enbridge Gas Distribution Inc.

TABLE OF CONTENTS

SECTION 1.0	GENERAL DATA
Section 1.1	Well Summary
Section 1.2	Special Notes
Section 1.3	Contact Numbers
SECTION 2.0	GEOLOGICAL PROGNOSIS
SECTION 3.0	CASING AND CEMENTING SUMMARY
Section 3.1	Summary
Section 3.2	Wellbore Diagram
Section 3.3	Wellhead Information
Section 3.4	Directional Planning Report
SECTION 4.0	DRILLING PROCEDURES
Section 4.1	Pre-Spud
Section 4.2	Conductor Casing
Section 4.3	Surface Hole and Surface Casing
Section 4.4	Intermediate Hole and Intermediate Casing
Section 4.5	Production Hole and Production Casing
Section 4.6	Main Hole
Section 4.7	Loss Circulation Contingency Program
SECTION 5.0	REPORTING PROCEDURES
Section 5.1	Tower Sheets
Section 5.2	Worker Injury
SECTION 6.0	SAFETY AND PROCEDURES
Section 6.1	General Safety
Section 6.2	Well Control

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**

Enbridge Gas Distribution Inc.

SECTION 1.0 - GENERAL DATA**Section 1.1 - Well Summary**

Well Name: TC 9H (Horiz. # 1) Moore 4-20-X

Operator: Enbridge Gas Distribution Inc.

Surface Hole Location: Tract 4, Lot 20, Con. 10, Moore Twp, Lambton County
N 4 748 698.00; E 387 377. 00

Surface Hole Coordinates: 532.7m South; 139.2m West

Bottom Hole Location : Tract 1, Lot 20, Con. 10, Moore Twp, Lambton County

Bottom Hole Coordinates: N 4 749 000.00; E 387 429.00

Ground Elevation: 196.72m

KB Elevation: 200.72m

Total Depth: 681mTVD; 940mMD

Target Formation: Guelph

Logging Program: CBL-GR – 219mm casing
Vertilog – 219mm casing

Spud Date: April 15, 2016

Duration: 30 days

Section 1.2 – Special Notes

1. Safety of personnel and environment is our primary concern. Section 6.1 of this program, outlines Enbridge's general safety requirements which obliges all personnel on the wellsite to follow the Occupational Health and Safety Act and Regulations (Ministry of Labour (MOL)) and the Oil, Gas & Salt Resources Act and Regulations (Ministry of Natural Resources and Forestry (MNR)). Safety and/or environmental ("tailgate") meetings shall be conducted as per Section 6. Wellsite Supervisor shall conduct daily 'walk around' inspections of the equipment on site and record the results on the daily reports. Please refer to Section 5.2 for the procedure to be followed if a worker injury occurs.

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**Enbridge Gas Distribution Inc.

2. The Wellsite Supervisor has authority over all activities conducted on the drilling location. The Wellsite Supervisor shall ensure that all applicable regulations and policies (MNRF, MOL, Ministry of the Environment and Climate Change (MOECC), and Enbridge) are followed and that all permits are kept on site and/or signed off as required.
3. All operations are to be to MNRF standards.
4. BOPs are to be installed, maintained and used as per MNRF requirements. Testing of the BOPs must be in accordance with Section 6.2 of this program.
5. Tower sheets must be completed daily and will include the information listed in Section 5.1 of this program. The Wellsite Supervisor will complete daily reports and forward the reports to Enbridge's office by 10am the following day.
6. The well will be drilled in 2 stages:
 - a. A cable tool rig will drive the conductor casing and will drill the surface casing into the Kettle Point formation and cement the casing to surface. Drilling this portion of the well with a cable tool rig will ensure that the fresh water zone will be exposed to a minimal amount of drilling fluid.
 - b. A rotary rig will be moved onto location and will drill to TD. The rotary will set the intermediate and production casings and will drill the open hole horizontal section in the Guelph reef.
7. During the rotary phase of the well, the well will be drilled with fresh water or formation brine, hauled to location by an approved contractor. The fresh water will be obtained from local municipal water systems, located at Brigden, Corruna and other available water systems. The brine used will be Guelph formation brine obtained from Enbridge's existing operations.
8. The production casing will be set in the A-2 Anhydrite to allow for an effective cement job and successful pressure testing, prior to penetrating the Guelph formation
9. A minimum of two 500 bbl frac tanks will be spotted on location prior to the drilling of the Detroit River formation. The tanks will be filled with fresh water / brine as reserve for the drilling of potential loss circulation zones. Potential loss circulation zones exist in the Detroit River formation (intermediate hole) and the Guelph formation (main hole).

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**

Enbridge Gas Distribution Inc.

Section 1.3 - Contact Numbers**Emergency Numbers:**

Police, Fire & Ambulance:* 911

911 Address: 1049 Petrolia Line, Corunna, Ontario

* For 911 Map and Map and Directions to Nearest Hospital see attached Map at end of Section 1.3

Enbridge Gas Distribution Inc.

Rob Carlson	Reservoir Field Supervisor	Office: 519-862-6036 Fax: 519-862-1168 Cell: 519-312-4863 robert.carlson@enbridge.com
Kathy McConnell	Manager Reservoir Development	Office: 519-862-6032 Fax: 519-862-1168 Cell: 519-312-2168 kathy.mcconnell@enbridge.com
Terry Chupa	Land Administrator	Office: 519-862-6008 Fax: 519-862-1168 Cell: 519-384-0215 terry.chupa@enbridge.com
Control Room		Office: 519-862-6012

Drilling Supervisor:

Wayne Bolton	Cell: 519-312-8437 kegconsulting@aim.com
--------------	---

Steve Thompson	Cell: 519-383-5404 omniconsulting@rogers.com
----------------	---

Geologist:

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**

Enbridge Gas Distribution Inc.

graham.shone@dnw.com

Karen Derrick	Stream-Flo Ltd. Technical Sales Rep.	Office: 832-647-0710 Fax: 519-688-0563 kderrick@streamflo.com
---------------	---	---

Drill Bits:

Brad Takenaka	Varel Rock Bits Canada Sales Manager	Office: 403-968-9369 Cell: 403-303-2533 btakenaka@varelintl.com
---------------	---	---

Mike Kellar	Trendon Bit Service Ltd. Director, Sales	Office: 403-990-1299 mkellar@trendoninc.com
-------------	---	--

Wireline Services:

Gord Mackenzie	Baker Atlas Station Manager	Office: 519-332-8030 Fax: 519-332-4714 Cell: 519-339-6783 gord.mackenzie@bakerhughes.com
----------------	--------------------------------	---

Dave Tipping	Weatherford Canada – Wireline & Logging Services Station Manager	Office: 519-683-2010 Fax: 519-683-2577 Cell: 519-436-3541 dave.tipping@canada.weatherford.com
--------------	---	--

Water Hauling:

Keith McKeegan	President McKeegan Trucking Limited	Office: 519-864-1037 Fax: 519-864-1036 Cell: 519-490-4042
----------------	---	---

Denis Marcus	President Harold Marcus Limited	Office: 519-695-3735 Fax: 519-695-2249 Cell: 519-380-5238 dmarcus@haroldmarcus.com
--------------	------------------------------------	---

Rental Equipment:

Dale Holland	Wheatley Wireline Services Ltd.	Office: 519-825-3680 Fax: 519-825-9348 Cell: 519-322-8015
--------------	------------------------------------	---

Keith Davis	Ecan Energy Services Inc.	Office: 519-627-3824
-------------	---------------------------	----------------------

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**

Enbridge Gas Distribution Inc.

Fax: 519-627-5306
 Cell: 519-437-7038
 kmecanen@kent.net

Brian Lackie	Weatherford Fishing Supervisor & Shop Manager	Office: 780-955-7933 Cell: 780-490-8710 brian.lackie@ca.weatherford.com
--------------	---	---

Orval Beam	Orval L. Beam Limited Operations Manager Tank Rentals	Office: 519-436-0164 Fax: 519-436-0164 Cell: 519-436-4801
------------	---	---

Welders:

John Dawson	St. Clair Mechanical President	Office: 519-864-0927 Fax: 519-864-0801 Cell: 519-330-9672
-------------	-----------------------------------	---

Government & Other Agencies

MNRF	Petroleum Resources Centre	Office: 519-873-4634 Fax: 519-873-4645 ogsr.mnr.gov.on.ca
------	----------------------------	---

MOECC	Spill Reporting	1-800-268-6060
-------	-----------------	----------------

MOL	Health & Safety	1-800-265-1676
-----	-----------------	----------------

Oil, Gas & Salt Resources Library		Office: 519-686-2772 Fax: 519-686-7225
-----------------------------------	--	---

Drilling Program

TC 9H (HORIZ. #1) MOORE 4-20-X

Enbridge Gas Distribution Inc.

911 Map & Directions to Nearest Hospital:

10/26/2015 1049 Petrolia Line to Bluewater Health, Sarnia, ON, Canada - Google Maps

Google Maps 1049 Petrolia Line to Bluewater Health, Sarnia, ON, Canada Drive 14.1 km, 16 min

Map data ©2015 Google 2 mi

1049 Petrolia Line
Corunna, ON N0N 1G0, Canada

↑ Head west on Petrolia Line toward Ladysmith Rd
2 min (2.2 km)

[https://www.google.com/maps/dir/1049+Petrolia+Line,+Corunna,+ON+N0N+1G0,+Canada/Bluewater+Health,+Sarnia,+ON,+Canada/@42.9330131,-8... 1/2](https://www.google.com/maps/dir/1049+Petrolia+Line,+Corunna,+ON+N0N+1G0,+Canada/Bluewater+Health,+Sarnia,+ON,+Canada/@42.9330131,-8...)

Drilling Program

TC 9H (HORIZ. #1) MOORE 4-20-X

Enbridge Gas Distribution Inc.

Drilling Program

TC 9H (HORIZ. #1) MOORE 4-20-X

Enbridge Gas Distribution Inc.


10/26/2015

1049 Petrolia Line to Bluewater Health, Sarnia, ON, Canada - Google Maps

Turn right onto ON-40 N
4 min (5.5 km)

Take Vidal St S and Hwy 40B to London Rd/Route 16 in Sarnia
10 min (6.4 km)

- 3. ON-40 N turns left and becomes Churchill Rd
450 m
- 4. Turn right onto Tashmoo Ave
1.0 km
- 5. Turn left onto Kenny St
39 m
- 6. Turn right onto Vidal St S
1.6 km
- 7. Vidal St S turns slightly right and becomes Hwy 40B
2.4 km
- 8. Turn right onto London Rd/Route 16
850 m
Destination will be on the right



Blue Water Health

Canada

These directions are for planning purposes only. You may find that construction projects, traffic, weather, or other events may cause conditions to differ from the map results, and you should plan your route accordingly. You must obey all signs or notices regarding your route.

Live traffic

Fast ■ ■ ■ Slow

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**

Enbridge Gas Distribution Inc.

Section 2.0 - Geological Prognosis**TC 9H Moore**

County: Lambton

Twp: Moore

Conc: X

Lot: 20

Tract: 5

Survey Co-ordinates:**4748698 Northig****387377
Easting****Elevation: 197.3m**

Formation	Top	Elevation	Thickness	Gas	Oil	Water	Pressure
K.B.	0.0	201.3	4.6				
Drift	4.0	197.3	41.4			Fresh @ 45m	
Kettle Point	45.4	155.9	30.4				
Hamilton	75.8	125.5	83.9				
Dundee	159.7	41.6	34.1				
Detroit River	193.8	7.5	110.3			Sulphur @199m	
Bois Blanc	304.1	-102.8	36.4				
Bass Islands	340.5	-139.2	53.6				
G-Shale	394.1	-192.8	5.8				
F-Shale	399.9	-198.6	99.8				
E-Carbonate	499.7	-298.4	25.0				
D-Salt	524.7	-323.4	8.9				
C-Shale	533.6	-332.3	23.5				
B-Salt	557.1	-355.8	59.5				
A-2 Carbonate	616.6	-415.3	30.3				
A-2 Anhydrite	646.9	-445.6	6.2				
Guelph	653.1	-451.8	200±	XX			2400 kPa

Note: Prognosis with TVD tops.**Note:** TC1 Moore 20-X and TC4 Moore 20-X used to build prog

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**

Enbridge Gas Distribution Inc.

Section 3.0 - Casing and Cementing Summary

Section 3.1 - Summary

Hole Size (mm)	Casing Size (mm)	Casing Grade	Casing Weight (kg/m)	Setting Depth (mKB)	How Set
508	508	LS	158.47	46	Driven – cement squeeze if necessary
508	406	LS	96.42	61	Cemented to surface with 100% excess Class G 0-1-0 cement + 2 – 3% CaCl ₂
375	298	J-55	69.94	405	Cemented to surface with Class ‘G’ 0-1-8% plus 1 to 3% CaCl ₂ , followed by Class ‘G’ neat cement plus 1 to 3% CaCl ₂ . Cement volumes will be calculated with a 50% excess- gel cement and 30% excess – neat cement. Depending upon hole conditions, consideration may be given to running thixotropic cement plus additional loss circulation materials, across porous zone(s).
270	219	J-55	47.62	649m TVD 663.63 mMD	Cemented to surface with Class ‘G’ 0-1-0% plus 1 to 2% CaCl ₂ plus 10% NaCl. Cement volumes will be calculated with a 50% excess on the open hole section and 30% excess on the cased hole section.


Main Hole: 200mm open hole will be drilled from 649m TVD at 47.5⁰ and will reach 90⁰ at 681mTVD (754.73mMD) and will be drilled horizontally for approximately 182m to a TD of 681mTVD (940mMD) at 90⁰.

Drilling Program

TC 9H (HORIZ. #1) MOORE 4-20-X

Enbridge Gas Distribution Inc.

Section 3.2 - Wellbore Diagram



Drilling Program


TC 9H (HORIZ. #1) MOORE 4-20-X

Enbridge Gas Distribution Inc.

Section 3.3 - Wellhead Summary

Weatherford 13.8 MPa Wellhead:

- 406mm x 425.5mm slip on casing bowl (for BOP installation)
- 298mm x 340mm slip on casing bowl
- 340mm x 228.6mm spool c/w 2 gate valves on side outlets
- 203.2mm ANSI 900 Cameron Grove full port ball valve



Drilling Program
TC 9H (HORIZ. #1) MOORE 4-20-X

Enbridge Gas Distribution Inc.

Section 3.4 - Directional Planning Report


4

5D Plan Report

ENBRIDGE GAS

Field Name: MOORE
Site Name: TRACT 5, LOT 20, CONC X, TWP MOORE, COUNTY LAMBTON
Well Name: TC 9H
Plan: P1:V6

30 September 2015



5D Plan Report

5D SD_Reporting 8.11.7.23 64-bit : 30 September 2015, 13:57:38 UTC

Weatherford International Limited

Drilling Program

TC 9H (HORIZ. #1) MOORE 4-20-X

Enbridge Gas Distribution Inc.

2

TC 9H

Map Units: m
Company Name: ENBRIDGE GAS
Vertical Reference Datum (VRD): Mean Sea Level
Projected Coordinate System: NAD83 / UTM zone 17N
Comment:

Units: m
North Reference: True
Convergence Angle: -0.94
Position: Northing: 4748698.00m
Eastings: 387377.00m
Latitude: 42.882579221
Longitude: -82.379102423
Elevation above MSL: 197.30 m
Comment:

Slot: TC 9H
Position (Relative to Site Centre): Northing: 4748698.00m
Eastings: 387377.00m
Latitude: 42.882579221
Longitude: -82.379102423
Slot TVD Reference: Ground Elevation
Elevation above MSL: 197.30m
Comment:

Well: TC 9H
Type: Main well
File Number:
UWT: Plan: P1:V6
Closure Distance: 306.444m
Comment:
Vertical Section: Position of Origin (Relative to Slot centre)
+N/-S: 0.00m
Closure Azimuth: 8.83°
Magnetic Parameters: +E/-W: 0.00m
Model: b9gm2015
Field Strength: 54039.8nT
Az: 8.83°
Declination: -8.38°
Dip: 69.62°
Date: 15/Sep/2015

Drill floor: Plan: P1:V6
Rig Height (Drill Floor): 4.00m
Elevation above MSL: 201.30m
Inclination: 0.00°
Azimuth: 0.00°

Plan Archive:

Plan Folder	Date	Comment	Plan	Date	Comment
P1	15/Sep/2015		P1:V1 P1:V2 P1:V3	15/Sep/2015 23/Sep/2015 23/Sep/2015	

Drilling Program
TC 9H (HORIZ. #1) MOORE 4-20-X

Enbridge Gas Distribution Inc.

3

5D Plan Report

Plan Archive:		Plans		Comment	
Plan Folder	Date	Plan	Date	Comment	
		P1.V4 P1.V5 P1.V6	24/Sep/2015 24/Sep/2015 24/Sep/2015	STRAIGHT BUILD ADJUSTED D/LEGS	

Wellpath created using minimum curvature.

File Point: MD: 0.00m Inclin: 0.00° Azimuth: 0.00° TVD: 0.00m North Offset: 0.00m East Offset: 0.00m

Interpolated Points: (Relative to Slot centre)(TVD relative to Drill Floor)

Comment	MD (m)	Inc (°)	Az (°)	TVD (m)	SS Elevation (m)	N. Offset (m)	E. Offset (m)	Northing (m)	Easting (m)	VS (m)	DLS (°/30m)	T. Face (°)	B. Rate (°/30m)	T. Rate (°/30m)
	0.00	0.00	0.00	0.00	201.30	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
KETTLE POINT	30.00	0.00	0.00	30.00	171.30	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	45.40	0.00	0.00	45.40	155.90	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
HAMILTON :	60.00	0.00	0.00	60.00	141.30	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	75.80	0.00	0.00	75.80	125.50	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	90.00	0.00	0.00	90.00	111.30	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	120.00	0.00	0.00	120.00	81.30	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	150.00	0.00	0.00	150.00	51.30	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
DUNDEE :	159.70	0.00	0.00	159.70	41.60	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	180.00	0.00	0.00	180.00	21.30	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
DETROIT RIVER :	193.80	0.00	0.00	193.80	7.50	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	210.00	0.00	0.00	210.00	-8.70	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	240.00	0.00	0.00	240.00	-38.70	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	270.00	0.00	0.00	270.00	-68.70	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	300.00	0.00	0.00	300.00	-98.70	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
BOIS BLANC :	304.10	0.00	0.00	304.10	-102.80	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	330.00	0.00	0.00	330.00	-128.70	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
BASS ISLANDS :	340.50	0.00	0.00	340.50	-139.20	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	360.00	0.00	0.00	360.00	-158.70	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
G-SHALE :	390.00	0.00	0.00	390.00	-188.70	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	394.10	0.00	0.00	394.10	-192.80	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
F-SHALE :	399.90	0.00	0.00	399.90	-198.60	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	420.00	0.00	0.00	420.00	-218.70	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	450.00	0.00	0.00	450.00	-248.70	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
	480.00	0.00	0.00	480.00	-278.70	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00

Weatherford International Limited

5D 5D_Reporting 8.1.7.23 64-bit : 30 September 2015, 13:57:38 UTC

Drilling Program
TC 9H (HORIZ. #1) MOORE 4-20-X

Enbridge Gas Distribution Inc.

SD Plan Report

Interpolated Points: (Relative to Slot centre)(TVD relative to Drill Floor)														
Comment	MD (m)	Inc (°)	Az (°)	TVD (m)	SS Elevation (m)	N. Offset (m)	E. Offset (m)	Northing (m)	Easting (m)	VS (m)	DLS (°/30m)	T. Face (°)	B. Rate (°/30m)	T. Rate (°/30m)
E-CARBONATE	499.70	0.00	0.00	499.70	-298.40	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
D-SALT :	510.00	0.00	0.00	510.00	-308.70	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
KOP	524.70	0.00	0.00	524.70	-323.40	0.00	0.00	4748698.00	387377.00	0.00	0.00	0.00	0.00	0.00
C-SHALE :	533.60	0.86	355.00	533.60	-332.30	0.02	-0.00	4748698.02	387377.00	0.02	10.75	355.00	10.75	0.00
B-SALT :	540.00	3.15	355.00	540.00	-338.70	0.24	-0.02	4748698.24	387376.98	0.24	10.75	0.00	10.75	0.00
A-2	557.21	9.32	355.00	557.10	-355.80	2.10	-0.18	4748700.11	387376.85	2.05	10.75	0.00	10.75	-0.00
CARBONATE :	570.00	13.90	355.00	569.62	-368.32	4.67	-0.41	4748702.67	387376.67	4.55	10.75	0.00	10.75	0.00
	600.00	24.65	355.00	597.90	-395.60	14.52	-1.27	4748712.54	387375.97	14.15	10.75	0.00	10.75	-0.00
	621.29	32.28	355.00	616.60	-415.30	24.62	-2.15	4748722.65	387375.25	24.00	10.75	0.00	10.75	-0.00
	630.00	35.40	355.00	623.83	-422.53	29.45	-2.58	4748727.49	387374.91	28.71	10.75	0.00	10.75	0.00
	660.00	46.15	355.00	646.52	-445.22	48.94	-4.28	4748747.01	387373.52	47.71	10.75	0.00	10.75	-0.00
	660.56	46.35	355.00	646.90	-445.60	49.34	-4.32	4748747.41	387373.49	48.10	10.75	0.00	10.75	-0.00
	663.63	47.45	355.00	649.00	-447.70	51.58	-4.51	4748749.65	387373.33	50.28	10.75	0.00	10.75	-0.00
	669.87	50.37	355.00	653.10	-451.80	56.26	-4.92	4748754.34	387373.00	54.84	14.01	0.00	14.01	-0.00
	690.00	59.77	355.00	664.61	-463.31	72.69	-6.36	4748770.78	387371.83	70.85	14.01	0.00	14.01	0.00
	720.00	73.78	355.00	676.42	-475.12	100.08	-8.76	4748796.21	387369.88	97.55	14.01	0.00	14.01	0.00
	750.00	87.79	355.00	681.21	-479.91	129.51	-11.33	4748822.68	387367.79	126.23	14.01	0.00	14.01	0.00
	754.73	90.00	355.00	681.30	-480.00	134.22	-11.74	4748832.40	387367.46	130.83	14.01	0.00	14.01	0.00
	780.00	90.00	3.42	681.30	-480.00	159.46	-12.09	4748857.64	387367.52	155.72	10.00	90.00	0.00	10.00
	810.00	90.00	13.42	681.30	-480.00	189.10	-7.70	4748887.20	387372.40	185.68	10.00	90.00	0.00	10.00
	840.00	90.00	23.42	681.30	-480.00	217.53	1.77	4748915.47	387382.33	215.22	10.00	90.00	0.00	10.00
	854.76	90.00	28.34	681.30	-480.00	230.81	8.21	4748928.64	387388.99	229.33	10.00	90.00	0.00	10.00
	870.00	90.00	28.34	681.30	-480.00	244.22	15.44	4748941.93	387396.44	243.69	0.00	0.00	0.00	0.00
	900.00	90.00	28.34	681.30	-480.00	270.62	29.68	4748966.10	387411.11	271.97	0.00	0.00	0.00	0.00
	930.00	90.00	28.34	681.30	-480.00	297.03	43.93	4748994.27	387425.79	300.25	0.00	0.00	0.00	0.00
	936.57	90.00	28.34	681.30	-480.00	302.81	47.05	4749000.00	387429.00	306.44	0.00	0.00	0.00	0.00

Formation Points: (Relative to Slot centre)(TVD relative to Drill Floor)									
Name	MD (m)	Inc (°)	Az (°)	TVD (m)	SS Elevation (m)	N. Offset (m)	E. Offset (m)	Northing (m)	Easting (m)
KETTLE POINT	45.40	0.00	0.00	45.40	155.90	0.00	0.00	4748698.00	387377.00
HAMILTON	75.80	0.00	0.00	75.80	125.50	0.00	0.00	4748698.00	387377.00
DUNDEE	159.70	0.00	0.00	159.70	41.60	0.00	0.00	4748698.00	387377.00
BOIS BLANC	304.10	0.00	0.00	193.80	7.50	0.00	0.00	4748698.00	387377.00
BASS ISLANDS	340.50	0.00	0.00	304.10	-102.80	0.00	0.00	4748698.00	387377.00
G-SHALE	394.10	0.00	0.00	340.50	-139.20	0.00	0.00	4748698.00	387377.00
F-SHALE	399.90	0.00	0.00	394.10	-192.80	0.00	0.00	4748698.00	387377.00
				399.90	-198.60	0.00	0.00	4748698.00	387377.00

Weatherford International Limited

5D SD_Reporting 8.1.7.23 64-bit : 30 September 2015, 13:57:38 UTC

Drilling Program

TC 9H (HORIZ. #1) MOORE 4-20-X

Enbridge Gas Distribution Inc.

5


5D Plan Report

Formation Points: (Relative to Slot centre)(TVD relative to Drill Floor)

Name	MD (m)	Inc (°)	Az (°)	TVD (m)	SS Elevation (m)	N. Offset (m)	E. Offset (m)	Northing (m)	Easting (m)
E-CARBONATE	459.70	0.00	0.00	499.70	-298.40	0.00	0.00	4748698.00	387377.00
D-SALT	524.70	0.00	0.00	524.70	-323.40	0.00	0.00	4748698.00	387377.00
C-SHALE	533.60	0.86	355.00	533.60	-332.30	0.02	-0.00	4748698.02	387377.00
B-SALT	557.21	9.32	355.00	557.10	-355.80	2.10	-0.18	4748700.11	387376.85
A-2 CARBONATE	621.29	32.28	355.00	616.60	-415.30	24.62	-2.15	4748722.65	387375.25
A-2 ANHYDRITE	660.56	46.35	355.00	646.90	-445.60	49.34	-4.32	4748747.41	387373.49
GUELPH	669.87	50.37	355.00	653.10	-451.80	56.26	-4.92	4748754.34	387373.00

Drilling Program TC 9H (HORIZ. #1) MOORE 4-20-X

Enbridge Gas Distribution Inc.



Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**Enbridge Gas Distribution Inc.

SECTION 4.0 - DRILLING PROCEDURES**Section 4.1 - Pre Spud**

1. Fresh Water Well Samples

Obtain samples from all fresh water wells located within a 750 metre radius of the proposed well. Have routine water analysis done on all water samples by an independent laboratory in Sarnia. Ensure that copies of these reports are placed in the well files in Enbridge's office

2. Site Preparation

Prepare drilling location as follows:

- a. Locate all drainage tiles crossing lease area
- b. Strip and properly stock pile all soil from the lease
- c. Cut, block and divert drainage tiles as required
- d. Construct adequate berms around lease and access road as required

3. Government Notification of Spud

48 hours prior to spud, notify the Ministry of Natural Resources and Forestry – Petroleum Resources Section by fax @ (519) 873 – 4645 of the date of commencement of drilling operations

4. Signs

Install rig signs on access road to lease.

5. Safety Meeting

Conduct a pre-spud safety meeting for Cable Tool and Rotary crews. Tool push and all crewmembers must be present. A similar meeting shall be conducted with the remaining crew(s) as they come on duty. Additional safety meetings shall be conducted at the Wellsite Supervisor's discretion.

Section 4.2 - Conductor Casing

1. Drilling Method

Move in and rig up Cable Tool Rig. Measure and record the distance from RF to ground and the RF elevation – include these measurements on the tower sheets and the daily report. Drill and drive 508mm casing to bedrock, to an approximate depth of 46m. Note any occurrence of water and record type of water, depth encountered, and static level of water and/or flow rate. If fresh water is

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**Enbridge Gas Distribution Inc.

encountered during drilling, the well must be bail tested for at least 15 minutes, after the casing is landed, to ensure that the fresh water has been shut-off. If the fresh water has not been shut-off, contact Enbridge's office and be prepared to perform a cement squeeze as per Enbridge's requirements.

2. Cement Squeeze (if necessary)

If fresh water is found in the drift and is not shut-off by the conductor casing, a flow rate will be established and a cement squeeze will be performed, using the cement volumes determined by Enbridge. Wait on cement 12 hours and bail the hole dry and monitor the well for at least 15 minutes to determine if the water has been shut-off. If necessary, the process will be repeated until the water is shut-off.

Section 4.3 - Surface Hole & Surface Casing**1. Drilling Method**

Drill a 508mm hole 15 metres into the Kettle Point formation, to an approximate depth of 61m. Ensure that drill cutting samples are taken every 3 metres and placed in the sample bags provided by the Ministry of Natural Resources and Forestry. The sample bags must be labeled with the well name, Township, Lot, Concession and Enbridge's name. Record on daily drilling reports any influx of fluids and/or hydrocarbons, static levels, pressures and any unusual hole conditions.

2. Casing Installation

Depending upon hole conditions encountered, the 406mm casing will be run in the following manner:

- Texas Shoe on bottom of first joint
- Centralizers on the top and bottom of the first joint and coincident with the shoe of the conductor casing
- 406mm casing to surface

3. Cementing Procedures

Move in and rig up Cementers. Ensure pressure recorder is rigged in and serviceable. Pressure charts will be attached to the job ticket. Conduct a pre-job safety meeting to confirm volumes and procedures. Establish circulation using pump truck. The casing and the hole will be circulated with fresh water for 15 minutes to clean the borehole and to fill the casing and hole prior to cementing. Pressure test surface equipment to 14 MPa. Ensure that preflush and mix water are from a clean source and that the water truck are also clean. Pump preflush of 2.0m³ of fresh water, with the addition of loss circulation material if necessary. Ensure that a minimum of 4 cement samples are taken and represent the cement at the beginning, middle and end of the cement job. Mix and pump

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**

Enbridge Gas Distribution Inc.

sufficient Class 'G' 0-1-0% cement plus 2 to 3% CaCl₂ with a density of 1901 kg/m³ to cement the casing to surface with 100% excess. Displace cement with fresh water – under displace cement such that the bottom joint of 406mm casing is full of cement. Shut-in cementing valve at surface and set casing on bottom. Wait on cement a minimum of 24 hours before installing the BOPs.

4. Arrange to have surface hole cuttings solidified and then disposed in an approved manner.
5. Release the cable tool rig.

Section 4.4 - Intermediate Hole & Intermediate Casing**1. BOP Installation and Pressure Testing**

Move in and rig up rotary rig. Measure and record the distance from KB to ground and the KB elevation – include these measurements on the tower sheets and the daily report.

Install 406mm x 425.5mm slip on weld casing bowl and temporarily blind flange, to secure well until drilling resumes with rotary rig. Install Class A (Rotary) BOPs as per MNRF requirements. After BOPs are installed and the cement samples indicate that the cement is competent, the rig will proceed to pressure test the BOPs, casing and shoe. Pressure test casing and each component of the BOPs as per Section 6.2. After successfully pressure testing the BOPs and casing, drill out cement and 0.5m of new formation and conduct a PIT, with the hole full of fresh water, using a bottom hole pressure equivalent to 18 kPa/m.

2. Drilling Method

Drill a 375mm hole with fresh water, 5m ± into the F Shale formation, to an approximate depth of 405m. Notify Geologist 12 hours in advance of reaching intermediate casing point, so that they can be on site to determine the proper casing setting depth. When casing setting depth has been determined, circulate the hole clean and run a deviation survey. Perform a flow check prior to tripping and strap out of the hole. Fast tripping of the drill string is to be avoided in order to eliminate high annular velocities, pressure surges and swabbing (maximum rate of 27 metres per minute). Keeping hole full of fluid, trip out of hole and laydown bottom hole assembly and stand back drill collars and drill pipe,

The potential for loss circulation exists while drilling through the Detroit River formations (Lucas and Amherstburg formations). If loss circulation is encountered use the loss circulation contingency program located in Section 4.7. Note all lost circulation intervals and monitor and record fluid loss volumes. If pit fluid must be hauled to disposal, keep solid content to a minimum to reduce costs.

Ensure that drill cutting samples are taken every 3 metres and placed in the sample bags provided by the Ministry of Natural Resources and Forestry. Surveys are to be taken every 100 metres. Deviation shall not exceed 1 degree per 100 metres and shall not exceed 2 degrees at any point.

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**Enbridge Gas Distribution Inc.

Record on daily tower sheets any influx of fluids (water and/or hydrocarbons), loss circulation (rate and depth) and/or any unusual hole conditions.

3. Casing Installation

Ensure that the threads are protected while hoisting casing to the floor. Drift all casing prior to running the casing in the well and apply proper API make-up torque to each connection.

Depending upon hole conditions encountered, the 298mm casing will be run in the following manner:

- Guide shoe
- 298mm joint of casing
- 298mm Float Insert or Float Collar
- Tack weld guide shoe, float collar and bottom 2 joints and use API modified pipe dope on all connections
- Centralizers will be installed one metre above the guide shoe, over the bottom of the first 2 collars and every 5 joints to surface
- 298mm casing to surface

4. Cementing Procedures

Move in and rig up Cementers. Ensure pressure recorder is rigged in and serviceable. Pressure charts will be attached to the job ticket. Conduct a pre-job safety meeting to confirm volumes and procedures. Establish circulation using pump truck. The casing and the hole will be circulated with fresh water for 15 minutes to clean the borehole and to fill the casing and hole prior to cementing. Pressure test surface equipment to 14MPa for 10 minutes. Preflush and mix water must be obtained from a clean source and the water trucks must be uncontaminated. Pump 3.0m³ citric preflush with a 1.0m³ fresh water spacer, with the addition of loss circulation material if necessary. Ensure that a minimum of 4 cement samples is taken and represent the cement at the beginning, middle and end of the cement job. Mix and pump sufficient 0-1-8% Class 'G' plus 1 to 3% CaCl₂ (50% excess) followed by 0-1-0% Class 'G' cement plus 1 to 3% CaCl₂ (30% excess) to cement casing to surface. Depending upon the severity of the loss circulation zones, thixotropic cement with additional loss circulation materials may be used to cover the loss zone. If there are no cement returns to surface, a feed rate will be established and the annulus will be grouted to surface. Drop wiper plug and displace cement and bump plug to 3.5 Mpa over final pumping pressure – do not exceed 60% of internal yield pressure of casing. Once plug is bumped bleed off casing pressure, close casing valves and bleed off surface line pressure and wash out BOPs. Wait on cement a minimum of 24 hours before slacking off casing. Remove 406mm x 425.5mm casing bowl and install the 298mm x 346.1mm casing bowl on the 298mm casing.

Section 4.5 - Production Hole & Production Casing**1. Pressure Testing**

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**

Enbridge Gas Distribution Inc.

Check cement samples for hardness – if cement samples are set to the satisfaction of the Wellsite Supervisor, proceed with installation of the BOPS. Install Class B (Rotary) BOPs as per MNRF requirements on 298mm casing bowl. Stump test BOPs prior to installation. After BOPs are installed and the cement samples indicate that the cement is competent, the rig will proceed to pressure test the BOPs, casing and shoe. Pressure test casing and each component of the BOPs as per Section 6.2. After successfully pressure testing the BOPs and casing, drill out cement and 0.5m of new formation and conduct a PIT, with the hole full of fresh water, using a bottom hole pressure equivalent to 18 kPa/m.

2. Drilling Method

Drill a 270mm conventional hole to the kick-off point of 531m±. Brine will be used to drill this portion of the well, to prevent the dissolution of the salt layers. Ensure that drill cutting samples are taken every 3 metres and placed in the sample bags provided by the Ministry of Natural Resources and Forestry. Record on daily tower sheets any influx of fluids (water and/or hydrocarbons), loss circulation (rate and depth) and any unusual hole conditions.

At the kick-off point, circulate the hole clean, run a deviation survey and strap out of the hole. Pick up directional equipment and run in the hole with the directional bottom hole assembly. Prior to penetrating the A-2 Carbonate, the Wellsite Geologist and Wellsite Supervisor must be on-site and a BOP drill shall be completed to familiarize all on-site personnel with the proper procedures.

Drill a 270mm directional hole a minimum of 2 metres into the A-2 Anhydrite formation, at an approximate depth of 649mTVD / 663.6mMD at an angle of 47.5°. The final casing point will be determined by the Wellsite Geologist. At casing total depth, circulate the hole clean and perform a flow check prior to tripping. Fast tripping of the drill string is to be avoided in order to eliminate high annular velocities, pressure surges and swabbing (maximum rate of 27 metres per minute). Keeping hole full of brine, trip out of hole – laydown bottom hole assembly, drill pipe and drill collars.

3. Casing Installation

Ensure that the threads are protected while hoisting casing to the floor. Drift all casing prior to running the casing in the well and apply proper API make-up torque to each connection.

Depending upon hole conditions encountered, the 219mm casing will be run in the following manner:

- Guide shoe
- 219mm joint of casing
- Float Insert or Float Collar
- Bottom 150 metres of 219mm casing shall have solid stand-off centralizers run on every other joint – above and below the collar

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**

Enbridge Gas Distribution Inc.

- Tack weld guide shoe, float collar and bottom 4 joints and use API modified pipe dope on all connections
- Centralizers will be installed on remaining casing – on every 5th joint to surface
- 219mm casing to surface

4. Cementing Procedures

Move in and rig up Cementers. Ensure pressure recorder is rigged in and serviceable. Pressure charts will be attached to the job ticket. Conduct a pre-job safety meeting to confirm volumes and procedures.

Establish circulation using pump truck. The casing and the hole will be circulated with brine for 15 minutes to clean the borehole and to fill the casing and hole prior to cementing. Pressure test surface equipment to 14 MPa for 10 minutes. Preflush and mix water must be obtained from a clean source and the water trucks must be uncontaminated. Pump preflush of 3.0m³ of clean brine, with the addition of loss circulation material if necessary. Ensure that a minimum of 4 cement samples is taken and represent the cement at the beginning, middle and end of the cement job. Mix and pump sufficient Class 'G' 0-1-0% cement plus 10% NaCl, to cement the 219mm casing to surface plus 50% excess over open hole and 30% excess in cased hole. Drop wiper plug and displace cement with fresh water and bump plug to 3500 kPa over final pumping pressure – do not exceed 60% of internal yield pressure of casing. Once plug is bumped bleed off casing pressure, close casing valves and bleed off surface line pressure. Wash out BOPs and split BOP stack at 346mm flange, install 219mm slips and set slips in casing bowl. Wait on cement a minimum of 48 hours and cut casing and remove BOPs. Cut and bevel 219mm casing and install primary and secondary seals. Install 346mm x 228.6mm spool piece and test wellhead seals to 14 Mpa for 10 minutes.

Section 4.6 - Main Hole**1. Installation of the BOPs**

Check cement samples for hardness – if cement samples are set to the satisfaction of the Wellsite Supervisor, proceed with installation of the BOPS. Install Class B (Rotary) BOPs as per MNR requirements on 228.6mm flange. After BOPs are installed and the cement samples indicate that the cement is competent, move in and rig up the Wireline Company and run a cement bond log (both pressure (7000kPa) and non-pressure pass) over the 219mm casing. After the cement bond log is completed and the cement job is deemed successful, the rig will proceed to pressure test the BOPs, casing and shoe. Pressure test casing and each component of the BOPs as per Section 6.2. After successfully pressure testing the BOPs and casing, drill out cement and 0.5m of new formation and conduct a PIT, with the hole full of fresh water, using a bottom hole pressure equivalent to 18 kPa/m.

2. Logging

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**Enbridge Gas Distribution Inc.

Move in and rig up Wireline Company. With hole full of fresh water, run a casing inspection log over the 219mm casing. Rig out Wireline Company and release.

3. Drilling Method

Drill a 200mm hole with fresh water system – ensure that the frac tank is full of fresh water and water trucks have been put on alert. Drill from 649mTVD (663.6mMD) at 47.5⁰ to 90⁰ at 681.3mTVD (754.7mMD) and continue drilling to a depth of 940mMD (681mTVD) for a horizontal distance of approximately 180m. After drilling 2 lengths of drill pipe, work the newly drilled hole to ensure that there will not be any issues running in and out of the open hole. A high vis sweep with floc will be added at each connection to assist with hole cleaning.

Ensure that Wellsite Geologist is on site to monitor cuttings and liaise with Directional Drillers concerning the path of the horizontal well. Drill to TD indicated by Wellsite Geologist. At TD pump a final sweep and if possible, circulate hole until clean returns are observed at surface.

The potential for loss circulation exists while drilling through the Guelph formation. If loss circulation is encountered, use the loss circulation contingency program located in Section 4.7. Note all lost circulation intervals and monitor and record fluid loss volumes.

Pull out of hole with drilling assembly and laydown drill pipe, drill collars and bottom hole assembly. Move in and rig up Wireline Company complete with full lubricators. Run in hole with gauge ring to ensure clear hole to bridge plug setting depth. Run in hole with wireline set, retrievable 219mm bridge plug and place as deep as possible in the 219mm casing and pull out of hole with the setting tool. Fill hole with fresh water and pressure test plug to 7000 kPa for 10 minutes. If the plug does not hold pressure, be prepared to set another 219mm retrievable bridge plug. Release Wireline Company and release Directional Drilling Company.

Nipple down BOPs and install 315mm x 900 ANSI full port ball (master) valve. Close master valve and install 315mm blind flange. Install pressure recorder, ensure that the well is full of fresh water and pressure test casing, wellhead and master valve to a surface pressure of 11,000 kPa for a minimum of 4 hours. Call Enbridge Office with the results.

4. Rig down rotary rig and move off of location.
5. Restore wellsite to Enbridge's specifications.

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**Enbridge Gas Distribution Inc.

Section 4.7 - Loss Circulation Procedure

1. Before drilling out the casing shoe:
 - a. Identify sources and location of fresh water and/or brine, loss circulation materials and weight materials
 - b. Ensure BOPs and manifold are properly installed
 - c. Ensure auxiliary tanks are connected to the pumping system and a standby mud pump is hooked up for annular injection in case of severe loss circulation (so that fluid can be pumped down both the drill pipe and annulus simultaneously)
 - d. Pressure test BOPs prior to drill out
2. After drilling out shoe:
 - a. Alert water suppliers and haulers
 - b. Ensure adequate amounts of fresh water and/or brine are readily available prior to penetrating the Detroit River and Guelph formations
 - c. Mechanically test BOPs and perform BOP drill prior to penetrating the Detroit River and Guelph formations.
3. Drilling Blind – Detroit River formations:
 - a. In an attempt to maintain or re-establish circulation, pump fluid down both the annulus and the drill pipe simultaneously
 - b. Should severe loss circulation occur while drilling, the thief zone may be plugged with cement and/or loss circulation material at Enbridge's discretion.
4. Drilling Blind – Guelph
 - a. In an attempt to maintain or re-establish circulation, pump fluid down both the annulus and the drill pipe simultaneously
 - b. Make wiper trips or reciprocate the drill pipe to maintain a clean hole every joint or two as directed by the Wellsite Supervisor
 - c. Sweep the hole every 1 to 3 joints
 - d. Use a. and b. in combination
 - e. At TD conduct a final sweep and then trip out BHA

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**Enbridge Gas Distribution Inc.

SECTION 5.0 - REPORTING PROCEDURES**Section 5.1 - Tower Sheets**

Shall be completed daily and shall include:

1. Bit size, fluid type and weight, weight on bit, deviation surveys, depth at the beginning of the shift and end of each shift.
2. Casing size, grade, weight, and number of joints, centralizers, cement baskets, total length and setting depth.
3. Cementing information – Service Company, cement type, amount, slurry density, additives, annular fluid returns, volume of displacement fluid and plug down time.
4. Water, gas or oil – type, depth encountered depth of sample collected and the static level and/or rate of flow.
5. Pressure tests – individually, surface pressures, fluid density used in the tests, bleed-off rate and duration of test.
6. Logging Details – type and interval.
7. Abandonment details – intervals, amount and type of cement, top of plug and time felt.
8. Rig release – date and time.

Section 5.2 – Worker Injury

Immediately provide first aid to the injured party and ensure that all personnel are removed from harm's way. Secure the area and ensure that the site is preserved in case an investigation is required.

Every work related accident or injury shall be reported immediately to the Wellsite Supervisor. The Supervisor shall immediately contact the Enbridge Gas Distribution Inc. Office, specifically the Senior Project Geologist, followed by the Reservoir Field Supervisor. The verbal report shall be followed with a written report, including but not limited to, the Contractor's Accident/Incident Investigation form. The affected Contractor is responsible to contact the proper authorities concerning the accident.

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**Enbridge Gas Distribution Inc.

SECTION 6.0 - SAFETY AND PROCEDURES**Section 6.1 - General Safety**

1. All works at the Wellsite shall be in compliance with the Occupational Health and Safety Act and the Oil, Gas & Salt Resources Act and all associated legislation. In addition, all work at the Wellsite shall be done in compliance with good oil field practices. All verbal notifications given to and approvals received from government agencies shall be recorded on the tower sheets.
2. Safety meetings are to be held with each crew, at the start of the well and periodically while drilling – meetings shall also be held prior to cementing and upon arrival of the logging company, prior to commencement of directional drilling operations and prior to penetrating the Detroit River formations and the A-2 Carbonate formation.
3. The Wellsite Supervisor shall ensure that the operations are in compliance with all applicable government regulations and shall complete daily walk around rig inspections.

Section 6.2 – Well Control

All blowout prevention systems are to be in strict compliance with MNR regulations. The function and pressure testing guidelines required by the regulatory bodies (such as daily function testing of the pipe rams) will be strictly adhered to.

1. All pressure tests of blowout prevention equipment will be conducted with fresh water and will be conducted in 2 stages – low and high pressure. It is essential that the low pressure test be done first, to prevent the high pressure test from healing leaks that would have been noted at low pressures.
2. The following pressure test will be conducted with fresh water prior to drilling out each casing string and the results recorded on the tower sheets and daily reports:
 - a. The blind rams, kill lines and choke manifold will be tested individually for 10 minutes each to:
 - i. Intermediate casing 2000 kPa low & 9000 kPa high
 - ii. Production casing 2000 kPa low and 10000 kPa high
 - b. Run in hole with BHA, drill pipe and drill collars and pressure test the casing string, pipe rams, kelly cock, stand pipe, swivel, safety valves, etc. will be tested individually for 10 minutes each to:
 - i. Surface casing 1400 kPa low and 3500 kPa high (using AP)
 - ii. Intermediate casing 2000kPa low & 9000 kPa high
 - iii. Production casing 2000 kPa low and 10000 kPa high

Drilling Program**TC 9H (HORIZ. #1) MOORE 4-20-X**Enbridge Gas Distribution Inc.



- c. The annular preventer will be tested for 10 minutes to
 - i. Surface casing 1400 kPa low and 3500 kPa high
 - ii. Intermediate casing 2000 kPa low & 9000 kPa high
 - iii. Production casing 2000 kPa low and 10000 kPa high
3. Upon drilling out the casing, drill 0.5m to 1.0m of new hole and test the formation, with the hole full of fluid, to a minimum bottom hole pressure of 18 kPa per metre.
4. After one day of drilling below the casing shoe, check the entire blowout prevention system and tighten all bolts.
5. Crews should be kept alert and familiar with the blowout prevention equipment. At least one member of the crew who has been trained in blowout prevention and well control procedures must be on the floor at all times.
6. Conduct blowout prevention drills prior to drilling out casing and once per week thereafter. Ensure that the drills are recorded in the tour book.
7. The blowout preventers are to be function tested once per tour. Ensure that the function test is recorded on the tower sheets.

PLAN OF PROPOSED WELL
LOT 20
CONCESSION 10
 GEOGRAPHIC TOWNSHIP OF MOORE
 TOWNSHIP OF ST. CLAIR
 COUNTY OF LAMBTON

SCALE 1:5000

NOTE (WELL SITE) CO-ORDINATES
 LATITUDE N.42°52'57.285" LONGITUDE W.82°22'44.769"
 U.T.M. N.4 748 698.00 E.387 377.00

WELL NAME
 TC 9H (HORIZ. #1) - MOORE - 4 - 20 -10



LEGEND FOR BORES AZIMUTHS AND DISTANCES

TRUE NORTH AZIMUTH	DIST.
1 355°00'00"	51.78 (CASING POINT)
2 355°00'00"	82.96 (HEEL AND START TURN)
3 3°43'45"	49.40
4 19°29'20"	50.20
5 28°20'40"	81.80 BOTTOM HOLE

NOTE GEODETIC HORIZONTAL CONTROL
 U.T.M. CO-ORDINATES ARE GEODETIC (DATUM NAD 83 ORIGINAL) AND REFERRED TO MONUMENTS No.S 693749 AND 693767

NOTE METRIC
 DISTANCES SHOWN ON THIS PLAN ARE IN METERS AND CAN BE CONVERTED TO FEET BY DIVIDING BY 0.3048

PREPARED BY
BRISCO AND O'ROURKE
 SERVING THE PETROLEUM INDUSTRY THROUGHOUT ONTARIO
 WELLS, CONSTRUCTION AND TECHNICAL SURVEYING
 DIGITAL MAPPING
 LAND AND LEASE SURVEYS

OFFICE (519) 351-5073
 CELL (519) 360-2134
 FAX (519) 351-3119
 P.O. BOX 327 - N7M-5K4
 CHATHAM, ONTARIO

NOTE BENCH MARK
 ELEVATIONS ARE REFERRED TO GEODETIC DATUM AND REFERENCE BENCH MARK BEING NO. 81U138 SARNIA
 ELEVATION = 180.512

PREPARED FOR
ENBRIDGE GAS DISTRIBUTION INC.

FILE NO. 14-5068 PLAN NO. ENB6804.DWG

Timothy J. O'Rourke
 OCT. 26, 2015

TIMOTHY J. O'ROURKE C.S.T. A.C.E.T.

AUTHORIZED BY THE MINISTER OF NATURAL RESOURCES UNDER THE PETROLEUM RESOURCES ACT OF ONTARIO

United Parcel Service

Daily Manifest Customer Copy

Exhibit C

Page : 1

ENBRIDGE GAS DISTRIBUTION INC.
500 CONSUMERS RD
NORTH YORK, ON, M2J1P8

UPS SHIPPER NUMBER: 4R7V94
PICK UP RECORD #: 4461011026
DATE SHIPPED: 08/DEC/2015

EDI

Domestic Shipments

Reference	Consignee Information	Service	Postal Code	Zone	Weight	Billed Charge
70.3620.14 GENRL61715-01	ELAINE OAKLEY BELL CANADA UTILITY CIRCULATIONS 100 BOROUGH DRIVE FLOOR 5 SCARBOROUGH, ON, M1P 4W2 CA	Saver	M1P 4W2	500	0	13.20
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.		Total :				13.20

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V940477696330		0		
		Total:	1 Package(s)		13.20
		Grand Total:	1 Package(s)		13.20

United Parcel Service

Daily Manifest Customer Copy

Page : 1

Exhibit C

ENBRIDGE GAS DISTRIBUTION INC.
500 CONSUMERS RD
NORTH YORK, ON. M2J1P8

UPS SHIPPER NUMBER: 4R7V94
PICK UP RECORD #: 4461011015
DATE SHIPPED: 08/DEC/2015

EDI

Domestic Shipments

Reference	Consignee Information	Service	Postal Code	Zone	Weight	Billed Charge
70.3620.14 GENRL61715-01	SHAWN BISSELL BELL CANADA 400 NEWBOLT STREET LONDON, ON. N6E 1K1 CA	Expedited	N6E 1K1	302	0	18.50
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.		Total :				18.50

PACKAGES

Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
1Z4R7V941777696324		0		
Total:	1 Package(s)			18.50
Grand Total:	1 Package(s)			18.50

United Parcel Service

Daily Manifest Customer Copy

Exhibit C

Page : 3

ENBRIDGE GAS DISTRIBUTION INC.
500 CONSUMERS RD
NORTH YORK, ON. M2J1P8

UPS SHIPPER NUMBER: 4R7V94
PICK UP RECORD #: 4562181304
DATE SHIPPED: 07/DEC/2015

EDI

Reference	Consignee Information	Service	Postal Code	Zone	Weight	Billed Charge
70.3620.14 GENRL61715-01	ENBRIDGE 3595 TECUMSEH ROAD RR #1 MOORETOWN, ON. N0N 1M0 CA	Expedited	N0N 1M0	303	0	16.80
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.		Total :				16.80

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777696048		0		

70.3620.14 GENRL61715-01	RICHARD JAMES WELLINGTON 380 ALBERT STREET CORUNNA, ON. N0N 1G0 CA	Expedited	N0N 1G0	303	0	16.80
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.		Total :				16.80

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777696057		0		

70.3620.14 GENRL61715-01	BRUCE KNIGHT & KATHLEEN KNIGHT 1163 PETROLIA LINE RR #1 CORUNNA, ON. N0N 1G0 CA	Expedited	N0N 1G0	303	0	16.80
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.		Total :				16.80

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777696066		0		

70.3620.14 GENRL61715-01	MATTHEW PHILIP HERGOTT 1685 PETROLIA LINE CORUNNA, ON. N0N 1G0 CA	Expedited	N0N 1G0	303	0	16.80
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.		Total :				16.80

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777696075		0		

70.3620.14 GENRL61715-01	KELLY SULLIVAN PLAINS MIDSTREAM CANADA 1182 PLANK ROAD SARNIA RR2, ON. N7T 7H3 CA	Expedited	N7T 7H3	302	0	16.65
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.		Total :				16.65

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777696084		0		

70.3620.14 GENRL61715-01	DOUG MATHANY NOVA CHEMICALS (CANADA) LTD. BOX 3060 SARNIA, ON. N7T 8C7 CA	Expedited	N7T 8C7	302	0	16.65
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.		Total :				16.65

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777696093		0		

United Parcel Service

Daily Manifest Customer Copy

Exhibit C

Page : 2

ENBRIDGE GAS DISTRIBUTION INC.
500 CONSUMERS RD
NORTH YORK, ON, M2J1P8

UPS SHIPPER NUMBER: 4R7V94
PICK UP RECORD #: 4562181304
DATE SHIPPED: 07/DEC/2015

EDI

Reference	Consignee Information	Service	Postal Code	Zone	Weight	Billed Charge
70.3620.14 GENRL61715-01	SCOTT WILLIAM ELLIOTT 2212 LASALLE LINE RR #1	Expedited	N0N 1G0	303	0	16.80
Payment Type: PREPAID		Total :				16.80
Bill to Account: 4R7V94	CORUNNA, ON, N0N 1G0					
Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.	CA					

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777695987		0		

70.3620.14 GENRL61715-01	BRENDA EILEEN ELLIOTT 2212 LASALLE LINE RR #1	Expedited	N0N 1G0	303	0	16.80
Payment Type: PREPAID		Total :				16.80
Bill to Account: 4R7V94	CORUNNA, ON, N0N 1G0					
Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.	CA					

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777695996		0		

70.3620.14 GENRL61715-01	JEFF BARANEK, CLERK THE CORP. OF TOWNSHIP OF ST CLAIR	Expedited	N0N 1M0	303	0	16.80
Payment Type: PREPAID		Total :				16.80
Bill to Account: 4R7V94	1155 EMILY STREET					
Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.	MOORETOWN, ON, N0N 1M0 CA					

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777696002		0		

70.3620.14 GENRL61715-01	GLEN FOX & SANDRA FOX 1210 PETROLIA LINE RR #1	Expedited	N0N 1G0	303	0	16.80
Payment Type: PREPAID		Total :				16.80
Bill to Account: 4R7V94	CORUNNA, ON, N0N 1G0					
Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.	CA					

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777696011		0		

70.3620.14 GENRL61715-01	JAMES ALFRED STENTON 2621 PETROLIA LINE RR #3	Expedited	N0N 1R0	303	0	16.80
Payment Type: PREPAID		Total :				16.80
Bill to Account: 4R7V94	PETROLIA, ON, N0N 1R0					
Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.	CA					

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777696020		0		

70.3620.14 GENRL61715-01	JAMES DOUGLAS O'NEILL 1245 PETROLIA LINE RR #1	Expedited	N0N 1G0	303	0	16.80
Payment Type: PREPAID		Total :				16.80
Bill to Account: 4R7V94	CORUNNA, ON, N0N 1G0					
Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.	CA					

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777696039		0		

United Parcel Service
Daily Manifest Customer Copy

ENBRIDGE GAS DISTRIBUTION INC.
500 CONSUMERS RD
NORTH YORK, ON, M2J1P8

UPS SHIPPER NUMBER: 4R7V94
PICK UP RECORD #: 4562181304
DATE SHIPPED: 07/DEC/2015

EDI

Domestic Shipments

Reference	Consignee Information	Service	Postal Code	Zone	Weight	Billed Charge
70.3620.14 GENRL61715-01	JOE VANOVERBERGHE MINISTRY OF NATURAL RESOURCES & FOR	Expedited	N6E 1L3	302	0	16.65
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.	PETROLEUM OPERATIONS SECTION 659 EXETER ROAD LONDON, ON, N6E 1L3 CA	Total :				16.65

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777695923		0		

70.3620.14 GENRL61715-01	DAVID CRIBBS THE CORP OF THE COUNTY OF LAMBTON	Expedited	N0N 1T0	303	0	16.80
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.	789 BROADWAY STREET BOX 3000 WYOMING, ON, N0N 1T0 CA	Total :				16.80

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777695932		0		

70.3620.14 GENRL61715-01	ESTATE OF PAULINE MARY WELLINGTON	Expedited	N7W 1B8	302	0	16.65
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.	1520 HERITAGE PARK DRIVE SARNIA, ON, N7W 1B8 CA	Total :				16.65

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777695941		0		

70.3620.14 GENRL61715-01	MARY DIANE PEARSON 383 APRIL COURT CORUNNA, ON, N0N 1G0	Expedited	N0N 1G0	303	0	16.80
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.	CA	Total :				16.80

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777695950		0		

70.3620.14 GENRL61715-01	PAUL ERNEST WELLINGTON 1520 HERITAGE PARK DRIVE SARNIA, ON, N7W 1B8	Expedited	N7W 1B8	302	0	16.65
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.	CA	Total :				16.65

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777695969		0		

70.3620.14 GENRL61715-01	NORMAN & JENNIFER O'NEILL 2306 MOORE LINE RR #1	Expedited	N0N 1M0	303	0	16.80
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.	MOORETOWN, ON, N0N 1M0 CA	Total :				16.80

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777695978		0		

United Parcel Service

Daily Manifest Customer Copy

Exhibit C

Page : 4

ENBRIDGE GAS DISTRIBUTION INC.
500 CONSUMERS RD
NORTH YORK, ON, M2J1P8

UPS SHIPPER NUMBER: 4R7V94
PICK UP RECORD #: 4562181304
DATE SHIPPED: 07/DEC/2015

EDI

Reference	Consignee Information	Service	Postal Code	Zone	Weight	Billed Charge
70.3620.14 GENRL61715-01	AIR PRODUCTS CANADA 20 INDIAN ROAD SOUTH SARNIA, ON, N7T 7K2 CA	Expedited	N7T 7K2	302	0	16.65
Payment Type: PREPAID Bill to Account: 4R7V94 Bill to Company: ENBRIDGE GAS DISTRIBUTION INC.		Total :				16.65

PACKAGES	Tracking Number	Delivery Confirmation	Weight	COD Amount	Declared Value
	1Z4R7V941777696100		0		
		Total:	19 Package(s)		318.30
		Grand Total:	19 Package(s)		318.30



Canada

New User | Log-In | Changing Languages | The UPS Store Search Sub

[My UPS](#) [Shipping](#) [Tracking](#) [Freight](#) [Locations](#) [Support](#) [UPS Solutions](#)

Save 20% on UPS Shipping.
Open a UPS account or apply to your existing account.

[Get Details](#)

Tracking Number [Log-In](#) for additional tracking details. [Other Tracking Options](#)

Tracking

Tracking Summary [Print](#) [Help](#)

Select a tracking number to see the full tracking detail.

1Z4R7V940477696330

Delivered	<p>Shipping Information</p> <p>To: SCARBOROUGH, CA</p>
<p>Delivered On: Wednesday, 12/09/2015 at 10:04</p> <p>Left At: Guard</p> <p>Signed By: JACOB</p> <p>Proof of Delivery</p>	<p>Notify me with Updates »</p> <p>Shipped By</p> <p>UPS Express Saver®</p>

1Z4R7V941777696324

Delivered	<p>Shipping Information</p> <p>To: LONDON, CA</p>
<p>Delivered On: Wednesday, 12/09/2015 at 11:58</p> <p>Left At: Receiver</p> <p>Signed By: BILL</p> <p>Proof of Delivery</p>	<p>Notify me with Updates »</p> <p>Shipped By</p> <p>UPS Expedited®</p>

Tracking results provided by UPS: 12/10/2015 15:45 Eastern Time

Subscribe to UPS E-mail: Enter e-mail address [View Examples](#)

Contact UPS

- [Browse Online Support](#)
- [E-mail UPS](#)
- [Call Customer Service](#)

Support

- [Get Started](#)
- [Register](#)
- [Open a Shipping Account](#)
- [Change Your Delivery](#)
- [More Ways to Track](#)

Solutions for:

- [Small Business](#)
- [International Trade](#)
- [International Shipping](#)
- [More..](#)

Other UPS Sites:

Select One

UPS UNITED PROBLEM SOLVERS™

[Home](#) [About UPS](#) [Site Guide](#) [Careers](#) [Pressroom](#) [UPS Global](#) [UPS Mobile](#)



Canada

New User | Log-In | Changing Languages | The UPS Store Search

[My UPS](#) | [Shipping](#) | [Tracking](#) | [Freight](#) | [Locations](#) | [Support](#) | [UPS Solutions](#)

Save 20% on UPS Shipping.
Open a UPS account or apply to your existing account.

Tracking Number

[Log-In](#) for additional tracking details.

Other Tracking Options

Tracking

Tracking Summary

[Print](#) [Help](#)

Select a tracking number to see the full tracking detail.

1Z4R7V941777696048

Delivered

Delivered On:
Tuesday, 12/08/2015 at 14:45

Left At:
Reception

Signed By:
CRAWFORD

[Proof of Delivery](#)

Shipping Information

To:
MOORETOWN, CA

Shipped By

UPS Expedited®

1Z4R7V941777696057

Delivered

Delivered On:
Tuesday, 12/08/2015 at 13:34

Left At:
Met customer man

[Proof of Delivery](#)

Shipping Information

To:
CORUNNA, CA

Shipped By

UPS Expedited®

1Z4R7V941777696066

Delivered

Delivered On:
Wednesday, 12/09/2015 at 18:21

Left At:
Mailbox

[Proof of Delivery](#)

Shipping Information

To:
CORUNNA, CA

Shipped By

UPS Expedited®

1Z4R7V941777696075

Delivered

Delivered On:
Wednesday, 12/09/2015 at 11:31

Left At:
Mailbox

[Proof of Delivery](#)

[Notify me with Updates »](#)

Shipping Information

To:
CORUNNA, CA

Shipped By

UPS Expedited®

1Z4R7V941777696084

Delivered

Delivered On:
Tuesday, 12/08/2015 at 13:04

Left At:
Receiver

Signed By:
PAVEY

[Proof of Delivery](#)

[Notify me with Updates »](#)

Shipping Information

To:
SARNIA, CA

Shipped By

UPS Expedited®

1Z4R7V941777696093

Delivered

Delivered On:
Tuesday, 12/08/2015 at 14:20

Left At:
Mail room

Signed By:
MORRISON

[Proof of Delivery](#)

[Notify me with Updates »](#)

Shipping Information

To:
CORUNNA, CA

Shipped By

UPS Expedited®

1Z4R7V941777695987

Delivered

Delivered On:
Wednesday, 12/09/2015 at 17:47

Left At:
Met customer man

[Proof of Delivery](#)

[Notify me with Updates »](#)

Shipping Information

To:
SARNIA, CA

Shipped By

UPS Expedited®

1Z4R7V941777695996

Delivered	Shipping Information To: SARNIA, CA
Delivered On: Wednesday, 12/09/2015 at 17:47 Left At: Met customer man Proof of Delivery	Shipped By UPS Expedited®
Notify me with Updates »	

1Z4R7V941777696002

Delivered	Shipping Information To: MOORETOWN, CA
Delivered On: Tuesday, 12/08/2015 at 15:04 Left At: Reception Signed By: BOGAERT Proof of Delivery	Shipped By UPS Expedited®
Notify me with Updates »	

1Z4R7V941777696011

Delivered	Shipping Information To: CORUNNA, CA
Delivered On: Wednesday, 12/09/2015 at 18:23 Left At: Front door Proof of Delivery	Shipped By UPS Expedited®
Notify me with Updates »	

1Z4R7V941777696020

Delivered	Shipping Information To: PETROLIA, CA
Delivered On: Tuesday, 12/08/2015 at 14:46 Left At: Front door Proof of Delivery	Shipped By UPS Expedited®
Notify me with Updates »	

1Z4R7V941777696039

Delivered	Shipping Information To: CORUNNA, CA
------------------	--

Delivered On:
Wednesday, 12/09/2015 at 17:34

Left At:
Front door

[Proof of Delivery](#)

[Notify me with Updates »](#)

Shipped By
UPS Expedited®

1Z4R7V941777695923

Delivered

Delivered On:
Tuesday, 12/08/2015 at 11:31

Left At:
Front desk

Signed By:
HARTWICK

[Proof of Delivery](#)

[Notify me with Updates »](#)

Shipping Information
To:
LONDON, CA

Shipped By
UPS Expedited®

1Z4R7V941777695941

Delivered

Delivered On:
Tuesday, 12/08/2015 at 13:05

Left At:
Front door

[Proof of Delivery](#)

[Notify me with Updates »](#)

Shipping Information
To:
SARNIA, CA

Shipped By
UPS Expedited®

1Z4R7V941777695950

Delivered

Delivered On:
Tuesday, 12/08/2015 at 13:26

Left At:
Met customer woman

[Proof of Delivery](#)

[Notify me with Updates »](#)

Shipping Information
To:
CORUNNA, CA

Shipped By
UPS Expedited®

1Z4R7V941777695969

Delivered

Delivered On:
Tuesday, 12/08/2015 at 13:05

Left At:
Front door

[Notify me with Updates »](#)

Shipping Information
To:
SARNIA, CA

Shipped By
UPS Expedited®

[Proof of Delivery](#)

1Z4R7V941777695978

Delivered

Delivered On:
Wednesday, 12/09/2015 at 14:01
Left At:
Front door
[Proof of Delivery](#)

[Notify me with Updates »](#)

Shipping Information

To:
MOORETOWN, CA

Shipped By

UPS Expedited®

1Z4R7V941777696100

Delivered

Delivered On:
Tuesday, 12/08/2015 at 13:16
Left At:
Office
Signed By:
FERGUSON
[Proof of Delivery](#)

[Notify me with Updates »](#)

Shipping Information

To:
SARNIA, CA

Shipped By

UPS Expedited®

1Z4R7V941777696048

Delivered

Delivered On:
Tuesday, 12/08/2015 at 14:45
Left At:
Reception
Signed By:
CRAWFORD
[Proof of Delivery](#)

[Notify me with Updates »](#)

Shipping Information

To:
MOORETOWN, CA

Shipped By

UPS Expedited®

1Z4R7V941777696048

Delivered

Delivered On:
Tuesday, 12/08/2015 at 14:45
Left At:
Reception
Signed By:
CRAWFORD

[Notify me with Updates »](#)

Shipping Information

To:
MOORETOWN, CA

Shipped By

UPS Expedited®

Regulatory Affairs - Enbridge Gas Distribution - Windows Internet Explorer

https://www.enbridgegas.com/about/regulatory-affairs/

Regulatory Affairs - Enbridge Gas Distribution

Regulatory Affairs

Since we're a rate-regulated company, the Ontario Energy Board approves our rates after a public review and hearing of our rate-change application. You can view all of our rate case information and evidence-as well as the evidence we filed in other regulatory proceedings-below. Please note that we haven't posted any evidence that was confidential or that required a non-disclosure agreement. Under the Franchises tab you will find the Ontario Energy Board Notice of Application (NOA) and Enbridge's Application and Evidence for recent franchise renewals.

Other Regulatory Proceedings: Rate Cases and QRAMs Franchises

- BB-2013-0044-2012 ESM
- BB-2013-0075 Clearance 2011 DSM Variance Accounts
- BB-2013-0089 2013 Open Bill Access
- BB-2013-0352 Clearance 2012 DSM Variance Accounts
- BB-2013-0430 - New and Updated DSM Measures
- BB-2014-0135 - Clearance 2013 D-V Accts
- BB-2014-0277 Clearance 2013 DSM Variance Accounts
- BB-2014-0323 Dawn Access Settlement Agreement
- BB-2014-0354 - 2014 New and Updated DSM Measures
- BB-2014-0378 - W/leasport Wells
- BB-2015-0023 - Exemption Application
- BB-2015-0033 - Exemption Application - W/leasport Gathering Line
- BB-2015-0049 - 2015-2020 DSM Plan
- BB-2015-0122 - 2014 ESM
- BB-2015-0175 Pre-Approval of a Long-Term Natural Gas Transportation Contract
- BB-2015-0233 - Application for Exemption for the Affiliate Relationships Code
- BB-2015-0267 - Clearance 2014 DSM Variance Accounts
- BB-2015-0303 - Corvina Well Application

Application and Evidence

NOA_ESD_20131204.pdf

Board Correspondence

Regulatory Affairs

- Leaves to Construct
- Contact Information
- General Project Enquiries
- Gas Storage
- Glossary

Regulatory Proceedings

Rate Cases and QRAMs

Franchises